

HEAT PUMP OUTDOOR UNITS



ENGINEERING DATA

HP13 ELITE® SERIES Expanded Rating Tables

Bulletin No. 210440R

April 2009

Supersedes April 2008

RATINGS

1.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

[CB26UH-018-R]

COOLING CAPACITY - HP13-018 with

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
						75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C
cfm	L/s	kBtuh	kW				kBtuh	kW				kBtuh	kW				kBtuh	kW				kBtuh	kW			
63°F (17°C)	525	250	18.1	5.3	1.06	.74	.87	.99	17.5	5.1	1.20	.75	.88	1.00	16.9	5.0	1.36	.76	.90	1.00	16.1	4.7	1.55	.78	.93	1.00
	625	295	18.8	5.5	1.07	.77	.92	1.00	18.2	5.3	1.21	.78	.93	1.00	17.5	5.1	1.36	.80	.95	1.00	16.8	4.9	1.56	.82	.98	1.00
	675	320	19.1	5.6	1.06	.78	.94	1.00	18.5	5.4	1.20	.80	.96	1.00	17.8	5.2	1.37	.82	.98	1.00	17.1	5.0	1.56	.84	1.00	1.00
67°F (19°C)	525	250	19.2	5.6	1.07	.59	.71	.83	18.6	5.5	1.21	.60	.72	.85	17.9	5.2	1.37	.60	.74	.87	17.1	5.0	1.55	.61	.75	.89
	625	295	19.9	5.8	1.07	.61	.74	.88	19.2	5.6	1.21	.62	.76	.90	18.5	5.4	1.37	.63	.78	.92	17.7	5.2	1.56	.64	.80	.95
	675	320	20.2	5.9	1.07	.62	.76	.90	19.5	5.7	1.21	.63	.78	.93	18.7	5.5	1.37	.64	.80	.95	17.9	5.2	1.56	.65	.82	.98
71°F (22°C)	525	250	20.4	6.0	1.07	.46	.58	.69	19.6	5.7	1.21	.46	.58	.70	18.9	5.5	1.37	.46	.59	.71	18.1	5.3	1.56	.46	.60	.73
	625	295	21.0	6.2	1.07	.46	.60	.72	20.2	5.9	1.21	.47	.60	.73	19.5	5.7	1.37	.47	.61	.75	18.7	5.5	1.56	.47	.62	.77
	675	320	21.2	6.2	1.07	.47	.61	.74	20.6	6.0	1.21	.47	.61	.75	19.8	5.8	1.37	.47	.62	.77	19.0	5.6	1.57	.47	.64	.79

HEATING CAPACITY - HP13-018 with

[CB26UH-018-R]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
525	250	20.2	5.9	1.19	15.7	4.6	1.10	10.9	3.2	1.02	7.9	2.3	.92	3.9	1.1	.68
625	295	20.4	6.0	1.13	15.9	4.7	1.05	11.1	3.3	.97	8.1	2.4	.87	4.2	1.2	.63
675	320	20.7	6.1	1.11	16.2	4.7	1.03	11.4	3.3	.94	8.4	2.5	.84	4.5	1.3	.61

HEATING PERFORMANCE at 625 cfm (295 L/s) Indoor Coil Air Volume HP13-018 with

[CB26UH-018-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.13	20.4	6.0
60	16	1.11	19.4	5.7
55	13	1.09	18.4	5.4
50	10	1.07	17.3	5.1
47	8	1.06	16.7	4.9
45	7	1.05	15.9	4.7
40	4	1.02	13.9	4.1
35	2	.99	11.8	3.5
30	-1	.98	11.5	3.4
25	-4	.97	11.1	3.3
20	-7	.96	10.8	3.2
17	-8	.95	10.6	3.1
15	-9	.94	10.2	3.0
10	-12	.92	9.1	2.7
5	-15	.87	8.1	2.4
0	-18	.81	7.1	2.1
-5	-21	.75	6.2	1.8
-10	-23	.69	5.2	1.5
-15	-26	.63	4.2	1.2
-20	-29	.57	3.2	.9

RATINGS

1.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-018 with

[CB26UH-024-R]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	620	295	18.8	5.5	1.06	.77	.91	1.00	18.1	5.3	1.20	.78	.93	1.00	17.5	5.1	1.36	.80	.95	1.00	16.8	4.9	1.56	.82	.98	1.00
	675	320	19.1	5.6	1.06	.78	.94	1.00	18.5	5.4	1.20	.80	.96	1.00	17.8	5.2	1.37	.82	.98	1.00	17.1	5.0	1.56	.84	1.00	1.00
67°F (19°C)	620	295	19.9	5.8	1.07	.61	.75	.88	19.2	5.6	1.21	.62	.76	.90	18.5	5.4	1.37	.62	.77	.92	17.7	5.2	1.56	.64	.79	.95
	675	320	20.2	5.9	1.07	.62	.76	.90	19.5	5.7	1.21	.63	.78	.93	18.7	5.5	1.37	.64	.80	.95	17.9	5.2	1.56	.65	.82	.98
71°F (22°C)	620	295	21.0	6.2	1.07	.46	.60	.72	20.2	5.9	1.21	.46	.60	.73	19.5	5.7	1.37	.47	.61	.75	18.6	5.5	1.56	.47	.62	.77
	675	320	21.2	6.2	1.07	.47	.61	.74	20.6	6.0	1.21	.47	.61	.75	19.8	5.8	1.37	.47	.62	.77	19.0	5.6	1.57	.47	.64	.79

COOLING CAPACITY - HP13-018 with

[CB30M-21/26]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	600	285	19.0	5.6	1.07	.78	.92	1.00	18.3	5.4	1.20	.79	.94	1.00	17.5	5.1	1.37	.80	.96	1.00	16.7	4.9	1.55	.82	.98	1.00
	675	320	19.5	5.7	1.07	.80	.96	1.00	18.7	5.5	1.21	.82	.97	1.00	18.0	5.3	1.37	.83	.99	1.00	17.2	5.0	1.56	.86	1.00	1.00
67°F (19°C)	600	285	20.0	5.9	1.07	.61	.75	.89	19.3	5.7	1.21	.62	.77	.91	18.5	5.4	1.37	.63	.78	.93	17.7	5.2	1.56	.63	.80	.95
	675	320	20.4	6.0	1.07	.63	.78	.93	19.7	5.8	1.21	.63	.79	.94	18.9	5.5	1.37	.64	.81	.97	18.0	5.3	1.56	.66	.83	.99
71°F (22°C)	600	285	21.0	6.2	1.07	.45	.60	.73	20.4	6.0	1.21	.46	.61	.74	19.5	5.7	1.38	.47	.61	.75	18.6	5.5	1.56	.47	.62	.77
	675	320	21.6	6.3	1.07	.47	.61	.76	20.8	6.1	1.21	.47	.62	.76	19.9	5.8	1.38	.48	.63	.79	19.0	5.6	1.56	.48	.64	.80

HEATING CAPACITY - HP13-018 with

[CB26UH-024-R]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
620	295	20.4	6.0	1.13	15.9	4.7	1.05	11.2	3.3	.97	8.2	2.4	.87	4.2	1.2	.63
675	320	20.6	6.0	1.11	16.1	4.7	1.03	11.3	3.3	.94	8.3	2.4	.84	4.3	1.3	.61

HEATING CAPACITY - HP13-018 with

[CB30M-21/26]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
600	285	20.4	6.0	1.14	15.9	4.7	1.07	11.2	3.3	.99	8.2	2.4	.90	4.2	1.2	.65
675	320	20.6	6.0	1.11	16.1	4.7	1.04	11.3	3.3	.96	8.4	2.5	.87	4.4	1.3	.62

HEATING PERFORMANCE at 675 cfm (320 L/s) Indoor Coil Air Volume HP13-018 with [CB26UH-024-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.13	20.4	6.0
60	16	1.11	19.4	5.7
55	13	1.10	18.4	5.4
50	10	1.08	17.4	5.1
47	8	1.07	16.8	4.9
45	7	1.05	15.9	4.7
40	4	1.02	13.9	4.1
35	2	.99	11.8	3.5
30	-1	.98	11.5	3.4
25	-4	.97	11.2	3.3
20	-7	.96	10.8	3.2
17	-8	.95	10.6	3.1
15	-9	.94	10.2	3.0
10	-12	.92	9.2	2.7
5	-15	.87	8.2	2.4
0	-18	.81	7.2	2.1
-5	-21	.75	6.2	1.8
-10	-23	.69	5.2	1.5
-15	-26	.63	4.2	1.2
-20	-29	.57	3.2	.9

HEATING PERFORMANCE at 600 cfm (285 L/s) Indoor Coil Air Volume HP13-018 with [CB30M-21/26]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.14	20.4	6.0
60	16	1.13	19.4	5.7
55	13	1.11	18.4	5.4
50	10	1.09	17.4	5.1
47	8	1.08	16.7	4.9
45	7	1.07	15.9	4.7
40	4	1.04	13.9	4.1
35	2	1.00	11.8	3.5
30	-1	1.00	11.5	3.4
25	-4	.99	11.2	3.3
20	-7	.99	10.8	3.2
17	-8	.99	10.6	3.1
15	-9	.98	10.2	3.0
10	-12	.96	9.2	2.7
5	-15	.90	8.2	2.4
0	-18	.84	7.2	2.1
-5	-21	.78	6.2	1.8
-10	-23	.72	5.2	1.5
-15	-26	.65	4.2	1.2
-20	-29	.59	3.2	.9

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

AIR HANDLERS

[CB26UH-024-R]

COOLING CAPACITY - HP13-024 with

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	700	330	24.0	7.0	1.53	.74	.87	.99	23.2	6.8	1.72	.75	.89	1.00	22.4	6.6	1.95	.76	.91	1.00	21.2	6.2	2.21	.78	.93	1.00
	825	390	24.8	7.3	1.54	.77	.91	1.00	24.0	7.0	1.73	.78	.93	1.00	23.0	6.7	1.95	.80	.96	1.00	22.0	6.4	2.22	.82	.98	1.00
	900	425	25.2	7.4	1.54	.79	.94	1.00	24.4	7.2	1.74	.80	.96	1.00	23.4	6.9	1.95	.82	.98	1.00	22.4	6.6	2.22	.85	1.00	1.00
67°F (19°C)	700	330	25.4	7.4	1.55	.59	.72	.84	24.6	7.2	1.73	.60	.73	.85	23.6	6.9	1.96	.61	.74	.87	22.6	6.6	2.22	.61	.76	.90
	825	390	26.2	7.7	1.55	.61	.75	.88	25.4	7.4	1.74	.62	.76	.90	24.4	7.2	1.96	.62	.78	.92	23.2	6.8	2.22	.64	.80	.95
	900	425	26.6	7.8	1.56	.62	.77	.91	25.6	7.5	1.75	.63	.78	.93	24.8	7.3	1.97	.64	.80	.95	23.6	6.9	2.23	.65	.82	.98
71°F (22°C)	700	330	26.8	7.9	1.56	.46	.58	.69	26.0	7.6	1.75	.46	.58	.70	25.0	7.3	1.97	.46	.59	.72	23.8	7.0	2.23	.46	.60	.73
	825	390	27.6	8.1	1.57	.46	.60	.72	26.8	7.9	1.75	.47	.60	.74	25.6	7.5	1.98	.47	.61	.75	24.6	7.2	2.24	.47	.63	.77
	900	425	28.0	8.2	1.57	.46	.61	.74	27.0	7.9	1.76	.47	.62	.76	26.0	7.6	1.98	.48	.63	.78	25.0	7.3	2.23	.48	.64	.80

COOLING CAPACITY - HP13-024 with

[CB30M-21/26]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	700	330	24.2	7.1	1.54	.75	.88	1.00	23.2	6.8	1.73	.75	.90	1.00	22.2	6.5	1.95	.77	.92	1.00	21.2	6.2	2.21	.79	.95	1.00
	800	380	24.8	7.3	1.54	.78	.92	1.00	23.8	7.0	1.73	.79	.94	1.00	22.8	6.7	1.95	.80	.96	1.00	21.8	6.4	2.21	.82	.98	1.00
	900	425	25.4	7.4	1.55	.80	.96	1.00	24.4	7.2	1.73	.82	.98	1.00	23.4	6.9	1.95	.84	.99	1.00	22.2	6.5	2.22	.86	1.00	1.00
67°F (19°C)	700	330	25.4	7.4	1.55	.59	.73	.85	24.6	7.2	1.74	.60	.74	.86	23.6	6.9	1.96	.61	.75	.88	22.4	6.6	2.22	.61	.76	.91
	800	380	26.0	7.6	1.55	.61	.74	.89	25.2	7.4	1.74	.62	.77	.91	24.2	7.1	1.96	.63	.78	.93	23.0	6.7	2.22	.64	.80	.96
	900	425	26.6	7.8	1.56	.63	.78	.93	25.6	7.5	1.75	.64	.80	.95	24.6	7.2	1.96	.65	.81	.97	23.4	6.9	2.23	.66	.83	.99
71°F (22°C)	700	330	26.8	7.9	1.56	.45	.58	.70	25.8	7.6	1.75	.46	.58	.71	24.8	7.3	1.97	.46	.59	.72	23.6	6.9	2.23	.46	.60	.74
	800	380	27.4	8.0	1.56	.46	.60	.72	26.4	7.7	1.75	.46	.60	.74	25.4	7.4	1.97	.47	.62	.76	24.2	7.1	2.23	.47	.63	.78
	900	425	28.0	8.2	1.57	.46	.62	.76	27.0	7.9	1.76	.47	.63	.76	26.0	7.6	1.98	.48	.64	.79	24.6	7.2	2.24	.48	.65	.81

HEATING CAPACITY - HP13-024 with

[CB26UH-024-R]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW
700	330	26.9			7.9			1.58			21.0			6.2		
825	390	27.0	7.9	1.51	21.1	6.2	1.45	14.8	4.3	1.39	10.8	3.2	1.24	5.5	1.6	.89
900	425	27.2	8.0	1.48	21.3	6.2	1.42	15.0	4.4	1.35	11.0	3.2	1.20	5.7	1.7	.86

HEATING CAPACITY - HP13-024 with

[CB30M-21/26]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW	Total Heating Capacity	Comp. Motor kW Input	kW
700	330	26.9			7.9			1.59			21.0			6.2		
800	380	27.0	7.9	1.53	21.1	6.2	1.48	14.9	4.4	1.43	10.8	3.2	1.28	5.5	1.6	.93
900	425	27.3	8.0	1.49	21.4	6.3	1.43	15.2	4.5	1.38	11.1	3.3	1.24	5.8	1.7	.88

HEATING PERFORMANCE at 825 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with [CB26UH-024-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.51	27.0	7.9
60	16	1.49	25.7	7.5
55	13	1.48	24.3	7.1
50	10	1.46	23.0	6.7
47	8	1.45	22.1	6.5
45	7	1.45	21.1	6.2
40	4	1.44	18.5	5.4
35	2	1.43	15.9	4.7
30	-1	1.41	15.3	4.5
25	-4	1.39	14.8	4.3
20	-7	1.36	14.3	4.2
17	-8	1.35	14.0	4.1
15	-9	1.34	13.5	4.0
10	-12	1.32	12.1	3.5
5	-15	1.24	10.8	3.2
0	-18	1.15	9.5	2.8
-5	-21	1.06	8.2	2.4
-10	-23	.98	6.8	2.0
-15	-26	.89	5.5	1.6
-20	-29	.81	4.2	1.2

HEATING PERFORMANCE at 800 cfm (380 L/s) Indoor Coil Air Volume HP13-024 with [CB30M-21/26]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.53	27.0	7.9
60	16	1.52	25.7	7.5
55	13	1.50	24.3	7.1
50	10	1.49	23.0	6.7
47	8	1.48	22.2	6.5
45	7	1.48	21.1	6.2
40	4	1.47	18.5	5.4
35	2	1.46	15.9	4.7
30	-1	1.44	15.4	4.5
25	-4	1.43	14.9	4.4
20	-7	1.41	14.4	4.2
17	-8	1.39	14.1	4.1
15	-9	1.39	13.5	4.0
10	-12	1.37	12.2	3.6
5	-15	1.28	10.8	3.2
0	-18	1.19	9.5	2.8
-5	-21	1.11	8.2	2.4
-10	-23	1.02	6.9	2.0
-15	-26	.93	5.5	1.6
-20	-29	.84	4.2	1.2

RATINGS

2 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

AIR HANDLERS

COOLING CAPACITY - HP13-024 with

[CB30M-31]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	700	330	25.4	7.4	1.55	.75	.89	1.00	24.4	7.2	1.74	.76	.91	1.00	23.4	6.9	1.96	.78	.93	1.00	22.2	6.5	2.22	.79	.95	1.00
	800	380	26.2	7.7	1.55	.78	.94	1.00	25.0	7.3	1.74	.79	.96	1.00	24.0	7.0	1.96	.81	.98	1.00	23.0	6.7	2.22	.84	1.00	1.00
	900	425	26.8	7.9	1.56	.82	.98	1.00	25.8	7.6	1.75	.83	1.00	1.00	24.8	7.3	1.97	.85	1.00	1.00	23.8	7.0	2.23	.87	1.00	1.00
67°F (19°C)	700	330	26.8	7.9	1.56	.60	.73	.86	25.8	7.6	1.75	.61	.74	.87	24.8	7.3	1.97	.61	.76	.89	23.6	6.9	2.23	.62	.77	.92
	800	380	27.6	8.1	1.57	.62	.76	.90	26.4	7.7	1.75	.62	.77	.92	25.4	7.4	1.97	.63	.79	.94	24.2	7.1	2.23	.65	.81	.97
	900	425	28.2	8.3	1.57	.63	.79	.95	27.0	7.9	1.76	.65	.81	.97	25.8	7.6	1.98	.66	.82	.99	24.6	7.2	2.23	.66	.85	1.00
71°F (22°C)	700	330	28.2	8.3	1.57	.45	.58	.71	27.2	8.0	1.76	.46	.59	.72	26.0	7.6	1.98	.46	.60	.73	24.8	7.3	2.24	.46	.61	.75
	800	380	29.0	8.5	1.58	.47	.60	.74	27.8	8.1	1.77	.47	.61	.75	26.6	7.8	1.98	.47	.62	.76	25.4	7.4	2.25	.47	.63	.79
	900	425	29.6	8.7	1.59	.47	.62	.77	28.4	8.3	1.77	.47	.63	.80	27.4	8.0	1.99	.48	.65	.80	26.0	7.6	2.25	.48	.66	.84

HEATING CAPACITY - HP13-024 with

[CB30M-31]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW				
700	330	26.8	7.9	1.63	20.8	6.1	1.61	14.5	4.2	1.60	10.5	3.1	1.46	5.3	1.6	1.06
800	380	27.0	7.9	1.57	21.0	6.2	1.55	14.7	4.3	1.54	10.7	3.1	1.40	5.5	1.6	1.01
900	425	27.2	8.0	1.52	21.2	6.2	1.50	14.9	4.4	1.49	10.8	3.2	1.35	5.6	1.6	.95

HEATING PERFORMANCE at 800 cfm (380 L/s) Indoor Coil-ir Volume HP13-024 with

[CB30M-31]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.57	27.0	7.9
60	16	1.56	25.7	7.5
55	13	1.56	24.3	7.1
50	10	1.55	22.9	6.7
47	8	1.55	22.1	6.5
45	7	1.55	21.0	6.2
40	4	1.57	18.4	5.4
35	2	1.58	15.7	4.6
30	-1	1.56	15.2	4.5
25	-4	1.54	14.7	4.3
20	-7	1.52	14.2	4.2
17	-8	1.51	13.9	4.1
15	-9	1.51	13.4	3.9
10	-12	1.50	12.0	3.5
5	-15	1.40	10.7	3.1
0	-18	1.30	9.4	2.8
-5	-21	1.20	8.1	2.4
-10	-23	1.10	6.8	2.0
-15	-26	1.01	5.5	1.6
-20	-29	.91	4.2	1.2

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[C33-24B + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	825	390	24.2	7.1	1.54	.77	.91	1.00	23.4	6.9	1.73	.78	.93	1.00	22.4	6.6	1.95	.80	.95	1.00	21.4	6.3	2.21	.82	.98	1.00
905	425	24.6	7.2	1.54	.79	.94	1.00	23.8	7.0	1.73	.80	.96	1.00	22.8	6.7	1.95	.82	.98	1.00	21.8	6.4	2.21	.84	1.00	1.00	
67°F (19°C)	825	390	25.4	7.4	1.55	.61	.75	.88	24.4	7.2	1.74	.62	.76	.90	23.4	6.9	1.95	.63	.78	.92	22.4	6.6	2.22	.64	.80	.95
905	425	25.8	7.6	1.55	.62	.77	.91	24.8	7.3	1.74	.63	.78	.93	23.8	7.0	1.96	.64	.80	.95	22.8	6.7	2.22	.65	.82	.97	
71°F (22°C)	825	390	26.4	7.7	1.55	.47	.60	.73	25.6	7.5	1.74	.47	.61	.74	24.6	7.2	1.97	.47	.61	.75	23.4	6.9	2.22	.47	.63	.77
905	425	26.8	7.9	1.56	.47	.61	.75	26.0	7.6	1.75	.47	.62	.76	25.0	7.3	1.97	.48	.63	.78	23.8	7.0	2.23	.48	.64	.80	

COOLING CAPACITY - HP13-024 with

[C33-30A + G60UHV-36A-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	830	390	24.0	7.0	1.55	.77	.91	1.00	23.2	6.8	1.73	.78	.93	1.00	22.4	6.6	1.96	.80	.95	1.00	21.4	6.3	2.23	.82	.98	1.00
915	430	24.4	7.2	1.55	.78	.93	1.00	23.6	6.9	1.74	.80	.95	1.00	22.8	6.7	1.96	.82	.98	1.00	21.8	6.4	2.23	.84	1.00	1.00	
67°F (19°C)	830	390	25.4	7.4	1.55	.61	.74	.87	24.6	7.2	1.75	.62	.76	.89	23.6	6.9	1.97	.63	.77	.92	22.6	6.6	2.23	.64	.79	.94
915	430	25.8	7.6	1.56	.62	.76	.90	25.0	7.3	1.75	.63	.78	.92	24.0	7.0	1.97	.64	.79	.95	23.0	6.7	2.24	.65	.82	.98	
71°F (22°C)	830	390	26.4	7.7	1.56	.47	.60	.72	25.6	7.5	1.75	.47	.61	.74	24.8	7.3	1.98	.47	.62	.75	23.6	6.9	2.24	.48	.63	.77
915	430	27.0	7.9	1.57	.47	.61	.74	26.2	7.7	1.76	.47	.62	.76	25.2	7.4	1.98	.48	.63	.77	24.0	7.0	2.25	.48	.64	.79	

HEATING CAPACITY - HP13-024 with

[C33-24B + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input					
825	390	26.5	7.8	1.71	20.6	6.0	1.62	14.4	4.2	1.53	10.4	3.0	1.35	5.4	1.6	.98
905	425	26.6	7.8	1.67	20.7	6.1	1.58	14.6	4.3	1.49	10.6	3.1	1.31	5.5	1.6	.94

HEATING CAPACITY - HP13-024 with

[C33-30A + G60UHV-36A-070]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input					
830	390	26.7	7.8	1.58	20.8	6.1	1.50	14.6	4.3	1.43	10.6	3.1	1.26	5.4	1.6	.91
915	430	26.7	7.8	1.54	20.8	6.1	1.46	14.6	4.3	1.39	10.6	3.1	1.22	5.4	1.6	.88

HEATING PERFORMANCE at 825 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with

[C33-24B + G60UHV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW	kBtuh	kW	kBtuh
65	18	1.71	26.5	7.8	26.5
60	16	1.68	25.1	7.4	25.1
55	13	1.66	23.8	7.0	23.8
50	10	1.63	22.4	6.6	22.4
47	8	1.62	21.6	6.3	21.6
45	7	1.62	20.6	6.0	20.6
40	4	1.60	18.0	5.3	18.0
35	2	1.59	15.5	4.5	15.5
30	-1	1.56	15.0	4.4	15.0
25	-4	1.53	14.4	4.2	14.4
20	-7	1.50	13.9	4.1	13.9
17	-8	1.48	13.6	4.0	13.6
15	-9	1.47	13.1	3.8	13.1
10	-12	1.44	11.7	3.4	11.7
5	-15	1.35	10.4	3.0	10.4
0	-18	1.26	9.2	2.7	9.2
-5	-21	1.16	7.9	2.3	7.9
-10	-23	1.07	6.6	1.9	6.6
-15	-26	.98	5.4	1.6	5.4
-20	-29	.89	4.1	1.2	4.1

HEATING PERFORMANCE at 830 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with

[C33-30A + G60UHV-36A-070]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW	kBtuh	kW	kBtuh
65	18	1.58	26.7	7.8	26.7
60	16	1.56	25.4	7.4	25.4
55	13	1.54	24.0	7.0	24.0
50	10	1.52	22.7	6.7	22.7
47	8	1.51	21.9	6.4	21.9
45	7	1.50	20.8	6.1	20.8
40	4	1.49	18.2	5.3	18.2
35	2	1.49	15.6	4.6	15.6
30	-1	1.46	15.1	4.4	15.1
25	-4	1.43	14.6	4.3	14.6
20	-7	1.40	14.1	4.1	14.1
17	-8	1.38	13.7	4.0	13.7
15	-9	1.37	13.2	3.9	13.2
10	-12	1.35	11.8	3.5	11.8
5	-15	1.26	10.6	3.1	10.6
0	-18	1.18	9.3	2.7	9.3
-5	-21	1.09	8.0	2.3	8.0
-10	-23	1.00	6.7	2.0	6.7
-15	-26	.91	5.4	1.6	5.4
-20	-29	.83	4.1	1.2	4.1

RATINGS

2 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[C33-30B + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	825	390	24.0	7.0	1.54	.77	.91	1.00	23.2	6.8	1.73	.78	.93	1.00	22.4	6.6	1.96	.80	.95	1.00	21.4	6.3	2.23	.82	.98	1.00
905	425	24.4	7.2	1.55	.78	.93	1.00	23.6	6.9	1.74	.80	.95	1.00	22.8	6.7	1.97	.81	.98	1.00	21.8	6.4	2.23	.84	1.00	1.00	
67°F (19°C)	825	390	25.4	7.4	1.55	.61	.74	.87	24.4	7.2	1.75	.62	.76	.89	23.6	6.9	1.97	.63	.77	.91	22.6	6.6	2.23	.64	.79	.94
905	425	25.8	7.6	1.56	.62	.76	.90	24.8	7.3	1.75	.63	.78	.92	24.0	7.0	1.97	.64	.79	.94	22.8	6.7	2.24	.65	.81	.97	
71°F (22°C)	825	390	26.4	7.7	1.56	.47	.60	.72	25.6	7.5	1.75	.47	.61	.74	24.6	7.2	1.98	.47	.62	.75	23.6	6.9	2.24	.48	.63	.77
905	425	27.0	7.9	1.57	.47	.61	.74	26.0	7.6	1.76	.47	.62	.75	25.2	7.4	1.98	.48	.63	.77	24.0	7.0	2.25	.48	.64	.79	

COOLING CAPACITY - HP13-024 with

[C33-30B + G61MPV-36B-045]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	840	395	24.0	7.0	1.55	.77	.91	1.00	23.2	6.8	1.74	.78	.93	1.00	22.4	6.6	1.96	.80	.95	1.00	21.4	6.3	2.23	.82	.98	1.00
945	445	24.6	7.2	1.55	.79	.94	1.00	23.8	7.0	1.74	.81	.96	1.00	23.0	6.7	1.96	.83	.98	1.00	22.2	6.5	2.23	.85	1.00	1.00	
67°F (19°C)	840	395	25.4	7.4	1.55	.61	.75	.88	24.6	7.2	1.75	.62	.76	.90	23.6	6.9	1.97	.63	.78	.92	22.6	6.6	2.23	.64	.80	.95
945	445	26.0	7.6	1.56	.63	.77	.91	25.0	7.3	1.75	.64	.79	.93	24.2	7.1	1.97	.65	.80	.96	23.0	6.7	2.23	.66	.83	.98	
71°F (22°C)	840	395	26.6	7.8	1.56	.47	.60	.72	25.6	7.5	1.75	.47	.61	.74	24.8	7.3	1.98	.47	.62	.75	23.6	6.9	2.24	.48	.63	.77
945	445	27.2	8.0	1.57	.48	.61	.75	26.2	7.7	1.76	.48	.62	.76	25.2	7.4	1.98	.48	.64	.78	24.2	7.1	2.25	.49	.65	.80	

HEATING CAPACITY - HP13-024 with

[C33-30B + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil																			
		65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input					
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW						
825	390	26.6	7.8	1.58	20.7	6.1	1.50	14.5	4.2	1.43	10.5	3.1	1.26	5.4	1.6	.92					
905	425	26.6	7.8	1.55	20.7	6.1	1.47	14.5	4.2	1.39	10.5	3.1	1.23	5.4	1.6	.88					

HEATING CAPACITY - HP13-024 with

[C33-30B + G61MPV-36B-045]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil																			
		65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input					
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW						
840	395	26.8	7.9	1.57	20.9	6.1	1.50	14.6	4.3	1.42	10.6	3.1	1.26	5.4	1.6	.91					
945	445	26.9	7.9	1.53	21.0	6.2	1.45	14.8	4.3	1.38	10.7	3.1	1.22	5.6	1.6	.87					

HEATING PERFORMANCE at 825 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with [C33-30B + G60UHV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.58	26.6	7.8
60	16	1.56	25.3	7.4
55	13	1.54	23.9	7.0
50	10	1.52	22.6	6.6
47	8	1.51	21.8	6.4
45	7	1.50	20.7	6.1
40	4	1.49	18.2	5.3
35	2	1.49	15.6	4.6
30	-1	1.46	15.0	4.4
25	-4	1.43	14.5	4.2
20	-7	1.40	14.0	4.1
17	-8	1.38	13.7	4.0
15	-9	1.37	13.1	3.8
10	-12	1.35	11.8	3.5
5	-15	1.26	10.5	3.1
0	-18	1.18	9.2	2.7
-5	-21	1.09	7.9	2.3
-10	-23	1.00	6.7	2.0
-15	-26	.92	5.4	1.6
-20	-29	.83	4.1	1.2

HEATING PERFORMANCE at 840 cfm (395 L/s) Indoor Coil Air Volume HP13-024 with [C33-30B + G61MPV-36B-045]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.57	26.8	7.9
60	16	1.55	25.4	7.4
55	13	1.53	24.1	7.1
50	10	1.51	22.7	6.7
47	8	1.50	21.9	6.4
45	7	1.50	20.9	6.1
40	4	1.49	18.3	5.4
35	2	1.48	15.7	4.6
30	-1	1.45	15.1	4.4
25	-4	1.42	14.6	4.3
20	-7	1.39	14.1	4.1
17	-8	1.38	13.8	4.0
15	-9	1.37	13.2	3.9
10	-12	1.35	11.9	3.5
5	-15	1.26	10.6	3.1
0	-18	1.17	9.3	2.7
-5	-21	1.09	8.0	2.3
-10	-23	1.00	6.7	2.0
-15	-26	.91	5.4	1.6
-20	-29	.83	4.1	1.2

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[C33-30B + G61MPV-36B-070]
[C33-30B + G71MPP-36B-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
						75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C
cfm	L/s	kBtuh	kW	kW				kBtuh	kW	kW				kBtuh	kW	kW				kBtuh	kW	kW				
63°F (17°C)	830	390	24.0	7.0	1.55	.77	.91	1.00	23.2	6.8	1.73	.78	.93	1.00	22.4	6.6	1.96	.80	.95	1.00	21.4	6.3	2.23	.82	.98	1.00
	930	440	24.6	7.2	1.55	.79	.94	1.00	23.8	7.0	1.74	.80	.96	1.00	22.8	6.7	1.96	.82	.98	1.00	22.0	6.4	2.23	.84	1.00	1.00
67°F (19°C)	830	390	25.4	7.4	1.55	.61	.74	.87	24.6	7.2	1.75	.62	.76	.89	23.6	6.9	1.97	.63	.77	.92	22.6	6.6	2.23	.64	.79	.94
	930	440	25.8	7.6	1.56	.62	.77	.91	25.0	7.3	1.75	.63	.78	.93	24.0	7.0	1.97	.64	.80	.95	23.0	6.7	2.24	.66	.82	.98
71°F (22°C)	830	390	26.4	7.7	1.56	.47	.60	.72	25.6	7.5	1.75	.47	.61	.74	24.8	7.3	1.98	.47	.62	.75	23.6	6.9	2.24	.48	.63	.77
	930	440	27.0	7.9	1.57	.47	.61	.74	26.2	7.7	1.76	.48	.62	.76	25.2	7.4	1.98	.48	.63	.78	24.2	7.1	2.25	.49	.64	.80

HEATING CAPACITY - HP13-024 with

[C33-30B + G61MPV-36B-070]
[C33-30B + G71MPP-36B-070]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh
830	390	26.7	7.8	1.58	20.8	6.1	1.50	14.6	4.3	1.43	10.6	3.1	1.26	5.4	1.6	.91				
930	440	26.8	7.9	1.54	20.9	6.1	1.46	14.7	4.3	1.38	10.6	3.1	1.22	5.5	1.6	.87				

HEATING PERFORMANCE at 830 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with

[C33-30B + G61MPV-36B-070]
[C33-30B + G71MPP-36B-070]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	1.58		26.7	7.8
60	16	1.56		25.4	7.4
55	13	1.54		24.0	7.0
50	10	1.52		22.7	6.7
47	8	1.51		21.9	6.4
45	7	1.50		20.8	6.1
40	4	1.49		18.2	5.3
35	2	1.49		15.6	4.6
30	-1	1.46		15.1	4.4
25	-4	1.43		14.6	4.3
20	-7	1.40		14.1	4.1
17	-8	1.38		13.7	4.0
15	-9	1.37		13.2	3.9
10	-12	1.35		11.8	3.5
5	-15	1.26		10.6	3.1
0	-18	1.18		9.3	2.7
-5	-21	1.09		8.0	2.3
-10	-23	1.00		6.7	2.0
-15	-26	.91		5.4	1.6
-20	-29	.83		4.1	1.2

RATINGS

2 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[CR33-24A-F + G60DFV-36A-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	875	415	25.0	7.3	1.55	.79	.94	1.00	24.0	7.0	1.74	.80	.96	1.00	23.2	6.8	1.96	.82	.98	1.00	22.0	6.4	2.23	.84	.99	1.00
1010	475	25.6	7.5	1.55	.82	.97	1.00	24.6	7.2	1.75	.84	.99	1.00	23.8	7.0	1.97	.86	1.00	1.00	22.8	6.7	2.24	.88	1.00	1.00	
67°F (19°C)	875	415	26.2	7.7	1.56	.62	.77	.91	25.2	7.4	1.75	.63	.78	.93	24.2	7.1	1.97	.64	.80	.95	23.2	6.8	2.24	.65	.82	.97
1010	475	26.8	7.9	1.56	.64	.80	.95	25.8	7.6	1.76	.65	.82	.97	24.8	7.3	1.97	.66	.84	.99	23.6	6.9	2.24	.68	.86	1.00	
71°F (22°C)	875	415	27.4	8.0	1.57	.47	.61	.75	26.6	7.8	1.76	.47	.62	.76	25.6	7.5	1.99	.48	.63	.77	24.4	7.2	2.25	.47	.64	.80
1010	475	28.0	8.2	1.58	.47	.63	.78	27.0	7.9	1.77	.47	.64	.80	26.0	7.6	1.99	.49	.65	.82	24.8	7.3	2.25	.49	.67	.84	

COOLING CAPACITY - HP13-024 with

[CR33-24B-F + G61MPV-36B-045]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	840	395	24.8	7.3	1.55	.78	.93	1.00	23.8	7.0	1.74	.79	.94	1.00	23.0	6.7	1.97	.81	.96	1.00	21.8	6.4	2.23	.83	.99	1.00
945	445	25.4	7.4	1.55	.81	.96	1.00	24.4	7.2	1.74	.82	.98	1.00	23.4	6.9	1.97	.84	.99	1.00	22.4	6.6	2.23	.87	1.00	1.00	
67°F (19°C)	840	395	26.0	7.6	1.56	.62	.76	.90	25.0	7.3	1.75	.62	.77	.91	24.0	7.0	1.97	.63	.79	.93	23.0	6.7	2.24	.64	.81	.96
945	445	26.6	7.8	1.56	.63	.79	.93	25.6	7.5	1.75	.64	.80	.95	24.6	7.2	1.98	.65	.82	.97	23.4	6.9	2.24	.66	.84	.99	
71°F (22°C)	840	395	27.2	8.0	1.57	.47	.60	.74	26.4	7.7	1.76	.47	.61	.75	25.4	7.4	1.98	.47	.62	.77	24.2	7.1	2.25	.47	.63	.79
945	445	27.8	8.1	1.57	.47	.62	.76	26.8	7.9	1.76	.47	.63	.78	25.8	7.6	1.99	.48	.64	.80	24.6	7.2	2.25	.48	.65	.82	

HEATING CAPACITY - HP13-024 with

[CR33-24A-F + G60DFV-36A-070]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW				
875	415	26.8	7.9	1.51	20.9	6.1	1.44	14.7	4.3	1.37	10.7	3.1	1.21	5.5	1.6	.88				
1010	475	27.1	7.9	1.46	21.2	6.2	1.39	15.0	4.4	1.32	10.9	3.2	1.17	5.7	1.7	.83				

HEATING CAPACITY - HP13-024 with

[CR33-24B-F + G61MPV-36B-045]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW				
840	395	26.9	7.9	1.53	20.9	6.1	1.45	14.7	4.3	1.38	10.7	3.1	1.22	5.5	1.6	.88				
945	445	27.0	7.9	1.49	21.1	6.2	1.41	14.9	4.4	1.33	10.9	3.2	1.18	5.6	1.6	.84				

HEATING PERFORMANCE at 875 cfm (415 L/s) Indoor Coil Air Volume HP13-024 with [CR33-24A-F + G60DFV-36A-070]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.51	26.8	7.9
60	16	1.49	25.5	7.5
55	13	1.47	24.1	7.1
50	10	1.45	22.8	6.7
47	8	1.44	22.0	6.4
45	7	1.44	20.9	6.1
40	4	1.43	18.3	5.4
35	2	1.42	15.8	4.6
30	-1	1.39	15.2	4.5
25	-4	1.37	14.7	4.3
20	-7	1.34	14.2	4.2
17	-8	1.32	13.9	4.1
15	-9	1.32	13.3	3.9
10	-12	1.30	12.0	3.5
5	-15	1.21	10.7	3.1
0	-18	1.13	9.4	2.8
-5	-21	1.05	8.1	2.4
-10	-23	.96	6.8	2.0
-15	-26	.88	5.5	1.6
-20	-29	.80	4.2	1.2

HEATING PERFORMANCE at 840 cfm (395 L/s) Indoor Coil Air Volume HP13-024 with [CR33-24B-F + G61MPV-36B-045]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.53	26.9	7.9
60	16	1.51	25.5	7.5
55	13	1.49	24.1	7.1
50	10	1.47	22.8	6.7
47	8	1.46	22.0	6.4
45	7	1.45	20.9	6.1
40	4	1.44	18.4	5.4
35	2	1.44	15.8	4.6
30	-1	1.41	15.2	4.5
25	-4	1.38	14.7	4.3
20	-7	1.35	14.2	4.2
17	-8	1.33	13.9	4.1
15	-9	1.32	13.3	3.9
10	-12	1.30	12.0	3.5
5	-15	1.22	10.7	3.1
0	-18	1.14	9.4	2.8
-5	-21	1.05	8.1	2.4
-10	-23	.97	6.8	2.0
-15	-26	.88	5.5	1.6
-20	-29	.80	4.2	1.2

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[CR33-24B-F + G61MPV-36B-070]
[CR33-24B-F + G71MPP-36B-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
						75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C
cfm	L/s	kBtuh	kW	kW				kBtuh	kW	kW				kBtuh	kW	kW				kBtuh	kW	kW				
63°F (17°C)	830	390	24.6	7.2	1.55	.78	.92	1.00	23.8	7.0	1.74	.79	.94	1.00	22.8	6.7	1.97	.81	.96	1.00	21.8	6.4	2.23	.83	.98	1.00
	930	440	25.2	7.4	1.55	.80	.95	1.00	24.4	7.2	1.74	.82	.97	1.00	23.4	6.9	1.97	.84	.99	1.00	22.2	6.5	2.23	.86	1.00	1.00
67°F (19°C)	830	390	26.0	7.6	1.56	.61	.75	.89	25.0	7.3	1.75	.62	.77	.91	24.0	7.0	1.97	.63	.79	.93	23.0	6.7	2.24	.64	.81	.95
	930	440	26.4	7.7	1.56	.63	.78	.93	25.4	7.4	1.75	.64	.80	.94	24.4	7.2	1.98	.65	.81	.96	23.2	6.8	2.24	.66	.84	.99
71°F (22°C)	830	390	27.2	8.0	1.57	.47	.60	.73	26.2	7.7	1.76	.47	.61	.74	25.2	7.4	1.98	.47	.62	.76	24.2	7.1	2.25	.47	.63	.78
	930	440	27.8	8.1	1.57	.46	.62	.76	26.8	7.9	1.76	.47	.63	.78	25.8	7.6	1.99	.48	.64	.80	24.6	7.2	2.25	.48	.65	.81

HEATING CAPACITY - HP13-024 with

[CR33-24B-F + G61MPV-36B-070]
[CR33-24B-F + G71MPP-36B-070]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input					
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh	kW		
830	390	26.7	7.8	1.53	20.8	6.1	1.46	14.7	4.3	1.38	10.6	3.1	1.22	5.4	1.6	.88				
930	440	27.0	7.9	1.49	21.1	6.2	1.42	14.9	4.4	1.34	10.9	3.2	1.18	5.7	1.7	.84				

HEATING PERFORMANCE at 830 cfm (390 L/s) Indoor Coil

Air Volume HP13-024 with [CR33-24B-F + G61MPV-36B-070]
[CR33-24B-F + G71MPP-36B-070]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.53	26.7	7.8
60	16	1.51	25.3	7.4
55	13	1.49	24.0	7.0
50	10	1.47	22.7	6.7
47	8	1.46	21.9	6.4
45	7	1.46	20.8	6.1
40	4	1.45	18.3	5.4
35	2	1.44	15.7	4.6
30	-1	1.41	15.2	4.5
25	-4	1.38	14.7	4.3
20	-7	1.35	14.1	4.1
17	-8	1.33	13.8	4.0
15	-9	1.33	13.3	3.9
10	-12	1.30	11.9	3.5
5	-15	1.22	10.6	3.1
0	-18	1.14	9.3	2.7
-5	-21	1.05	8.0	2.3
-10	-23	.97	6.7	2.0
-15	-26	.88	5.4	1.6
-20	-29	.80	4.1	1.2

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[CH23-21 + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	825	390	22.8	6.7	1.54	.76	.89	1.00	22.2	6.5	1.73	.77	.91	1.00	21.2	6.2	1.95	.78	.93	1.00	20.4	6.0	2.22	.80	.96	1.00
905	425	23.4	6.9	1.54	.77	.92	1.00	22.6	6.6	1.73	.79	.94	1.00	21.6	6.3	1.96	.80	.96	1.00	20.8	6.1	2.23	.82	.98	1.00	
67°F (19°C)	825	390	24.2	7.1	1.54	.60	.74	.86	23.6	6.9	1.74	.61	.75	.88	22.6	6.6	1.96	.62	.76	.90	21.6	6.3	2.23	.63	.78	.93
905	425	24.8	7.3	1.55	.62	.75	.89	24.0	7.0	1.74	.62	.77	.90	23.0	6.7	1.96	.63	.78	.93	22.0	6.4	2.23	.65	.80	.96	
71°F (22°C)	825	390	25.6	7.5	1.55	.45	.59	.72	24.6	7.2	1.74	.47	.60	.73	23.8	7.0	1.97	.47	.61	.74	22.8	6.7	2.24	.48	.62	.76
905	425	26.0	7.6	1.56	.46	.60	.73	25.2	7.4	1.75	.47	.61	.75	24.2	7.1	1.97	.47	.62	.76	23.2	6.8	2.24	.48	.64	.78	

COOLING CAPACITY - HP13-024 with

[CH23-31 + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	825	390	23.2	6.8	1.54	.76	.90	1.00	22.4	6.6	1.73	.77	.91	1.00	21.6	6.3	1.96	.79	.94	1.00	20.6	6.0	2.22	.81	.96	1.00
905	425	23.6	6.9	1.54	.78	.92	1.00	22.8	6.7	1.73	.79	.94	1.00	22.0	6.4	1.96	.81	.96	1.00	21.2	6.2	2.23	.83	.98	1.00	
67°F (19°C)	825	390	24.6	7.2	1.55	.61	.74	.87	23.8	7.0	1.74	.61	.75	.88	22.8	6.7	1.97	.62	.77	.91	21.8	6.4	2.23	.63	.79	.93
905	425	25.0	7.3	1.55	.62	.76	.89	24.2	7.1	1.74	.63	.77	.91	23.2	6.8	1.97	.63	.79	.93	22.2	6.5	2.23	.65	.81	.96	
71°F (22°C)	825	390	25.8	7.6	1.56	.46	.60	.72	25.0	7.3	1.75	.47	.60	.73	24.0	7.0	1.97	.47	.61	.75	23.0	6.7	2.24	.48	.62	.76
905	425	26.4	7.7	1.56	.46	.61	.74	25.4	7.4	1.75	.47	.62	.75	24.6	7.2	1.98	.47	.62	.77	23.4	6.9	2.24	.47	.64	.79	

HEATING CAPACITY - HP13-024 with

[CH23-21 + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW					
825	390	26.5	7.8	1.69	20.7	6.1	1.59	14.5	4.2	1.50	10.5	3.1	1.32	5.4	1.6	.96	
905	425	26.7	7.8	1.65	20.8	6.1	1.55	14.6	4.3	1.46	10.6	3.1	1.28	5.5	1.6	.92	

HEATING CAPACITY - HP13-024 with

[CH23-31 + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW					
825	390	26.7	7.8	1.63	20.8	6.1	1.54	14.5	4.2	1.45	10.5	3.1	1.28	5.4	1.6	.93	
905	425	26.8	7.9	1.59	20.9	6.1	1.50	14.6	4.3	1.41	10.6	3.1	1.24	5.5	1.6	.89	

HEATING PERFORMANCE at 825 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with [CH23-21 + G60UHV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.69	26.5	7.8
60	16	1.66	25.2	7.4
55	13	1.64	23.8	7.0
50	10	1.61	22.5	6.6
47	8	1.60	21.7	6.4
45	7	1.59	20.7	6.1
40	4	1.58	18.1	5.3
35	2	1.56	15.5	4.5
30	-1	1.53	15.0	4.4
25	-4	1.50	14.5	4.2
20	-7	1.46	14.0	4.1
17	-8	1.44	13.7	4.0
15	-9	1.43	13.1	3.8
10	-12	1.41	11.8	3.5
5	-15	1.32	10.5	3.1
0	-18	1.23	9.2	2.7
-5	-21	1.14	7.9	2.3
-10	-23	1.05	6.7	2.0
-15	-26	.96	5.4	1.6
-20	-29	.87	4.1	1.2

HEATING PERFORMANCE at 825 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with [CH23-31 + G60UHV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.63	26.7	7.8
60	16	1.61	25.3	7.4
55	13	1.58	24.0	7.0
50	10	1.56	22.6	6.6
47	8	1.54	21.8	6.4
45	7	1.54	20.8	6.1
40	4	1.53	18.2	5.3
35	2	1.52	15.6	4.6
30	-1	1.48	15.0	4.4
25	-4	1.45	14.5	4.2
20	-7	1.42	14.0	4.1
17	-8	1.40	13.7	4.0
15	-9	1.39	13.1	3.8
10	-12	1.36	11.8	3.5
5	-15	1.28	10.5	3.1
0	-18	1.19	9.2	2.7
-5	-21	1.10	7.9	2.3
-10	-23	1.01	6.7	2.0
-15	-26	.93	5.4	1.6
-20	-29	.84	4.1	1.2

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-024 with

[CH33-24/30A-2F + G60UHV-36A-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb				
				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C		
cfm	L/s	kBtuh	kW				kBtuh	kW				kBtuh	kW				kBtuh	kW				kBtuh	kW			
63°F (17°C)	830	390	24.4	7.2	1.55	.77	.92	1.00	23.6	6.9	1.74	.79	.94	1.00	22.6	6.6	1.96	.80	.96	1.00	21.6	6.3	2.23	.82	.98	1.00
	915	430	25.0	7.3	1.55	.79	.95	1.00	24.0	7.0	1.74	.81	.97	1.00	23.0	6.7	1.97	.83	.99	1.00	22.0	6.4	2.23	.85	1.00	1.00
67°F (19°C)	830	390	25.6	7.5	1.55	.61	.75	.89	24.8	7.3	1.74	.62	.77	.91	23.8	7.0	1.97	.63	.78	.93	22.6	6.6	2.24	.64	.80	.95
	915	430	26.0	7.6	1.56	.62	.77	.91	25.2	7.4	1.75	.63	.79	.93	24.2	7.1	1.97	.64	.80	.96	23.0	6.7	2.24	.65	.82	.98
71°F (22°C)	830	390	26.8	7.9	1.56	.47	.60	.73	25.8	7.6	1.75	.47	.61	.74	24.8	7.3	1.98	.47	.62	.76	23.8	7.0	2.24	.48	.63	.78
	915	430	27.2	8.0	1.57	.47	.61	.75	26.2	7.7	1.76	.47	.62	.77	25.2	7.4	1.98	.48	.63	.78	24.2	7.1	2.25	.48	.64	.80

HEATING CAPACITY - HP13-024 with

[CH33-24/30A-2F + G60UHV-36A-070]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW
830	390	26.7	7.8	1.64	20.8	6.1	1.56	14.6	4.3	1.49	10.6	3.1	1.33	5.4	1.6	.96
915	430	26.8	7.9	1.60	20.9	6.1	1.52	14.6	4.3	1.45	10.6	3.1	1.29	5.5	1.6	.92

HEATING PERFORMANCE at 830 cfm (390 L/s) Indoor Coil Air Volume HP13-024 with

[CH33-24/30A-2F + G60UHV-36A-070]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	1.64	26.7	7.8
60	16	1.62	25.3	7.4
55	13	1.60	24.0	7.0
50	10	1.58	22.6	6.6
47	8	1.57	21.8	6.4
45	7	1.56	20.8	6.1
40	4	1.56	18.2	5.3
35	2	1.55	15.6	4.6
30	-1	1.52	15.1	4.4
25	-4	1.49	14.6	4.3
20	-7	1.46	14.1	4.1
17	-8	1.45	13.7	4.0
15	-9	1.44	13.2	3.9
10	-12	1.42	11.9	3.5
5	-15	1.33	10.6	3.1
0	-18	1.24	9.3	2.7
-5	-21	1.14	8.0	2.3
-10	-23	1.05	6.7	2.0
-15	-26	.96	5.4	1.6
-20	-29	.87	4.1	1.2

RATINGS

2.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-030 with

[CB26UH-030-R]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	875	415	30.4	8.9	2.00	.75	.88	1.00	29.4	8.6	2.23	.76	.90	1.00	28.2	8.3	2.49	.78	.93	1.00	26.8	7.9	2.79	.79	.95	1.00
1000	470	31.2	9.1	2.00	.77	.92	1.00	30.2	8.9	2.24	.79	.94	1.00	29.0	8.5	2.50	.81	.97	1.00	27.6	8.1	2.80	.83	.99	1.00	
1125	530	31.8	9.3	2.01	.80	.95	1.00	30.8	9.0	2.25	.82	.98	1.00	29.8	8.7	2.51	.84	1.00	1.00	28.6	8.4	2.81	.86	1.00	1.00	
67°F (19°C)	875	415	32.2	9.4	2.02	.60	.72	.84	31.2	9.1	2.25	.60	.74	.87	30.0	8.8	2.51	.61	.75	.89	28.8	8.4	2.81	.62	.77	.91
1000	470	33.0	9.7	2.02	.61	.75	.88	32.0	9.4	2.26	.62	.76	.91	30.8	9.0	2.52	.63	.78	.93	29.4	8.6	2.82	.64	.80	.96	
1125	530	33.6	9.8	2.03	.62	.77	.92	32.6	9.6	2.27	.64	.79	.94	31.4	9.2	2.53	.65	.81	.97	30.0	8.8	2.82	.66	.84	1.00	
71°F (22°C)	875	415	33.8	9.9	2.03	.46	.58	.70	32.8	9.6	2.27	.45	.59	.71	31.8	9.3	2.53	.46	.60	.73	30.6	9.0	2.83	.46	.61	.74
1000	470	34.8	10.2	2.04	.47	.60	.72	33.8	9.9	2.28	.47	.61	.74	32.6	9.6	2.54	.47	.62	.76	31.4	9.2	2.84	.47	.63	.78	
1125	530	35.4	10.4	2.05	.47	.61	.75	34.4	10.1	2.29	.47	.62	.77	33.2	9.7	2.55	.48	.63	.79	32.0	9.4	2.84	.48	.65	.81	

COOLING CAPACITY - HP13-030 with

[CB27UH-030]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	800	380	29.8	8.7	1.98	.74	.88	1.00	28.6	8.4	2.21	.75	.90	1.00	27.4	8.0	2.48	.77	.92	1.00	26.0	7.6	2.78	.79	.94	1.00
1000	470	31.2	9.1	1.99	.79	.95	1.00	30.0	8.8	2.23	.81	.97	1.00	28.8	8.4	2.49	.83	.99	1.00	27.4	8.0	2.79	.85	1.00	1.00	
67°F (19°C)	800	380	31.6	9.3	2.00	.59	.72	.84	30.4	8.9	2.23	.59	.73	.86	29.2	8.6	2.50	.60	.74	.88	27.8	8.1	2.79	.61	.76	.91
1000	470	33.0	9.7	2.01	.62	.77	.91	31.8	9.3	2.25	.63	.78	.94	30.4	8.9	2.51	.63	.80	.96	29.0	8.5	2.80	.65	.82	.98	
1125	530	33.4	9.8	2.02	.63	.78	.92	32.2	9.4	2.25	.64	.79	.94	30.8	9.0	2.51	.64	.81	.97	29.4	8.6	2.81	.66	.83	1.00	
71°F (22°C)	800	380	33.4	9.8	2.02	.45	.58	.70	32.2	9.4	2.25	.45	.58	.70	30.8	9.0	2.51	.45	.59	.72	29.4	8.6	2.81	.45	.60	.73
1000	470	34.8	10.2	2.03	.47	.61	.74	33.6	9.8	2.27	.47	.61	.76	32.2	9.4	2.53	.47	.62	.78	30.8	9.0	2.82	.47	.64	.80	

HEATING CAPACITY - HP13-030 with

[CB26UH-030-R]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh
875	415	35.0	10.3	2.15	27.0	7.9	2.00	18.5	5.4	1.83	13.7	4.0	1.66	6.9	2.0	1.23				
1000	470	35.1	10.3	2.08	27.1	7.9	1.93	18.6	5.5	1.76	13.8	4.0	1.59	7.1	2.1	1.16				
1125	530	35.5	10.4	2.03	27.5	8.1	1.88	18.9	5.5	1.71	14.1	4.1	1.54	7.4	2.2	1.11				

HEATING CAPACITY - HP13-030 with

[CB27UH-030]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh
800	380	34.3	10.1	2.14	26.3	7.7	2.10	17.7	5.2	2.05	12.9	3.8	1.95	6.4	1.9	1.43				
1000	470	34.7	10.2	2.02	26.7	7.8	1.98	18.1	5.3	1.93	13.3	3.9	1.83	6.9	2.0	1.31				

HEATING PERFORMANCE at 1000 cfm (470 L/s) Indoor Coil Air Volume HP13-030 with

[CB26UH-030-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.08	35.1	10.3
60	16	2.05	33.3	9.8
55	13	2.01	31.6	9.3
50	10	1.98	29.8	8.7
47	8	1.96	28.7	8.4
45	7	1.93	27.1	7.9
40	4	1.85	23.2	6.8
35	2	1.78	19.4	5.7
30	-1	1.77	19.0	5.6
25	-4	1.76	18.6	5.5
20	-7	1.75	18.2	5.3
17	-8	1.75	18.0	5.3
15	-9	1.73	17.3	5.1
10	-12	1.70	15.5	4.5
5	-15	1.59	13.8	4.0
0	-18	1.48	12.1	3.5
-5	-21	1.37	10.4	3.0
-10	-23	1.26	8.8	2.6
-15	-26	1.16	7.1	2.1
-20	-29	1.05	5.4	1.6

HEATING PERFORMANCE at 1000 cfm (470 L/s) Indoor Coil Air Volume HP13-030 with

[CB27UH-030]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.02	34.7	10.2
60	16	2.02	32.9	9.6
55	13	2.01	31.1	9.1
50	10	2.01	29.3	8.6
47	8	2.00	28.3	8.3
45	7	1.98	26.7	7.8
40	4	1.94	22.8	6.7
35	2	1.89	18.9	5.5
30	-1	1.91	18.5	5.4
25	-4	1.93	18.1	5.3
20	-7	1.96	17.7	5.2
17	-8	1.97	17.5	5.1
15	-9	1.97	16.7	4.9
10	-12	1.96	14.9	4.4
5	-15	1.83	13.3	3.9
0	-18	1.70	11.7	3.4
-5	-21	1.57	10.1	3.0
-10	-23	1.44	8.5	2.5
-15	-26	1.31	6.9	2.0
-20	-29	1.18	5.2	1.5

RATINGS

2.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-030 with

[CB27UH-036]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	840	395	30.2	8.9	1.98	.75	.89	1.00	29.0	8.5	2.22	.76	.91	1.00	27.6	8.1	2.48	.78	.94	1.00	26.2	7.7	2.78	.80	.96	1.00
	1000	470	31.2	9.1	1.99	.79	.95	1.00	30.0	8.8	2.23	.81	.97	1.00	28.8	8.4	2.49	.83	.99	1.00	27.4	8.0	2.79	.85	1.00	1.00
67°F (19°C)	840	395	32.0	9.4	2.00	.60	.73	.86	30.8	9.0	2.24	.60	.74	.87	29.4	8.6	2.50	.61	.75	.90	28.0	8.2	2.79	.62	.77	.92
	1000	470	33.0	9.7	2.01	.62	.77	.91	31.8	9.3	2.25	.63	.78	.94	30.4	8.9	2.51	.63	.80	.96	29.0	8.5	2.80	.65	.82	.98
71°F (22°C)	840	395	33.6	9.8	2.02	.46	.58	.71	32.4	9.5	2.26	.46	.59	.72	31.2	9.1	2.52	.45	.60	.73	29.8	8.7	2.81	.46	.60	.75
	1000	470	34.8	10.2	2.03	.47	.61	.74	33.6	9.8	2.27	.47	.61	.76	32.2	9.4	2.53	.47	.62	.78	30.8	9.0	2.82	.47	.64	.80

COOLING CAPACITY - HP13-030 with

[CB30M-31]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	875	415	30.2	8.9	1.99	.76	.90	1.00	29.0	8.5	2.23	.77	.92	1.00	27.8	8.1	2.49	.79	.95	1.00	26.4	7.7	2.78	.81	.97	1.00
	1000	470	31.0	9.1	2.00	.79	.94	1.00	29.8	8.7	2.24	.80	.97	1.00	28.6	8.4	2.50	.82	.98	1.00	27.2	8.0	2.79	.84	1.00	1.00
	1115	525	31.6	9.3	2.01	.82	.97	1.00	30.6	9.0	2.24	.84	.99	1.00	29.2	8.6	2.50	.85	1.00	1.00	28.0	8.2	2.80	.88	1.00	1.00
67°F (19°C)	875	415	32.0	9.4	2.01	.60	.74	.87	30.8	9.0	2.25	.61	.75	.89	29.6	8.7	2.51	.61	.76	.91	28.0	8.2	2.80	.62	.78	.94
	1000	470	32.8	9.6	2.02	.62	.77	.91	31.6	9.3	2.26	.63	.78	.93	30.4	8.9	2.52	.63	.80	.96	28.8	8.4	2.81	.65	.82	.98
	1115	525	33.4	9.8	2.03	.63	.79	.95	32.2	9.4	2.27	.64	.81	.97	30.8	9.0	2.52	.66	.83	.99	29.4	8.6	2.81	.67	.85	1.00
71°F (22°C)	875	415	33.8	9.9	2.03	.46	.59	.71	32.4	9.5	2.27	.46	.59	.73	31.2	9.1	2.53	.45	.60	.74	29.8	8.7	2.82	.46	.61	.76
	1000	470	34.6	10.1	2.04	.46	.60	.74	33.4	9.8	2.28	.47	.61	.76	32.0	9.4	2.54	.47	.62	.77	30.6	9.0	2.83	.47	.63	.79
	1115	525	35.2	10.3	2.05	.47	.62	.77	34.0	10.0	2.28	.48	.63	.79	32.6	9.6	2.54	.48	.64	.81	31.0	9.1	2.83	.48	.66	.83

HEATING CAPACITY - HP13-030 with

[CB27UH-036]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW				
840	395	34.5	10.1	2.11	26.5	7.8	2.07	17.9	5.2	2.01	13.1	3.8	1.91	6.7	2.0	1.39
1000	470	34.7	10.2	2.02	26.6	7.8	1.98	18.0	5.3	1.93	13.3	3.9	1.83	6.8	2.0	1.31

HEATING CAPACITY - HP13-030 with

[CB30M-31]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW				
875	415	34.8	10.2	2.08	26.8	7.9	2.04	18.2	5.3	1.99	13.4	3.9	1.90	6.8	2.0	1.38
1000	470	35.0	10.3	2.02	27.0	7.9	1.98	18.4	5.4	1.93	13.7	4.0	1.84	7.0	2.1	1.32
1115	525	35.3	10.3	1.98	27.3	8.0	1.94	18.7	5.5	1.88	14.0	4.1	1.79	7.3	2.1	1.27

HEATING PERFORMANCE at 1000 cfm (470 L/s) Indoor Coil Air Volume HP13-030 with

[CB27UH-036]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C			kBtuh	kW
65	18	2.02		34.7	10.2
60	16	2.02		32.9	9.6
55	13	2.01		31.1	9.1
50	10	2.01		29.3	8.6
47	8	2.00		28.2	8.3
45	7	1.98		26.6	7.8
40	4	1.94		22.7	6.7
35	2	1.89		18.8	5.5
30	-1	1.91		18.4	5.4
25	-4	1.93		18.0	5.3
20	-7	1.96		17.6	5.2
17	-8	1.97		17.4	5.1
15	-9	1.97		16.7	4.9
10	-12	1.96		14.9	4.4
5	-15	1.83		13.3	3.9
0	-18	1.70		11.7	3.4
-5	-21	1.57		10.1	3.0
-10	-23	1.44		8.4	2.5
-15	-26	1.31		6.8	2.0
-20	-29	1.18		5.2	1.5

HEATING PERFORMANCE at 1000 cfm (470 L/s) Indoor Coil Air Volume HP13-030 with

[CB30M-31]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C			kBtuh	kW
65	18	2.02		35.0	10.3
60	16	2.02		33.2	9.7
55	13	2.01		31.4	9.2
50	10	2.01		29.6	8.7
47	8	2.00		28.6	8.4
45	7	1.98		27.0	7.9
40	4	1.92		23.1	6.8
35	2	1.87		19.1	5.6
30	-1	1.90		18.8	5.5
25	-4	1.93		18.4	5.4
20	-7	1.96		18.0	5.3
17	-8	1.98		17.8	5.2
15	-9	1.97		17.1	5.0
10	-12	1.97		15.3	4.5
5	-15	1.84		13.7	4.0
0	-18	1.71		12.0	3.5
-5	-21	1.58		10.3	3.0
-10	-23	1.45		8.7	2.5
-15	-26	1.32		7.0	2.1
-20	-29	1.19		5.3	1.6

RATINGS

2.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-030 with

[CBX32MV-036] [CBX40UHV-036]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	900	425	30.6	9.0	2.00	.77	.91	1.00	29.4	8.6	2.23	.78	.94	1.00	28.0	8.2	2.49	.80	.96	1.00	26.6	7.8	2.79	.82	.98	1.00
	1000	470	31.2	9.1	2.00	.80	.95	1.00	30.0	8.8	2.24	.81	.97	1.00	28.6	8.4	2.50	.83	.99	1.00	27.2	8.0	2.79	.85	1.00	1.00
	1125	530	32.0	9.4	2.01	.82	.98	1.00	30.8	9.0	2.25	.84	1.00	1.00	29.4	8.6	2.51	.86	1.00	1.00	28.2	8.3	2.80	.89	1.00	1.00
67°F (19°C)	900	425	32.4	9.5	2.02	.61	.74	.88	31.2	9.1	2.25	.61	.76	.90	29.8	8.7	2.51	.62	.77	.92	28.4	8.3	2.80	.63	.79	.95
	1000	470	33.0	9.7	2.02	.62	.77	.91	31.8	9.3	2.26	.63	.79	.94	30.4	8.9	2.52	.63	.80	.96	29.0	8.5	2.81	.65	.82	.98
	1125	530	33.6	9.8	2.03	.64	.80	.95	32.4	9.5	2.27	.64	.82	.97	31.0	9.1	2.53	.66	.84	.99	29.6	8.7	2.82	.67	.86	1.00
71°F (22°C)	900	425	34.2	10.0	2.03	.46	.59	.72	32.8	9.6	2.27	.46	.60	.73	31.4	9.2	2.53	.46	.61	.75	30.0	8.8	2.82	.46	.61	.76
	1000	470	34.8	10.2	2.04	.46	.61	.74	33.4	9.8	2.28	.47	.61	.76	32.2	9.4	2.54	.47	.62	.78	30.6	9.0	2.83	.47	.64	.80
	1125	530	35.6	10.4	2.05	.48	.63	.77	34.2	10.0	2.29	.47	.64	.79	32.8	9.6	2.55	.48	.65	.82	31.4	9.2	2.84	.48	.66	.84

HEATING CAPACITY - HP13-030 with

[CBX32MV-036] [CBX40UHV-036]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh
900	425	34.6	10.1	2.07	26.5	7.8	2.03	17.9	5.2	1.97	13.2	3.9	1.87	6.7	2.0	1.35				
1000	470	34.8	10.2	2.02	26.7	7.8	1.98	18.1	5.3	1.93	13.4	3.9	1.83	6.9	2.0	1.31				
1125	530	35.0	10.3	1.98	27.0	7.9	1.94	18.4	5.4	1.89	13.6	4.0	1.79	7.1	2.1	1.27				

HEATING PERFORMANCE at 1000 cfm (470 L/s) Indoor Coil Air Volume HP13-030 with [CBX32MV-036] [CBX40UHV-036]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.02	34.8	10.2
60	16	2.02	33.0	9.7
55	13	2.01	31.2	9.1
50	10	2.01	29.4	8.6
47	8	2.00	28.3	8.3
45	7	1.98	26.7	7.8
40	4	1.94	22.8	6.7
35	2	1.89	18.9	5.5
30	-1	1.91	18.5	5.4
25	-4	1.93	18.1	5.3
20	-7	1.96	17.7	5.2
17	-8	1.97	17.5	5.1
15	-9	1.97	16.8	4.9
10	-12	1.96	15.0	4.4
5	-15	1.83	13.4	3.9
0	-18	1.70	11.7	3.4
-5	-21	1.57	10.1	3.0
-10	-23	1.44	8.5	2.5
-15	-26	1.31	6.9	2.0
-20	-29	1.18	5.2	1.5

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-030 with

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	905	425	30.2	8.9	1.99	.77	.91	1.00	29.0	8.5	2.23	.78	.93	1.00	27.8	8.1	2.49	.80	.95	1.00	26.4	7.7	2.79	.81	.98	1.00
	1010	475	30.8	9.0	2.00	.79	.94	1.00	29.6	8.7	2.23	.80	.96	1.00	28.4	8.3	2.49	.82	.98	1.00	27.0	7.9	2.79	.84	1.00	1.00
	1145	540	31.6	9.3	2.01	.82	.97	1.00	30.4	8.9	2.24	.83	1.00	1.00	29.2	8.6	2.50	.86	1.00	1.00	28.0	8.2	2.80	.88	1.00	1.00
67°F (19°C)	905	425	31.6	9.3	2.01	.61	.74	.87	30.6	9.0	2.24	.61	.75	.89	29.4	8.6	2.50	.62	.77	.91	28.0	8.2	2.80	.63	.79	.94
	1010	475	32.4	9.5	2.02	.62	.76	.90	31.2	9.1	2.25	.63	.78	.93	30.0	8.8	2.51	.64	.80	.95	28.4	8.3	2.81	.65	.82	.98
	1145	540	33.0	9.7	2.02	.64	.79	.94	32.0	9.4	2.26	.65	.81	.97	30.6	9.0	2.52	.66	.83	.99	29.2	8.6	2.81	.67	.85	1.00
71°F (22°C)	905	425	33.0	9.7	2.02	.46	.59	.72	32.0	9.4	2.26	.46	.60	.73	30.8	9.0	2.52	.47	.61	.75	29.4	8.6	2.81	.47	.62	.76
	1010	475	33.8	9.9	2.03	.47	.61	.74	32.6	9.6	2.27	.47	.62	.76	31.4	9.2	2.53	.47	.63	.77	30.0	8.8	2.82	.48	.64	.79
	1145	540	34.6	10.1	2.04	.48	.62	.77	33.4	9.8	2.28	.48	.64	.79	32.2	9.4	2.54	.48	.65	.81	30.8	9.0	2.83	.49	.66	.83

HEATING CAPACITY - HP13-030 with

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)			
	cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input		
905	425	34.3	10.1	2.28	26.4	7.7	2.14	17.9	5.2	1.99	13.2	3.9	1.83	6.7	2.0	1.34
1010	475	34.5	10.1	2.21	26.6	7.8	2.07	18.1	5.3	1.92	13.3	3.9	1.76	6.9	2.0	1.27
1145	540	34.7	10.2	2.14	26.8	7.9	2.00	18.3	5.4	1.85	13.6	4.0	1.69	7.1	2.1	1.21

HEATING PERFORMANCE at 1010 cfm (475 L/s) Indoor Coil Air Volume HP13-030 with

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.21	34.5	10.1
60	16	2.18	32.7	9.6
55	13	2.15	30.9	9.1
50	10	2.12	29.2	8.6
47	8	2.10	28.1	8.2
45	7	2.07	26.6	7.8
40	4	1.99	22.7	6.7
35	2	1.91	18.8	5.5
30	-1	1.92	18.5	5.4
25	-4	1.92	18.1	5.3
20	-7	1.92	17.7	5.2
17	-8	1.92	17.4	5.1
15	-9	1.91	16.7	4.9
10	-12	1.88	15.0	4.4
5	-15	1.76	13.3	3.9
0	-18	1.63	11.7	3.4
-5	-21	1.51	10.1	3.0
-10	-23	1.39	8.5	2.5
-15	-26	1.27	6.9	2.0
-20	-29	1.15	5.2	1.5

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

[CR33-30/36B-F + G61MPV-36B-070]
[CR33-30/36B-F + G71MPP-36B-070]

COOLING CAPACITY - HP13-030 with

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity, and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-030 with

[CR33-30/36C-F + G61MPV-36C-090]
[CR33-30/36C-F + G71MPP-36C-090]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity, and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-030 with

[CR33-30/36B-F + G61MPV-36B-070]
[CR33-30/36B-F + G71MPP-36B-070]

Table with columns for Indoor Coil Air Volume, Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity, and Comp. Motor kW Input.

HEATING CAPACITY - HP13-030 with

[CR33-30/36C-F + G61MPV-36C-090]
[CR33-30/36C-F + G71MPP-36C-090]

Table with columns for Indoor Coil Air Volume, Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity, and Comp. Motor kW Input.

HEATING PERFORMANCE at 1010 cfm (475 L/s) Indoor Coil Air Volume HP13-030 with

HEATING PERFORMANCE at 1010 cfm (475 L/s) Indoor Coil Air Volume HP13-030 with

Table with columns for Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

Table with columns for Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

[CB26UH-036-R]

COOLING CAPACITY - HP13-036 with

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1050	495	34.6	10.1	2.31	.75	.88	1.00	33.4	9.8	2.58	.76	.90	1.00	32.2	9.4	2.89	.77	.92	1.00	31.0	9.1	3.24	.79	.94	1.00
67°F (19°C)	1225	580	35.6	10.4	2.33	.78	.93	1.00	34.4	10.1	2.60	.79	.94	1.00	33.2	9.7	2.90	.81	.97	1.00	32.0	9.4	3.25	.83	.99	1.00
71°F (22°C)	1350	635	36.2	10.6	2.33	.80	.96	1.00	35.0	10.3	2.60	.81	.97	1.00	33.8	9.9	2.91	.83	.99	1.00	32.6	9.6	3.26	.85	1.00	1.00

COOLING CAPACITY - HP13-036 with

[CB27UH-036]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1000	470	34.0	10.0	2.30	.76	.90	1.00	32.8	9.6	2.57	.77	.92	1.00	31.4	9.2	2.87	.78	.93	1.00	30.0	8.8	3.22	.80	.95	1.00
67°F (19°C)	1200	565	35.0	10.3	2.32	.80	.96	1.00	33.8	9.9	2.59	.81	.97	1.00	32.6	9.6	2.89	.83	.99	1.00	31.2	9.3	3.23	.85	1.00	1.00
71°F (22°C)	1350	635	36.2	10.6	2.33	.80	.96	1.00	35.0	10.3	2.60	.81	.97	1.00	33.8	9.9	2.91	.83	.99	1.00	32.6	9.6	3.26	.85	1.00	1.00

HEATING CAPACITY - HP13-036 with

[CB26UH-036-R]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil		Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	
1050	495	41.1	12.0	2.45	31.6	9.3	2.28	21.6	6.3	2.10	15.8	4.6	1.88	8.0	2.3	1.40						
1225	580	41.3	12.1	2.36	31.9	9.3	2.19	21.8	6.4	2.01	16.1	4.7	1.79	8.3	2.4	1.31						
1350	635	41.6	12.2	2.31	32.2	9.4	2.14	22.1	6.5	1.96	16.4	4.8	1.74	8.5	2.5	1.25						

HEATING CAPACITY - HP13-036 with

[CB27UH-036]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil		Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	
1000	470	40.4	11.8	2.46	31.0	9.1	2.36	21.0	6.2	2.26	15.2	4.5	2.10	7.6	2.2	1.54						
1200	565	40.8	12.0	2.34	31.4	9.2	2.25	21.4	6.3	2.15	15.7	4.6	1.98	8.1	2.4	1.43						

HEATING PERFORMANCE at 1225 cfm (580 L/s) Indoor Coil
Air Volume HP13-036 with [CB26UH-036-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.36	41.3	12.1
60	16	2.32	39.2	11.5
55	13	2.28	37.1	10.9
50	10	2.24	35.0	10.3
47	8	2.22	33.7	9.9
45	7	2.19	31.9	9.3
40	4	2.13	27.4	8.0
35	2	2.06	22.9	6.7
30	-1	2.04	22.4	6.6
25	-4	2.01	21.8	6.4
20	-7	1.99	21.3	6.2
17	-8	1.97	21.0	6.2
15	-9	1.96	20.2	5.9
10	-12	1.92	18.1	5.3
5	-15	1.79	16.1	4.7
0	-18	1.67	14.1	4.1
-5	-21	1.55	12.2	3.6
-10	-23	1.43	10.2	3.0
-15	-26	1.31	8.3	2.4
-20	-29	1.18	6.3	1.8

HEATING PERFORMANCE at 1200 cfm (565 L/s) Indoor Coil
Air Volume HP13-036 with [CB27UH-036]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.34	40.8	12.0
60	16	2.32	38.7	11.3
55	13	2.30	36.6	10.7
50	10	2.28	34.5	10.1
47	8	2.27	33.2	9.7
45	7	2.25	31.4	9.2
40	4	2.19	26.9	7.9
35	2	2.14	22.5	6.6
30	-1	2.14	21.9	6.4
25	-4	2.15	21.4	6.3
20	-7	2.15	20.9	6.1
17	-8	2.15	20.5	6.0
15	-9	2.14	19.7	5.8
10	-12	2.12	17.6	5.2
5	-15	1.98	15.7	4.6
0	-18	1.85	13.8	4.0
-5	-21	1.71	11.9	3.5
-10	-23	1.57	10.0	2.9
-15	-26	1.43	8.1	2.4
-20	-29	1.29	6.2	1.8

RATINGS

3 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-036 with

[CB27UH-042] [CBX40UHV-042]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1000	470	35.2	10.3	2.32	.75	.89	1.00	34.0	10.0	2.59	.76	.91	1.00	32.6	9.6	2.89	.78	.93	1.00	31.2	9.1	3.23	.79	.95	1.00
	1200	565	36.6	10.7	2.34	.79	.95	1.00	35.2	10.3	2.60	.81	.97	1.00	33.8	9.9	2.91	.83	.99	1.00	32.4	9.5	3.25	.84	1.00	1.00
67°F (19°C)	1000	470	37.2	10.9	2.35	.59	.73	.86	36.0	10.6	2.61	.60	.74	.88	34.6	10.1	2.92	.61	.75	.90	33.2	9.7	3.27	.62	.77	.92
	1200	565	38.5	11.3	2.37	.62	.77	.92	37.2	10.9	2.63	.63	.79	.94	35.8	10.5	2.94	.64	.80	.96	34.2	10.0	3.28	.65	.82	.98
71°F (22°C)	1000	470	39.0	11.4	2.37	.45	.58	.70	37.8	11.1	2.64	.45	.59	.72	36.4	10.7	2.95	.46	.60	.73	35.0	10.3	3.29	.46	.61	.75
	1200	565	40.5	11.9	2.39	.46	.61	.75	39.0	11.4	2.66	.47	.62	.76	37.6	11.0	2.97	.47	.63	.78	36.0	10.6	3.31	.47	.64	.80

COOLING CAPACITY - HP13-036 with

[CB30M-41]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1050	495	34.4	10.1	2.31	.77	.91	1.00	33.0	9.7	2.58	.78	.93	1.00	31.8	9.3	2.88	.79	.95	1.00	30.4	8.9	3.23	.81	.97	1.00
	1175	555	35.0	10.3	2.32	.79	.95	1.00	33.8	9.9	2.59	.81	.96	1.00	32.4	9.5	2.89	.82	.98	1.00	31.2	9.1	3.24	.84	1.00	1.00
	1350	635	36.0	10.6	2.33	.83	.99	1.00	34.8	10.2	2.60	.85	1.00	1.00	33.4	9.8	2.91	.86	1.00	1.00	32.2	9.4	3.25	.88	1.00	1.00
67°F (19°C)	1050	495	36.2	10.6	2.34	.61	.75	.88	35.0	10.3	2.60	.61	.76	.90	33.6	9.8	2.91	.62	.77	.92	32.2	9.4	3.26	.63	.78	.93
	1175	555	37.0	10.8	2.34	.62	.77	.92	35.8	10.5	2.61	.62	.78	.94	34.4	10.1	2.92	.64	.80	.96	32.8	9.6	3.26	.65	.82	.97
	1350	635	37.8	11.1	2.36	.64	.81	.96	36.6	10.7	2.63	.65	.82	.98	35.0	10.3	2.93	.66	.84	.99	33.6	9.8	3.28	.68	.86	1.00
71°F (22°C)	1050	495	38.0	11.1	2.36	.46	.59	.72	36.8	10.8	2.63	.46	.60	.73	35.4	10.4	2.94	.46	.61	.75	34.0	10.0	3.28	.47	.62	.76
	1175	555	39.0	11.4	2.37	.46	.61	.75	37.6	11.0	2.64	.47	.61	.76	36.2	10.6	2.95	.47	.63	.78	34.6	10.1	3.29	.47	.64	.80
	1350	635	40.0	11.7	2.38	.47	.63	.79	38.5	11.3	2.65	.48	.64	.80	37.0	10.8	2.96	.48	.65	.82	35.4	10.4	3.31	.49	.67	.84

HEATING CAPACITY - HP13-036 with

[CB27UH-042] [CBX40UHV-042]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input	
cfm	L/s	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	
1000	470	40.3	11.8	2.53	31.0	9.1	2.40	21.1	6.2	2.25	15.4	4.5	2.05	7.8	2.3	1.52
1200	565	40.6	11.9	2.40	31.3	9.2	2.27	21.3	6.2	2.12	15.6	4.6	1.92	8.0	2.3	1.39

HEATING CAPACITY - HP13-036 with

[CB30M-41]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input	
cfm	L/s	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	
1050	495	40.8	12.0	2.43	31.5	9.2	2.33	21.4	6.3	2.21	15.7	4.6	2.05	7.9	2.3	1.49
1175	555	41.1	12.0	2.37	31.7	9.3	2.27	21.7	6.4	2.15	16.0	4.7	1.99	8.2	2.4	1.43
1350	635	41.5	12.2	2.30	32.1	9.4	2.20	22.1	6.5	2.09	16.3	4.8	1.92	8.6	2.5	1.37

HEATING PERFORMANCE at 1200 cfm (565 L/s) Indoor Coil Air Volume HP13-036 with [CB27UH-042] [CBX40UHV-042]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.40	40.6	11.9
60	16	2.37	38.5	11.3
55	13	2.34	36.4	10.7
50	10	2.31	34.3	10.1
47	8	2.29	33.0	9.7
45	7	2.27	31.3	9.2
40	4	2.21	26.8	7.9
35	2	2.16	22.4	6.6
30	-1	2.14	21.9	6.4
25	-4	2.12	21.3	6.2
20	-7	2.11	20.8	6.1
17	-8	2.10	20.5	6.0
15	-9	2.09	19.6	5.7
10	-12	2.05	17.5	5.1
5	-15	1.92	15.6	4.6
0	-18	1.79	13.7	4.0
-5	-21	1.66	11.8	3.5
-10	-23	1.52	9.9	2.9
-15	-26	1.39	8.0	2.3
-20	-29	1.26	6.1	1.8

HEATING PERFORMANCE at 1175 cfm (555 L/s) Indoor Coil Air Volume HP13-036 with [CB30M-41]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.37	41.1	12.0
60	16	2.35	39.0	11.4
55	13	2.32	36.9	10.8
50	10	2.30	34.8	10.2
47	8	2.29	33.5	9.8
45	7	2.27	31.7	9.3
40	4	2.21	27.2	8.0
35	2	2.15	22.8	6.7
30	-1	2.15	22.2	6.5
25	-4	2.15	21.7	6.4
20	-7	2.16	21.2	6.2
17	-8	2.16	20.9	6.1
15	-9	2.15	20.0	5.9
10	-12	2.13	17.9	5.2
5	-15	1.99	16.0	4.7
0	-18	1.85	14.0	4.1
-5	-21	1.71	12.1	3.5
-10	-23	1.57	10.2	3.0
-15	-26	1.43	8.2	2.4
-20	-29	1.29	6.3	1.8

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

COOLING CAPACITY - HP13-036 with

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F).

COOLING CAPACITY - HP13-036 with

[C33-36C + G61MPV-60C-090]
[C33-36C + G71MPP-60C-090]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F).

HEATING CAPACITY - HP13-036 with

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

Table with columns: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input.

HEATING CAPACITY - HP13-036 with

[C33-36C + G61MPV-60C-090]
[C33-36C + G71MPP-60C-090]

Table with columns: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input.

HEATING PERFORMANCE at 1185 cfm (560 L/s) Indoor Coil Air Volume HP13-036 with

[C33-36C + G61MPV-36C-090]
[C33-36C + G71MPP-36C-090]

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-036 with

[C33-36C + G61MPV-60C-090]
[C33-36C + G71MPP-60C-090]

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

[C33-36C + G61MPV-60C-110]
[C33-36C + G71MPP-60C-110]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F).

COOLING CAPACITY - HP13-036 with

[C33-42B + G60UHV-36B-090]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F).

HEATING CAPACITY - HP13-036 with

[C33-36C + G61MPV-60C-110]
[C33-36C + G71MPP-60C-110]

Table with columns: Indoor Coil Air Volume (70°F db, 21°C db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input.

HEATING CAPACITY - HP13-036 with

[C33-42B + G60UHV-36B-090]

Table with columns: Indoor Coil Air Volume (70°F db, 21°C db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input.

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-036 with

[C33-36C + G61MPV-60C-110]
[C33-36C + G71MPP-60C-110]

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1225 cfm (580 L/s) Indoor Coil Air Volume HP13-036 with

[C33-42B + G60UHV-36B-090]

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

RATINGS

3 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

[CR33-30/36C-F + G61MPV-60C-090]
[CR33-30/36C-F + G71MPP-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1275	600	35.6	10.4	2.32	.80	.96	1.00	34.4	10.1	2.59	.82	.97	1.00	33.0	9.7	2.90	.83	.99	1.00	31.6	9.3	3.24	.85	1.00	1.00
	1380	650	36.0	10.6	2.33	.82	.98	1.00	34.8	10.2	2.60	.84	.99	1.00	33.4	9.8	2.91	.86	1.00	1.00	32.0	9.4	3.25	.87	1.00	1.00
67°F (19°C)	1275	600	37.2	10.9	2.35	.63	.78	.93	36.0	10.6	2.62	.64	.80	.94	34.6	10.1	2.92	.65	.81	.96	33.2	9.7	3.27	.66	.83	.98
	1380	650	37.8	11.1	2.35	.64	.80	.95	36.4	10.7	2.62	.65	.82	.97	35.0	10.3	2.93	.66	.83	.99	33.6	9.8	3.28	.67	.85	1.00
71°F (22°C)	1275	600	39.0	11.4	2.37	.47	.62	.76	37.8	11.1	2.65	.47	.63	.77	36.4	10.7	2.95	.47	.63	.79	35.0	10.3	3.30	.48	.65	.81
	1380	650	39.5	11.6	2.38	.47	.63	.78	38.5	11.3	2.65	.48	.64	.80	36.8	10.8	2.96	.48	.65	.81	35.4	10.4	3.30	.49	.66	.83

COOLING CAPACITY - HP13-036 with

[CR33-30/36C-F + G61MPV-60C-110]
[CR33-30/36C-F + G71MPP-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1290	610	35.6	10.4	2.33	.81	.96	1.00	34.4	10.1	2.60	.82	.98	1.00	33.0	9.7	2.90	.84	.99	1.00	31.6	9.3	3.25	.86	1.00	1.00
	1405	665	36.2	10.6	2.33	.83	.98	1.00	35.0	10.3	2.60	.84	.99	1.00	33.6	9.8	2.91	.86	1.00	1.00	32.2	9.4	3.26	.88	1.00	1.00
67°F (19°C)	1290	610	37.4	11.0	2.35	.63	.79	.93	36.0	10.6	2.62	.64	.80	.95	34.6	10.1	2.93	.65	.82	.97	33.2	9.7	3.27	.66	.83	.99
	1405	665	37.8	11.1	2.35	.64	.81	.96	36.4	10.7	2.62	.65	.82	.97	35.2	10.3	2.93	.66	.84	.99	33.6	9.8	3.28	.67	.86	1.00
71°F (22°C)	1290	610	39.0	11.4	2.38	.47	.62	.76	37.8	11.1	2.65	.47	.63	.78	36.4	10.7	2.95	.48	.64	.79	35.0	10.3	3.30	.48	.65	.81
	1405	665	39.5	11.6	2.38	.48	.63	.79	38.5	11.3	2.65	.48	.64	.80	37.0	10.8	2.96	.48	.65	.82	35.4	10.4	3.30	.49	.67	.84

HEATING CAPACITY - HP13-036 with

[CR33-30/36C-F + G61MPV-60C-090]
[CR33-30/36C-F + G71MPP-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW		
1275	600	41.1	12.0	2.33	31.7	9.3	2.17	21.7	6.4	1.99	15.9	4.7	1.78	8.2	2.4	1.29	
1380	650	41.3	12.1	2.30	31.9	9.3	2.13	21.9	6.4	1.95	16.1	4.7	1.74	8.4	2.5	1.25	

HEATING CAPACITY - HP13-036 with

[CR33-30/36C-F + G61MPV-60C-110]
[CR33-30/36C-F + G71MPP-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW		
1290	610	41.1	12.0	2.32	31.7	9.3	2.16	21.7	6.4	1.99	15.9	4.7	1.77	8.2	2.4	1.29	
1405	665	41.3	12.1	2.29	31.9	9.3	2.12	21.9	6.4	1.95	16.1	4.7	1.74	8.4	2.5	1.25	

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-036 with

[CR33-30/36C-F + G61MPV-60C-090]
[CR33-30/36C-F + G71MPP-60C-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.33	41.1	12.0
60	16	2.29	39.0	11.4
55	13	2.25	36.9	10.8
50	10	2.21	34.8	10.2
47	8	2.19	33.5	9.8
45	7	2.17	31.7	9.3
40	4	2.10	27.2	8.0
35	2	2.04	22.7	6.7
30	-1	2.02	22.2	6.5
25	-4	1.99	21.7	6.4
20	-7	1.97	21.1	6.2
17	-8	1.95	20.8	6.1
15	-9	1.94	20.0	5.9
10	-12	1.90	17.9	5.2
5	-15	1.78	15.9	4.7
0	-18	1.65	14.0	4.1
-5	-21	1.53	12.1	3.5
-10	-23	1.41	10.1	3.0
-15	-26	1.29	8.2	2.4
-20	-29	1.17	6.2	1.8

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-036 with

[CR33-30/36C-F + G61MPV-60C-110]
[CR33-30/36C-F + G71MPP-60C-110]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.32	41.1	12.0
60	16	2.29	39.0	11.4
55	13	2.25	36.9	10.8
50	10	2.21	34.8	10.2
47	8	2.18	33.5	9.8
45	7	2.16	31.7	9.3
40	4	2.10	27.2	8.0
35	2	2.03	22.7	6.7
30	-1	2.01	22.2	6.5
25	-4	1.99	21.7	6.4
20	-7	1.96	21.1	6.2
17	-8	1.95	20.8	6.1
15	-9	1.93	20.0	5.9
10	-12	1.89	17.8	5.2
5	-15	1.77	15.9	4.7
0	-18	1.65	14.0	4.1
-5	-21	1.53	12.0	3.5
-10	-23	1.41	10.1	3.0
-15	-26	1.29	8.2	2.4
-20	-29	1.17	6.2	1.8

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

[CR33-48B-F + G60DFV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1040	490	34.0	10.0	2.30	.74	.87	.99	32.8	9.6	2.58	.75	.89	1.00	31.8	9.3	2.88	.77	.91	1.00	30.4	8.9	3.23	.78	.93	1.00
	1195	565	34.8	10.2	2.31	.77	.91	1.00	33.8	9.9	2.59	.78	.93	1.00	32.6	9.6	2.89	.79	.95	1.00	31.2	9.1	3.24	.81	.97	1.00
	1330	630	35.4	10.4	2.32	.79	.94	1.00	34.4	10.1	2.60	.80	.96	1.00	33.2	9.7	2.90	.82	.98	1.00	31.8	9.3	3.25	.84	1.00	1.00
67°F (19°C)	1040	490	35.8	10.5	2.33	.59	.72	.84	34.8	10.2	2.60	.60	.73	.86	33.6	9.8	2.91	.61	.74	.88	32.2	9.4	3.26	.62	.76	.90
	1195	565	36.8	10.8	2.34	.61	.74	.88	35.6	10.4	2.61	.62	.76	.89	34.4	10.1	2.92	.62	.77	.92	33.0	9.7	3.27	.63	.79	.94
	1330	630	37.4	11.0	2.35	.62	.76	.91	36.2	10.6	2.62	.63	.78	.93	35.0	10.3	2.93	.64	.80	.95	33.6	9.8	3.28	.65	.81	.98
71°F (22°C)	1040	490	37.8	11.1	2.36	.45	.58	.70	36.6	10.7	2.63	.45	.59	.71	35.4	10.4	2.94	.45	.59	.72	34.0	10.0	3.28	.46	.60	.73
	1195	565	38.5	11.3	2.37	.46	.59	.72	37.4	11.0	2.64	.46	.60	.73	36.2	10.6	2.95	.46	.61	.75	34.8	10.2	3.29	.47	.62	.77
	1330	630	39.5	11.6	2.38	.47	.61	.74	38.0	11.1	2.65	.47	.62	.76	36.8	10.8	2.96	.48	.63	.77	35.4	10.4	3.30	.48	.64	.79

HEATING CAPACITY - HP13-036 with

[CR33-48B-F + G60DFV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)	cfm L/s		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW					
1040	490	40.4	11.8	2.55	31.1	9.1	2.37	21.2	6.2	2.17	15.5	4.5	1.94	7.8	2.3	1.44	
1195	565	40.7	11.9	2.47	31.4	9.2	2.28	21.5	6.3	2.09	15.8	4.6	1.86	8.1	2.4	1.35	
1330	630	41.1	12.0	2.41	31.8	9.3	2.22	21.8	6.4	2.02	16.2	4.7	1.79	8.5	2.5	1.29	

HEATING PERFORMANCE at 1195 cfm (565 L/s) Indoor Coil Air Volume HP13-036 with [CR33-48B-F + G60DFV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.47	40.7	11.9
60	16	2.42	38.7	11.3
55	13	2.38	36.6	10.7
50	10	2.34	34.5	10.1
47	8	2.31	33.2	9.7
45	7	2.28	31.4	9.2
40	4	2.21	27.0	7.9
35	2	2.14	22.5	6.6
30	-1	2.11	22.0	6.4
25	-4	2.09	21.5	6.3
20	-7	2.06	21.0	6.2
17	-8	2.04	20.7	6.1
15	-9	2.03	19.8	5.8
10	-12	1.98	17.7	5.2
5	-15	1.86	15.8	4.6
0	-18	1.73	13.9	4.1
-5	-21	1.61	12.0	3.5
-10	-23	1.48	10.0	2.9
-15	-26	1.35	8.1	2.4
-20	-29	1.23	6.2	1.8

RATINGS

3 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

[CH23-41 + G60UHV-36B-090]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F) with sub-columns for Cooling Capacity and S/T Ratio.

COOLING CAPACITY - HP13-036 with

[CH23-41 + G61MPV-36C-090]

[CH23-41 + G71MPP-36C-090]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F) with sub-columns for Cooling Capacity and S/T Ratio.

HEATING CAPACITY - HP13-036 with

[CH23-41 + G60UHV-36B-090]

Table with columns for Indoor Coil Air Volume (70°F db) and Air Temperature (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Heating Capacity and Comp. Motor kW Input.

HEATING CAPACITY - HP13-036 with

[CH23-41 + G61MPV-36C-090]

[CH23-41 + G71MPP-36C-090]

Table with columns for Indoor Coil Air Volume (70°F db) and Air Temperature (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Heating Capacity and Comp. Motor kW Input.

HEATING PERFORMANCE at 1225 cfm (580 L/s) Indoor Coil Air Volume HP13-036 with

[CH23-41 + G60UHV-36B-090]

Table with columns for Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1185 cfm (560 L/s) Indoor Coil Air Volume HP13-036 with

[CH23-41 + G61MPV-36C-090]

[CH23-41 + G71MPP-36C-090]

Table with columns for Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

**[CH23-41 + G61MPV-60C-110]
[CH23-41 + G71MPP-60C-110]**

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1290	610	34.6	10.1	2.31	.78	.93	1.00	33.6	9.8	2.58	.79	.95	1.00	32.4	9.5	2.89	.81	.97	1.00	31.2	9.1	3.24	.83	.99	1.00
	1405	665	35.2	10.3	2.32	.80	.96	1.00	34.2	10.0	2.59	.81	.97	1.00	33.0	9.7	2.90	.83	.99	1.00	32.0	9.4	3.25	.85	1.00	1.00
67°F (19°C)	1290	610	36.6	10.7	2.34	.62	.76	.90	35.4	10.4	2.61	.63	.77	.92	34.2	10.0	2.92	.63	.79	.94	32.8	9.6	3.27	.65	.81	.96
	1405	665	37.2	10.9	2.35	.63	.78	.93	36.0	10.6	2.62	.64	.79	.95	34.6	10.1	2.92	.65	.81	.97	33.2	9.7	3.27	.66	.83	.99
71°F (22°C)	1290	610	39.0	11.4	2.37	.46	.61	.74	37.6	11.0	2.64	.46	.61	.75	36.4	10.7	2.95	.47	.62	.77	35.0	10.3	3.30	.47	.64	.79
	1405	665	39.5	11.6	2.38	.47	.62	.76	38.0	11.1	2.65	.47	.63	.77	36.8	10.8	2.96	.47	.63	.79	35.4	10.4	3.31	.48	.65	.81

COOLING CAPACITY - HP13-036 with

**[CH33-36C-2F + G61MPV-36C-090]
[CH33-36C-2F + G71MPV-36C-090]**

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1060	500	34.4	10.1	2.31	.77	.91	1.00	33.2	9.7	2.58	.78	.92	1.00	31.8	9.3	2.88	.79	.94	1.00	30.4	8.9	3.23	.81	.97	1.00
	1185	560	35.0	10.3	2.32	.79	.94	1.00	33.8	9.9	2.59	.80	.96	1.00	32.4	9.5	2.89	.82	.98	1.00	31.2	9.1	3.24	.83	1.00	1.00
	1395	660	36.2	10.6	2.33	.83	.99	1.00	35.0	10.3	2.60	.84	1.00	1.00	33.6	9.8	2.91	.86	1.00	1.00	32.4	9.5	3.26	.88	1.00	1.00
67°F (19°C)	1060	500	36.0	10.6	2.33	.61	.74	.88	34.8	10.2	2.60	.61	.76	.89	33.4	9.8	2.91	.62	.77	.91	32.2	9.4	3.25	.63	.78	.93
	1185	560	36.8	10.8	2.34	.62	.77	.91	35.6	10.4	2.61	.63	.78	.93	34.2	10.0	2.92	.64	.80	.95	32.8	9.6	3.27	.65	.81	.97
	1395	660	37.8	11.1	2.36	.65	.81	.97	36.4	10.7	2.63	.65	.82	.98	35.2	10.3	2.93	.66	.84	1.00	33.6	9.8	3.28	.68	.86	1.00
71°F (22°C)	1060	500	37.4	11.0	2.35	.46	.59	.72	36.2	10.6	2.62	.46	.60	.73	35.0	10.3	2.93	.47	.61	.75	33.6	9.8	3.28	.47	.62	.76
	1185	560	38.5	11.3	2.37	.47	.61	.75	37.0	10.8	2.64	.47	.62	.76	35.6	10.4	2.94	.47	.63	.77	34.2	10.0	3.29	.47	.64	.79
	1395	660	39.5	11.6	2.38	.48	.64	.79	38.0	11.1	2.65	.48	.64	.80	36.8	10.8	2.96	.49	.66	.82	35.4	10.4	3.30	.49	.67	.84

HEATING CAPACITY - HP13-036 with

**[CH23-41 + G61MPV-60C-110]
[CH23-41 + G71MPP-60C-110]**

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)			
	cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW
1290	610	40.9	12.0	2.44	31.6	9.3	2.25	21.6	6.3	2.07	15.9	4.7	1.84	8.2	2.4	1.34
1405	665	41.2	12.1	2.40	31.9	9.3	2.21	21.9	6.4	2.03	16.2	4.7	1.80	8.5	2.5	1.30

HEATING CAPACITY - HP13-036 with

**[CH33-36C-2F + G61MPV-36C-090]
[CH33-36C-2F + G71MPV-36C-090]**

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)			
	cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW
1060	500	40.5	11.9	2.57	31.1	9.1	2.41	21.2	6.2	2.25	15.5	4.5	2.05	7.8	2.3	1.50
1185	560	40.7	11.9	2.50	31.4	9.2	2.34	21.5	6.3	2.18	15.8	4.6	1.98	8.1	2.4	1.43
1395	660	41.3	12.1	2.40	31.9	9.3	2.24	22.0	6.4	2.08	16.3	4.8	1.88	8.6	2.5	1.33

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-036 with

**[CH23-41 + G61MPV-60C-110]
[CH23-41 + G71MPP-60C-110]**

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.44	40.9	12.0
60	16	2.39	38.8	11.4
55	13	2.35	36.7	10.8
50	10	2.31	34.6	10.1
47	8	2.28	33.4	9.8
45	7	2.25	31.6	9.3
40	4	2.19	27.1	7.9
35	2	2.12	22.6	6.6
30	-1	2.09	22.1	6.5
25	-4	2.07	21.6	6.3
20	-7	2.04	21.1	6.2
17	-8	2.02	20.8	6.1
15	-9	2.01	19.9	5.8
10	-12	1.96	17.9	5.2
5	-15	1.84	15.9	4.7
0	-18	1.71	14.0	4.1
-5	-21	1.59	12.0	3.5
-10	-23	1.46	10.1	3.0
-15	-26	1.34	8.2	2.4
-20	-29	1.21	6.2	1.8

HEATING PERFORMANCE at 1185 cfm (560 L/s) Indoor Coil Air Volume HP13-036 with

**[CH33-36C + G61MPV-36C-090]
[CH33-36C-2F + G71MPV-36C-090]**

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.50	40.7	11.9
60	16	2.46	38.6	11.3
55	13	2.43	36.5	10.7
50	10	2.39	34.5	10.1
47	8	2.37	33.2	9.7
45	7	2.34	31.4	9.2
40	4	2.28	27.0	7.9
35	2	2.21	22.5	6.6
30	-1	2.20	22.0	6.4
25	-4	2.18	21.5	6.3
20	-7	2.17	21.0	6.2
17	-8	2.16	20.7	6.1
15	-9	2.15	19.8	5.8
10	-12	2.11	17.7	5.2
5	-15	1.98	15.8	4.6
0	-18	1.84	13.9	4.1
-5	-21	1.71	12.0	3.5
-10	-23	1.57	10.0	2.9
-15	-26	1.43	8.1	2.4
-20	-29	1.30	6.2	1.8

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-036 with

[CH33-36C-2F + G61MPV-60C-090]
[CH33-36C-2F + G71MPP-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb				
				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C		
63°F (17°C)	1275	600	35.6	10.4	2.32	.81	.97	1.00	34.4	10.1	2.60	.82	.98	1.00	33.0	9.7	2.90	.84	1.00	1.00	31.8	9.3	3.25	.85	1.00	1.00
	1380	650	36.0	10.6	2.33	.83	.99	1.00	34.8	10.2	2.60	.84	1.00	1.00	33.6	9.8	2.91	.86	1.00	1.00	32.4	9.5	3.26	.88	1.00	1.00
67°F (19°C)	1275	600	37.2	10.9	2.35	.63	.78	.94	36.0	10.6	2.62	.64	.80	.95	34.6	10.1	2.93	.65	.81	.97	33.2	9.7	3.27	.66	.83	.99
	1380	650	37.8	11.1	2.36	.64	.81	.96	36.4	10.7	2.63	.65	.82	.98	35.2	10.3	2.93	.66	.84	.99	33.6	9.8	3.28	.68	.86	1.00
71°F (22°C)	1275	600	39.0	11.4	2.37	.47	.62	.76	37.6	11.0	2.64	.48	.63	.78	36.2	10.6	2.95	.48	.64	.79	34.8	10.2	3.29	.48	.65	.81
	1380	650	39.5	11.6	2.38	.48	.63	.78	38.0	11.1	2.65	.48	.64	.80	36.8	10.8	2.96	.49	.65	.82	35.2	10.3	3.30	.49	.67	.84

COOLING CAPACITY - HP13-036 with

[CH33-36C-2F + G61MPV-60C-110]
[CH33-36C-2F + G71MPP-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb				
				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C		
63°F (17°C)	1290	610	35.6	10.4	2.32	.81	.97	1.00	34.4	10.1	2.60	.82	.98	1.00	33.0	9.7	2.90	.84	1.00	1.00	31.8	9.3	3.25	.86	1.00	1.00
	1405	665	36.2	10.6	2.33	.83	.99	1.00	35.0	10.3	2.60	.85	1.00	1.00	33.8	9.9	2.91	.86	1.00	1.00	32.4	9.5	3.26	.88	1.00	1.00
67°F (19°C)	1290	610	37.4	11.0	2.35	.63	.79	.94	36.0	10.6	2.62	.64	.80	.96	34.8	10.2	2.93	.65	.82	.98	33.2	9.7	3.27	.66	.84	1.00
	1405	665	38.0	11.1	2.36	.65	.81	.97	36.6	10.7	2.63	.65	.82	.98	35.2	10.3	2.93	.66	.84	1.00	33.6	9.8	3.28	.68	.86	1.00
71°F (22°C)	1290	610	39.0	11.4	2.37	.47	.62	.77	37.8	11.1	2.64	.48	.63	.78	36.4	10.7	2.95	.48	.64	.80	34.8	10.2	3.30	.48	.65	.82
	1405	665	39.5	11.6	2.38	.48	.64	.79	38.5	11.3	2.65	.48	.65	.80	36.8	10.8	2.96	.49	.66	.82	35.4	10.4	3.30	.49	.67	.84

HEATING CAPACITY - HP13-036 with

[CH33-36C-2F + G61MPV-60C-090]
[CH33-36C-2F + G71MPP-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input			
1275	600	40.9	12.0	2.44	31.5	9.2	2.30	21.6	6.3	2.15	15.9	4.7	1.96	8.1	2.4	1.42				
	1380	650	41.1	12.0	2.39	31.8	9.3	2.25	21.8	6.4	2.10	16.1	4.7	1.91	8.4	2.5	1.37			

HEATING CAPACITY - HP13-036 with

[CH33-36C-2F + G61MPV-60C-110]
[CH33-36C-2F + G71MPP-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input			
1290	610	40.9	12.0	2.43	31.5	9.2	2.29	21.6	6.3	2.15	15.8	4.6	1.95	8.1	2.4	1.41				
	1405	665	41.1	12.0	2.38	31.8	9.3	2.24	21.8	6.4	2.10	16.1	4.7	1.90	8.4	2.5	1.36			

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-036 with [CH33-36C-2F + G61MPV-60C-090]
[CH33-36C-2F + G71MPP-60C-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.50	40.7	11.9
60	16	2.46	38.6	11.3
55	13	2.43	36.5	10.7
50	10	2.39	34.5	10.1
47	8	2.37	33.2	9.7
45	7	2.34	31.4	9.2
40	4	2.28	27.0	7.9
35	2	2.21	22.5	6.6
30	-1	2.20	22.0	6.4
25	-4	2.18	21.5	6.3
20	-7	2.17	21.0	6.2
17	-8	2.16	20.7	6.1
15	-9	2.15	19.8	5.8
10	-12	2.11	17.7	5.2
5	-15	1.98	15.8	4.6
0	-18	1.84	13.9	4.1
-5	-21	1.71	12.0	3.5
-10	-23	1.57	10.0	2.9
-15	-26	1.43	8.1	2.4
-20	-29	1.30	6.2	1.8

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-036 with [CH33-36C-2F + G61MPV-60C-110]
[CH33-36C-2F + G71MPP-60C-110]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.43	40.9	12.0
60	16	2.40	38.8	11.4
55	13	2.37	36.7	10.8
50	10	2.34	34.6	10.1
47	8	2.32	33.3	9.8
45	7	2.29	31.5	9.2
40	4	2.23	27.1	7.9
35	2	2.17	22.6	6.6
30	-1	2.16	22.1	6.5
25	-4	2.15	21.6	6.3
20	-7	2.14	21.0	6.2
17	-8	2.13	20.7	6.1
15	-9	2.12	19.9	5.8
10	-12	2.09	17.8	5.2
5	-15	1.95	15.8	4.6
0	-18	1.82	13.9	4.1
-5	-21	1.68	12.0	3.5
-10	-23	1.55	10.1	3.0
-15	-26	1.41	8.1	2.4
-20	-29	1.28	6.2	1.8

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

[CB26UH-042-R]

COOLING CAPACITY - HP13-042 with

Table with 3 columns: Entering Wet Bulb Temperature (63°F, 67°F, 71°F), Total Air Volume (1325, 1500, 1675 cfm), and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F). Each cell contains Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-042 with

[CB30M-46]

Table with 3 columns: Entering Wet Bulb Temperature (63°F, 67°F, 71°F), Total Air Volume (1270, 1400, 1555 cfm), and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F). Each cell contains Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-042 with

[CB26UH-042-R]

Table with 4 columns: Indoor Coil Air Volume (1325, 1500, 1675), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F). Each cell contains Total Heating Capacity, Comp. Motor kW Input, and kW.

HEATING CAPACITY - HP13-042 with

[CB30M-46]

Table with 4 columns: Indoor Coil Air Volume (1270, 1400, 1555), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F). Each cell contains Total Heating Capacity, Comp. Motor kW Input, and kW.

HEATING PERFORMANCE at 1500 cfm (710 L/s) Indoor Coil Air Volume HP13-042 with [CB26UH-042-R]

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1400 cfm (660 L/s) Indoor Coil Air Volume HP13-042 with [CB30M-46]

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-042 with

[CBX32MV-048] [CBX40UHV-048]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1205	570	39.0	11.4	2.34	.77	.92	1.00	37.4	11.0	2.63	.78	.93	1.00	36.0	10.6	2.96	.79	.95	1.00	34.4	10.1	3.34	.81	.97	1.00
	1375	650	39.5	11.6	2.35	.80	.96	1.00	38.5	11.3	2.64	.81	.97	1.00	36.8	10.8	2.97	.83	.99	1.00	35.2	10.3	3.35	.85	1.00	1.00
	1555	735	40.5	11.9	2.36	.83	.99	1.00	39.0	11.4	2.65	.85	1.00	1.00	37.8	11.1	2.98	.87	1.00	1.00	36.4	10.7	3.35	.89	1.00	1.00
67°F (19°C)	1205	570	41.0	12.0	2.36	.61	.75	.88	39.5	11.6	2.65	.61	.76	.90	38.0	11.1	2.98	.62	.77	.92	36.4	10.7	3.35	.63	.79	.94
	1375	650	42.0	12.3	2.37	.63	.78	.93	40.5	11.9	2.66	.63	.79	.94	39.0	11.4	2.98	.64	.81	.96	37.2	10.9	3.36	.65	.82	.98
	1555	735	43.0	12.6	2.38	.64	.81	.96	41.5	12.2	2.66	.65	.83	.98	39.5	11.6	2.99	.66	.84	.99	38.0	11.1	3.36	.67	.87	1.00
71°F (22°C)	1205	570	43.0	12.6	2.39	.46	.59	.72	42.0	12.3	2.67	.46	.60	.74	40.0	11.7	2.99	.46	.61	.75	38.5	11.3	3.36	.46	.62	.76
	1375	650	44.5	13.0	2.40	.47	.61	.76	42.5	12.5	2.68	.47	.62	.77	41.0	12.0	3.00	.47	.63	.78	39.5	11.6	3.37	.47	.64	.80
	1555	735	45.0	13.2	2.41	.48	.64	.79	43.5	12.7	2.69	.48	.64	.80	42.0	12.3	3.01	.48	.65	.82	40.0	11.7	3.38	.49	.67	.84

HEATING CAPACITY - HP13-042 with

[CBX32MV-048] [CBX40UHV-048]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)				45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
	cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW
1205	570	44.8	13.1	3.06	34.8	10.2	2.79	24.4	7.2	2.51	17.2	5.0	2.21	8.7	2.5	1.64
1375	650	45.1	13.2	2.97	35.2	10.3	2.70	24.8	7.3	2.42	17.6	5.2	2.12	9.0	2.6	1.56
1555	735	45.6	13.4	2.90	35.6	10.4	2.63	25.2	7.4	2.35	18.0	5.3	2.06	9.4	2.8	1.49

HEATING PERFORMANCE at 1375 cfm (650 L/s) Indoor Coil

Air Volume HP13-042 with [CBX32MV-048] [CBX40UHV-048]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.97	45.1	13.2
60	16	2.91	42.8	12.5
55	13	2.84	40.5	11.9
50	10	2.78	38.2	11.2
47	8	2.74	36.8	10.8
45	7	2.70	35.2	10.3
40	4	2.60	31.1	9.1
35	2	2.50	27.1	7.9
30	-1	2.46	25.9	7.6
25	-4	2.42	24.8	7.3
20	-7	2.38	23.6	6.9
17	-8	2.36	22.9	6.7
15	-9	2.33	22.0	6.4
10	-12	2.27	19.7	5.8
5	-15	2.12	17.6	5.2
0	-18	1.98	15.4	4.5
-5	-21	1.84	13.3	3.9
-10	-23	1.70	11.2	3.3
-15	-26	1.56	9.0	2.6
-20	-29	1.41	6.9	2.0

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-38B + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)			95°F (35°C)			105°F (41°C)			115°F (46°C)														
			Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb												
63°F (17°C)	1110	525	39.0	11.4	2.38	.74	.88	1.00	37.8	11.1	2.67	.75	.89	1.00	36.4	10.7	3.00	.76	.91	1.00	34.8	10.2	3.38	.78	.93	1.00
67°F (19°C)	1290	610	40.5	11.9	2.39	.77	.92	1.00	39.0	11.4	2.68	.78	.94	1.00	37.4	11.0	3.01	.80	.96	1.00	35.8	10.5	3.39	.82	.98	1.00
71°F (22°C)	1385	655	41.0	12.0	2.40	.79	.94	1.00	39.5	11.6	2.69	.80	.96	1.00	38.0	11.1	3.02	.82	.98	1.00	36.4	10.7	3.40	.84	1.00	1.00

COOLING CAPACITY - HP13-042 with

[C33-38B + G61MPV-36B-045]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)			95°F (35°C)			105°F (41°C)			115°F (46°C)														
			Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity	Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb												
63°F (17°C)	1150	545	39.5	11.6	2.38	.75	.89	1.00	38.0	11.1	2.67	.76	.90	1.00	36.6	10.7	3.01	.77	.92	1.00	35.0	10.3	3.39	.79	.94	1.00
67°F (19°C)	1330	630	40.5	11.9	2.40	.78	.93	1.00	39.0	11.4	2.68	.79	.95	1.00	37.6	11.0	3.01	.81	.97	1.00	36.2	10.6	3.39	.83	.99	1.00
71°F (22°C)	1330	630	40.5	11.9	2.40	.78	.93	1.00	39.0	11.4	2.68	.79	.95	1.00	37.6	11.0	3.01	.81	.97	1.00	36.2	10.6	3.39	.83	.99	1.00

HEATING CAPACITY - HP13-042 with

[C33-38B + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil											
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)			
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input		
1110	525	44.0	12.9	34.7	10.2	24.8	7.3	18.1	5.3	9.0	2.6		
1290	610	44.5	13.0	35.1	10.3	25.3	7.4	18.6	5.5	9.4	2.8		
1385	655	44.7	13.1	35.4	10.4	25.5	7.5	18.8	5.5	9.7	2.8		

HEATING CAPACITY - HP13-042 with

[C33-38B + G61MPV-36B-045]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil									
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)	
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input
1150	540	44.2	13.0	34.8	10.2	25.0	7.3	18.2	5.3	8.9	2.6
1330	630	45.0	13.2	35.6	10.4	25.8	7.6	19.0	5.6	9.7	2.8

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-042 with

[C33-38B + G60UHV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.94	44.5	13.0
60	16	2.88	42.3	12.4
55	13	2.81	40.2	11.8
50	10	2.75	38.0	11.1
47	8	2.71	36.8	10.8
45	7	2.68	35.1	10.3
40	4	2.58	31.1	9.1
35	2	2.48	27.1	7.9
30	-1	2.44	26.2	7.7
25	-4	2.40	25.3	7.4
20	-7	2.36	24.4	7.2
17	-8	2.34	23.9	7.0
15	-9	2.31	23.0	6.7
10	-12	2.25	20.9	6.1
5	-15	2.11	18.6	5.5
0	-18	1.97	16.3	4.8
-5	-21	1.83	14.0	4.1
-10	-23	1.69	11.7	3.4
-15	-26	1.54	9.4	2.8
-20	-29	1.40	7.2	2.1

HEATING PERFORMANCE at 1330 cfm (630 L/s) Indoor Coil Air Volume HP13-042 with

[C33-38B + G61MPV-36B-045]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.91	45.0	13.2
60	16	2.85	42.8	12.5
55	13	2.79	40.7	11.9
50	10	2.73	38.5	11.3
47	8	2.69	37.2	10.9
45	7	2.65	35.6	10.4
40	4	2.56	31.6	9.3
35	2	2.47	27.5	8.1
30	-1	2.43	26.6	7.8
25	-4	2.39	25.8	7.6
20	-7	2.35	24.9	7.3
17	-8	2.33	24.4	7.2
15	-9	2.30	23.5	6.9
10	-12	2.24	21.4	6.3
5	-15	2.10	19.0	5.6
0	-18	1.96	16.7	4.9
-5	-21	1.82	14.3	4.2
-10	-23	1.68	12.0	3.5
-15	-26	1.54	9.7	2.8
-20	-29	1.40	7.3	2.1

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-43B + G61MPV-36B-045]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1150	545	39.5	11.6	2.38	.74	.88	1.00	38.5	11.3	2.67	.75	.89	1.00	36.8	10.8	3.00	.77	.91	1.00	35.2	10.3	3.38	.78	.93	1.00
	1330	630	41.0	12.0	2.40	.77	.92	1.00	39.5	11.6	2.68	.78	.94	1.00	38.0	11.1	3.01	.80	.96	1.00	36.2	10.6	3.39	.82	.98	1.00
67°F (19°C)	1150	545	42.0	12.3	2.41	.59	.72	.84	40.5	11.9	2.69	.60	.73	.86	38.5	11.3	3.02	.60	.74	.88	37.2	10.9	3.40	.61	.76	.90
	1330	630	43.0	12.6	2.42	.61	.75	.89	41.5	12.2	2.70	.61	.76	.90	40.0	11.7	3.03	.63	.78	.93	38.0	11.1	3.40	.64	.79	.95
71°F (22°C)	1150	545	44.0	12.9	2.43	.45	.58	.70	42.5	12.5	2.71	.46	.58	.71	41.0	12.0	3.04	.46	.59	.72	39.5	11.6	3.41	.46	.60	.73
	1330	630	45.5	13.3	2.45	.46	.59	.73	44.0	12.9	2.73	.46	.60	.74	42.0	12.3	3.05	.47	.61	.75	40.5	11.9	3.42	.47	.62	.77

COOLING CAPACITY - HP13-042 with

[C33-43B + G61MPV-36B-070]

[C33-43B + G71MPP-36B-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1105	520	39.5	11.6	2.38	.74	.87	.99	38.0	11.1	2.67	.75	.88	1.00	36.6	10.7	3.01	.76	.90	1.00	35.0	10.3	3.39	.77	.92	1.00
	1280	605	40.5	11.9	2.40	.76	.91	1.00	39.5	11.6	2.68	.78	.92	1.00	37.8	11.1	3.01	.79	.95	1.00	36.2	10.6	3.39	.81	.97	1.00
	1395	660	41.5	12.2	2.40	.78	.93	1.00	40.0	11.7	2.69	.79	.95	1.00	38.5	11.3	3.02	.81	.97	1.00	36.8	10.8	3.40	.83	.99	1.00
67°F (19°C)	1105	520	41.5	12.2	2.40	.59	.71	.83	40.0	11.7	2.69	.59	.72	.85	38.5	11.3	3.02	.60	.73	.86	36.8	10.8	3.40	.61	.75	.88
	1280	605	43.0	12.6	2.42	.60	.74	.87	41.5	12.2	2.70	.61	.75	.89	39.5	11.6	3.03	.62	.77	.91	38.0	11.1	3.41	.63	.78	.93
	1395	660	43.5	12.7	2.43	.61	.76	.90	42.0	12.3	2.71	.62	.77	.92	40.5	11.9	3.04	.63	.79	.94	39.0	11.4	3.41	.64	.80	.96
71°F (22°C)	1105	520	44.0	12.9	2.43	.45	.57	.69	42.5	12.5	2.71	.45	.58	.70	41.0	12.0	3.04	.46	.58	.71	39.0	11.4	3.42	.46	.59	.73
	1280	605	45.0	13.2	2.45	.46	.59	.72	43.5	12.7	2.73	.46	.60	.73	42.0	12.3	3.05	.46	.60	.74	40.5	11.9	3.43	.47	.62	.76
	1395	660	46.0	13.5	2.45	.46	.60	.74	44.0	12.9	2.73	.47	.61	.75	42.5	12.5	3.06	.47	.62	.77	41.0	12.0	3.43	.47	.63	.78

HEATING CAPACITY - HP13-042 with

[C33-43B + G61MPV-36B-045]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1150	540	44.2	13.0	3.04	34.9	10.2	2.76	25.1	7.4	2.48	18.4	5.4	2.18	9.0	2.6	1.64
1330	630	44.9	13.2	2.90	35.5	10.4	2.62	25.7	7.5	2.33	19.0	5.6	2.03	9.6	2.8	1.49

HEATING CAPACITY - HP13-042 with

[C33-43B + G61MPV-36B-070]

[C33-43B + G71MPP-36B-070]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
		Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1105	520	44.2	13.0	3.13	34.8	10.2	2.83	25.0	7.3	2.53	18.3	5.4	2.22	9.1	2.7	1.67
1280	605	44.6	13.1	2.98	35.3	10.3	2.69	25.5	7.5	2.38	18.8	5.5	2.07	9.5	2.8	1.52
1395	660	45.1	13.2	2.91	35.7	10.5	2.62	25.9	7.6	2.31	19.2	5.6	2.00	10.0	2.9	1.45

HEATING PERFORMANCE at 1330 cfm (630 L/s) Indoor Coil Air Volume HP13-042 with

[C33-43B + G61MPV-36B-045]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.90	44.9	13.2
60	16	2.83	42.7	12.5
55	13	2.76	40.6	11.9
50	10	2.70	38.4	11.3
47	8	2.66	37.2	10.9
45	7	2.62	35.5	10.4
40	4	2.52	31.5	9.2
35	2	2.43	27.4	8.0
30	-1	2.38	26.6	7.8
25	-4	2.33	25.7	7.5
20	-7	2.29	24.8	7.3
17	-8	2.26	24.3	7.1
15	-9	2.24	23.5	6.9
10	-12	2.17	21.3	6.2
5	-15	2.03	19.0	5.6
0	-18	1.90	16.7	4.9
-5	-21	1.76	14.3	4.2
-10	-23	1.63	12.0	3.5
-15	-26	1.49	9.6	2.8
-20	-29	1.36	7.3	2.1

HEATING PERFORMANCE at 1280 cfm (605 L/s) Indoor Coil Air Volume HP13-042 with

[C33-43B + G61MPV-36B-070]

[C33-43B + G71MPP-36B-070]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.98	44.6	13.1
60	16	2.91	42.5	12.5
55	13	2.84	40.4	11.8
50	10	2.77	38.2	11.2
47	8	2.73	36.9	10.8
45	7	2.69	35.3	10.3
40	4	2.58	31.3	9.2
35	2	2.47	27.2	8.0
30	-1	2.43	26.4	7.7
25	-4	2.38	25.5	7.5
20	-7	2.33	24.6	7.2
17	-8	2.31	24.1	7.1
15	-9	2.28	23.3	6.8
10	-12	2.21	21.1	6.2
5	-15	2.07	18.8	5.5
0	-18	1.93	16.5	4.8
-5	-21	1.80	14.2	4.2
-10	-23	1.66	11.9	3.5
-15	-26	1.52	9.5	2.8
-20	-29	1.39	7.2	2.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-43C + G60UHV-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1355	640	41.0	12.0	2.40	.77	.92	1.00	39.5	11.6	2.69	.79	.94	1.00	38.5	11.3	3.02	.80	.96	1.00	36.6	10.7	3.40	.82	.98	1.00
	1520	715	42.0	12.3	2.41	.80	.96	1.00	40.5	11.9	2.70	.82	.98	1.00	39.0	11.4	3.03	.83	1.00	1.00	37.4	11.0	3.40	.85	1.00	1.00
67°F (19°C)	1355	640	43.0	12.6	2.42	.61	.75	.89	42.0	12.3	2.71	.62	.77	.91	40.0	11.7	3.04	.63	.78	.93	38.5	11.3	3.41	.64	.80	.95
	1520	715	44.5	13.0	2.43	.63	.78	.93	42.5	12.5	2.72	.64	.79	.95	41.0	12.0	3.04	.65	.81	.97	39.0	11.4	3.42	.66	.83	.99
71°F (22°C)	1355	640	45.5	13.3	2.45	.46	.60	.73	44.0	12.9	2.73	.46	.60	.74	42.5	12.5	3.05	.47	.62	.76	40.5	11.9	3.43	.47	.62	.77
	1520	715	46.5	13.6	2.46	.47	.62	.76	45.0	13.2	2.74	.47	.62	.77	43.5	12.7	3.06	.48	.64	.79	41.5	12.2	3.43	.48	.65	.81

COOLING CAPACITY - HP13-042 with

[C33-43C + G60UHV-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1295	610	41.0	12.0	2.40	.77	.91	1.00	39.5	11.6	2.68	.78	.93	1.00	37.8	11.1	3.01	.79	.95	1.00	36.2	10.6	3.39	.81	.97	1.00
	1460	690	42.0	12.3	2.41	.79	.95	1.00	40.5	11.9	2.69	.81	.97	1.00	39.0	11.4	3.02	.82	.99	1.00	37.0	10.8	3.40	.84	1.00	1.00
67°F (19°C)	1295	610	43.0	12.6	2.42	.60	.74	.88	41.5	12.2	2.70	.61	.76	.90	40.0	11.7	3.03	.62	.77	.91	38.0	11.1	3.41	.63	.79	.94
	1460	690	44.0	12.9	2.43	.62	.77	.91	42.5	12.5	2.71	.63	.78	.93	41.0	12.0	3.04	.64	.80	.96	39.0	11.4	3.42	.65	.82	.98
71°F (22°C)	1295	610	45.5	13.3	2.45	.46	.59	.72	44.0	12.9	2.73	.46	.60	.73	42.0	12.3	3.05	.47	.61	.75	40.5	11.9	3.43	.47	.62	.76
	1460	690	46.0	13.5	2.46	.46	.61	.75	44.5	13.0	2.73	.47	.62	.76	43.0	12.6	3.06	.47	.63	.78	41.0	12.0	3.43	.48	.64	.79

HEATING CAPACITY - HP13-042 with

[C33-43C + G60UHV-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil															
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)							
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input	
		kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW
1355	640	44.3	13.0	2.86	35.0	10.3	2.63	25.2	7.4	2.39	18.6	5.5	2.13	9.4	2.8	1.56	
1520	715	44.8	13.1	2.79	35.5	10.4	2.56	25.6	7.5	2.32	19.0	5.6	2.05	9.9	2.9	1.48	

HEATING CAPACITY - HP13-042 with

[C33-43C + G60UHV-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil															
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)							
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input		Total Heating Capacity		Comp. Motor kW Input	
		kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW
1295	610	44.3	13.0	2.97	34.9	10.2	2.68	25.1	7.4	2.38	18.4	5.4	2.07	9.4	2.8	1.52	
1460	690	44.7	13.1	2.87	35.3	10.3	2.58	25.5	7.5	2.28	18.8	5.5	1.97	9.8	2.9	1.42	

HEATING PERFORMANCE at 1355 cfm (640 L/s) Indoor Coil Air Volume HP13-042 with

[C33-43C + G60UHV-60C-090]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.86		44.3	13.0
60	16	2.81		42.2	12.4
55	13	2.76		40.1	11.8
50	10	2.70		37.9	11.1
47	8	2.67		36.6	10.7
45	7	2.63		35.0	10.3
40	4	2.54		31.0	9.1
35	2	2.45		27.0	7.9
30	-1	2.42		26.1	7.6
25	-4	2.39		25.2	7.4
20	-7	2.37		24.3	7.1
17	-8	2.35		23.8	7.0
15	-9	2.33		23.0	6.7
10	-12	2.28		20.8	6.1
5	-15	2.13		18.6	5.5
0	-18	1.99		16.3	4.8
-5	-21	1.84		14.0	4.1
-10	-23	1.70		11.7	3.4
-15	-26	1.56		9.4	2.8
-20	-29	1.41		7.1	2.1

HEATING PERFORMANCE at 1295 cfm (610 L/s) Indoor Coil Air Volume HP13-042 with

[C33-43C + G60UHV-60C-110]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.97		44.3	13.0
60	16	2.90		42.1	12.3
55	13	2.83		40.0	11.7
50	10	2.76		37.8	11.1
47	8	2.72		36.5	10.7
45	7	2.68		34.9	10.2
40	4	2.58		30.9	9.1
35	2	2.47		26.9	7.9
30	-1	2.43		26.0	7.6
25	-4	2.38		25.1	7.4
20	-7	2.33		24.2	7.1
17	-8	2.30		23.7	6.9
15	-9	2.27		22.8	6.7
10	-12	2.21		20.6	6.0
5	-15	2.07		18.4	5.4
0	-18	1.93		16.1	4.7
-5	-21	1.79		13.9	4.1
-10	-23	1.66		11.6	3.4
-15	-26	1.52		9.4	2.8
-20	-29	1.38		7.1	2.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-43C + G61MPV-60C-090]
[C33-43C + G71MPP-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)				95°F (35°C)				105°F (41°C)				115°F (46°C)											
	cfm	L/s	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb								
63°F (17°C)	1275	600	40.5	11.9	2.40	.76	.91	1.00	39.0	11.4	2.68	.78	.92	1.00	37.6	11.0	3.02	.79	.94	1.00	36.2	10.6	3.39	.80	.97	1.00
	1440	680	41.5	12.2	2.41	.79	.94	1.00	40.0	11.7	2.69	.80	.96	1.00	38.5	11.3	3.02	.82	.98	1.00	37.0	10.8	3.40	.84	1.00	1.00
67°F (19°C)	1275	600	43.0	12.6	2.42	.60	.74	.87	41.5	12.2	2.70	.61	.75	.89	39.5	11.6	3.03	.62	.76	.91	38.0	11.1	3.41	.63	.78	.93
	1440	680	44.0	12.9	2.43	.62	.77	.91	42.5	12.5	2.71	.63	.78	.93	41.0	12.0	3.04	.64	.80	.95	39.0	11.4	3.42	.65	.81	.97
71°F (22°C)	1275	600	45.0	13.2	2.44	.46	.59	.72	43.5	12.7	2.73	.46	.59	.73	42.0	12.3	3.05	.46	.60	.74	40.5	11.9	3.43	.47	.62	.76
	1440	680	46.0	13.5	2.46	.46	.61	.74	44.5	13.0	2.73	.47	.62	.76	43.0	12.6	3.06	.47	.63	.77	41.0	12.0	3.43	.48	.64	.79

COOLING CAPACITY - HP13-042 with

[C33-43C + G61MPV-60C-110]
[C33-43C + G71MPP-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)				95°F (35°C)				105°F (41°C)				115°F (46°C)											
	cfm	L/s	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb								
63°F (17°C)	1110	525	39.5	11.6	2.38	.74	.87	.99	38.0	11.1	2.67	.75	.88	1.00	36.6	10.7	3.00	.76	.90	1.00	35.0	10.3	3.39	.77	.92	1.00
	1290	610	41.0	12.0	2.40	.76	.91	1.00	39.5	11.6	2.68	.78	.93	1.00	37.8	11.1	3.01	.79	.95	1.00	36.2	10.6	3.39	.81	.97	1.00
67°F (19°C)	1110	525	41.5	12.2	2.40	.78	.93	1.00	40.0	11.7	2.69	.79	.95	1.00	38.5	11.3	3.02	.81	.97	1.00	36.8	10.8	3.40	.83	.99	1.00
	1290	610	43.0	12.6	2.42	.60	.74	.88	40.0	11.7	2.69	.59	.73	.85	38.5	11.3	3.02	.60	.73	.87	37.0	10.8	3.40	.61	.75	.89
71°F (22°C)	1110	525	44.0	12.9	2.43	.45	.57	.69	42.5	12.5	2.71	.45	.58	.70	41.0	12.0	3.04	.46	.59	.71	39.0	11.4	3.42	.46	.59	.73
	1290	610	45.0	13.2	2.45	.46	.59	.72	44.0	12.9	2.73	.46	.60	.73	42.0	12.3	3.05	.47	.61	.74	40.5	11.9	3.43	.47	.62	.76

HEATING CAPACITY - HP13-042 with

[C33-43C + G61MPV-60C-090]
[C33-43C + G71MPP-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)							
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input			
1275	600	44.4	13.0	2.99	35.0	10.3	2.69	25.2	7.4	2.38	18.5	5.4	2.07	9.4	2.8	1.52
1440	680	44.7	13.1	2.88	35.4	10.4	2.58	25.6	7.5	2.27	18.9	5.5	1.96	9.8	2.9	1.41

HEATING CAPACITY - HP13-042 with

[C33-43C + G61MPV-60C-110]
[C33-43C + G71MPP-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil															
	65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)							
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input			
1110	525	44.0	12.9	3.12	34.7	10.2	2.82	24.8	7.3	2.52	18.2	5.3	2.21	9.1	2.7	1.66
1290	610	44.4	13.0	2.97	35.0	10.3	2.68	25.2	7.4	2.38	18.5	5.4	2.07	9.4	2.8	1.52
1385	655	44.7	13.1	2.92	35.4	10.4	2.62	25.5	7.5	2.32	18.8	5.5	2.01	9.7	2.8	1.46

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-042 with
[C33-43C + G61MPV-60C-090]
[C33-43C + G71MPP-60C-090]

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-042 with
[C33-43C + G61MPV-60C-110]
[C33-43C + G71MPP-60C-110]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.99		44.4	13.0
60	16	2.92		42.2	12.4
55	13	2.85		40.1	11.8
50	10	2.78		37.9	11.1
47	8	2.74		36.6	10.7
45	7	2.69		35.0	10.3
40	4	2.58		31.0	9.1
35	2	2.48		27.0	7.9
30	-1	2.43		26.1	7.6
25	-4	2.38		25.2	7.4
20	-7	2.34		24.3	7.1
17	-8	2.31		23.8	7.0
15	-9	2.28		22.9	6.7
10	-12	2.21		20.8	6.1
5	-15	2.07		18.5	5.4
0	-18	1.94		16.2	4.7
-5	-21	1.80		14.0	4.1
-10	-23	1.66		11.7	3.4
-15	-26	1.52		9.4	2.8
-20	-29	1.39		7.1	2.1

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.97		44.4	13.0
60	16	2.90		42.2	12.4
55	13	2.83		40.1	11.8
50	10	2.76		37.9	11.1
47	8	2.72		36.6	10.7
45	7	2.68		35.0	10.3
40	4	2.57		31.0	9.1
35	2	2.47		26.9	7.9
30	-1	2.42		26.1	7.6
25	-4	2.38		25.2	7.4
20	-7	2.33		24.3	7.1
17	-8	2.30		23.8	7.0
15	-9	2.28		22.9	6.7
10	-12	2.21		20.8	6.1
5	-15	2.07		18.5	5.4
0	-18	1.93		16.2	4.7
-5	-21	1.79		13.9	4.1
-10	-23	1.66		11.7	3.4
-15	-26	1.52		9.4	2.8
-20	-29	1.38		7.1	2.1

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-44C + G60UHV-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1355	640	40.5	11.9	2.39	.78	.92	1.00	39.0	11.4	2.68	.78	.94	1.00	37.4	11.0	3.01	.80	.96	1.00	35.8	10.5	3.39	.82	.98	1.00
	1520	715	41.0	12.0	2.40	.80	.96	1.00	39.5	11.6	2.69	.81	.98	1.00	38.0	11.1	3.02	.83	.99	1.00	36.6	10.7	3.40	.85	1.00	1.00
67°F (19°C)	1355	640	42.5	12.5	2.42	.61	.75	.89	41.5	12.2	2.70	.61	.76	.90	39.5	11.6	3.03	.62	.78	.93	38.0	11.1	3.41	.63	.79	.95
	1520	715	43.5	12.7	2.43	.62	.77	.92	42.0	12.3	2.71	.63	.79	.94	40.5	11.9	3.04	.64	.81	.96	38.5	11.3	3.41	.65	.82	.99
71°F (22°C)	1355	640	45.0	13.2	2.44	.46	.60	.73	43.5	12.7	2.73	.46	.60	.74	42.0	12.3	3.05	.46	.61	.75	40.0	11.7	3.42	.47	.62	.77
	1520	715	46.0	13.5	2.45	.47	.61	.75	44.5	13.0	2.73	.47	.62	.77	42.5	12.5	3.06	.47	.63	.78	41.0	12.0	3.43	.48	.64	.80

COOLING CAPACITY - HP13-042 with

[C33-44C + G60UHV-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1295	610	40.0	11.7	2.39	.77	.91	1.00	38.5	11.3	2.68	.78	.92	1.00	37.0	10.8	3.01	.79	.95	1.00	35.4	10.4	3.39	.81	.97	1.00
	1460	690	41.0	12.0	2.40	.79	.94	1.00	39.5	11.6	2.68	.80	.96	1.00	37.8	11.1	3.01	.82	.98	1.00	36.2	10.6	3.39	.84	1.00	1.00
67°F (19°C)	1295	610	42.5	12.5	2.41	.60	.74	.88	41.0	12.0	2.70	.61	.75	.89	39.5	11.6	3.03	.62	.76	.91	37.6	11.0	3.40	.63	.78	.94
	1460	690	43.0	12.6	2.42	.62	.76	.91	41.5	12.2	2.71	.62	.78	.93	40.0	11.7	3.03	.64	.80	.95	38.5	11.3	3.41	.65	.81	.97
71°F (22°C)	1295	610	44.5	13.0	2.44	.46	.59	.72	43.0	12.6	2.72	.46	.60	.73	41.5	12.2	3.05	.46	.60	.74	40.0	11.7	3.42	.47	.61	.76
	1460	690	45.5	13.3	2.45	.47	.60	.74	44.0	12.9	2.73	.47	.61	.75	42.5	12.5	3.05	.47	.62	.77	40.5	11.9	3.43	.48	.63	.79

HEATING CAPACITY - HP13-042 with

[C33-44C + G60UHV-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1355	640	44.4	13.0	2.94	35.0	10.3	2.66	25.1	7.4	2.37	18.4	5.4	2.07	9.4	2.8	1.52
1520	715	44.8	13.1	2.84	35.4	10.4	2.56	25.5	7.5	2.27	18.8	5.5	1.97	9.8	2.9	1.42

HEATING CAPACITY - HP13-042 with

[C33-44C + G60UHV-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1295	610	44.2	13.0	2.99	34.9	10.2	2.69	25.1	7.4	2.39	18.4	5.4	2.08	9.4	2.8	1.53
1460	690	44.6	13.1	2.89	35.3	10.3	2.59	25.5	7.5	2.29	18.8	5.5	1.98	9.8	2.9	1.43

HEATING PERFORMANCE at 1355 cfm (640 L/s) Indoor Coil

HEATING PERFORMANCE at 1295 cfm (610 L/s) Indoor Coil

Air Volume HP13-042 with [C33-44C + G60UHV-60C-090]

Air Volume HP13-042 with [C33-44C + G60UHV-60C-110]

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.94		44.4	13.0
60	16	2.87		42.2	12.4
55	13	2.81		40.1	11.8
50	10	2.74		37.9	11.1
47	8	2.70		36.6	10.7
45	7	2.66		35.0	10.3
40	4	2.56		31.0	9.1
35	2	2.45		26.9	7.9
30	-1	2.41		26.0	7.6
25	-4	2.37		25.1	7.4
20	-7	2.32		24.3	7.1
17	-8	2.30		23.7	6.9
15	-9	2.27		22.9	6.7
10	-12	2.21		20.7	6.1
5	-15	2.07		18.4	5.4
0	-18	1.93		16.2	4.7
-5	-21	1.79		13.9	4.1
-10	-23	1.66		11.6	3.4
-15	-26	1.52		9.4	2.8
-20	-29	1.38		7.1	2.1

*Outdoor Temperature		Compressor Motor kW Input		Total Output	
°F	°C	kW Input		kBtuh	kW
65	18	2.99		44.2	13.0
60	16	2.92		42.1	12.3
55	13	2.85		39.9	11.7
50	10	2.78		37.8	11.1
47	8	2.74		36.5	10.7
45	7	2.69		34.9	10.2
40	4	2.59		30.9	9.1
35	2	2.48		26.9	7.9
30	-1	2.43		26.0	7.6
25	-4	2.39		25.1	7.4
20	-7	2.34		24.2	7.1
17	-8	2.32		23.6	6.9
15	-9	2.29		22.8	6.7
10	-12	2.22		20.6	6.0
5	-15	2.08		18.4	5.4
0	-18	1.94		16.1	4.7
-5	-21	1.81		13.9	4.1
-10	-23	1.67		11.6	3.4
-15	-26	1.53		9.4	2.8
-20	-29	1.39		7.1	2.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

**[C33-44C + G61MPV-60C-090]
[C33-44C + G71MPP-60C-090]**

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)					95°F (35°C)					105°F (41°C)					115°F (46°C)								
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1275 1440	600 680	40.0 41.0	11.7 12.0	2.39 2.40	.76 .78	.90 .94	1.00 1.00	38.5 39.5	11.3 11.6	2.68 2.68	.77 .80	.92 .96	1.00 1.00	37.0 37.8	10.8 11.1	3.01 3.01	.78 .82	.94 .98	1.00 1.00	35.2 36.2	10.3 10.6	3.39 3.39	.80 .83	.96 1.00	1.00 1.00
67°F (19°C)	1275 1440	600 680	42.0 43.0	12.3 12.6	2.41 2.42	.60 .61	.74 .77	.87 .90	41.0 41.5	12.0 12.2	2.70 2.70	.61 .62	.75 .78	.89 .93	39.0 40.0	11.4 11.7	3.02 3.03	.61 .63	.76 .79	.90 .95	37.6 38.5	11.0 11.3	3.40 3.41	.62 .64	.78 .81	.93 .97
71°F (22°C)	1275 1440	600 680	44.5 45.5	13.0 13.3	2.44 2.45	.46 .47	.59 .60	.71 .74	43.0 44.0	12.6 12.9	2.72 2.73	.46 .47	.60 .61	.73 .75	41.5 42.5	12.2 12.5	3.05 3.05	.46 .47	.60 .62	.74 .77	39.5 40.5	11.6 11.9	3.42 3.43	.46 .47	.61 .63	.75 .79

COOLING CAPACITY - HP13-042 with

**[C33-44C + G61MPV-60C-110]
[C33-44C + G71MPP-60C-110]**

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)					95°F (35°C)					105°F (41°C)					115°F (46°C)								
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1110 1290 1385	525 610 655	38.5 40.0 40.5	11.3 11.7 11.9	2.38 2.39 2.39	.73 .77 .78	.87 .91 .93	.99 1.00 1.00	37.4 38.5 39.0	11.0 11.3 11.4	2.67 2.68 2.68	.75 .78 .79	.88 .92 .95	1.00 1.00 1.00	36.0 37.0 37.4	10.6 10.8 11.0	3.00 3.01 3.01	.76 .79 .81	.90 .94 .97	1.00 1.00 1.00	34.4 35.4 36.0	10.1 10.4 10.6	3.38 3.39 3.39	.77 .81 .83	.92 .97 .99	1.00 1.00 1.00
67°F (19°C)	1110 1290 1385	525 610 655	41.0 42.5 43.0	12.0 12.5 12.6	2.40 2.41 2.42	.59 .60 .61	.71 .74 .76	.83 .87 .89	39.5 41.0 41.5	11.6 12.0 12.2	2.69 2.70 2.70	.59 .61 .62	.72 .75 .77	.85 .89 .91	38.0 39.5 40.0	11.1 11.6 11.7	3.02 3.03 3.03	.60 .62 .62	.73 .76 .78	.86 .91 .93	36.6 37.6 38.0	10.7 11.0 11.1	3.40 3.40 3.41	.60 .63 .64	.75 .78 .80	.88 .93 .95
71°F (22°C)	1110 1290 1385	525 610 655	43.5 44.5 45.0	12.7 13.0 13.2	2.42 2.44 2.45	.45 .46 .46	.57 .59 .60	.69 .72 .73	42.0 43.0 43.5	12.3 12.6 12.7	2.71 2.72 2.73	.45 .46 .47	.58 .60 .60	.70 .73 .74	40.5 41.5 42.0	11.9 12.2 12.3	3.03 3.05 3.05	.46 .46 .47	.58 .60 .61	.71 .75 .76	38.5 40.0 40.5	11.3 11.7 11.9	3.41 3.42 3.43	.46 .47 .47	.59 .61 .63	.72 .76 .78

HEATING CAPACITY - HP13-042 with

**[C33-44C + G61MPV-60C-090]
[C33-44C + G71MPP-60C-090]**

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input
1275	600	44.3	13.0	3.01	35.0	10.3	2.71	25.2	7.4	2.40	18.5	5.4	2.09	9.4	2.8	1.53
1440	680	44.7	13.1	2.91	35.4	10.4	2.60	25.6	7.5	2.29	18.9	5.5	1.98	9.8	2.9	1.42

HEATING CAPACITY - HP13-042 with

**[C33-44C + G61MPV-60C-110]
[C33-44C + G71MPP-60C-110]**

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input	Total Heating Capacity kBtuh	kW	Comp. Motor kW Input
1110	525	44.0	12.9	3.14	34.7	10.2	2.85	24.9	7.3	2.54	18.2	5.3	2.23	9.1	2.7	1.68
1290	610	44.3	13.0	2.99	35.0	10.3	2.70	25.2	7.4	2.39	18.5	5.4	2.08	9.4	2.8	1.53
1385	655	44.7	13.1	2.93	35.3	10.3	2.64	25.5	7.5	2.33	18.8	5.5	2.02	9.8	2.9	1.47

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-042 with

**[C33-44C + G61MPV-60C-090]
[C33-44C + G71MPP-60C-090]**

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.01	44.3	13.0
60	16	2.94	42.2	12.4
55	13	2.87	40.0	11.7
50	10	2.80	37.9	11.1
47	8	2.76	36.6	10.7
45	7	2.71	35.0	10.3
40	4	2.60	31.0	9.1
35	2	2.49	27.0	7.9
30	-1	2.44	26.1	7.6
25	-4	2.40	25.2	7.4
20	-7	2.35	24.3	7.1
17	-8	2.32	23.8	7.0
15	-9	2.30	22.9	6.7
10	-12	2.22	20.8	6.1
5	-15	2.09	18.5	5.4
0	-18	1.95	16.2	4.7
-5	-21	1.81	14.0	4.1
-10	-23	1.67	11.7	3.4
-15	-26	1.53	9.4	2.8
-20	-29	1.40	7.1	2.1

HEATING PERFORMANCE at 1290 cfm (610 L/s) Indoor Coil Air Volume HP13-042 with

**[C33-44C + G61MPV-60C-110]
[C33-44C + G71MPP-60C-110]**

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.99	44.3	13.0
60	16	2.92	42.2	12.4
55	13	2.85	40.0	11.7
50	10	2.78	37.9	11.1
47	8	2.74	36.6	10.7
45	7	2.70	35.0	10.3
40	4	2.59	31.0	9.1
35	2	2.48	26.9	7.9
30	-1	2.44	26.0	7.6
25	-4	2.39	25.2	7.4
20	-7	2.35	24.3	7.1
17	-8	2.32	23.7	6.9
15	-9	2.29	22.9	6.7
10	-12	2.22	20.7	6.1
5	-15	2.08	18.5	5.4
0	-18	1.95	16.2	4.7
-5	-21	1.81	13.9	4.1
-10	-23	1.67	11.7	3.4
-15	-26	1.53	9.4	2.8
-20	-29	1.39	7.1	2.1

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-48B + G60UHV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1090	515	38.5	11.3	2.38	.73	.86	1.00	37.4	11.0	2.67	.74	.87	.99	36.0	10.6	3.00	.75	.88	1.00	34.4	10.1	3.38	.76	.91	1.00
	1260	595	40.0	11.7	2.39	.76	.89	1.00	38.5	11.3	2.68	.77	.91	1.00	37.2	10.9	3.01	.78	.93	1.00	35.6	10.4	3.39	.80	.95	1.00
	1350	635	40.5	11.9	2.39	.77	.91	1.00	39.0	11.4	2.68	.78	.93	1.00	37.6	11.0	3.01	.80	.95	1.00	36.0	10.6	3.39	.81	.97	1.00
67°F (19°C)	1090	515	41.0	12.0	2.40	.58	.70	.82	39.5	11.6	2.69	.59	.71	.84	38.0	11.1	3.02	.59	.73	.85	36.6	10.7	3.40	.60	.74	.87
	1260	595	42.5	12.5	2.41	.60	.73	.86	41.0	12.0	2.70	.60	.74	.87	39.5	11.6	3.03	.61	.75	.89	37.6	11.0	3.40	.62	.77	.91
	1350	635	43.0	12.6	2.42	.60	.75	.88	41.5	12.2	2.70	.61	.75	.90	40.0	11.7	3.03	.62	.77	.92	38.0	11.1	3.41	.63	.79	.94
71°F (22°C)	1090	515	43.5	12.7	2.42	.45	.57	.68	42.0	12.3	2.71	.45	.57	.69	40.5	11.9	3.03	.45	.58	.70	38.5	11.3	3.41	.46	.59	.72
	1260	595	44.5	13.0	2.44	.46	.58	.71	43.0	12.6	2.72	.46	.59	.72	41.5	12.2	3.05	.46	.60	.73	40.0	11.7	3.42	.46	.61	.75
	1350	635	45.0	13.2	2.45	.46	.59	.72	43.5	12.7	2.72	.46	.60	.73	42.0	12.3	3.05	.46	.61	.75	40.5	11.9	3.43	.47	.62	.76

COOLING CAPACITY - HP13-042 with

[C33-48B + G61MPV-36B-045]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C		kBtuh	kW	75°F 24°C	80°F 27°C	85°F 29°C				
63°F (17°C)	1150	545	39.0	11.4	2.38	.74	.87	.99	37.8	11.1	2.67	.75	.88	1.00	36.4	10.7	3.01	.76	.90	1.00	34.8	10.2	3.39	.77	.92	1.00
	1330	630	40.5	11.9	2.39	.76	.91	1.00	39.0	11.4	2.68	.78	.92	1.00	37.6	11.0	3.01	.79	.94	1.00	36.0	10.6	3.39	.81	.97	1.00
	1150	545	41.5	12.2	2.40	.59	.71	.84	40.0	11.7	2.69	.59	.73	.85	38.5	11.3	3.02	.60	.74	.86	37.0	10.8	3.40	.61	.75	.89
67°F (19°C)	1330	630	43.0	12.6	2.42	.60	.75	.87	41.5	12.2	2.70	.61	.75	.89	39.5	11.6	3.03	.62	.77	.91	38.0	11.1	3.41	.63	.78	.93
	1150	545	44.0	12.9	2.43	.45	.57	.69	42.5	12.5	2.71	.46	.58	.70	41.0	12.0	3.04	.46	.58	.71	39.0	11.4	3.42	.46	.59	.72
	1330	630	45.0	13.2	2.45	.46	.59	.72	43.5	12.7	2.73	.46	.60	.73	42.0	12.3	3.05	.46	.61	.74	40.5	11.9	3.43	.47	.62	.76

HEATING CAPACITY - HP13-042 with

[C33-48B + G60UHV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)			Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	
1090	515	43.8	12.8	3.25	34.5	10.1	2.91	24.7	7.2	2.56	18.1	5.3	2.22	9.0	2.6	1.68						
1260	595	44.2	13.0	3.11	34.9	10.2	2.77	25.2	7.4	2.42	18.5	5.4	2.08	9.4	2.8	1.53						
1350	635	44.5	13.0	3.05	35.2	10.3	2.71	25.5	7.5	2.35	18.8	5.5	2.02	9.7	2.8	1.47						

HEATING CAPACITY - HP13-042 with

[C33-48B + G61MPV-36B-045]

Indoor Coil Air Volume 70°F db (21°C db)			Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	
1149	540	44.0	12.9	3.19	34.7	10.2	2.86	25.0	7.3	2.53	18.3	5.4	2.21	8.9	2.6	1.67						
1330	625	44.8	13.1	3.04	35.5	10.4	2.72	25.7	7.5	2.38	19.0	5.6	2.06	9.7	2.8	1.52						

HEATING PERFORMANCE at 1260 cfm (595 L/s) Indoor Coil Air Volume HP13-042 with [C33-48B + G60UHV-36B-090]

HEATING PERFORMANCE at 1330 cfm (630 L/s) Indoor Coil Air Volume HP13-042 with [C33-48B + G61MPV-36B-045]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.11	44.2	13.0
60	16	3.03	42.1	12.3
55	13	2.95	39.9	11.7
50	10	2.87	37.8	11.1
47	8	2.82	36.5	10.7
45	7	2.77	34.9	10.2
40	4	2.65	30.9	9.1
35	2	2.52	26.9	7.9
30	-1	2.47	26.0	7.6
25	-4	2.42	25.2	7.4
20	-7	2.36	24.3	7.1
17	-8	2.33	23.8	7.0
15	-9	2.30	22.9	6.7
10	-12	2.21	20.8	6.1
5	-15	2.08	18.5	5.4
0	-18	1.94	16.2	4.7
-5	-21	1.81	14.0	4.1
-10	-23	1.67	11.7	3.4
-15	-26	1.53	9.4	2.8
-20	-29	1.40	7.1	2.1

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.04	44.8	13.1
60	16	2.96	42.6	12.5
55	13	2.88	40.5	11.9
50	10	2.81	38.4	11.3
47	8	2.76	37.1	10.9
45	7	2.72	35.5	10.4
40	4	2.60	31.5	9.2
35	2	2.48	27.4	8.0
30	-1	2.43	26.6	7.8
25	-4	2.38	25.7	7.5
20	-7	2.33	24.9	7.3
17	-8	2.30	24.4	7.2
15	-9	2.27	23.5	6.9
10	-12	2.20	21.4	6.3
5	-15	2.06	19.0	5.6
0	-18	1.93	16.7	4.9
-5	-21	1.79	14.4	4.2
-10	-23	1.66	12.0	3.5
-15	-26	1.52	9.7	2.8
-20	-29	1.38	7.3	2.1

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-48B + G61MPV-36B-070]
[C33-48B + G71MPP-36B-070]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F) with sub-columns for Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-042 with

[C33-48C + G60UHV-60C-090]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F) with sub-columns for Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-042 with

[C33-48B + G61MPV-36B-070]
[C33-48B + G71MPP-36B-070]

Table with columns for Indoor Coil Air Volume (70°F db, 21°C db) and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Total Heating Capacity and Comp. Motor kW Input.

HEATING CAPACITY - HP13-042 with

[C33-48C + G60UHV-60C-090]

Table with columns for Indoor Coil Air Volume (70°F db, 21°C db) and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Total Heating Capacity and Comp. Motor kW Input.

HEATING PERFORMANCE at 1280 cfm (605 L/s) Indoor Coil Air Volume HP13-042 with

[C33-48B + G61MPV-36B-070]
[C33-48B + G71MPP-36B-070]

Table with columns for *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

HEATING PERFORMANCE at 1355 cfm (640 L/s) Indoor Coil Air Volume HP13-042 with

[C33-48C + G60UHV-60C-090]

Table with columns for *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-48C + G60UHV-60C-110]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1295	610	40.5	11.9	2.39	.76	.90	1.00	39.0	11.4	2.68	.77	.92	1.00	37.4	11.0	3.01	.79	.94	1.00	35.8	10.5	3.39	.80	.96	1.00
	1460	690	41.0	12.0	2.40	.78	.93	1.00	40.0	11.7	2.69	.80	.95	1.00	38.0	11.1	3.02	.81	.97	1.00	36.6	10.7	3.40	.83	.99	1.00
67°F (19°C)	1295	610	42.5	12.5	2.42	.60	.74	.87	41.0	12.0	2.70	.61	.75	.88	39.5	11.6	3.03	.61	.76	.90	37.8	11.1	3.40	.62	.78	.92
	1460	690	43.5	12.7	2.42	.62	.76	.90	42.0	12.3	2.71	.62	.78	.92	40.5	11.9	3.04	.63	.79	.94	38.5	11.3	3.41	.64	.81	.96
71°F (22°C)	1295	610	45.0	13.2	2.44	.46	.59	.71	43.5	12.7	2.72	.46	.59	.73	42.0	12.3	3.05	.46	.60	.74	40.0	11.7	3.42	.47	.61	.75
	1460	690	46.0	13.5	2.45	.46	.60	.74	44.5	13.0	2.73	.46	.61	.75	42.5	12.5	3.06	.47	.62	.77	41.0	12.0	3.43	.47	.63	.78

COOLING CAPACITY - HP13-042 with

[C33-48C + G61MPV-60C-090]

[C33-48C + G71MPP-60C-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1275	600	40.0	11.7	2.39	.76	.89	1.00	38.5	11.3	2.68	.77	.91	1.00	37.2	10.9	3.01	.78	.93	1.00	35.6	10.4	3.39	.80	.95	1.00
	1440	680	41.0	12.0	2.40	.78	.93	1.00	39.5	11.6	2.69	.80	.95	1.00	38.0	11.1	3.02	.81	.97	1.00	36.4	10.7	3.40	.83	.99	1.00
67°F (19°C)	1275	600	42.5	12.5	2.41	.60	.73	.86	41.0	12.0	2.70	.60	.75	.88	39.5	11.6	3.03	.61	.76	.90	37.8	11.1	3.40	.62	.77	.92
	1440	680	43.5	12.7	2.42	.61	.75	.90	42.0	12.3	2.71	.62	.77	.92	40.5	11.9	3.04	.63	.79	.94	38.5	11.3	3.41	.64	.80	.96
71°F (22°C)	1275	600	44.5	13.0	2.44	.46	.59	.71	43.0	12.6	2.72	.46	.59	.72	41.5	12.2	3.05	.46	.60	.73	40.0	11.7	3.42	.47	.61	.75
	1440	680	45.5	13.3	2.45	.46	.61	.73	44.0	12.9	2.73	.46	.60	.75	42.5	12.5	3.06	.47	.62	.76	41.0	12.0	3.43	.47	.63	.78

HEATING CAPACITY - HP13-042 with

[C33-48C + G60UHV-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW				
1295	610	44.1	12.9	3.08	34.8	10.2	2.74	25.0	7.3	2.40	18.4	5.4	2.07	9.4	2.8	1.53						
1460	690	44.5	13.0	2.97	35.3	10.3	2.64	25.5	7.5	2.29	18.8	5.5	1.96	9.8	2.9	1.42						

HEATING CAPACITY - HP13-042 with

[C33-48C + G61MPV-60C-090]

[C33-48C + G71MPP-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW				
1275	600	44.2	13.0	3.09	34.9	10.2	2.76	25.2	7.4	2.41	18.5	5.4	2.07	9.4	2.8	1.53						
1440	680	44.6	13.1	2.99	35.3	10.3	2.65	25.6	7.5	2.30	18.9	5.5	1.97	9.8	2.9	1.43						

HEATING PERFORMANCE at 1295 cfm (610 L/s) Indoor Coil Air Volume HP13-042 with

[C33-48C + G60UHV-60C-110]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.08	44.1	12.9
60	16	3.00	42.0	12.3
55	13	2.92	39.8	11.7
50	10	2.84	37.7	11.0
47	8	2.79	36.4	10.7
45	7	2.74	34.8	10.2
40	4	2.62	30.8	9.0
35	2	2.50	26.8	7.9
30	-1	2.45	25.9	7.6
25	-4	2.40	25.0	7.3
20	-7	2.35	24.2	7.1
17	-8	2.32	23.6	6.9
15	-9	2.28	22.8	6.7
10	-12	2.20	20.7	6.1
5	-15	2.07	18.4	5.4
0	-18	1.93	16.1	4.7
-5	-21	1.80	13.9	4.1
-10	-23	1.66	11.6	3.4
-15	-26	1.53	9.4	2.8
-20	-29	1.39	7.1	2.1

HEATING PERFORMANCE at 1275 cfm (600 L/s) Indoor Coil Air Volume HP13-042 with

[C33-48C + G61MPV-60C-090]

[C33-48C + G71MPP-60C-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.09	44.2	13.0
60	16	3.01	42.1	12.3
55	13	2.93	39.9	11.7
50	10	2.85	37.8	11.1
47	8	2.80	36.5	10.7
45	7	2.76	34.9	10.2
40	4	2.64	30.9	9.1
35	2	2.51	26.9	7.9
30	-1	2.46	26.0	7.6
25	-4	2.41	25.2	7.4
20	-7	2.35	24.3	7.1
17	-8	2.32	23.8	7.0
15	-9	2.29	22.9	6.7
10	-12	2.21	20.8	6.1
5	-15	2.07	18.5	5.4
0	-18	1.94	16.2	4.7
-5	-21	1.80	14.0	4.1
-10	-23	1.67	11.7	3.4
-15	-26	1.53	9.4	2.8
-20	-29	1.39	7.1	2.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

**[C33-50/60C + G61MPV-60C-110]
[C33-50/60C + G71MPP-60C-110]**

Table with columns: Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb. Rows include temperatures like 63°F, 67°F, 71°F.

COOLING CAPACITY - HP13-042 with

[C33-60D + G60UHV-60D-135]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb. Rows include temperatures like 63°F, 67°F, 71°F.

HEATING CAPACITY - HP13-042 with

**[C33-50/60C + G61MPV-60C-110]
[C33-50/60C + G71MPP-60C-110]**

Table with columns: Indoor Coil Air Volume, Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity, Comp. Motor kW Input. Rows include air volumes 1290, 1405, 1605.

HEATING CAPACITY - HP13-042 with

[C33-60D + G60UHV-60D-135]

Table with columns: Indoor Coil Air Volume, Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity, Comp. Motor kW Input. Rows include air volumes 1275, 1430, 1575.

**HEATING PERFORMANCE at 1405 cfm (665 L/s) Indoor Coil Air Volume HP13-042 with [C33-50/60C + G61MPV-60C-110]
[C33-50/60C + G71MPP-60C-110]**

HEATING PERFORMANCE at 1430 cfm (675 L/s) Indoor Coil Air Volume HP13-042 with [C33-60D + G60UHV-60D-135]

Table with columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW). Rows show performance from 65°F down to -20°F.

Table with columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW). Rows show performance from 65°F down to -20°F.

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-62C + G60UHV-60C-110]

Table with 22 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F), and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F).

COOLING CAPACITY - HP13-042 with

[C33-62C + G61MPV-60C-090]

[C33-62C + G71MPP-60C-090]

Table with 22 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Total Cooling Capacity (kBtuh, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F), and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F).

HEATING CAPACITY - HP13-042 with

[C33-62C + G60UHV-60C-110]

Table with 14 columns: Indoor Coil Air Volume (70°F db), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input, and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F).

HEATING CAPACITY - HP13-042 with

[C33-62C + G61MPV-60C-090]

[C33-62C + G71MPP-60C-090]

Table with 14 columns: Indoor Coil Air Volume (70°F db), Total Heating Capacity (kBtuh, kW), Comp. Motor kW Input, and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F).

HEATING PERFORMANCE at 1395 cfm (660 L/s) Indoor Coil Air Volume HP13-042 with

[C33-62C + G60UHV-60C-110]

Table with 5 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1380 cfm (650 L/s) Indoor Coil Air Volume HP13-042 with

[C33-62C + G61MPV-60C-090]

[C33-62C + G71MPP-60C-090]

Table with 5 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[C33-62D + G61MPV-60D-135]
[C33-62D + G71MPP-60D-135]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
						75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C
cfm	L/s	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW	kBtuh	kW			
63°F (17°C)	1305	615	41.5	12.2	2.40	.77	.91	1.00	40.0	11.7	2.69	.78	.93	1.00	38.5	11.3	3.02	.80	.95	1.00	36.8	10.8	3.40	.82	.98	1.00
	1400	660	42.0	12.3	2.41	.79	.93	1.00	40.5	11.9	2.69	.80	.96	1.00	39.0	11.4	3.02	.82	.98	1.00	37.4	11.0	3.40	.84	1.00	1.00
	1600	755	43.0	12.6	2.42	.81	.98	1.00	41.5	12.2	2.70	.83	1.00	1.00	40.0	11.7	3.03	.85	1.00	1.00	38.5	11.3	3.41	.87	1.00	1.00
67°F (19°C)	1305	615	43.5	12.7	2.43	.61	.75	.88	42.0	12.3	2.71	.62	.76	.90	40.5	11.9	3.04	.63	.78	.92	39.0	11.4	3.41	.64	.79	.95
	1400	660	44.0	12.9	2.43	.62	.76	.90	43.0	12.6	2.72	.63	.78	.92	41.5	12.2	3.04	.64	.79	.95	39.5	11.6	3.42	.65	.81	.97
	1600	755	45.5	13.3	2.45	.64	.80	.95	44.0	12.9	2.73	.65	.81	.97	42.0	12.3	3.05	.66	.83	.99	40.5	11.9	3.42	.67	.85	1.00
71°F (22°C)	1305	615	46.0	13.5	2.45	.46	.59	.73	44.5	13.0	2.73	.46	.60	.73	42.5	12.5	3.06	.47	.61	.75	41.0	12.0	3.43	.47	.62	.77
	1400	660	46.5	13.6	2.46	.46	.61	.71	45.0	13.2	2.74	.47	.62	.75	43.5	12.7	3.06	.47	.63	.77	41.5	12.2	3.43	.48	.64	.79
	1600	755	48.0	14.1	2.48	.48	.63	.78	46.0	13.5	2.75	.48	.64	.79	44.5	13.0	3.08	.48	.65		42.5	12.5	3.45	.49	.66	

HEATING CAPACITY - HP13-042 with

[C33-62D + G61MPV-60D-135]
[C33-62D + G71MPP-60D-135]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
cfm	L/s	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh
1305	615	44.4	13.0	2.84	35.0	10.3	2.64	25.1	7.4	2.42	18.4	5.4	2.17	9.3	2.7	1.60				
1400	660	44.6	13.1	2.79	35.2	10.3	2.59	25.3	7.4	2.38	18.6	5.5	2.13	9.5	2.8	1.55				
1600	755	45.1	13.2	2.70	35.7	10.5	2.49	25.8	7.6	2.28	19.1	5.6	2.03	10.0	2.9	1.45				

HEATING PERFORMANCE at 1400 cfm (660 L/s) Indoor Coil Air Volume HP13-042 with

[C33-62D + G61MPV-60D-135]
[C33-62D + G71MPP-60D-135]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.79	44.6	13.1
60	16	2.75	42.4	12.4
55	13	2.70	40.3	11.8
50	10	2.65	38.1	11.2
47	8	2.62	36.8	10.8
45	7	2.59	35.2	10.3
40	4	2.51	31.1	9.1
35	2	2.42	27.0	7.9
30	-1	2.40	26.2	7.7
25	-4	2.38	25.3	7.4
20	-7	2.35	24.4	7.2
17	-8	2.34	23.9	7.0
15	-9	2.32	23.0	6.7
10	-12	2.27	20.9	6.1
5	-15	2.13	18.6	5.5
0	-18	1.98	16.3	4.8
-5	-21	1.84	14.0	4.1
-10	-23	1.69	11.7	3.4
-15	-26	1.55	9.5	2.8
-20	-29	1.40	7.2	2.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[CR33-48B-F + G60DFV-36B-090]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1235	585	40.0	11.7	2.39	.75	.88	1.00	39.0	11.4	2.70	.76	.90	1.00	37.6	11.0	3.05	.77	.92	1.00	36.0	10.6	3.46	.79	.94	1.00
	1405	665	41.0	12.0	2.40	.77	.91	1.00	40.0	11.7	2.70	.78	.93	1.00	38.5	11.3	3.05	.80	.96	1.00	36.8	10.8	3.46	.82	.98	1.00
	1555	735	42.0	12.3	2.40	.79	.94	1.00	40.5	11.9	2.70	.80	.96	1.00	39.0	11.4	3.05	.82	.99	1.00	37.6	11.0	3.46	.84	.99	1.00
67°F (19°C)	1235	585	42.5	12.5	2.41	.60	.72	.85	41.5	12.2	2.72	.60	.73	.86	40.0	11.7	3.05	.61	.75	.88	38.5	11.3	3.45	.62	.76	.91
	1405	665	43.5	12.7	2.41	.61	.75	.88	42.5	12.5	2.71	.62	.76	.90	40.5	11.9	3.06	.62	.77	.92	39.0	11.4	3.45	.64	.79	.94
	1555	735	44.5	13.0	2.42	.62	.77	.91	43.0	12.6	2.72	.63	.78	.93	41.5	12.2	3.06	.64	.80	.95	39.5	11.6	3.45	.65	.82	.98
71°F (22°C)	1235	585	45.0	13.2	2.43	.45	.58	.70	43.5	12.7	2.72	.46	.59	.71	42.0	12.3	3.07	.45	.60	.72	40.5	11.9	3.45	.46	.61	.74
	1405	665	46.0	13.5	2.43	.46	.60	.72	44.5	13.0	2.73	.46	.60	.73	43.0	12.6	3.07	.46	.61	.75	41.5	12.2	3.46	.47	.62	.77
	1555	735	46.5	13.6	2.44	.47	.61	.75	45.5	13.3	2.73	.47	.62	.76	43.5	12.7	3.07	.47	.63	.78	42.0	12.3	3.46	.47	.64	.79

COOLING CAPACITY - HP13-042 with

[CR33-48B-F + G61MPV-36B-070]

[CR33-48B-F + G71MPP-36B-070]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1395	660	41.0	12.0	2.40	.77	.91	1.00	40.0	11.7	2.70	.78	.93	1.00	38.5	11.3	3.05	.80	.95	1.00	36.8	10.8	3.46	.82	.98	1.00
	1560	735	42.0	12.3	2.40	.79	.94	1.00	40.5	11.9	2.70	.81	.96	1.00	39.0	11.4	3.05	.82	.98	1.00	37.6	11.0	3.46	.84	1.00	1.00
	1395	660	43.5	12.7	2.41	.61	.74	.88	42.0	12.3	2.71	.62	.76	.90	40.5	11.9	3.06	.62	.77	.92	39.0	11.4	3.45	.64	.79	.94
67°F (19°C)	1560	735	44.5	13.0	2.42	.62	.77	.91	43.0	12.6	2.72	.63	.78	.93	41.5	12.2	3.06	.64	.80	.95	39.5	11.6	3.45	.65	.82	.98
	1395	660	46.0	13.5	2.43	.46	.60	.72	44.5	13.0	2.73	.46	.60	.74	43.0	12.6	3.07	.46	.61	.75	41.5	12.2	3.46	.47	.62	.77
	1560	735	46.5	13.6	2.44	.47	.61	.75	45.5	13.3	2.74	.47	.62	.76	43.5	12.7	3.07	.47	.63	.77	42.0	12.3	3.46	.47	.64	.79

HEATING CAPACITY - HP13-042 with

[CR33-48B-F + G60DFV-36B-090]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW					
1235	585	49.0	14.4	3.76	38.4	11.3	3.25	27.2	8.0	2.67	20.0	5.9	2.46	10.0	2.9	1.85	
1405	660	49.4	14.5	3.66	38.8	11.4	3.14	27.6	8.1	2.56	20.4	6.0	2.35	10.4	3.0	1.74	
1555	735	49.8	14.6	3.57	39.2	11.5	3.06	28.0	8.2	2.48	20.8	6.1	2.27	10.8	3.2	1.66	

HEATING CAPACITY - HP13-042 with

[CR33-48B-F + G61MPV-36B-070]

[CR33-48B-F + G71MPP-36B-070]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW					
1395	660	48.9	14.3	3.66	38.3	11.2	3.15	27.1	7.9	2.56	19.9	5.8	2.35	9.7	2.8	1.74	
1560	735	49.3	14.4	3.57	38.7	11.3	3.06	27.5	8.1	2.47	20.2	5.9	2.26	10.1	3.0	1.65	

HEATING PERFORMANCE at 1405 cfm (660 L/s) Indoor Coil Air Volume HP13-042 with [CR33-48B-F + G60DFV-36B-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.66	49.4	14.5
60	16	3.55	47.0	13.8
55	13	3.45	44.6	13.1
50	10	3.34	42.2	12.4
47	8	3.28	40.7	11.9
45	7	3.14	38.8	11.4
40	4	2.80	34.1	10.0
35	2	2.45	29.3	8.6
30	-1	2.51	28.5	8.4
25	-4	2.56	27.6	8.1
20	-7	2.62	26.8	7.9
17	-8	2.65	26.3	7.7
15	-9	2.61	25.3	7.4
10	-12	2.50	22.9	6.7
5	-15	2.35	20.4	6.0
0	-18	2.20	17.9	5.2
-5	-21	2.05	15.4	4.5
-10	-23	1.89	12.9	3.8
-15	-26	1.74	10.4	3.0
-20	-29	1.59	7.9	2.3

HEATING PERFORMANCE at 1395 cfm (660 L/s) Indoor Coil Air Volume HP13-042 with [CR33-48B-F + G61MPV-36B-070]

[CR33-48B-F + G71MPP-36B-070]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.66	49.8	14.6
60	16	3.56	47.4	13.9
55	13	3.45	45.0	13.2
50	10	3.35	42.5	12.5
47	8	3.28	41.1	12.0
45	7	3.15	39.2	11.5
40	4	2.80	34.4	10.1
35	2	2.45	29.6	8.7
30	-1	2.51	28.8	8.4
25	-4	2.56	28.0	8.2
20	-7	2.62	27.1	7.9
17	-8	2.65	26.6	7.8
15	-9	2.61	25.7	7.5
10	-12	2.50	23.2	6.8
5	-15	2.35	20.7	6.1
0	-18	2.20	18.2	5.3
-5	-21	2.05	15.6	4.6
-10	-23	1.90	13.1	3.8
-15	-26	1.74	10.5	3.1
-20	-29	1.59	8.0	2.3

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[CR33-48C-F + G60DFV-60C-090]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1390	655	41.0	12.0	2.40	.77	.91	1.00	40.0	11.7	2.70	.78	.93	1.00	38.5	11.3	3.05	.80	.95	1.00	36.8	10.8	3.46	.81	.97	1.00
67°F (19°C)	1390	655	43.5	12.7	2.41	.61	.74	.88	42.0	12.3	2.71	.62	.76	.89	40.5	11.9	3.06	.62	.77	.92	39.0	11.4	3.45	.64	.79	.94
71°F (22°C)	1390	655	46.0	13.5	2.43	.46	.60	.72	44.5	13.0	2.73	.46	.60	.73	43.0	12.6	3.07	.46	.61	.75	41.5	12.2	3.46	.47	.62	.76

COOLING CAPACITY - HP13-042 with

[CR33-48C-F + G60DFV-60C-110]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1340	630	41.0	12.0	2.40	.76	.90	1.00	39.5	11.6	2.70	.77	.92	1.00	38.0	11.1	3.05	.79	.94	1.00	36.6	10.7	3.46	.81	.97	1.00
67°F (19°C)	1340	630	43.5	12.7	2.41	.61	.74	.87	42.0	12.3	2.71	.61	.75	.89	40.5	11.9	3.05	.62	.76	.91	39.0	11.4	3.45	.63	.78	.93
71°F (22°C)	1340	630	45.5	13.3	2.43	.45	.59	.71	44.5	13.0	2.73	.46	.60	.73	42.5	12.5	3.07	.46	.61	.74	41.0	12.0	3.45	.46	.62	.76

HEATING CAPACITY - HP13-042 with

[CR33-48C-F + G60DFV-60C-090]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1390	655	49.1	14.4	3.67	38.5	11.3	3.15	27.3	8.0	2.56	20.1	5.9	2.35	10.3	3.0	1.74
1563	740	49.5	14.5	3.57	38.9	11.4	3.05	27.7	8.1	2.47	20.5	6.0	2.26	10.6	3.1	1.65

HEATING CAPACITY - HP13-042 with

[CR33-48C-F + G60DFV-60C-110]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1340	630	49.1	14.4	3.68	38.5	11.3	3.18	27.2	8.0	2.61	20.0	5.9	2.40	10.1	3.0	1.80
1450	685	49.3	14.4	3.62	38.7	11.3	3.12	27.5	8.1	2.55	20.2	5.9	2.34	10.3	3.0	1.73
1645	775	49.8	14.6	3.52	39.2	11.5	3.02	27.9	8.2	2.44	20.7	6.1	2.24	10.8	3.2	1.63

HEATING PERFORMANCE at 1390 cfm (655 L/s) Indoor Coil Air Volume HP13-042 with [CR33-48C-F + G60DFV-60C-090]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.67	49.1	14.4
60	16	3.56	46.7	13.7
55	13	3.46	44.3	13.0
50	10	3.35	41.9	12.3
47	8	3.29	40.4	11.8
45	7	3.15	38.5	11.3
40	4	2.80	33.8	9.9
35	2	2.46	29.0	8.5
30	-1	2.51	28.2	8.3
25	-4	2.56	27.3	8.0
20	-7	2.62	26.5	7.8
17	-8	2.65	26.0	7.6
15	-9	2.61	25.0	7.3
10	-12	2.50	22.6	6.6
5	-15	2.35	20.1	5.9
0	-18	2.20	17.7	5.2
-5	-21	2.05	15.2	4.5
-10	-23	1.90	12.7	3.7
-15	-26	1.74	10.3	3.0
-20	-29	1.59	7.8	2.3

HEATING PERFORMANCE at 1450 cfm (685 L/s) Indoor Coil Air Volume HP13-042 with [CR33-48C-F + G60DFV-60C-110]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.62	49.3	14.4
60	16	3.52	46.9	13.7
55	13	3.42	44.5	13.0
50	10	3.32	42.1	12.3
47	8	3.25	40.6	11.9
45	7	3.12	38.7	11.3
40	4	2.78	33.9	9.9
35	2	2.43	29.2	8.6
30	-1	2.49	28.3	8.3
25	-4	2.55	27.5	8.1
20	-7	2.60	26.6	7.8
17	-8	2.64	26.1	7.6
15	-9	2.60	25.1	7.4
10	-12	2.49	22.7	6.7
5	-15	2.34	20.2	5.9
0	-18	2.19	17.8	5.2
-5	-21	2.04	15.3	4.5
-10	-23	1.89	12.8	3.8
-15	-26	1.73	10.3	3.0
-20	-29	1.58	7.8	2.3

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), and various capacity metrics (Total Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb).

COOLING CAPACITY - HP13-042 with

[CR33-50/60C-F + G60DFV-60C-110]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), and various capacity metrics (Total Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb).

HEATING CAPACITY - HP13-042 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with columns for Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), and various capacity metrics (Total Heating Capacity, Comp. Motor kW Input).

HEATING CAPACITY - HP13-042 with

[CR33-50/60C-F + G60DFV-60C-110]

Table with columns for Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), and various capacity metrics (Total Heating Capacity, Comp. Motor kW Input).

HEATING PERFORMANCE at 1390 cfm (655 L/s) Indoor Coil Air Volume HP13-042 with [CR33-50/60C-F + G60DFV-60C-090]

Table with columns for *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

HEATING PERFORMANCE at 1450 cfm (685 L/s) Indoor Coil Air Volume HP13-042 with [CR33-50/60C-F + G60DFV-60C-110]

Table with columns for *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

[CH23-41 + G60UHV-36B-090]

Table with 24 columns: Entering Wet Bulb Temperature, Total Air Volume, Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb at 85°F, 95°F, 105°F, and 115°F.

COOLING CAPACITY - HP13-042 with

[CH23-41 + G60UHV-60C-090]

Table with 24 columns: Entering Wet Bulb Temperature, Total Air Volume, Cooling Capacity, Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb at 85°F, 95°F, 105°F, and 115°F.

HEATING CAPACITY - HP13-042 with

[CH23-41 + G60UHV-36B-090]

Table with 16 columns: Indoor Coil Air Volume, Total Heating Capacity, Comp. Motor kW Input at 65°F, 45°F, 25°F, 5°F, and -15°F.

HEATING CAPACITY - HP13-042 with

[CH23-41 + G60UHV-60C-090]

Table with 16 columns: Indoor Coil Air Volume, Total Heating Capacity, Comp. Motor kW Input at 65°F, 45°F, 25°F, 5°F, and -15°F.

HEATING PERFORMANCE at 1385 cfm (655 L/s) Indoor Coil

Air Volume HP13-042 with [CH23-41 + G60UHV-36B-090]

Table with 5 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1355 cfm (640 L/s) Indoor Coil

Air Volume HP13-042 with [CH23-41 + G60UHV-60C-090]

Table with 5 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtuh, kW).

RATINGS

3.5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-042 with

**[CH23-51 + G61MPV-60C-090]
[CH23-51 + G71MPP-60C-090]**

Table with 23 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and four sets of data for Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F) including Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-042 with

**[CH23-51 + G61MPV-60C-110]
[CH23-51 + G71MPP-60C-110]**

Table with 23 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), and four sets of data for Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F) including Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-042 with

**[CH23-51 + G61MPV-60C-090]
[CH23-51 + G71MPP-60C-110]**

Table with 14 columns: Indoor Coil Air Volume (70°F db, 21°C db) and five sets of data for Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) including Total Heating Capacity, Comp. Motor kW Input, and Total Heating Capacity.

HEATING CAPACITY - HP13-042 with

**[CH23-51 + G61MPV-60C-110]
[CH23-51 + G71MPP-60C-110]**

Table with 14 columns: Indoor Coil Air Volume (70°F db, 21°C db) and five sets of data for Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) including Total Heating Capacity, Comp. Motor kW Input, and Total Heating Capacity.

HEATING PERFORMANCE at 1380 cfm (650 L/s) Indoor Coil Air Volume HP13-042 with

**[CH23-51 + G61MPV-60C-090]
[CH23-51 + G71MPP-60C-090]**

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

HEATING PERFORMANCE at 1405 cfm (665 L/s) Indoor Coil Air Volume HP13-042 with

**[CH23-51 + G61MPV-60C-110]
[CH23-51 + G71MPP-60C-110]**

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

AIR HANDLERS

COOLING CAPACITY - HP13-048 with

[CB26UH-048]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1400	660	50.0	14.7	3.21	.75	.87	.99	48.5	14.2	3.58	.76	.89	1.00	46.5	13.6	4.01	.77	.90	1.00	44.5	13.0	4.52	.78	.92	1.00
1600	755	51.5	15.1	3.22	.77	.91	1.00	50.0	14.7	3.59	.78	.93	1.00	48.0	14.1	4.03	.80	.95	1.00	46.0	13.5	4.53	.81	.97	1.00	
67°F (19°C)	1400	660	52.5	15.4	3.24	.60	.72	.84	51.0	14.9	3.61	.61	.73	.85	49.0	14.4	4.04	.61	.74	.87	47.0	13.8	4.55	.62	.76	.89
1600	755	54.0	15.8	3.26	.62	.75	.88	52.5	15.4	3.63	.62	.76	.90	50.5	14.8	4.06	.63	.78	.91	48.0	14.1	4.56	.64	.79	.94	
71°F (22°C)	1400	660	55.5	16.3	3.28	.47	.58	.70	53.5	15.7	3.65	.47	.59	.71	51.5	15.1	4.08	.47	.60	.73	49.5	14.5	4.58	.47	.61	.77
1600	755	57.0	16.7	3.31	.47	.61	.73	55.0	16.1	3.67	.48	.61	.74	53.0	15.5	4.10	.48	.62	.75	51.0	14.9	4.59	.48	.63	.73	

COOLING CAPACITY - HP13-048 with

[CB27UH-048]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1400	660	48.5	14.2	3.18	.74	.87	.99	47.0	13.8	3.56	.75	.89	1.00	45.0	13.2	4.00	.76	.90	1.00	43.0	12.6	4.51	.77	.92	1.00
1600	755	50.0	14.7	3.20	.77	.91	1.00	48.0	14.1	3.57	.78	.93	1.00	46.5	13.6	4.01	.79	.95	1.00	44.5	13.0	4.52	.81	.97	1.00	
67°F (19°C)	1400	660	51.0	14.9	3.22	.59	.72	.84	49.5	14.5	3.59	.59	.72	.85	47.5	13.9	4.03	.60	.74	.87	45.5	13.3	4.54	.61	.75	.89
1600	755	52.5	15.4	3.24	.60	.74	.88	50.5	14.8	3.61	.61	.75	.90	49.0	14.4	4.04	.62	.77	.92	47.0	13.8	4.55	.63	.79	.94	
71°F (22°C)	1400	660	53.5	15.7	3.26	.45	.57	.69	52.0	15.2	3.63	.45	.58	.70	50.0	14.7	4.06	.45	.59	.71	48.0	14.1	4.56	.46	.60	.73
1600	755	55.0	16.1	3.28	.46	.59	.72	53.5	15.7	3.65	.46	.60	.73	51.0	14.9	4.07	.46	.61	.75	49.0	14.4	4.57	.46	.62	.76	

HEATING CAPACITY - HP13-048 with

[CB26UH-048]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input					
1400	660	57.1	16.7	3.38	44.5	13.0	3.27	30.9	9.1	3.13	24.1	7.1	3.00	12.1	3.5	2.19
1600	755	57.3	16.8	3.25	44.8	13.1	3.13	31.1	9.1	2.99	24.3	7.1	2.86	12.3	3.6	2.05

HEATING CAPACITY - HP13-048 with

[CB27UH-048]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)		45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)						
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input					
1400	660	57.1	16.7	3.16	44.1	12.9	2.96	30.0	8.8	2.73	22.9	6.7	2.53	11.5	3.4	1.87
1600	755	57.6	16.9	3.05	44.6	13.1	2.85	30.6	9.0	2.62	23.4	6.9	2.42	12.0	3.5	1.76

HEATING PERFORMANCE at 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with

[CB26UH-048]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.25	57.3	16.8
60	16	3.23	54.6	16.0
55	13	3.21	51.9	15.2
50	10	3.20	49.2	14.4
47	8	3.19	47.5	13.9
45	7	3.13	44.8	13.1
40	4	3.00	37.9	11.1
35	2	2.87	31.1	9.1
30	-1	2.93	31.1	9.1
25	-4	2.99	31.1	9.1
20	-7	3.05	31.2	9.1
17	-8	3.08	31.2	9.1
15	-9	3.08	30.1	8.8
10	-12	3.06	27.4	8.0
5	-15	2.86	24.4	7.2
0	-18	2.66	21.4	6.3
-5	-21	2.46	18.4	5.4
-10	-23	2.25	15.4	4.5
-15	-26	2.05	12.4	3.6
-20	-29	1.85	9.4	2.8

HEATING PERFORMANCE at 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with

[CB27UH-048]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.05	57.5	16.9
60	16	3.01	54.7	16.0
55	13	2.96	51.8	15.2
50	10	2.92	49.0	14.4
47	8	2.90	47.3	13.9
45	7	2.85	44.5	13.0
40	4	2.71	37.7	11.0
35	2	2.58	30.9	9.1
30	-1	2.60	30.7	9.0
25	-4	2.62	30.5	8.9
20	-7	2.64	30.3	8.9
17	-8	2.65	30.2	8.9
15	-9	2.63	29.1	8.5
10	-12	2.59	26.2	7.7
5	-15	2.42	23.4	6.9
0	-18	2.26	20.5	6.0
-5	-21	2.09	17.6	5.2
-10	-23	1.92	14.8	4.3
-15	-26	1.76	11.9	3.5
-20	-29	1.59	9.1	2.7

RATINGS

4 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

AIR HANDLERS

COOLING CAPACITY - HP13-048 with

[CB27UH-060]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1260	595	46.5	13.6	3.16	.71	.83	.93	45.0	13.2	3.54	.72	.84	.95	43.5	12.7	3.99	.73	.85	.97	41.5	12.2	4.50	.74	.87	.98
1600	755	49.0	14.4	3.19	.75	.88	.99	47.5	13.9	3.57	.76	.90	1.00	45.5	13.3	4.01	.77	.92	1.00	44.0	12.9	4.52	.79	.94	1.00	
67°F (19°C)	1260	595	49.0	14.4	3.19	.58	.69	.80	47.5	13.9	3.57	.58	.70	.81	45.5	13.3	4.01	.59	.71	.82	44.0	12.9	4.52	.60	.72	.84
1600	755	51.5	15.1	3.23	.60	.73	.85	50.0	14.7	3.60	.61	.74	.87	48.0	14.1	4.03	.62	.75	.89	46.0	13.5	4.54	.62	.77	.91	
71°F (22°C)	1260	595	51.0	14.9	3.22	.45	.57	.67	49.5	14.5	3.59	.45	.57	.68	48.0	14.1	4.03	.45	.58	.69	46.0	13.5	4.54	.46	.58	.70
1600	755	54.0	15.8	3.26	.46	.59	.71	52.5	15.4	3.63	.46	.60	.72	50.5	14.8	4.06	.46	.60	.73	48.5	14.2	4.56	.46	.61	.75	

COOLING CAPACITY - HP13-048 with

[CB30M-51]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1400	660	49.0	14.4	3.19	.75	.88	1.00	47.0	13.8	3.56	.76	.90	1.00	45.5	13.3	4.00	.77	.92	1.00	43.5	12.7	4.52	.79	.94	1.00
1600	755	50.0	14.7	3.20	.78	.92	1.00	48.5	14.2	3.58	.79	.94	1.00	46.5	13.6	4.02	.81	.96	1.00	44.5	13.0	4.53	.82	.98	1.00	
67°F (19°C)	1400	660	51.5	15.1	3.22	.60	.73	.85	50.0	14.7	3.60	.61	.74	.87	48.0	14.1	4.03	.61	.75	.88	46.0	13.5	4.54	.62	.76	.90
1600	755	53.0	15.5	3.24	.62	.76	.89	51.0	14.9	3.61	.63	.77	.91	49.0	14.4	4.04	.63	.78	.93	47.0	13.8	4.55	.64	.80	.95	
71°F (22°C)	1400	660	54.0	15.8	3.26	.46	.59	.70	52.0	15.2	3.63	.47	.59	.71	50.5	14.8	4.06	.47	.60	.73	48.5	14.2	4.56	.47	.61	.74
1600	755	55.5	16.3	3.28	.47	.61	.74	53.5	15.7	3.65	.47	.61	.75	51.5	15.1	4.08	.48	.62	.76	49.5	14.5	4.58	.48	.63	.78	

HEATING CAPACITY - HP13-048 with

[CB27UH-060]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	
1260	595	56.7	16.6	3.27	43.7	12.8	3.07	29.7	8.7	2.85	22.5	6.6	2.65	11.1	3.3	1.98
1600	755	57.5	16.9	3.04	44.5	13.0	2.85	30.5	8.9	2.62	23.3	6.8	2.43	11.9	3.5	1.76

HEATING CAPACITY - HP13-048 with

[CB30M-51]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	Total Heating Capacity	Comp. Motor kW Input	
1400	660	57.2	16.8	3.12	44.5	13.0	2.99	30.6	9.0	2.83	23.7	6.9	2.71	11.9	3.5	1.98
1600	755	57.6	16.9	3.01	44.8	13.1	2.88	31.0	9.1	2.72	24.1	7.1	2.59	12.2	3.6	1.87

HEATING PERFORMANCE at 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with

[CB27UH-060]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.04	57.5	16.9
60	16	3.00	54.7	16.0
55	13	2.96	51.8	15.2
50	10	2.92	49.0	14.4
47	8	2.90	47.3	13.9
45	7	2.85	44.5	13.0
40	4	2.71	37.7	11.0
35	2	2.58	30.9	9.1
30	-1	2.60	30.7	9.0
25	-4	2.62	30.5	8.9
20	-7	2.64	30.3	8.9
17	-8	2.66	30.2	8.9
15	-9	2.64	29.0	8.5
10	-12	2.60	26.2	7.7
5	-15	2.43	23.3	6.8
0	-18	2.26	20.5	6.0
-5	-21	2.10	17.6	5.2
-10	-23	1.93	14.8	4.3
-15	-26	1.76	11.9	3.5
-20	-29	1.59	9.1	2.7

HEATING PERFORMANCE at 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with

[CB30M-51]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.01	57.6	16.9
60	16	2.99	54.8	16.1
55	13	2.97	52.0	15.2
50	10	2.94	49.2	14.4
47	8	2.93	47.6	14.0
45	7	2.88	44.8	13.1
40	4	2.75	38.0	11.1
35	2	2.61	31.1	9.1
30	-1	2.67	31.0	9.1
25	-4	2.72	31.0	9.1
20	-7	2.77	31.0	9.1
17	-8	2.80	30.9	9.1
15	-9	2.80	29.8	8.7
10	-12	2.77	27.0	7.9
5	-15	2.59	24.1	7.1
0	-18	2.41	21.1	6.2
-5	-21	2.23	18.2	5.3
-10	-23	2.05	15.2	4.5
-15	-26	1.87	12.2	3.6
-20	-29	1.68	9.3	2.7

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

AIR HANDLERS

COOLING CAPACITY - HP13-048 with

[CBX32MV-048] [CBX40UHV-048]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
	Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb				
				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C				75°F 24°C	80°F 27°C	85°F 29°C		
cfm	L/s	kBtuh	kW				kBtuh	kW				kBtuh	kW				kBtuh	kW								
63°F (17°C)	1425	675	49.0	14.4	3.19	.75	.89	1.00	47.5	13.9	3.56	.76	.90	1.00	45.5	13.3	4.00	.78	.92	1.00	43.5	12.7	4.52	.79	.94	1.00
	1625	765	50.0	14.7	3.20	.78	.93	1.00	48.5	14.2	3.58	.79	.94	1.00	46.5	13.6	4.02	.81	.96	1.00	44.5	13.0	4.53	.82	.98	1.00
	1820	860	51.5	15.1	3.22	.81	.97	1.00	49.5	14.5	3.60	.83	.98	1.00	48.0	14.1	4.03	.84	.99	1.00	46.0	13.5	4.53	.86	1.00	1.00
67°F (19°C)	1425	675	51.5	15.1	3.23	.60	.73	.86	50.0	14.7	3.60	.61	.74	.87	48.0	14.1	4.03	.62	.75	.89	46.0	13.5	4.54	.62	.77	.91
	1625	765	53.0	15.5	3.25	.62	.76	.90	51.0	14.9	3.61	.62	.77	.91	49.0	14.4	4.04	.63	.78	.93	47.0	13.8	4.55	.64	.80	.95
	1820	860	54.0	15.8	3.26	.64	.79	.94	52.0	15.2	3.63	.65	.81	.96	50.5	14.8	4.06	.66	.82	.97	48.0	14.1	4.56	.67	.84	.99
71°F (22°C)	1425	675	54.0	15.8	3.27	.46	.59	.71	52.5	15.4	3.63	.46	.59	.72	50.5	14.8	4.06	.47	.60	.73	48.5	14.2	4.56	.47	.61	.74
	1625	765	55.5	16.3	3.28	.47	.60	.74	53.5	15.7	3.65	.47	.61	.75	51.5	15.1	4.08	.47	.62	.76	49.5	14.5	4.58	.48	.63	.78
	1820	860	56.5	16.6	3.30	.48	.63	.77	55.0	16.1	3.67	.49	.64	.78	53.0	15.5	4.10	.49	.65	.80	50.5	14.8	4.59	.50	.66	.82

HEATING CAPACITY - HP13-048 with

[CBX32MV-048] [CBX40UHV-048]

Indoor Coil Air Volume 70°F db (21°C db)		Air Temperature Entering Outdoor Coil														
		65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
cfm	L/s	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1425	675	57.1	16.7	3.10	44.3	13.0	2.97	30.6	9.0	2.82	23.6	6.9	2.69	12.0	3.5	1.97
1625	765	57.2	16.8	2.98	44.4	13.0	2.86	30.6	9.0	2.70	23.7	6.9	2.58	12.1	3.5	1.86
1820	860	58.3	17.1	2.92	45.6	13.4	2.79	31.8	9.3	2.64	24.9	7.3	2.51	13.2	3.9	1.79

HEATING PERFORMANCE at 1625 cfm (765 L/s) Indoor Coil Air Volume HP13-048 with [CBX32MV-048] [CBX40UHV-048]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	2.98	57.2	16.8
60	16	2.96	54.4	15.9
55	13	2.94	51.6	15.1
50	10	2.92	48.8	14.3
47	8	2.91	47.2	13.8
45	7	2.86	44.4	13.0
40	4	2.73	37.6	11.0
35	2	2.60	30.8	9.0
30	-1	2.65	30.7	9.0
25	-4	2.70	30.6	9.0
20	-7	2.76	30.6	9.0
17	-8	2.79	30.5	8.9
15	-9	2.78	29.4	8.6
10	-12	2.76	26.7	7.8
5	-15	2.58	23.7	6.9
0	-18	2.40	20.8	6.1
-5	-21	2.22	17.9	5.2
-10	-23	2.04	15.0	4.4
-15	-26	1.86	12.1	3.5
-20	-29	1.67	9.2	2.7

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section. Expanded rating tables are sorted by smallest to largest indoor unit model no.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-048 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with 23 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), 85°F (29°C) cooling capacity (Total, Comp. Motor kW, Sensible To Total Ratio (S/T) Dry Bulb), 95°F (35°C) cooling capacity, 105°F (41°C) cooling capacity, and 115°F (46°C) cooling capacity. Rows include temperatures 63°F, 67°F, and 71°F.

COOLING CAPACITY - HP13-048 with

[CR33-50/60C-F + G60DFV-60C-110]

Table with 23 columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), 85°F (29°C) cooling capacity (Total, Comp. Motor kW, Sensible To Total Ratio (S/T) Dry Bulb), 95°F (35°C) cooling capacity, 105°F (41°C) cooling capacity, and 115°F (46°C) cooling capacity. Rows include temperatures 63°F, 67°F, and 71°F.

HEATING CAPACITY - HP13-048 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with 17 columns: Indoor Coil Air Volume (70°F db, 21°C db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtu/h, kW), and Comp. Motor kW Input. Rows include air volumes 1390, 1685, and 1860 cfm.

HEATING CAPACITY - HP13-048 with

[CR33-50/60C-F + G60DFV-60C-110]

Table with 17 columns: Indoor Coil Air Volume (70°F db, 21°C db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtu/h, kW), and Comp. Motor kW Input. Rows include air volumes 1450, 1645, and 1800 cfm.

HEATING PERFORMANCE at 1685 cfm (795 L/s) Indoor Coil Air Volume HP13-048 with [CR33-50/60C-F + G60DFV-60C-090]

HEATING PERFORMANCE at 1645 cfm (775 L/s) Indoor Coil Air Volume HP13-048 with [CR33-50/60C-F + G60DFV-60C-110]

Table with 6 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW). Rows range from 65°F to -20°F.

Table with 6 columns: Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtu/h, kW). Rows range from 65°F to -20°F.

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.
Expanded rating tables are sorted by smallest to largest indoor unit model no.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-048 with

[CR33-60D-F + G61MPV-60D-135]
[CR33-60D-F + G71MPP-60D-135]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1500	710	48.5	14.2	3.18	.75	.89	.99	47.0	13.8	3.57	.77	.90	1.00	45.5	13.3	4.00	.78	.92	1.00	43.5	12.7	4.51	.79	.94	1.00
	1600	755	49.5	14.5	3.20	.77	.91	1.00	47.5	13.9	3.57	.78	.93	1.00	46.0	13.5	4.01	.80	.95	1.00	44.0	12.9	4.52	.81	.97	1.00
	1780	840	50.0	14.7	3.20	.79	.94	1.00	48.5	14.2	3.58	.81	.96	1.00	47.0	13.8	4.02	.82	.98	1.00	45.0	13.2	4.53	.84	.99	1.00
67°F (19°C)	1500	710	51.0	14.9	3.22	.60	.73	.86	49.5	14.5	3.60	.61	.74	.87	48.0	14.1	4.03	.62	.76	.89	46.0	13.5	4.54	.63	.77	.91
	1600	755	52.0	15.2	3.23	.62	.75	.88	50.5	14.8	3.60	.62	.76	.90	48.5	14.2	4.04	.63	.77	.91	46.5	13.6	4.54	.64	.79	.94
	1780	840	53.0	15.5	3.24	.63	.77	.91	51.5	15.1	3.62	.64	.79	.93	49.5	14.5	4.05	.65	.80	.95	47.5	13.9	4.55	.66	.82	.97
71°F (22°C)	1500	710	54.0	15.8	3.26	.46	.59	.71	52.0	15.2	3.63	.47	.60	.72	50.5	14.8	4.06	.47	.60	.73	48.5	14.2	4.56	.47	.62	.75
	1600	755	54.5	16.0	3.27	.47	.60	.73	53.0	15.5	3.64	.47	.61	.74	51.0	14.9	4.07	.48	.62	.75	49.0	14.4	4.56	.48	.63	.77
	1780	840	55.5	16.3	3.28	.48	.62	.75	53.5	15.7	3.65	.48	.63	.76	52.0	15.2	4.08	.49	.64	.78	49.5	14.5	4.57	.49	.65	.80

HEATING CAPACITY - HP13-048 with

[CR33-60D-F + G61MPV-60D-135]
[CR33-60D-F + G71MPP-60D-135]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil																			
	65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	
1500	710	56.9	16.7	3.06	44.2	13.0	2.90	30.3	8.9	2.72	23.4	6.9	2.58	11.7	3.4	1.87				
1600	755	57.4	16.8	3.01	44.6	13.1	2.86	30.8	9.0	2.67	23.9	7.0	2.53	12.1	3.5	1.83				
1780	840	57.9	17.0	2.94	45.1	13.2	2.79	31.3	9.2	2.60	24.3	7.1	2.46	12.6	3.7	1.76				

HEATING PERFORMANCE at 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with [CR33-60D-F + G61MPV-60D-135]
[CR33-60D-F + G71MPP-60D-135]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.01	57.4	16.8
60	16	2.98	54.6	16.0
55	13	2.96	51.8	15.2
50	10	2.93	49.1	14.4
47	8	2.91	47.4	13.9
45	7	2.86	44.6	13.1
40	4	2.72	37.8	11.1
35	2	2.58	31.0	9.1
30	-1	2.63	30.9	9.1
25	-4	2.67	30.8	9.0
20	-7	2.72	30.7	9.0
17	-8	2.75	30.7	9.0
15	-9	2.74	29.6	8.7
10	-12	2.71	26.8	7.9
5	-15	2.53	23.9	7.0
0	-18	2.36	20.9	6.1
-5	-21	2.18	18.0	5.3
-10	-23	2.00	15.1	4.4
-15	-26	1.83	12.1	3.5
-20	-29	1.65	9.2	2.7

RATINGS

4 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section. Expanded rating tables are sorted by smallest to largest indoor unit model no.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-048 with

[CH33-50/60C-2F + G60UHV-60C-090]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-048 with

[CH33-50/60C-2F + G60UHV-60C-110]

Table with columns: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-048 with

[CH33-50/60C-2F + G60UHV-60C-090]

Table with columns: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), and Comp. Motor kW Input.

HEATING CAPACITY - HP13-048 with

[CH33-50/60C-2F + G60UHV-60C-110]

Table with columns: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), and Comp. Motor kW Input.

HEATING PERFORMANCE AT 1635 cfm (770 L/s) Indoor Coil Air Volume HP13-048 with [CH33-50/60C-2F + G60UHV-60C-090]

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

HEATING PERFORMANCE AT 1600 cfm (755 L/s) Indoor Coil Air Volume HP13-048 with [CH33-50/60C-2F + G60UHV-60C-110]

Table with columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

RATINGS

5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

[CB26UH-060-R]

COOLING CAPACITY - HP13-060 with

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1800	850	57.0	16.7	3.67	.77	.91	1.00	55.0	16.1	4.10	.78	.93	1.00	53.0	15.5	4.60	.80	.95	1.00	51.0	14.9	5.16	.81	.97	1.00
	1925	910	58.0	17.0	3.68	.78	.94	1.00	56.0	16.4	4.11	.80	.95	1.00	53.5	15.7	4.61	.81	.97	1.00	51.5	15.1	5.17	.83	1.00	1.00
67°F (19°C)	1800	850	60.5	17.7	3.72	.61	.74	.88	58.5	17.1	4.15	.61	.76	.90	56.0	16.4	4.64	.62	.77	.92	54.0	15.8	5.20	.63	.78	.94
	1925	910	61.0	17.9	3.73	.62	.76	.90	59.0	17.3	4.16	.62	.77	.92	57.0	16.7	4.65	.63	.79	.94	54.5	16.0	5.21	.64	.80	.96
71°F (22°C)	1800	850	63.5	18.6	3.77	.46	.59	.72	61.5	18.0	4.20	.46	.60	.74	59.5	17.4	4.69	.46	.61	.75	57.0	16.7	5.24	.47	.61	.76
	1925	910	64.5	18.9	3.78	.46	.60	.74	62.5	18.3	4.21	.46	.61	.75	60.0	17.6	4.70	.47	.62	.77	57.5	16.9	5.25	.47	.63	.78

COOLING CAPACITY - HP13-060 with

[CB27UH-060]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1600	755	53.5	15.7	3.70	.74	.86	.98	51.5	15.1	4.15	.75	.88	.99	50.0	14.7	4.66	.76	.90	1.00	48.0	14.1	5.25	.77	.92	1.00
	1800	850	55.0	16.1	3.72	.76	.89	1.00	53.0	15.5	4.17	.77	.91	1.00	51.5	15.1	4.68	.78	.93	1.00	49.5	14.5	5.26	.80	.95	1.00
	2000	945	56.0	16.4	3.74	.78	.92	1.00	54.5	16.0	4.18	.79	.94	1.00	52.5	15.4	4.70	.81	.96	1.00	50.5	14.8	5.28	.82	.98	1.00
67°F (19°C)	1600	755	56.5	16.6	3.74	.59	.72	.83	55.0	16.1	4.19	.60	.73	.85	53.0	15.5	4.70	.61	.74	.86	51.0	14.9	5.28	.61	.75	.88
	1800	850	58.0	17.0	3.77	.61	.74	.86	56.0	16.4	4.21	.61	.75	.88	54.0	15.8	4.72	.62	.76	.90	52.0	15.2	5.30	.63	.77	.92
	2000	945	59.5	17.4	3.79	.62	.76	.89	57.5	16.9	4.23	.63	.77	.91	55.5	16.3	4.74	.63	.78	.93	53.0	15.5	5.31	.64	.80	.95
71°F (22°C)	1600	755	59.5	17.4	3.79	.46	.58	.69	57.5	16.9	4.23	.46	.59	.70	55.5	16.3	4.74	.46	.59	.71	53.5	15.7	5.32	.47	.60	.73
	1800	850	61.0	17.9	3.81	.46	.59	.72	59.0	17.3	4.26	.46	.60	.73	57.0	16.7	4.76	.46	.61	.74	55.0	16.1	5.34	.47	.62	.75
	2000	945	62.5	18.3	3.83	.47	.61	.74	60.5	17.7	4.28	.47	.61	.75	58.5	17.1	4.78	.47	.62	.76	56.0	16.4	5.36	.48	.63	.78

HEATING CAPACITY - HP13-060 with

[CB26UH-060-R]

Indoor Coil Air Volume 70°F db (21°C db)	cfm L/s		Air Temperature Entering Outdoor Coil														
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)		
			Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input	
1800	850	66.4	19.5	4.43	52.2	15.3	4.02	37.1	10.9	3.59	27.6	8.1	3.14	14.0	4.1	2.33	
		1925	910	66.5	19.5	4.35	52.3	15.3	3.93	37.2	10.9	3.51	27.6	8.1	3.05	14.1	4.1

HEATING CAPACITY - HP13-060 with

[CB27UH-060]

Indoor Coil Air Volume 70°F db (21°C db)	cfm L/s		Air Temperature Entering Outdoor Coil															
			65°F (18°C)			45°F (7°C)			25°F (-4°C)			5°F (-15°C)			-15°F (-26°C)			
			Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		Total Heating Capacity	Comp. Motor kW Input		
1600	755	67.0	19.6	4.34	52.2	15.3	3.89	36.5	10.7	3.43	26.7	7.8	2.99	13.3	3.9	2.24		
		1800	850	67.7	19.8	4.20	52.9	15.5	3.75	37.2	10.9	3.29	27.3	8.0	2.85	13.9	4.1	2.10
		2000	945	69.3	20.3	4.08	54.5	16.0	3.64	38.8	11.4	3.18	29.0	8.5	2.74	15.6	4.6	1.99

HEATING PERFORMANCE at 1800 cfm (850 L/s) Indoor Coil Air Volume HP13-060 with [CB26UH-060-R]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	4.35	66.5	19.5
60	16	4.25	63.2	18.5
55	13	4.15	60.0	17.6
50	10	4.05	56.8	16.6
47	8	3.99	54.9	16.1
45	7	3.93	52.3	15.3
40	4	3.79	45.8	13.4
35	2	3.64	39.3	11.5
30	-1	3.58	38.3	11.2
25	-4	3.51	37.2	10.9
20	-7	3.44	36.2	10.6
17	-8	3.39	35.5	10.4
15	-9	3.35	34.2	10.0
10	-12	3.26	31.0	9.1
5	-15	3.05	27.6	8.1
0	-18	2.85	24.2	7.1
-5	-21	2.65	20.8	6.1
-10	-23	2.44	17.4	5.1
-15	-26	2.24	14.1	4.1
-20	-29	2.04	10.7	3.1

HEATING PERFORMANCE at 1800 cfm (850 L/s) Indoor Coil Air Volume HP13-060 with [CB27UH-060]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	4.20	67.7	19.8
60	16	4.09	64.3	18.8
55	13	3.99	60.9	17.8
50	10	3.88	57.6	16.9
47	8	3.82	55.6	16.3
45	7	3.75	52.9	15.5
40	4	3.59	46.1	13.5
35	2	3.42	39.4	11.5
30	-1	3.36	38.3	11.2
25	-4	3.29	37.2	10.9
20	-7	3.23	36.0	10.6
17	-8	3.19	35.3	10.3
15	-9	3.15	34.0	10.0
10	-12	3.04	30.6	9.0
5	-15	2.85	27.3	8.0
0	-18	2.66	24.0	7.0
-5	-21	2.48	20.6	6.0
-10	-23	2.29	17.3	5.1
-15	-26	2.10	13.9	4.1
-20	-29	1.91	10.6	3.1

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-060 with

[CB30M-65]

Entering Wet Bulb Temperature	Total Air Volume		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)						95°F (35°C)						105°F (41°C)						115°F (46°C)					
			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb			Total Cooling Capacity		Comp Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb		
			kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C	kBtuh	kW		75°F 24°C	80°F 27°C	85°F 29°C
63°F (17°C)	1750	825	58.5	17.1	3.53	.76	.90	1.00	56.5	16.6	3.96	.77	.92	1.00	54.5	16.0	4.44	.78	.93	1.00	52.0	15.2	4.98	.80	.95	1.00
	1960	925	60.0	17.6	3.55	.79	.94	1.00	58.0	17.0	3.97	.80	.95	1.00	55.5	16.3	4.45	.81	.97	1.00	53.5	15.7	5.00	.83	.98	1.00
67°F (19°C)	1750	825	61.5	18.0	3.58	.80	.74	.87	59.5	17.4	4.00	.61	.75	.88	57.5	16.9	4.47	.62	.76	.90	55.0	16.1	5.02	.62	.78	.92
	1960	925	63.0	18.5	3.59	.62	.76	.90	60.5	17.7	4.01	.62	.78	.92	58.5	17.1	4.49	.63	.79	.94	56.5	16.6	5.03	.64	.80	.96
71°F (22°C)	1750	825	65.0	19.0	3.62	.46	.59	.71	63.0	18.5	4.04	.46	.60	.73	60.5	17.7	4.52	.46	.60	.74	58.5	17.1	5.06	.47	.61	.75
	1960	925	66.0	19.3	3.64	.46	.61	.74	64.0	18.8	4.05	.47	.61	.75	62.0	18.2	4.53	.47	.62	.77	59.5	17.4	5.07	.47	.63	.78

HEATING CAPACITY - HP13-060 with

[CB30M-65]

Indoor Coil Air Volume 70°F db (21°C db)	Total Air Volume		Air Temperature Entering Outdoor Coil																			
			65°F (18°C)				45°F (7°C)				25°F (-4°C)				5°F (-15°C)				-15°F (-26°C)			
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input		
kBtuh	kW	kBtuh	kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW	kBtuh		kW				
1750	825	66.7	19.5	4.12	52.4	15.4	3.70	37.2	10.9	3.27	27.5	8.1	2.85	13.7	4.0	2.13						
1960	925	67.3	19.7	4.00	53.0	15.5	3.58	37.8	11.1	3.14	28.1	8.2	2.72	14.3	4.2	2.01						

HEATING PERFORMANCE at 1750 cfm (825 L/s) Indoor Coil Air Volume HP13-060 with

[CB30M-65]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	4.00	67.3	19.7
60	16	3.90	64.1	18.8
55	13	3.80	60.8	17.8
50	10	3.70	57.6	16.9
47	8	3.64	55.6	16.3
45	7	3.58	53.0	15.5
40	4	3.42	46.5	13.6
35	2	3.26	39.9	11.7
30	-1	3.20	38.9	11.4
25	-4	3.14	37.8	11.1
20	-7	3.08	36.7	10.8
17	-8	3.04	36.1	10.6
15	-9	3.00	34.8	10.2
10	-12	2.90	31.5	9.2
5	-15	2.72	28.1	8.2
0	-18	2.54	24.6	7.2
-5	-21	2.36	21.2	6.2
-10	-23	2.19	17.7	5.2
-15	-26	2.01	14.3	4.2
-20	-29	1.83	10.8	3.2

RATINGS

5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

AIR HANDLERS

COOLING CAPACITY - HP13-060 with

[CBX32MV-048] [CBX40UHV-048]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)			95°F (35°C)			105°F (41°C)			115°F (46°C)														
			Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb												
63°F (17°C)	1805	850	57.5	16.9	3.52	.78	.93	1.00	55.5	16.3	3.95	.79	.94	1.00	53.5	15.7	4.43	.80	.96	1.00	51.0	14.9	4.98	.82	.98	1.00
67°F (19°C)	1805	850	61.0	17.9	3.57	.61	.75	.89	59.0	17.3	3.99	.62	.76	.91	56.5	16.6	4.46	.62	.78	.93	54.5	16.0	5.01	.63	.79	.95
71°F (22°C)	1805	850	64.0	18.8	3.61	.46	.60	.73	62.0	18.2	4.03	.46	.60	.74	60.0	17.6	4.50	.46	.61	.75	57.5	16.9	5.05	.47	.62	.77

COOLING CAPACITY - HP13-060 with

[CBX32MV-060] [CBX40UHV-060]

Entering Wet Bulb Temperature	Total Air Volume cfm L/s		Outdoor Air Temperature Entering Outdoor Coil																							
			85°F (29°C)			95°F (35°C)			105°F (41°C)			115°F (46°C)														
			Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb	Total Cooling Capacity kBtuh kW	Comp. Motor kW Input	Sensible To Total Ratio (S/T) Dry Bulb												
63°F (17°C)	1805	850	59.0	17.3	3.54	.77	.91	1.00	57.0	16.7	3.96	.78	.93	1.00	54.5	16.0	4.44	.79	.94	1.00	52.5	15.4	4.99	.81	.96	1.00
67°F (19°C)	1805	850	62.0	18.2	3.58	.61	.74	.88	60.0	17.6	4.00	.61	.76	.89	58.0	17.0	4.48	.62	.77	.91	55.5	16.3	5.02	.63	.78	.93
71°F (22°C)	1805	850	65.0	19.0	3.63	.46	.59	.72	63.5	18.6	4.04	.46	.60	.73	61.0	17.9	4.52	.46	.61	.74	58.5	17.1	5.06	.47	.62	.76

HEATING CAPACITY - HP13-060 with

[CBX32MV-048] [CBX40UHV-048]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil		65°F (18°C)						45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
			kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1805	850	66.9	19.6	4.08	52.5	15.4	3.68	37.3	10.9	3.26	27.6	8.1	2.85	13.6	4.0	2.13	
2005	945	67.6	19.8	3.97	53.2	15.6	3.56	38.0	11.1	3.14	28.3	8.3	2.74	14.4	4.2	2.01	
2145	1010	68.2	20.0	3.91	53.8	15.8	3.50	38.6	11.3	3.08	28.9	8.5	2.68	15.0	4.4	1.95	

COOLING CAPACITY - HP13-060 with

[CBX32MV-060] [CBX40UHV-060]

Indoor Coil Air Volume 70°F db (21°C db)	Air Temperature Entering Outdoor Coil		65°F (18°C)						45°F (7°C)		25°F (-4°C)		5°F (-15°C)		-15°F (-26°C)		
			Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input	Total Heating Capacity		Comp. Motor kW Input
			kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW		kBtuh	kW	
1805	850	66.9	19.6	4.07	52.5	15.4	3.66	37.3	10.9	3.23	27.5	8.1	2.81	13.6	4.0	2.10	
2005	945	67.6	19.8	3.98	53.3	15.6	3.56	38.0	11.1	3.13	28.3	8.3	2.72	14.4	4.2	2.00	
2145	1010	68.2	20.0	3.91	53.9	15.8	3.49	38.6	11.3	3.06	28.9	8.5	2.65	14.9	4.4	1.93	

HEATING PERFORMANCE AT 2005 cfm (945 L/s) Indoor Coil Air Volume HP13-060 with [CBX32MV-048] [CBX40UHV-048]

HEATING PERFORMANCE AT 2005 cfm (945 L/s) Indoor Coil Air Volume HP13-060 with [CBX32MV-060] [CBX40UHV-060]

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.97	67.6	19.8
60	16	3.87	64.3	18.8
55	13	3.78	61.1	17.9
50	10	3.68	57.8	16.9
47	8	3.63	55.9	16.4
45	7	3.56	53.2	15.6
40	4	3.41	46.7	13.7
35	2	3.26	40.1	11.8
30	-1	3.20	39.1	11.5
25	-4	3.14	38.0	11.1
20	-7	3.09	37.0	10.8
17	-8	3.05	36.3	10.6
15	-9	3.01	35.0	10.3
10	-12	2.92	31.8	9.3
5	-15	2.74	28.3	8.3
0	-18	2.56	24.8	7.3
-5	-21	2.38	21.3	6.2
-10	-23	2.19	17.9	5.2
-15	-26	2.01	14.4	4.2
-20	-29	1.83	10.9	3.2

*Outdoor Temperature		Compressor Motor kW Input	Total Output	
°F	°C		kBtuh	kW
65	18	3.98	67.6	19.8
60	16	3.88	64.4	18.9
55	13	3.78	61.1	17.9
50	10	3.68	57.9	17.0
47	8	3.62	55.9	16.4
45	7	3.56	53.3	15.6
40	4	3.40	46.7	13.7
35	2	3.25	40.2	11.8
30	-1	3.19	39.1	11.5
25	-4	3.13	38.0	11.1
20	-7	3.07	37.0	10.8
17	-8	3.04	36.3	10.6
15	-9	3.00	35.0	10.3
10	-12	2.90	31.8	9.3
5	-15	2.72	28.3	8.3
0	-18	2.54	24.8	7.3
-5	-21	2.36	21.3	6.2
-10	-23	2.18	17.9	5.2
-15	-26	2.00	14.4	4.2
-20	-29	1.82	10.9	3.2

RATINGS

5 TON

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

[C33-62C + G61MPV-60C-090]
[C33-62C + G71MPP-60C-090]

COOLING CAPACITY - HP13-060 with

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F) with sub-columns for Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

COOLING CAPACITY - HP13-060 with

[C33-62C + G61MPV-60C-110]
[C33-62C + G71MPP-60C-110]

Table with columns for Entering Wet Bulb Temperature, Total Air Volume, and Outdoor Air Temperature Entering Outdoor Coil (85°F, 95°F, 105°F, 115°F) with sub-columns for Total Cooling Capacity, Comp Motor kW Input, and Sensible To Total Ratio (S/T) Dry Bulb.

HEATING CAPACITY - HP13-060 with

[C33-62C + G61MPV-60C-090]
[C33-62C + G71MPP-60C-090]

Table with columns for Indoor Coil Air Volume (70°F db) and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Total Heating Capacity and Comp. Motor kW Input.

HEATING CAPACITY - HP13-060 with

[C33-62C + G61MPV-60C-110]
[C33-62C + G71MPP-60C-110]

Table with columns for Indoor Coil Air Volume (70°F db) and Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F) with sub-columns for Total Heating Capacity and Comp. Motor kW Input.

HEATING PERFORMANCE at 1960 cfm (925 L/s) Indoor Coil

Air Volume HP13-060 with [C33-62C + G61MPV-60C-090]

Table with columns for *Outdoor Temperature, Compressor Motor kW Input, and Total Output (kBtuh, kW).

HEATING PERFORMANCE at 1995 cfm (940 L/s) Indoor Coil

Air Volume HP13-060 with [C33-62C + G61MPV-60C-110]

Table with columns for *Outdoor Temperature, Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

UP-FLOW INDOOR COIL WITH GAS FURNACES

COOLING CAPACITY - HP13-060 with

[C33-62D + G60UHV-60D-135]

Table for Cooling Capacity - HP13-060 with. Columns include: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), and Comp Motor kW Input.

COOLING CAPACITY - HP13-060 with

[C33-62D + G61MPV-60D-135]

[C33-62D + G71MPP-60D-135]

Table for Cooling Capacity - HP13-060 with (G61/G71). Columns include: Entering Wet Bulb Temperature, Total Air Volume (cfm, L/s), Outdoor Air Temperature (85°F, 95°F, 105°F, 115°F), Total Cooling Capacity (kBtuh, kW), and Comp Motor kW Input.

HEATING CAPACITY - HP13-060 with

[C33-62D + G60UHV-60D-135]

Table for Heating Capacity - HP13-060 with (G60). Columns include: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), and Comp. Motor kW Input.

HEATING CAPACITY - HP13-060 with

[C33-62D + G61MPV-60D-135]

[C33-62D + G71MPP-60D-135]

Table for Heating Capacity - HP13-060 with (G61/G71). Columns include: Indoor Coil Air Volume (70°F db), Air Temperature Entering Outdoor Coil (65°F, 45°F, 25°F, 5°F, -15°F), Total Heating Capacity (kBtuh, kW), and Comp. Motor kW Input.

HEATING PERFORMANCE at 1945 cfm (920 L/s) Indoor Coil Air Volume HP13-060 with

[C33-62D + G60UHV-60D-135]

HEATING PERFORMANCE at 1985 cfm (935 L/s) Indoor Coil Air Volume HP13-060 with

[C33-62D + G61MPV-60D-135]

[C33-62D + G71MPP-60D-135]

Table for Heating Performance at 1945 cfm. Columns include: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

Table for Heating Performance at 1985 cfm. Columns include: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, and Total Output (kBtuh, kW).

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

DOWN-FLOW INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-060 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with 24 columns: Entering Wet Bulb Temperature (63°F, 67°F, 71°F), Total Air Volume (cfm, L/s), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C).

COOLING CAPACITY - HP13-060 with

[CR33-60D-F + G60DFV-60D-135]

Table with 24 columns: Entering Wet Bulb Temperature (63°F, 67°F, 71°F), Total Air Volume (cfm, L/s), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C), Total Cooling Capacity (kBtu/h, kW), Comp Motor kW Input, Sensible To Total Ratio (S/T) Dry Bulb (75°F, 80°F, 85°F at 24°C, 27°C, 29°C).

HEATING CAPACITY - HP13-060 with

[CR33-50/60C-F + G60DFV-60C-090]

Table with 15 columns: Indoor Coil Air Volume (70°F db, 21°C db) (cfm, L/s), Total Heating Capacity (65°F, 45°F, 25°F, 5°F, -15°F) (kBtu/h, kW), Comp. Motor kW Input (65°F, 45°F, 25°F, 5°F, -15°F).

HEATING CAPACITY - HP13-060 with

[CR33-60D-F + G60DFV-60D-135]

Table with 15 columns: Indoor Coil Air Volume (70°F db, 21°C db) (cfm, L/s), Total Heating Capacity (65°F, 45°F, 25°F, 5°F, -15°F) (kBtu/h, kW), Comp. Motor kW Input (65°F, 45°F, 25°F, 5°F, -15°F).

HEATING PERFORMANCE at 1920 cfm (905 L/s) Indoor Coil Air Volume HP13-060 with [CR33-50/60C-F + G60DFV-60C-090]

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtu/h, kW). Rows range from 65°F to -20°F.

HEATING PERFORMANCE at 2050 cfm (970 L/s) Indoor Coil Air Volume HP13-060 with [CR33-60D-F + G60DFV-60D-135]

Table with 5 columns: *Outdoor Temperature (°F, °C), Compressor Motor kW Input, Total Output (kBtu/h, kW). Rows range from 65°F to -20°F.

NOTES: For Temperatures and Capacities not shown in tables, see bulletin - Cooling Unit Rating Table Correction Factor Data in Miscellaneous Engineering Data section.

HORIZONTAL INDOOR COILS WITH GAS FURNACES

COOLING CAPACITY - HP13-060 with

[CH33-62D-2F + G60UHV-60D-135]

Table with 22 columns for cooling capacity metrics and 12 rows for outdoor air temperatures ranging from 63°F to 71°F.

COOLING CAPACITY - HP13-060 with

[CH33-62D-2F + G61MPV-60D-135]

[CH33-62D-2F + G71MPP-60D-135]

Table with 22 columns for cooling capacity metrics and 12 rows for outdoor air temperatures ranging from 63°F to 71°F.

HEATING CAPACITY - HP13-060 with

[CH33-62D-2F + G60UHV-60D-135]

Table with 18 columns for heating capacity metrics and 4 rows for indoor coil air volumes (1745, 1945, 2140 cfm).

HEATING CAPACITY - HP13-060 with

[CH33-62D-2F + G61MPV-60D-135]

[CH33-62D-2F + G71MPP-60D-135]

Table with 18 columns for heating capacity metrics and 4 rows for indoor coil air volumes (1730, 1985, 2190 cfm).

HEATING PERFORMANCE at 1945 cfm (920 L/s) Indoor Coil Air Volume HP13-060 with [CH33-62D-2F + G60UHV-60D-135]

Table with 6 columns for heating performance metrics and 18 rows for outdoor temperatures from 65°F to -20°F.

HEATING PERFORMANCE at 1985 cfm (935 L/s) Indoor Coil Air Volume HP13-060 with [CH33-62D-2F + G61MPV-60D-135]

[CH33-62D-2F + G71MPP-60D-135]

Table with 6 columns for heating performance metrics and 18 rows for outdoor temperatures from 65°F to -20°F.

REVISIONS

Description of Change

Added ratings for CBX40UHV Air Handlers.



Visit us at www.lennox.com
For the latest technical information, www.lennoxdagenet.com
Contact us at 1-800-4-LENNOX

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

©2009 Lennox Industries Inc.