

SUBMITTAL DATA - CEILING CASSETTE

M22A012S4-2P

MULTI-ZONE MINI-SPLIT HEAT PUMP

| Job: | Engineer: | |
|---------------------|---|--|
| Location: | Architect: | |
| Schedule No.: | Date: | |
| System Designation: | For: □Reference □Approval □Review □Construction | |

FEATURES

- Pre Heat Function
- 360° Airflow Panel
- Auto Restart
 Built-In Condensate Pump
- Flare Connections
- Refrigerant R-410A
- · LED Readout Panel
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

| Product registration required. | | | |
|--|-----------------|---|--|
| SPECIFICATIONS | | | |
| PERFORMANCE | | | |
| Cooling Capacity ¹ (Btu/h) | | 12,000 | |
| Heating Capacity ¹ (Btu/h) | | 12,000 | |
| Airflow (CFM) | High | 400 | |
| | Medium | 340 | |
| | Low | 280 | |
| External Static Pressure (in. w.g.) | | | |
| Sound Pressure (dBA) | High | 41 | |
| | Medium | 38 | |
| | Low | 35 | |
| ELECTRICAL DATA | | | |
| | | | |
| Power Supply (V/Hz/Φ) | | 208-230/60/1 | |
| Power Supply (V/Hz/Φ) Rated load amps (RLA) | | 208-230/60/1 1.0 | |
| , | | | |
| Rated load amps (RLA) | | 1.0 | |
| Rated load amps (RLA) Power Output (W) | Height | 1.0 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | Height Width | 1.0 46 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | _ | 1.0 46 10-3/8 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | Width | 1.0 46 10-3/8 22-1/2 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) | Width | 1.0 46 10-3/8 22-1/2 22-1/2 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) | Width | 1.0 46 10-3/8 22-1/2 22-1/2 1/4 | |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) | Width Depth | 1.0 46 10-3/8 22-1/2 22-1/2 1/4 1/2 | |



| OPTIONAL ACCESSORIES | |
|--|----|
| Non-Programmable Controller (M0STAT61Q-1): | |
| Wireless Remote Controller (M0STAT60Q-1): | 1+ |
| Programmable Controller (M0STAT64Q-1): | |

NOTES

- Cooling and Heating capacity data is rated at the following conditions:
 Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor
 Cassette Panel (M0STAT62Q-1) ordered separately.
- 2. Casselle Faller (MOSTATO2Q-1) Ordered Separately












SUBMITTAL DATA - CEILING CASSETTE


M22A012S4-2P


MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)




SIDE VIEW





RIGHT SIDE VIEW

BOTTOM VIEW (Body)



SIDE VIEW

