

Job: Location: Schedule No.: **System Designation:**

SUBMITTAL DATA - DUCTED

MMDA009S4-2P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Engineer:
Architect:
Date:
For: □Reference □Approval □Review □Construction

FEATURES

Auto Restart

- Pre Heat Function
- · Low Charge Detection
- Built-In Condensate Pump
- Flare Connections
- Refrigerant R-410A
- Three Speed Fan · Wired Controller included

Product Warranty

All covered components - Five year limited warranty.

SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity ¹ (Btu/h)		9,000
Heating Capacity ¹ (Btu/h)		10,000
Airflow (CFM)	High	400
	Medium	330
	Low	270
External Static Pressure (in. v	v.g.)	-
Sound Pressure (dBA)	High	37
	Medium	34
	Low	31
ELECTRICAL DATA		
Power Supply (V/Hz/Φ)		208-230/60/1
Rated load amps (RLA)		0.9
Power Output (W)		55
DIMENSIONS		
Unit Dimensions (in)	Height	8-1/4
	-	
	Width	31-1/8
	Width Depth	31-1/8 25
Liquid Pipe Connection (in)		
Gas Pipe Connection (in)	Depth	25 1/4 3/8
	Depth	25 1/4
Gas Pipe Connection (in) Condensate drain connection Unit Shipping Weight (lb)	Depth	25 1/4 3/8
Gas Pipe Connection (in) Condensate drain connection	Depth	25 1/4 3/8 1



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): 1+ Wireless Remote Controller (M0STAT60Q-1): Programmable Controller (M0STAT64Q-1):

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA - DUCTED

MMDA009S4-2P

MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)

