

SUBMITTAL DATA - WALL-MOUNTED

MWMA009S4-3P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Job:	Engineer:	
Location:	Architect:	
Schedule No.:	Date:	
System Designation:	For: □Reference □Approval □Review □Construction	

FEATURES

- Pre Heat Function
- Multi-Refrigerant Outlet
- Auto Restart
 Three Speed Fan
- Flare Connections
- Refrigerant R-410A
- LED Readout Panel
- Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.		
SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity ¹ (Btu/h)		9,000
Heating Capacity ¹ (Btu/h)		10,000
Airflow (CFM)	High	340
	Medium	260
	Low	205
External Static Pressure (in. w.g.)		
Sound Pressure (dBA)	High	43.3
	Medium	36.2
	Low	29.1
ELECTRICAL DATA		
Power Supply (V/Hz/Φ)		208-230/60/1
Power Supply (V/Hz/Φ) Rated load amps (RLA)		208-230/60/1 0.20
Rated load amps (RLA)		0.20
Rated load amps (RLA) Power Output (W)	Height	0.20
Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	0.20 20
Rated load amps (RLA) Power Output (W) DIMENSIONS		0.20 20 11
Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	0.20 20 11 32-7/8
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in)	Width	0.20 20 11 32-7/8 7-7/8
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): Wireless Remote Controller (M0STAT60Q-1): 1+ Programmable Controller (M0STAT64Q-1):

NOTES

Cooling and Heating capacity data is rated at the following conditions:

 Cooling and Heating capacity data is rated at the following conditions:

 Cooling and Heating capacity data is rated at the following conditions:

 Cooling and Heating capacity data is rated at the following conditions:

 Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA - WALL-MOUNTED MWMA009S4-3P

MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)

