

SUBMITTAL DATA - WALL-MOUNTED

MWMA009S4-2P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Engineer:
Architect:
Date:
For: Deference DAnnroyal Deview DConstruction

FEATURES

Job:
Location:
Schedule No.:
System Designation:

- Pre Heat Function
- Multi-Refrigerant Outlet
- Auto Restart
 Three Speed Fan
- Flare Connections
- Refrigerant R-410A
- · LED Readout Panel
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.			
SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		9,000	
Heating Capacity ¹ (Btu/h)		10,000	
Airflow (CFM)	High	340	
	Medium	260	
	Low	205	
External Static Pressure (in. w.g.)			
Sound Pressure (dBA)	High	43.3	
	Medium	36.2	
	Low	29.1	
ELECTRICAL DATA			
ELECTRICAL BATTA			
Power Supply (V/Hz/Φ)		208-230/60/1	
		208-230/60/1 0.20	
Power Supply (V/Hz/Φ)			
Power Supply (V/Hz/Φ) Rated load amps (RLA)		0.20	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W)	Height	0.20	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	0.20 20	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS	-	0.20 20 11	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	0.20 20 11 32-7/8	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in)	Width	0.20 20 11 32-7/8 7-7/8	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8	
Power Supply (V/Hz/Φ) Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8	



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): Wireless Remote Controller (M0STAT60Q-1): 1+ Programmable Controller (M0STAT64Q-1):

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA - WALL-MOUNTED

MWMA009S4-**2**P

MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)

