



SUBMITTAL DATA - MINI-SPLIT SYSTEMS

(1) MS8-ZO-36P4 with (3) MS8-HI-09P1

Multi-Zone Heat Pump

Job: _____
 Location: _____
 Engineer: _____
 Schedule No.: _____
 System Designation: _____

Engineer: _____
 Architect: _____
 Location: _____
 Date: _____
 For: Reference Approval Review Construction

FEATURES

- Variable Frequency Rotary Compressor (R-410A)
- DC Inverter Control
- Compressor Crankcase Heater
- High Pressure Discharge Temperature Protection
- Reversing Valve
- Defrost Control
- Low Voltage Protection
- Indoor Coil Freeze Protection
- Indoor Unit Microprocessor
- Oscillating Air Deflection Louvers
- Turbo Function Blower
- Wireless Remote Control

PRODUCT WARRANTY

Compressor - limited warranty for five years.
 All other covered components - five years in residential installations and one year in non-residential installations.

OUTDOOR UNIT - MS8-ZO-36P4

Number of Zones		3
SEER/EER		16.00 / 7.95
HSPF - Region IV		8.20
AHRI Reference No.		6484324
Cooling Capacity (Btuh)		34,400
Heating Capacity (Btuh)	High	37,200
	Low	22,000
Ambient Temp. Operating Range (°F)	Cooling	23 to 118
	Heating	5 to 80
Connections	Liquid line o.d. - flare	1/4
(in.)	Suction line o.d. - flare	3/8
Refrigerant (R-410A) furnished		6 lbs. 4 oz.
Outdoor	Diameter - in.	22
Fan Motor	No. of blades	3
	Cfm (High/Standard/Low)	2200/1600/1400
	Rpm (High/Standard/Low)	820/640/560
Shipping Data - lbs.		152

ELECTRICAL DATA

Line voltage data - 60 hz - 1ph		208 / 230V
Maximum overcurrent protection (amps)		32
Minimum circuit ampacity		20
Compressor	Rated load amps	21
Compressor Power Input (W)		2200
Outdoor	Rated load amps	0.59
Fan Motor	Output (W)	120

OPTIONAL ACCESSORIES - OUTDOOR

Description		Cat. No.
Condenser Pad (18 x 36 x 2)		48X92
Disconnects	30 amp, fused, 1 ph	27P37
	60 amp, non-fused, 1 ph	27P39
Fuses	30A	83P75
	60A	83P77
Line Sets	1/4 in. x 3/8 in. x 25 ft.	90X53
	1/4 in. x 3/8 in. x 50 ft.	X0258
Male Flare Adaptor	5/16 in. quick connect x 1/4 in. MF	Y0576
Wall Bracket	36 in.	Y5021
Whips	10 Gauge - 1/2 in. x 6 ft.	29P54
	8 Gauge - 3/4 in. x 6 ft.	27P44

INDOOR UNIT - MS8-HI-09P1

Model No.		(3) MS8-HI-09P1
Connections	Liquid/Suction	1/4 / 3/8
(in.) o.d. flare		
Line Sets Required		(3) 1/4 in. x 3/8 in.
Indoor Blower	Maximum	305
Air Volume	High	275
	Medium	255
	Low	220
Indoor Blower	D x L (in.)	3.6 x 25.4
Shipping Data - lbs.		31

ELECTRICAL DATA

Line voltage data - 60 hz - 1ph	208/230V
Rated Load Amps	0.20
Output (W)	20


OPTIONAL ACCESSORIES - INDOOR

Condensate Pump	
3.70 US gph, 26 ft. lift - 115V	X8250
3.70 US gph, 26 ft. lift, 230V	X8251
7.9 US gph, 35 ft. lift - 120/240V	Y5170
Condensate Mini-Split Drain Line - 5/8 in. I.D. 160 ft.	Y3401
Indoor/Outdoor Wiring Cable 14 Gauge, 4 conductor wire, THHN, 250 ft.	Y2067
Wireless Remote Control Holder	Y5073


SOUND DATA (Sound Rating Number dBA)

Outdoor Unit Pressure		59
Indoor Unit	Low	32
Pressure	Medium	35
	High	38
	Maximum	42

INDOOR UNIT



OUTDOOR UNIT



WIRELESS REMOTE CONTROL



Intertek

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

495064 (201308)

©2013 Lennox Industries Inc.