




## Field Replacement Guide for iComfort® E30 Smart Hub (15S64)

507694-01, 7/2018

Supersedes 2/2017



### **WARNING**

Improper installation, adjustment, alteration, service or maintenance can cause property damage, personal injury or loss of life.

Installation and service must be performed by a licensed professional HVAC installer (or equivalent) or a service agency.

This Smart Hub replacement kit is used to replace the E30 Smart Hub.

### Removing Smart Hub

Obtain a copy of the original installation report from the dealer portal which can be used during commissioning once the original Smart Hub has been replaced.

1. Make note of homeowner account information and home Wi-Fi access information.
2. Go to the homeowner web portal and remove the original system from the account.
3. Disconnect power to the entire system.
4. Remove the access cover from Smart Hub.
5. Take a picture or make a drawing showing the control wires and what terminals they are connected too.
6. Disconnect control wiring.
7. Remove all the screws securing the Smart Hub to wall.
8. Lift up and out to remove Smart Hub from the key hole.
9. Discard old Smart Hub.

## Installing New Smart Hub

1. Remove new Smart Hub from shipping container.
2. Remove the access cover from the Smart Hub.
3. Mount the Smart Hub on the wall with key hole support.
4. Use the through-hole screw previously removed to secure the Smart Hub.
5. Reconnect all wiring that was documented during the removal of the old Smart Hub.
6. Replace the access cover.
7. Unfold the antenna and position as noted during removal of the original Smart Hub.
8. Restore power to system.
9. Use the previous mentioned installation report if available and any other additional information noted to recommission the system.