



**PRODUCT CATALOG**

# AHRI HEAT PUMP SYSTEM MATCHES

Bulletin No: 210561HP  
July 2016  
Supersedes February 2016



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.





# CONTENTS

TXV USAGE . . . . .	.5
14HPX . . . . .	.9
XP14 . . . . .	39
XP16 . . . . .	71
XP17 . . . . .	79
XP20 . . . . .	111
XP21 . . . . .	117
XP25 . . . . .	139
SL18XP1 . . . . .	145

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.





# HEAT PUMPS TXV USAGE

## PRODUCT CATALOG

July 2016  
Supersedes February 2016

### TXV USAGE

Use this table for C33, CH23, CH33, and CR33 Field Installed TXV Match-Ups.

Model No.	Order No.
14HPX-018	12J18
14HPX-024	12J18
14HPX-030	12J18
14HPX-036	12J19
14HPX-042	12J20
14HPX-048	12J20
14HPX-060	12J20
SL18XP1-024	12J18
SL18XP1-030	12J18
SL18XP1-036	12J19
SL18XP1-042	12J20
SL18XP1-048	12J20
SL18XP1-060	12J20
XP14-018	12J18
XP14-024	12J18
XP14-030	12J18
XP14-036	12J19
XP14-042	12J20
XP14-048	12J20
XP14-060	12J20
XP16-024	12J18
XP16-036	12J19
XP16-048	12J20
XP16-060	12J20

CX34 upflow coils and all Lennox air handlers are shipped with a factory installed TXV. In most cases, no change out of the valve is needed.

If a change out is required it will be listed in the "TXV SUBSTITUTIONS" table. The correct TXV must be ordered and field installed.

C33 and CH33 coils - Replace the factory installed orifice with the expansion valve listed.

CR33 and CH23 - Use the expansion valve listed.

### TXV USAGE

Use this table for C33, CH23, CH33, and CR33 Field Installed TXV Match-Ups.

Model No.	Order No.
XP17-024	12J18
XP17-030	12J18
XP17-036	12J19
XP17-042	12J20
XP17-048	12J20
XP17-060	12J20
XP20-024	12J18
XP20-036	12J19
XP20-048	12J20
XP20-060	12J20
XP21-024	12J18
XP21-036	12J19
XP21-048	12J20
XP21-060	12J20
XP25-024	12J18
XP25-036	12J19
XP25-048	12J20
XP25-060	12J20

CX34 upflow coils and all Lennox air handlers are shipped with a factory installed TXV. In most cases, no change out of the valve is needed.

If a change out is required it will be listed in the "TXV SUBSTITUTIONS" table. The correct TXV must be ordered and field installed.

C33 and CH33 coils - Replace the factory installed orifice with the expansion valve listed.

CR33 and CH23 - Use the expansion valve listed.

**FACTORY INSTALLED TXV/CHECK**

Indoor Coil	Factory Installed TXV/Check Valves
CX34-18/24A-6F	12J18
CX34-18/24B-6F	12J18
CX34-18/24C-6F	12J18
CX34-19A-6F	12J18
CX34-25A-6F	12J18
CX34-25B-6F	12J18
CX34-30A-6F	12J18
CX34-30B-6F	12J18
CX34-30C-6F	12J18
CX34-31A-6F	12J18
CX34-31B-6F	12J18
CX34-36A-6F	12J19
CX34-36B-6F	12J19
CX34-36C-6F	12J19
CX34-38A-6F	12J19
CX34-38B-6F	12J19
CX34-42B-6F	12J20
CX34-43B-6F	12J20
CX34-43C-6F	12J20
CX34-44/48B-6F	12J20
CX34-44/48C-6F	12J20
CX34-49C-6F	12J20
CX34-50-60C-6F	12J20
CX34-60D-6F	12J20
CX34-62C-6F	12J20
CX34-62D-6F	12J20

**FACTORY INSTALLED TXV/CHECK**

Air Handler	Factory Installed TXV/Check Valves
CBX25UH-018	12J18
CBX25UH-024	12J18
CBX25UH-030	12J18
CBX25UH-036	12J19
CBX25UH-042	12J20
CBX25UH-048	12J20
CBX25UH-060	12J20
CBX25UHV-018	12J18
CBX25UHV-024	12J18
CBX25UHV-030	12J18
CBX25UHV-036	12J19
CBX25UHV-042	12J20
CBX25UHV-048	12J20
CBX25UHV-060	12J20
CBX27UH-018	12J18
CBX27UH-024	12J18
CBX27UH-030	12J18
CBX27UH-036	12J19
CBX27UH-042	12J20
CBX27UH-048	12J20
CBX27UH-060	12J20
CBX32M-018/024	12J18
CBX32M-030	12J18
CBX32M-036	12J19
CBX32M-042	12J20
CBX32M-048	12J20
CBX32M-060	12J20
CBX32MV-018/024	12J18
CBX23MV-024/030	12J18
CBX32MV-036	12J19
CBX32MV-048	12J20
CBX32MV-060	12J20
CBX32MV-068	12J20
CBX40UHV-024	12J18
CBX40UHV-030	12J18
CBX40UHV-036	12J19
CBX40UHV-042	12J20
CBX40UHV-048	12J20
CBX40UHV-060	12J20

## \*TXV SUBSTITUTIONS

Use this table to determine if the factory installed TXV in the indoor unit needs to be replaced.

Model No.	Indoor Coil or Air Handler	Factory TXV	Replacement TXV
14HPX-030	CX34-44/48	12J20	12J18
SL18XP1-030	CX34-43	12J20	12J18
SL18XP1-030	CX34-50/60	12J20	12J18
XP14-030	CX34-42	12J20	12J18
XP14-030	CX34-43	12J20	12J18
XP14-030	CX34-44/48	12J20	12J18
XP17-030	CX34-43	12J20	12J18
XP17-042	CX34-38	12J19	12J20
XP21-024	CX34-38	12J19	12J18

\*CX34 coils and all air handlers - The factory installed expansion valve must be replaced with the expansion valve listed (ordered separately).

If the combination is not listed above, the factory installed TXV is used.

## AHRI STANDARD 210/240

Cooling or heating capacities are net values, including the effects of blower motor heat, and do not include supplementary heat. Power input is the total power input to the compressor(s) and fan(s), plus any controls and other items required as part of the system for normal operation.

Units which do not have an indoor air-circulating blower furnished as part of the model, i.e., split system with indoor coil only, is established by subtracting from the total cooling capacity 1250 Btu/h per 1,000 cfm, and by adding the same amount to the heating capacity. Total power input for both heating and cooling is increased by 365 W per 1,000 cfm of indoor air circulated.







PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES - ALL REGIONS

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-018-230	18,000	16.00	13.00	17,500	11,100	3.80	2.56	8.50	C33-25A	EL180UH045E36A	7524644
14HPX-018-230	18,000	16.00	13.00	17,600	11,100	3.86	2.58	8.50	C33-31A	EL180UH045E36A	7524641
14HPX-018-230	19,200	16.00	13.00	17,800	11,300	3.92	2.62	8.50	C33-31B	EL195UH045E36A	8897168
14HPX-018-230	18,000	14.00	12.00	17,800	11,800	3.52	2.48	8.20	CBX25UH-018		7524628
14HPX-018-230	18,000	15.00	12.50	17,600	11,600	3.64	2.54	8.50	CBX25UHV-018		7524630
14HPX-018-230	18,000	15.50	12.50	18,000	11,600	3.80	2.62	8.50	CBX25UHV-024		7524647
14HPX-018-230	18,000	16.00	13.00	17,500	11,100	3.92	2.62	8.50	CBX27UH-018		7524632
14HPX-018-230	18,000	16.00	13.00	17,500	11,100	3.96	2.64	8.50	CBX27UH-024		7524631
14HPX-018-230	18,000	15.50	12.50	17,700	11,100	3.84	2.56	8.50	CBX32MV-018/024		7524634
14HPX-018-230	18,000	16.00	13.00	17,700	11,300	3.90	2.62	8.50	CH33-25A	EL180UH045E36A	7524637
14HPX-018-230	18,000	14.00	12.00	18,000	11,700	3.56	2.42	8.20	CH33-25A		7524635
14HPX-018-230	18,000	14.00	11.50	18,000	11,700	3.56	2.42	8.20	CH33-25B		7524638
14HPX-018-230	18,000	16.00	13.00	18,000	11,400	4.06	2.66	8.50	CR33-30/36A	EL180DF045E36A	7524645
14HPX-018-230	18,000	16.00	13.00	17,500	11,100	3.80	2.56	8.50	CX34-25A	EL180UH045E36A	7524643
14HPX-018-230	18,000	16.00	13.00	17,600	11,100	3.86	2.58	8.50	CX34-31A	EL180UH045E36A	7524640
14HPX-018-230	19,200	16.00	13.00	17,800	11,300	3.92	2.62	8.50	CX34-31B	EL195UH045E36A	8897167
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	C33-25	CBWMV-24B-040	7045644
14HPX-024-230	24,000	15.50	13.00	21,400	13,500	3.50	2.44	8.20	C33-25	EL180UH045E36A	7045584
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.68	2.52	8.50	C33-25	EL180UH070E36B	7045570
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	C33-25	EL195UH045XE36B	7045662
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	C33-25	EL195UH070XE36B	7045647
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	C33-25	EL296UH045XE36B	7045607
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	C33-25	EL296UH045XV36B	7045564
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	C33-25	EL296UH070XE36B	7045601
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-25	EL296UH070XV36B	7045552
14HPX-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	C33-25	SL280UH070V36A	7045625
14HPX-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	C33-25	SL280UH070XV36A	8133578
14HPX-024-230	24,800	16.00	13.00	21,600	13,500	3.72	2.52	8.50	C33-25	SL280UH090V36B	7045614
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	C33-25	SL280UH090V48B	7045537
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	C33-25	SL280UH090XV48B	8133625
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-25	SLP98UH070XV36B	7045675
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-31	CBWMV-24B-040	7045665
14HPX-024-230	24,400	15.70	13.20	21,400	13,500	3.60	2.48	8.50	C33-31	EL180UH045E36A	7045575
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.70	2.52	8.50	C33-31	EL180UH070E36B	7045578
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	C33-31	EL195UH045XE36B	7045663
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	C33-31	EL195UH070XE36B	7045648
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	C33-31	EL296UH045XE36B	7045603
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-31	EL296UH045XV36B	7045556
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	C33-31	EL296UH070XE36B	7045592
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	C33-31	EL296UH070XV36B	7045555
14HPX-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH070V36A	7045624
14HPX-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH070XV36A	8133577
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH090V36B	7045620
14HPX-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	C33-31	SL280UH090V48B	7045538
14HPX-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	C33-31	SL280UH090XV48B	8133626
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	C33-31	SLP98UH070XV36B	7045664
14HPX-024-230	24,400	15.70	13.20	21,600	13,500	3.68	2.50	8.50	C33-36	CBWMV-24B-040	7045666
14HPX-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	C33-36	EL195UH045XE36B	7045652
14HPX-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	EL195UH070XE36B	7045649
14HPX-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	C33-36	EL296UH045XE36B	7045608
14HPX-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	EL296UH070XE36B	7045593
14HPX-024-230	23,200	14.00	11.70	22,200	14,000	3.46	2.36	8.20	CBX25UH-024		7045589
14HPX-024-230	23,200	14.00	11.70	22,200	14,100	3.48	2.38	8.20	CBX25UH-030		7045547
14HPX-024-230	23,600	15.50	12.50	21,400	13,400	3.64	2.48	8.50	CBX25UHV-024		7045543
14HPX-024-230	23,200	15.00	12.50	21,800	13,700	3.68	2.50	8.20	CBX25UHV-030		8703417
14HPX-024-230	25,200	16.00	13.50	21,800	13,700	3.88	2.64	9.00	CBX27UH-024		7045677
14HPX-024-230	25,000	16.00	13.50	21,800	13,600	3.96	2.66	9.00	CBX27UH-030		7045549
14HPX-024-230	24,800	14.20	11.70	22,800	14,100	3.54	2.42	8.20	CBX32M-018/024		7045678
14HPX-024-230	25,000	15.20	12.70	22,400	14,000	3.76	2.52	8.70	CBX32M-030		7045679
14HPX-024-230	25,000	14.50	12.20	22,600	14,000	3.58	2.44	8.20	CBX32MV-018/024		7045680
14HPX-024-230	24,800	15.20	12.70	22,200	14,000	3.72	2.52	8.70	CBX32MV-024/030		7045681
14HPX-024-230	25,200	15.50	13.00	22,400	14,000	3.92	2.60	9.00	CBX32MV-036		7045670
14HPX-024-230	24,800	15.20	12.70	22,200	14,000	3.82	2.58	8.70	CBX40UHV-024		7045671
14HPX-024-230	24,800	15.50	13.00	22,200	13,900	3.82	2.58	8.70	CBX40UHV-030		7045672
14HPX-024-230	25,200	15.50	13.00	22,400	14,000	3.92	2.60	9.00	CBX40UHV-036		7045548
14HPX-024-230	24,200	15.70	13.20	21,400	13,500	3.60	2.48	8.50	CH23-41	EL180UH045E36A	7045580
14HPX-024-230	24,600	15.70	13.20	21,600	13,500	3.70	2.50	8.50	CH23-41	EL296UH045XV36B	7045557
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CH23-41	EL296UH070XV36B	7045550
14HPX-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	CH23-41	SL280UH090V36B	7045604
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CH23-41	SL280UH090V48B	7045673
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CH23-41	SL280UH090XV48B	8133633
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CH23-41	SLP98UH070XV36B	7045639
14HPX-024-230	24,400	15.70	13.20	21,600	13,500	3.64	2.48	8.50	CH33-25A	EL180UH045E36A	7045581
14HPX-024-230	24,800	15.70	13.00	21,800	13,700	3.72	2.52	8.50	CH33-25A	SL280UH070V36A	7045618
14HPX-024-230	24,800	15.70	13.00	21,800	13,700	3.72	2.52	8.50	CH33-25A	SL280UH070XV36A	8133572
14HPX-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	EL180UH070E36B	7045569
14HPX-024-230	24,000	15.50	13.00	21,600	13,500	3.60	2.46	8.50	CH33-25B	EL195UH045XE36B	7045654
14HPX-024-230	24,400	15.50	13.00	21,800	13,600	3.68	2.50	8.50	CH33-25B	EL195UH070XE36B	7045651
14HPX-024-230	24,000	15.50	13.00	21,600	13,500	3.60	2.46	8.50	CH33-25B	EL296UH045XE36B	7045597
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.72	2.54	8.70	CH33-25B	EL296UH045XV36B	7045566
14HPX-024-230	24,400	15.50	13.00	21,800	13,600	3.68	2.50	8.50	CH33-25B	EL296UH070XE36B	7045596
14HPX-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	EL296UH070XV36B	7045560
14HPX-024-230	24,600	15.10	13.00	21,600	13,500	3.78	2.56	8.50	CH33-25B	SL280UH090V36B	7045615
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.66	2.50	8.50	CH33-25B	SL280UH090V48B	7045668
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.66	2.50	8.50	CH33-25B	SL280UH090XV48B	8133630
14HPX-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	SLP98UH070XV36B	7045628
14HPX-024-230	24,400	15.70	13.20	21,600	13,600	3.66	2.52	8.50	CH33-31A	EL180UH045E36A	7045585
14HPX-024-230	25,200	16.00	13.00	22,000	13,700	3.86	2.58	8.50	CH33-31A	SL280UH070V36A	7045623
14HPX-024-230	25,200	16.00	13.00	22,000	13,700	3.86	2.58	8.50	CH33-31A	SL280UH070XV36A	8133575
14HPX-024-230	24,400	14.20	12.00	22,400	14,200	3.54	2.40	8.20	CH33-31A		7045535
14HPX-024-230	23,800	15.20	12.70	21,400	13,500	3.50	2.42	8.20	CH33-36A	EL180UH045E36A	7045583
14HPX-024-230	24,600	15.10	13.00	21,800	13,600	3.68	2.48	8.50	CH33-36A	SL280UH070V36A	7045622
14HPX-024-230	24,600	15.10	13.00	21,800	13,600	3.68	2.48	8.50	CH33-36A	SL280UH070XV36A	8133574
14HPX-024-230	24,600	16.00	13.50	21,800	13,500	3.84	2.58	8.50	CH33-36C	EL296UH090XV36C	7045546
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-024-230	24,600	16.00	13.50	21,800	13,500	3.84	2.58	8.50	CH33-36C	SLP98UH090XV36C	7045635
14HPX-024-230	24,000	14.00	11.70	22,400	14,200	3.50	2.38	8.20	CH33-36C		7045527
14HPX-024-230	24,800	15.70	13.20	22,000	13,600	3.76	2.54	8.70	CR33-30/36	EL180DF045E36A	7045590
14HPX-024-230	25,400	16.00	13.50	22,200	13,600	3.92	2.60	9.00	CR33-30/36	EL180DF070E36B	7045574
14HPX-024-230	25,200	16.00	13.00	22,200	13,600	3.84	2.56	8.50	CR33-30/36	EL195DF045XE36B	7045660
14HPX-024-230	25,400	16.00	13.50	22,200	13,600	3.90	2.60	9.00	CR33-30/36	EL195DF070XE48B	7045661
14HPX-024-230	25,200	16.00	13.00	22,200	13,600	3.84	2.56	8.50	CR33-30/36	EL296DF045XE36B	7045594
14HPX-024-230	25,200	16.00	13.50	22,200	13,600	3.86	2.58	8.70	CR33-30/36	EL296DF045XV36B	7505744
14HPX-024-230	25,400	16.00	13.50	22,200	13,600	3.90	2.60	9.00	CR33-30/36	EL296DF070XE48B	7045595
14HPX-024-230	25,600	15.70	13.20	22,400	13,800	3.88	2.58	8.70	CR33-30/36	EL296DF070XV48B	7487530
14HPX-024-230	25,200	15.70	13.00	22,200	13,700	3.82	2.56	8.50	CR33-30/36	SL280DF070V36A	7045540
14HPX-024-230	25,600	15.10	13.50	22,200	13,700	3.94	2.62	9.00	CR33-30/36	SL280DF090V48B	7045633
14HPX-024-230	25,400	16.00	13.50	22,200	13,600	3.92	2.60	9.00	CR33-30/36	SLP98DF070XV36B	7045636
14HPX-024-230	25,400	16.00	13.50	22,200	13,600	3.94	2.62	9.00	CR33-30/36	SLP98DF090XV36C	7045637
14HPX-024-230	24,800	14.20	12.20	22,600	14,200	3.54	2.40	8.20	CR33-30/36		7045528
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	CX34-25	CBWMV-24B-040	7045645
14HPX-024-230	24,000	15.50	13.00	21,400	13,500	3.50	2.44	8.20	CX34-25	EL180UH045E36A	7045577
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.68	2.52	8.50	CX34-25	EL180UH070E36B	7045579
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	CX34-25	EL195UH045XE36B	7045655
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	CX34-25	EL195UH070XE36B	7045640
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	CX34-25	EL296UH045XE36B	7045586
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	CX34-25	EL296UH045XV36B	7045559
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	CX34-25	EL296UH070XE36B	7045588
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-25	EL296UH070XV36B	7045551
14HPX-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	CX34-25	SL280UH070V36A	7045616
14HPX-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	CX34-25	SL280UH070XV36A	8133569
14HPX-024-230	24,800	16.00	13.00	21,600	13,500	3.72	2.52	8.50	CX34-25	SL280UH090V36B	7045613
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	CX34-25	SL280UH090V48B	7045676
14HPX-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	CX34-25	SL280UH090XV48B	8133634
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-25	SLP98UH070XV36B	7045638
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-31	CBWMV-24B-040	7045674
14HPX-024-230	24,400	15.70	13.20	21,400	13,500	3.60	2.48	8.50	CX34-31	EL180UH045E36A	7045582
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.70	2.52	8.50	CX34-31	EL180UH070E36B	7045562
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	CX34-31	EL195UH045XE36B	7045656
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	CX34-31	EL195UH070XE36B	7045641
14HPX-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	CX34-31	EL296UH045XE36B	7045587
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-31	EL296UH045XV36B	7045558
14HPX-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	CX34-31	EL296UH070XE36B	7045606
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-31	EL296UH070XV36B	7045561
14HPX-024-230	24,800	15.10	13.00	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH070V36A	7045617
14HPX-024-230	24,800	15.10	13.00	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH070XV36A	8133570
14HPX-024-230	24,800	16.00	13.50	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH090V36B	7045610
14HPX-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CX34-31	SL280UH090V48B	7045669
14HPX-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CX34-31	SL280UH090XV48B	8133631
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-31	SLP98UH070XV36B	7045629
14HPX-024-230	24,400	15.70	13.20	21,600	13,500	3.68	2.50	8.50	CX34-36	CBWMV-24B-040	7045667
14HPX-024-230	24,000	15.70	13.00	21,400	13,500	3.58	2.48	8.50	CX34-36	EL180UH045E36A	7045576
14HPX-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-36	EL180UH070E36B	7045571
14HPX-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	CX34-36	EL195UH045XE36B	7045657
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	CX34-36	EL195UH070XE36B	7045642
14HPX-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	CX34-36	EL296UH045XE36B	7045605
14HPX-024-230	24,400	15.70	13.20	21,600	13,600	3.68	2.52	8.50	CX34-36	EL296UH045XV36B	7045565
14HPX-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	CX34-36	EL296UH070XE36B	7045598
14HPX-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CX34-36	EL296UH070XV36B	7045554
14HPX-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	CX34-36	EL296UH090XV36C	7045545
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	CX34-36	SL280UH070V36A	7045627
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	CX34-36	SL280UH070XV36A	8133580
14HPX-024-230	24,600	16.00	13.00	21,600	13,500	3.74	2.54	8.50	CX34-36	SL280UH090V36B	7045621
14HPX-024-230	24,400	15.10	12.50	21,600	13,600	3.62	2.48	8.20	CX34-36	SL280UH090V48B	7045658
14HPX-024-230	24,400	15.10	12.50	21,600	13,600	3.62	2.48	8.20	CX34-36	SL280UH090XV48B	8133628
14HPX-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CX34-36	SLP98UH070XV36B	7045630
14HPX-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	CX34-36	SLP98UH090XV36C	7045631
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	C33-31	CBWMV-24B-040	7044346
14HPX-030-230	30,000	15.20	13.20	25,600	16,500	3.60	2.52	8.50	C33-31	CBWMV-36B-070	7044293
14HPX-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-31	EL180UH045E36A	7044164
14HPX-030-230	30,000	15.70	13.50	25,600	16,400	3.64	2.52	8.50	C33-31	EL180UH070E36B	7044175
14HPX-030-230	30,200	15.70	13.50	25,600	16,500	3.66	2.56	8.70	C33-31	EL180UH090E48B	7044140
14HPX-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL195UH045XE36B	7044323
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL195UH070XE36B	7044359
14HPX-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL296UH045XE36B	7044207
14HPX-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	C33-31	EL296UH045XV36B	7044124
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL296UH070XE36B	7044211
14HPX-030-230	29,800	15.50	13.20	25,600	16,500	3.60	2.52	8.50	C33-31	EL296UH070XV36B	7044120
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	C33-31	SL280UH070V36A	7044257
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	C33-31	SL280UH070XV36A	8133562
14HPX-030-230	30,000	15.70	13.50	25,400	16,400	3.62	2.54	8.50	C33-31	SL280UH090V36B	7044232
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	C33-31	SL280UH090V48B	7044083
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	C33-31	SL280UH090XV48B	8133583
14HPX-030-230	30,000	15.20	13.20	25,600	16,600	3.62	2.52	8.50	C33-31	SLP98UH070XV36B	7044277
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.62	2.50	8.50	C33-36	CBWMV-24B-040	7044301
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-36	CBWMV-36B-070	7044305
14HPX-030-230	29,200	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-36	CBWMV-36C-090	7044289
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	EL180UH070E36B	7044180
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	C33-36	EL180UH090E48B	7044156
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-36	EL195UH045XE36B	7044324
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-36	EL195UH070XE36B	7044360
14HPX-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	C33-36	EL195UH090XE48C	7044336
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-36	EL296UH045XE36B	7044199
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	C33-36	EL296UH045XV36B	7044132
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-36	EL296UH070XE36B	7044220
14HPX-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	C33-36	EL296UH070XV36B	7044118
14HPX-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	C33-36	EL296UH090XE48C	7044213
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	EL296UH090XV36C	7044088
14HPX-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	C33-36	SL280UH070V36A	7044250
14HPX-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	C33-36	SL280UH070XV36A	8133557
14HPX-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	C33-36	SL280UH090V36B	7044238
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-36	SL280UH090V48B	7044084
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-36	SL280UH090XV48B	8133585
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-36	SLP98UH070XV36B	7044284
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	SLP98UH090XV36C	7044287
14HPX-030-230	29,600	15.20	13.20	25,600	16,600	3.66	2.54	8.70	C33-36	SLP98UH090XV48C	7044288
14HPX-030-230	30,800	15.50	13.50	25,600	16,600	3.66	2.54	8.50	C33-38	CBWMV-24B-040	7044338
14HPX-030-230	30,800	15.50	13.50	25,600	16,500	3.64	2.54	8.50	C33-38	CBWMV-36B-070	7044297
14HPX-030-230	30,800	15.50	13.50	25,800	16,600	3.66	2.54	8.50	C33-38	EL180UH045E36A	7044160
14HPX-030-230	30,800	15.70	13.70	25,600	16,400	3.70	2.54	8.70	C33-38	EL180UH070E36B	7044172
14HPX-030-230	31,000	15.70	13.70	25,600	16,500	3.72	2.58	8.70	C33-38	EL180UH090E48B	7044146
14HPX-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	C33-38	EL195UH045XE36B	7044313
14HPX-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	C33-38	EL195UH070XE36B	7044349
14HPX-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	C33-38	EL296UH045XE36B	7044203
14HPX-030-230	30,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	C33-38	EL296UH045XV36B	7044134
14HPX-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	C33-38	EL296UH070XE36B	7044218
14HPX-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	C33-38	EL296UH070XV36B	7044110
14HPX-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	C33-38	SL280UH070V36A	7044247
14HPX-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	C33-38	SL280UH070XV36A	8133554
14HPX-030-230	30,800	15.70	13.70	25,400	16,400	3.68	2.56	8.70	C33-38	SL280UH090V36B	7044230
14HPX-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	C33-38	SL280UH090V48B	7044382
14HPX-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	C33-38	SL280UH090XV48B	8133605
14HPX-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	C33-38	SLP98UH070XV36B	7044278
14HPX-030-230	30,400	14.00	12.20	26,200	17,200	3.44	2.40	8.20	C33-38		7044060
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.62	2.50	8.50	C33-42	CBWMV-24B-040	7044344
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-42	CBWMV-36B-070	7044347
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-42	EL180UH070E36B	7044178
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	C33-42	EL180UH090E48B	7044142
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-42	EL195UH045XE36B	7044314
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-42	EL195UH070XE36B	7044350
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-42	EL296UH045XE36B	7044215
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	C33-42	EL296UH045XV36B	7044138
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-42	EL296UH070XE36B	7044194
14HPX-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	C33-42	EL296UH070XV36B	7044126
14HPX-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	C33-42	SL280UH090V36B	7044236
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-42	SL280UH090V48B	7044085
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-42	SL280UH090XV48B	8133587
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-42	SLP98UH070XV36B	7044279
14HPX-030-230	30,400	15.50	13.50	25,800	16,500	3.66	2.52	8.50	C33-43	CBWMV-24B-040	7044294
14HPX-030-230	30,400	15.50	13.50	25,800	16,500	3.66	2.52	8.50	C33-43	CBWMV-36B-070	7044302
14HPX-030-230	30,600	16.00	13.50	25,600	16,400	3.72	2.56	8.50	C33-43	CBWMV-36C-090	7044306
14HPX-030-230	30,400	15.70	13.70	25,600	16,400	3.66	2.54	8.70	C33-43	EL180UH070E36B	7044176
14HPX-030-230	30,600	16.00	13.50	25,800	16,500	3.72	2.56	8.50	C33-43	EL180UH090E48B	7044141
14HPX-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	C33-43	EL195UH045XE36B	7044315
14HPX-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	C33-43	EL195UH070XE36B	7044351
14HPX-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	C33-43	EL195UH090XE48C	7044325
14HPX-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	C33-43	EL296UH045XE36B	7044181
14HPX-030-230	30,200	15.50	13.20	25,800	16,600	3.62	2.50	8.50	C33-43	EL296UH045XV36B	7044135
14HPX-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	C33-43	EL296UH070XE36B	7044196
14HPX-030-230	30,200	15.70	13.50	25,600	16,500	3.64	2.54	8.50	C33-43	EL296UH070XV36B	7044109
14HPX-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	C33-43	EL296UH090XE48C	7044192
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	C33-43	EL296UH090XV36C	7044108
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	C33-43	EL296UH090XV48C	7044093
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.68	2.56	8.50	C33-43	SL280UH090V36B	7044239
14HPX-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	C33-43	SL280UH090V48B	7044383
14HPX-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	C33-43	SL280UH090XV48B	8133606
14HPX-030-230	30,400	15.70	13.50	25,800	16,600	3.66	2.54	8.50	C33-43	SLP98UH070XV36B	7044266
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	C33-43	SLP98UH090XV36C	7044267
14HPX-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	C33-43	SLP98UH090XV48C	7044268
14HPX-030-230	29,600	15.20	13.00	25,400	16,500	3.52	2.48	8.20	C33-48	CBWMV-24B-040	7044290
14HPX-030-230	29,600	15.20	13.00	25,400	16,400	3.50	2.46	8.20	C33-48	CBWMV-36B-070	7044353
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	C33-48	CBWMV-36C-090	7044298
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	EL180UH070E36B	7044163
14HPX-030-230	29,800	15.50	13.20	25,400	16,400	3.58	2.50	8.50	C33-48	EL180UH090E48B	7044152
14HPX-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	C33-48	EL195UH045XE36B	7044316
14HPX-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	C33-48	EL195UH070XE36B	7044309
14HPX-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-48	EL195UH090XE48C	7044326
14HPX-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	C33-48	EL296UH045XE36B	7044184
14HPX-030-230	29,600	15.00	13.00	25,600	16,500	3.50	2.44	8.20	C33-48	EL296UH045XV36B	7044125
14HPX-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	C33-48	EL296UH070XE36B	7044204
14HPX-030-230	29,600	15.20	13.20	25,400	16,400	3.52	2.46	8.20	C33-48	EL296UH070XV36B	7044119
14HPX-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-48	EL296UH090XE48C	7044183
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	EL296UH090XV36C	7044106
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.60	2.50	8.50	C33-48	EL296UH090XV48C	7044101
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.56	2.48	8.20	C33-48	SL280UH090V36B	7044244
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	C33-48	SL280UH090V48B	7044086
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	C33-48	SL280UH090XV48B	8133588
14HPX-030-230	29,600	15.20	13.00	25,600	16,500	3.54	2.48	8.20	C33-48	SLP98UH070XV36B	7044280
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	SLP98UH090XV36C	7044265
14HPX-030-230	28,200	14.00	12.00	26,200	17,100	3.64	2.52	8.20	CBX25UH-030		7044185
14HPX-030-230	28,200	14.00	12.00	26,600	17,100	3.58	2.48	8.20	CBX25UH-036		7044089
14HPX-030-230	28,600	15.00	12.50	25,600	16,400	3.66	2.54	8.50	CBX25UHV-030		7044090
14HPX-030-230	28,200	15.00	12.50	26,000	16,700	3.72	2.58	8.20	CBX25UHV-036		8703419
14HPX-030-230	30,000	15.00	13.00	26,400	16,800	3.88	2.66	9.00	CBX27UH-030		7044384
14HPX-030-230	30,000	15.00	13.00	26,200	16,700	3.88	2.68	9.00	CBX27UH-036		7044363
14HPX-030-230	29,200	14.50	12.50	26,200	16,900	3.68	2.56	8.70	CBX32M-030		7044373
14HPX-030-230	30,000	14.50	12.00	26,800	17,300	3.74	2.58	8.70	CBX32M-036		7044374
14HPX-030-230	29,200	14.20	12.20	26,400	17,100	3.68	2.54	8.70	CBX32MV-024/030		7044375
14HPX-030-230	30,000	14.50	12.50	26,600	17,000	3.80	2.62	8.70	CBX32MV-036		7044376
14HPX-030-230	30,000	14.50	12.50	26,600	17,000	3.78	2.60	8.70	CBX40UHV-030		7044377
14HPX-030-230	30,000	15.00	12.50	26,400	16,900	3.80	2.62	8.70	CBX40UHV-036		7044378
14HPX-030-230	29,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	CH23-41	EL180UH045E36A	7044158
14HPX-030-230	29,800	15.50	13.50	25,600	16,400	3.70	2.54	8.70	CH23-41	EL180UH070E36B	7044179
14HPX-030-230	29,800	15.70	13.50	25,600	16,400	3.72	2.56	8.70	CH23-41	EL180UH090E48B	7044147
14HPX-030-230	29,600	15.00	13.00	25,800	16,600	3.62	2.50	8.50	CH23-41	EL195UH045XE36B	7044317
14HPX-030-230	29,600	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CH23-41	EL195UH070XE36B	7044310
14HPX-030-230	29,600	15.00	13.00	25,800	16,600	3.62	2.50	8.50	CH23-41	EL296UH045XE36B	7044189
14HPX-030-230	29,400	15.20	13.20	25,600	16,400	3.62	2.50	8.50	CH23-41	EL296UH045XV36B	7044121
14HPX-030-230	29,600	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CH23-41	EL296UH070XE36B	7044216
14HPX-030-230	29,400	15.50	13.20	25,400	16,300	3.62	2.50	8.50	CH23-41	EL296UH070XV36B	7044115
14HPX-030-230	29,400	15.70	13.50	25,400	16,300	3.68	2.56	8.50	CH23-41	SL280UH090V36B	7044231
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	29,800	15.50	13.20	25,600	16,400	3.68	2.54	8.70	CH23-41	SL280UH090V48B	7044367
14HPX-030-230	29,800	15.50	13.20	25,600	16,400	3.68	2.54	8.70	CH23-41	SL280UH090XV48B	8133592
14HPX-030-230	29,600	15.20	13.20	25,600	16,400	3.64	2.52	8.50	CH23-41	SLP98UH070XV36B	7044269
14HPX-030-230	29,600	15.70	13.20	25,600	16,500	3.74	2.58	8.70	CH23-51	EL180UH070E36B	7044151
14HPX-030-230	29,800	15.70	13.20	25,800	16,500	3.78	2.60	8.70	CH23-51	EL180UH090E48B	7044143
14HPX-030-230	29,600	15.20	13.00	25,800	16,700	3.66	2.54	8.50	CH23-51	EL195UH045XE36B	7044318
14HPX-030-230	29,600	15.00	12.70	26,000	16,700	3.66	2.52	8.50	CH23-51	EL195UH070XE36B	7044352
14HPX-030-230	29,600	15.20	13.00	25,800	16,700	3.66	2.54	8.50	CH23-51	EL296UH045XE36B	7044198
14HPX-030-230	29,600	15.00	12.70	26,000	16,700	3.66	2.52	8.50	CH23-51	EL296UH070XE36B	7044205
14HPX-030-230	29,400	15.50	13.20	25,400	16,400	3.68	2.58	8.70	CH23-51	EL296UH090XV36C	7044100
14HPX-030-230	29,800	15.70	13.50	25,800	16,500	3.80	2.60	8.70	CH23-51	EL296UH090XV48C	7044092
14HPX-030-230	29,400	15.50	13.20	25,400	16,400	3.68	2.58	8.70	CH23-51	SLP98UH090XV36C	7044270
14HPX-030-230	29,800	15.20	13.00	26,000	16,800	3.72	2.60	8.70	CH33-31A	EL180UH045E36A	7044167
14HPX-030-230	30,000	15.20	13.20	26,000	16,700	3.74	2.60	8.70	CH33-31A	SL280UH070V36A	7044258
14HPX-030-230	30,000	15.20	13.20	26,000	16,700	3.74	2.60	8.70	CH33-31A	SL280UH070XV36A	8133564
14HPX-030-230	29,600	14.00	12.20	26,600	17,300	3.54	2.46	8.20	CH33-31A		7044081
14HPX-030-230	30,400	15.70	13.50	25,800	16,500	3.72	2.56	8.70	CH33-31B	EL180UH070E36B	7044162
14HPX-030-230	30,400	15.70	13.70	25,600	16,500	3.72	2.58	8.70	CH33-31B	EL180UH090E48B	7044153
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.64	2.52	8.50	CH33-31B	EL195UH045XE36B	7044307
14HPX-030-230	30,400	15.50	13.20	26,000	16,800	3.68	2.54	8.70	CH33-31B	EL195UH070XE36B	7044339
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.64	2.52	8.50	CH33-31B	EL296UH045XE36B	7044208
14HPX-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.52	8.50	CH33-31B	EL296UH045XV36B	7044127
14HPX-030-230	30,400	15.50	13.20	26,000	16,800	3.68	2.54	8.70	CH33-31B	EL296UH070XE36B	7044201
14HPX-030-230	30,000	15.70	13.20	25,600	16,500	3.66	2.54	8.50	CH33-31B	EL296UH070XV36B	7044117
14HPX-030-230	30,200	15.70	13.70	25,600	16,400	3.70	2.56	8.70	CH33-31B	SL280UH090V36B	7044237
14HPX-030-230	30,400	15.70	13.50	25,800	16,600	3.72	2.58	8.70	CH33-31B	SL280UH090V48B	7044368
14HPX-030-230	30,400	15.70	13.50	25,800	16,600	3.72	2.58	8.70	CH33-31B	SL280UH090XV48B	8133593
14HPX-030-230	30,200	15.50	13.20	25,800	16,600	3.68	2.54	8.70	CH33-31B	SLP98UH070XV36B	7044260
14HPX-030-230	29,800	14.00	12.20	26,400	17,200	3.46	2.40	8.20	CH33-31B		7044072
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.52	2.48	8.20	CH33-36A	EL180UH045E36A	7044166
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.54	2.50	8.20	CH33-36A	SL280UH070V36A	7044248
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.54	2.50	8.20	CH33-36A	SL280UH070XV36A	8133555
14HPX-030-230	29,600	15.20	13.20	25,600	16,500	3.66	2.54	8.50	CH33-36B	EL180UH070E36B	7044161
14HPX-030-230	29,400	15.20	13.20	25,600	16,400	3.66	2.54	8.70	CH33-36B	EL180UH090E48B	7044155
14HPX-030-230	29,400	14.70	12.70	25,800	16,600	3.60	2.50	8.50	CH33-36B	EL195UH045XE36B	7044308
14HPX-030-230	29,600	15.00	12.70	26,000	16,700	3.64	2.50	8.50	CH33-36B	EL195UH070XE36B	7044340
14HPX-030-230	29,400	14.70	12.70	25,800	16,600	3.60	2.50	8.50	CH33-36B	EL296UH045XE36B	7044200
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.56	2.50	8.50	CH33-36B	EL296UH045XV36B	7044137
14HPX-030-230	29,600	15.00	12.70	26,000	16,700	3.64	2.50	8.50	CH33-36B	EL296UH070XE36B	7044212
14HPX-030-230	29,200	15.20	13.00	25,600	16,400	3.62	2.50	8.50	CH33-36B	EL296UH070XV36B	7044113
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.54	8.50	CH33-36B	SL280UH090V36B	7044243
14HPX-030-230	29,600	15.20	13.20	25,600	16,500	3.64	2.54	8.50	CH33-36B	SL280UH090V48B	7044370
14HPX-030-230	29,600	15.20	13.20	25,600	16,500	3.64	2.54	8.50	CH33-36B	SL280UH090XV48B	8133597
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.62	2.52	8.50	CH33-36B	SLP98UH070XV36B	7044261
14HPX-030-230	29,800	15.20	13.00	26,000	16,700	3.70	2.54	8.70	CH33-36C	EL195UH090XE48C	7044327
14HPX-030-230	29,800	15.20	13.00	26,000	16,700	3.70	2.54	8.70	CH33-36C	EL296UH090XE48C	7044225
14HPX-030-230	29,400	15.50	13.20	25,600	16,500	3.72	2.58	8.70	CH33-36C	EL296UH090XV36C	7044098
14HPX-030-230	30,000	15.50	13.20	26,000	16,700	3.80	2.62	8.70	CH33-36C	EL296UH090XV48C	7044091
14HPX-030-230	29,400	15.50	13.20	25,600	16,500	3.72	2.58	8.70	CH33-36C	SLP98UH090XV36C	7044262
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	30,000	15.50	13.20	26,000	16,700	3.80	2.62	8.70	CH33-36C	SLP98UH090XV48C	7044263
14HPX-030-230	30,000	15.70	13.20	25,600	16,500	3.66	2.54	8.50	CH33-42	EL180UH070E36B	7044139
14HPX-030-230	30,000	15.70	13.50	25,600	16,500	3.68	2.56	8.70	CH33-42	EL180UH090E48B	7044133
14HPX-030-230	30,000	15.20	13.20	25,800	16,600	3.60	2.50	8.50	CH33-42	EL195UH045XE36B	7044364
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.62	2.52	8.50	CH33-42	EL195UH070XE36B	7044341
14HPX-030-230	30,000	15.20	13.20	25,800	16,600	3.60	2.50	8.50	CH33-42	EL296UH045XE36B	7044219
14HPX-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	CH33-42	EL296UH045XV36B	7044129
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.62	2.52	8.50	CH33-42	EL296UH070XE36B	7044191
14HPX-030-230	29,800	15.50	13.20	25,600	16,400	3.62	2.50	8.50	CH33-42	EL296UH070XV36B	7044105
14HPX-030-230	29,800	15.70	13.50	25,400	16,400	3.64	2.54	8.50	CH33-42	SL280UH090V36B	7044235
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.70	CH33-42	SL280UH090V48B	7044371
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.70	CH33-42	SL280UH090XV48B	8133598
14HPX-030-230	30,000	15.50	13.20	25,600	16,600	3.62	2.54	8.50	CH33-42	SLP98UH070XV36B	7044264
14HPX-030-230	31,000	15.70	13.70	26,000	16,700	3.74	2.56	8.70	CH33-43C	EL195UH090XE48C	7044328
14HPX-030-230	31,000	15.70	13.70	26,000	16,700	3.74	2.56	8.70	CH33-43C	EL296UH090XE48C	7044228
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.72	2.58	8.50	CH33-43C	EL296UH090XV36C	7044099
14HPX-030-230	31,000	16.00	14.00	25,800	16,500	3.80	2.60	8.50	CH33-43C	EL296UH090XV48C	7044102
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.72	2.58	8.50	CH33-43C	SLP98UH090XV36C	7044253
14HPX-030-230	31,000	16.00	14.00	25,800	16,500	3.80	2.60	8.50	CH33-43C	SLP98UH090XV48C	7044254
14HPX-030-230	30,000	14.20	12.20	26,400	17,200	3.46	2.40	8.20	CH33-43C		7044067
14HPX-030-230	29,800	15.00	13.00	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL180DF045E36A	7044186
14HPX-030-230	29,800	15.50	13.20	26,800	17,100	3.84	2.64	9.00	CR33-30/36	EL180DF070E36B	7044174
14HPX-030-230	29,800	15.50	13.20	26,800	17,100	3.82	2.64	9.00	CR33-30/36	EL180DF090E48B	7044171
14HPX-030-230	29,600	15.00	12.70	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL195DF045XE36B	7044320
14HPX-030-230	30,000	15.20	13.20	27,000	17,300	3.82	2.64	9.00	CR33-30/36	EL195DF070XE48B	7044321
14HPX-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	EL195DF090XE48C	7044322
14HPX-030-230	29,600	15.00	12.70	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL296DF045XE36B	7044210
14HPX-030-230	29,600	15.20	13.20	26,800	17,100	3.76	2.60	8.70	CR33-30/36	EL296DF045XV36B	7505742
14HPX-030-230	30,000	15.20	13.20	27,000	17,300	3.82	2.64	9.00	CR33-30/36	EL296DF070XE48B	7044188
14HPX-030-230	29,600	15.00	13.00	26,800	17,200	3.72	2.58	8.70	CR33-30/36	EL296DF070XV48B	7487536
14HPX-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	EL296DF090XE48C	7044214
14HPX-030-230	29,600	15.20	13.00	26,800	17,200	3.76	2.60	8.70	CR33-30/36	SL280DF070V36A	7044372
14HPX-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	SL280DF090V48B	7044249
14HPX-030-230	29,600	15.20	13.00	26,800	17,200	3.76	2.60	8.70	CR33-30/36	SLP98DF070XV36B	7044255
14HPX-030-230	29,800	15.50	13.20	26,800	17,100	3.82	2.64	9.00	CR33-30/36	SLP98DF090XV36C	7044256
14HPX-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	SLP98DF090XV48C	7044285
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	CX34-31	CBWMV-24B-040	7044291
14HPX-030-230	30,000	15.20	13.20	25,600	16,500	3.60	2.52	8.50	CX34-31	CBWMV-36B-070	7044311
14HPX-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-31	EL180UH045E36A	7044159
14HPX-030-230	30,000	15.70	13.50	25,600	16,400	3.64	2.52	8.50	CX34-31	EL180UH070E36B	7044177
14HPX-030-230	30,200	15.70	13.50	25,600	16,500	3.66	2.56	8.70	CX34-31	EL180UH090E48B	7044154
14HPX-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL195UH045XE36B	7044365
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL195UH070XE36B	7044342
14HPX-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL296UH045XE36B	7044190
14HPX-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	CX34-31	EL296UH045XV36B	7044130
14HPX-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL296UH070XE36B	7044182
14HPX-030-230	29,800	15.50	13.20	25,600	16,500	3.60	2.52	8.50	CX34-31	EL296UH070XV36B	7044114
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	CX34-31	SL280UH070V36A	7044251
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	CX34-31	SL280UH070XV36A	8133559
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	30,000	15.70	13.50	25,400	16,400	3.62	2.54	8.50	CX34-31	SL280UH090V36B	7044242
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	CX34-31	SL280UH090V48B	7044369
14HPX-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	CX34-31	SL280UH090XV48B	8133595
14HPX-030-230	30,000	15.20	13.20	25,600	16,600	3.62	2.52	8.50	CX34-31	SLP98UH070XV36B	7044259
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.62	2.50	8.50	CX34-36	CBWMV-24B-040	7044303
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-36	CBWMV-36B-070	7044299
14HPX-030-230	29,200	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-36	CBWMV-36C-090	7044348
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	EL180UH070E36B	7044157
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	CX34-36	EL180UH090E48B	7044149
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-36	EL195UH045XE36B	7044366
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-36	EL195UH070XE36B	7044331
14HPX-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	CX34-36	EL195UH090XE48C	7044329
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-36	EL296UH045XE36B	7044217
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	CX34-36	EL296UH045XV36B	7044123
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-36	EL296UH070XE36B	7044187
14HPX-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	CX34-36	EL296UH070XV36B	7044112
14HPX-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	CX34-36	EL296UH090XE48C	7044227
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	EL296UH090XV36C	7044096
14HPX-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	CX34-36	SL280UH070V36A	7044252
14HPX-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	CX34-36	SL280UH070XV36A	8133560
14HPX-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	CX34-36	SL280UH090V36B	7044246
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-36	SL280UH090V48B	7044087
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-36	SL280UH090XV48B	8133590
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-36	SLP98UH070XV36B	7044281
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	SLP98UH090XV36C	7044282
14HPX-030-230	29,600	15.20	13.20	25,600	16,600	3.66	2.54	8.70	CX34-36	SLP98UH090XV48C	7044271
14HPX-030-230	30,800	15.50	13.50	25,600	16,600	3.66	2.54	8.50	CX34-38	CBWMV-24B-040	7044295
14HPX-030-230	30,800	15.50	13.50	25,600	16,500	3.64	2.54	8.50	CX34-38	CBWMV-36B-070	7044354
14HPX-030-230	30,800	15.50	13.50	25,800	16,600	3.66	2.54	8.50	CX34-38	EL180UH045E36A	7044165
14HPX-030-230	30,800	15.70	13.70	25,600	16,400	3.70	2.54	8.70	CX34-38	EL180UH070E36B	7044168
14HPX-030-230	31,000	15.70	13.70	25,600	16,500	3.72	2.58	8.70	CX34-38	EL180UH090E48B	7044148
14HPX-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	CX34-38	EL195UH045XE36B	7044355
14HPX-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	CX34-38	EL195UH070XE36B	7044332
14HPX-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	CX34-38	EL296UH045XE36B	7044193
14HPX-030-230	30,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	CX34-38	EL296UH045XV36B	7044136
14HPX-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	CX34-38	EL296UH070XE36B	7044197
14HPX-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	CX34-38	EL296UH070XV36B	7044104
14HPX-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	CX34-38	SL280UH070V36A	7044241
14HPX-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	CX34-38	SL280UH070XV36A	8133552
14HPX-030-230	30,800	15.70	13.70	25,400	16,400	3.68	2.56	8.70	CX34-38	SL280UH090V36B	7044240
14HPX-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	CX34-38	SL280UH090V48B	7044082
14HPX-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	CX34-38	SL280UH090XV48B	8133582
14HPX-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	CX34-38	SLP98UH070XV36B	7044283
14HPX-030-230	30,400	14.00	12.20	26,200	17,200	3.44	2.40	8.20	CX34-38		7044062
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.62	2.50	8.50	CX34-42	CBWMV-24B-040	7044345
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-42	CBWMV-36B-070	7044292
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-42	EL180UH070E36B	7044170
14HPX-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	CX34-42	EL180UH090E48B	7044144
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-42	EL195UH045XE36B	7044356
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-42	EL195UH070XE36B	7044333
14HPX-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-42	EL296UH045XE36B	7044195
14HPX-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	CX34-42	EL296UH045XV36B	7044122
14HPX-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-42	EL296UH070XE36B	7044206
14HPX-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	CX34-42	EL296UH070XV36B	7044116
14HPX-030-230	29,200	15.10	13.00	25,400	16,300	3.62	2.52	8.50	CX34-42	SL280UH090V36B	7044229
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-42	SL280UH090V48B	7044379
14HPX-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-42	SL280UH090XV48B	8133600
14HPX-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-42	SLP98UH070XV36B	7044272
14HPX-030-230	30,400	15.50	13.50	25,800	16,500	3.66	2.52	8.50	CX34-43	CBWMV-24B-040	7044312
14HPX-030-230	30,400	15.50	13.50	25,800	16,500	3.66	2.52	8.50	CX34-43	CBWMV-36B-070	7044304
14HPX-030-230	30,600	16.00	13.50	25,600	16,400	3.72	2.56	8.50	CX34-43	CBWMV-36C-090	7044300
14HPX-030-230	30,400	15.70	13.70	25,600	16,400	3.66	2.54	8.70	CX34-43	EL180UH070E36B	7044169
14HPX-030-230	30,600	16.00	13.50	25,800	16,500	3.72	2.56	8.50	CX34-43	EL180UH090E48B	7044150
14HPX-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	CX34-43	EL195UH045XE36B	7044357
14HPX-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	CX34-43	EL195UH070XE36B	7044334
14HPX-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	CX34-43	EL195UH090XE48C	7044330
14HPX-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	CX34-43	EL296UH045XE36B	7044221
14HPX-030-230	30,200	15.50	13.20	25,800	16,600	3.62	2.50	8.50	CX34-43	EL296UH045XV36B	7044128
14HPX-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	CX34-43	EL296UH070XE36B	7044209
14HPX-030-230	30,200	15.70	13.50	25,600	16,500	3.64	2.54	8.50	CX34-43	EL296UH070XV36B	7044103
14HPX-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	CX34-43	EL296UH090XE48C	7044224
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	CX34-43	EL296UH090XV36C	7044107
14HPX-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	CX34-43	EL296UH090XV48C	7044094
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.68	2.56	8.50	CX34-43	SL280UH090V36B	7044245
14HPX-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	CX34-43	SL280UH090V48B	7044380
14HPX-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	CX34-43	SL280UH090XV48B	8133602
14HPX-030-230	30,400	15.70	13.50	25,800	16,600	3.66	2.54	8.50	CX34-43	SLP98UH070XV36B	7044273
14HPX-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	CX34-43	SLP98UH090XV36C	7044274
14HPX-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	CX34-43	SLP98UH090XV48C	7044275
14HPX-030-230	29,600	15.20	13.00	25,400	16,500	3.52	2.48	8.20	CX34-44/48	CBWMV-24B-040	7044337
14HPX-030-230	29,600	15.20	13.00	25,400	16,400	3.50	2.46	8.20	CX34-44/48	CBWMV-36B-070	7044296
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	CX34-44/48	CBWMV-36C-090	7044343
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	EL180UH070E36B	7044173
14HPX-030-230	29,800	15.50	13.20	25,400	16,400	3.58	2.50	8.50	CX34-44/48	EL180UH090E48B	7044145
14HPX-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	CX34-44/48	EL195UH045XE36B	7044358
14HPX-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	CX34-44/48	EL195UH070XE36B	7044335
14HPX-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-44/48	EL195UH090XE48C	7044319
14HPX-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	CX34-44/48	EL296UH045XE36B	7044222
14HPX-030-230	29,600	15.00	13.00	25,600	16,500	3.50	2.44	8.20	CX34-44/48	EL296UH045XV36B	7044131
14HPX-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	CX34-44/48	EL296UH070XE36B	7044202
14HPX-030-230	29,600	15.20	13.20	25,400	16,400	3.52	2.46	8.20	CX34-44/48	EL296UH070XV36B	7044111
14HPX-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-44/48	EL296UH090XE48C	7044226
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	EL296UH090XV36C	7044097
14HPX-030-230	30,000	15.50	13.20	25,600	16,500	3.60	2.50	8.50	CX34-44/48	EL296UH090XV48C	7044095
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.56	2.48	8.20	CX34-44/48	SL280UH090V36B	7044233
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	CX34-44/48	SL280UH090V48B	7044381
14HPX-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	CX34-44/48	SL280UH090XV48B	8133603
14HPX-030-230	29,600	15.20	13.00	25,600	16,500	3.54	2.48	8.20	CX34-44/48	SLP98UH070XV36B	7044276
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	SLP98UH090XV36C	7044286
14HPX-036-230	34,200	15.20	12.70	32,600	20,800	3.44	2.44	8.20	C33-38	CBWMV-24B-040	7044603
14HPX-036-230	34,200	15.20	12.70	32,600	20,800	3.44	2.42	8.20	C33-38	CBWMV-36B-070	7044606
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL180UH045E36A	7044496
14HPX-036-230	34,200	15.70	13.00	32,400	20,400	3.48	2.44	8.50	C33-38	EL180UH070E36B	7044497
14HPX-036-230	34,600	15.50	13.00	32,600	20,600	3.52	2.46	8.50	C33-38	EL180UH090E48B	7044477
14HPX-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	C33-38	EL195UH045XE36B	7044708
14HPX-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	C33-38	EL195UH070XE36B	7044703
14HPX-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	C33-38	EL296UH045XE36B	7044561
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL296UH045XV36B	7044465
14HPX-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	C33-38	EL296UH070XE36B	7044546
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL296UH070XV36B	7044452
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	C33-38	SL280UH070V36A	7044579
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	C33-38	SL280UH070XV36A	8133565
14HPX-036-230	34,400	15.70	13.00	32,600	20,600	3.50	2.46	8.20	C33-38	SL280UH090V36B	7044572
14HPX-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	C33-38	SL280UH090V48B	7044756
14HPX-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	C33-38	SL280UH090XV48B	8133620
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	SLP98UH070XV36B	7044684
14HPX-036-230	35,200	15.20	13.00	32,600	20,400	3.44	2.46	8.20	C33-43	CBWMV-24B-040	7044599
14HPX-036-230	35,200	15.20	13.00	32,600	20,400	3.42	2.46	8.20	C33-43	CBWMV-36B-070	7044630
14HPX-036-230	35,200	15.50	13.00	32,600	20,400	3.46	2.48	8.20	C33-43	CBWMV-36C-090	7044597
14HPX-036-230	35,200	15.70	13.20	32,400	20,200	3.46	2.50	8.50	C33-43	EL180UH070E36B	7044502
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL180UH090E48B	7044482
14HPX-036-230	35,600	15.70	13.20	32,600	20,200	3.52	2.50	8.20	C33-43	EL180UH090E60C	7044473
14HPX-036-230	35,200	15.70	13.20	32,400	20,200	3.48	2.50	8.50	C33-43	EL180UH110E60C	7044507
14HPX-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	C33-43	EL195UH045XE36B	7044709
14HPX-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	C33-43	EL195UH070XE36B	7044692
14HPX-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	C33-43	EL195UH090XE48C	7044687
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL195UH110XE60C	7044616
14HPX-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	C33-43	EL296UH045XE36B	7044532
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.46	8.20	C33-43	EL296UH045XV36B	7044474
14HPX-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	C33-43	EL296UH070XE36B	7044542
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	C33-43	EL296UH070XV36B	7044463
14HPX-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	C33-43	EL296UH090XE48C	7044547
14HPX-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	C33-43	EL296UH090XV36C	7044457
14HPX-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	EL296UH090XV48C	7044438
14HPX-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	C33-43	EL296UH090XV60C	7044431
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL296UH110XE60C	7044558
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	C33-43	EL296UH110XV48C	7044526
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	C33-43	EL296UH110XV60C	7044419
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	C33-43	SL280UH090V36B	7044573
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SL280UH090V48B	7044405
14HPX-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	C33-43	SL280UH090V60C	7044748
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SL280UH090XV48B	8133608
14HPX-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	C33-43	SL280UH090XV60C	8133653
14HPX-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	C33-43	SL280UH110V60C	7044754
14HPX-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	C33-43	SL280UH110XV60C	8133700
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	C33-43	SLP98UH070XV36B	7044685
14HPX-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	C33-43	SLP98UH090XV36C	7044691
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
14HPX-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SLP98UH090XV48C	7044680
14HPX-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	C33-43	SLP98UH090XV60C	7044681
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	C33-43	SLP98UH110XV60C	7044682
14HPX-036-230	34,000	15.00	12.70	32,400	20,600	3.34	2.36	8.20	C33-48	CBWMV-24B-040	7044592
14HPX-036-230	33,800	15.20	12.70	32,400	20,600	3.34	2.38	8.20	C33-48	CBWMV-36C-090	7044590
14HPX-036-230	33,800	15.50	13.00	32,200	20,400	3.36	2.38	8.20	C33-48	EL180UH070E36B	7044505
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL180UH090E48B	7044491
14HPX-036-230	34,200	15.50	13.00	32,400	20,400	3.40	2.38	8.20	C33-48	EL180UH090E60C	7044470
14HPX-036-230	34,000	15.50	13.00	32,200	20,400	3.36	2.38	8.20	C33-48	EL180UH110E60C	7044511
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL195UH090XE48C	7044688
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL195UH110XE60C	7044617
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL296UH090XE48C	7044543
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL296UH090XV36C	7044446
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	C33-48	EL296UH090XV48C	7044437
14HPX-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	C33-48	EL296UH090XV60C	7044424
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL296UH110XE60C	7044550
14HPX-036-230	34,200	15.50	13.00	32,200	20,400	3.38	2.38	8.20	C33-48	EL296UH110XV48C	7044522
14HPX-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	C33-48	EL296UH110XV60C	7044417
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.36	2.38	8.20	C33-48	SL280UH090V36B	7044576
14HPX-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	C33-48	SL280UH090V48B	7044755
14HPX-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	C33-48	SL280UH090V60C	7044710
14HPX-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	C33-48	SL280UH090XV48B	8133618
14HPX-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	C33-48	SL280UH090XV60C	8133639
14HPX-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	C33-48	SL280UH110V60C	7044749
14HPX-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	C33-48	SL280UH110XV60C	8133697
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	SLP98UH090XV36C	7044678
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	C33-48	SLP98UH090XV48C	7044679
14HPX-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	C33-48	SLP98UH090XV60C	7044586
14HPX-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	C33-48	SLP98UH110XV60C	7044668
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.56	2.48	8.70	C33-49	CBWMV-36C-090	7044604
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL180UH090E60C	7044499
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.62	2.50	8.70	C33-49	EL180UH110E60C	7044508
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	C33-49	EL195UH090XE48C	7044631
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL195UH110XE60C	7044618
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	C33-49	EL296UH090XE48C	7044565
14HPX-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	C33-49	EL296UH090XV36C	7044450
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	C33-49	EL296UH090XV48C	7044445
14HPX-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	C33-49	EL296UH090XV60C	7044425
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL296UH110XE60C	7044538
14HPX-036-230	35,000	15.70	13.20	31,400	20,200	3.60	2.50	8.70	C33-49	EL296UH110XV48C	7044512
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL296UH110XV60C	7044410
14HPX-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	C33-49	SL280UH090V60C	7044750
14HPX-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	C33-49	SL280UH090XV60C	8133654
14HPX-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	C33-49	SL280UH110V60C	7044751
14HPX-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	C33-49	SL280UH110XV60C	8133698
14HPX-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	C33-49	SLP98UH090XV36C	7044669
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	C33-49	SLP98UH090XV48C	7044670
14HPX-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	C33-49	SLP98UH090XV60C	7044671
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	SLP98UH110XV60C	7044672
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-036-230	34,400	14.20	12.00	32,200	21,000	3.40	2.36	8.20	C33-49		7044390
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.54	2.48	8.70	C33-50/60C	CBWMV-36C-090	7044607
14HPX-036-230	34,600	15.50	13.00	31,400	20,200	3.60	2.50	8.70	C33-50/60C	EL180UH090E60C	7044483
14HPX-036-230	34,200	15.50	13.00	31,200	20,200	3.56	2.50	8.70	C33-50/60C	EL180UH110E60C	7044500
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL195UH090XE48C	7044620
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	C33-50/60C	EL195UH110XE60C	7044619
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL296UH090XE48C	7044557
14HPX-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL296UH090XV36C	7044448
14HPX-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	C33-50/60C	EL296UH090XV48C	7044439
14HPX-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	C33-50/60C	EL296UH090XV60C	7044422
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	C33-50/60C	EL296UH110XE60C	7044531
14HPX-036-230	34,400	15.50	13.00	31,400	20,200	3.58	2.50	8.70	C33-50/60C	EL296UH110XV48C	7044528
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	C33-50/60C	EL296UH110XV60C	7044414
14HPX-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	C33-50/60C	SL280UH090V60C	7044741
14HPX-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	C33-50/60C	SL280UH090XV60C	8133649
14HPX-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	C33-50/60C	SL280UH110V60C	7044742
14HPX-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	C33-50/60C	SL280UH110XV60C	8133693
14HPX-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	SLP98UH090XV36C	7044663
14HPX-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	C33-50/60C	SLP98UH090XV48C	7044664
14HPX-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	C33-50/60C	SLP98UH090XV60C	7044587
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	C33-50/60C	SLP98UH110XV60C	7044673
14HPX-036-230	33,800	14.00	11.70	32,000	21,000	3.34	2.36	8.20	C33-50/60C		7044397
14HPX-036-230	34,600	14.00	12.00	34,600	21,400	3.50	2.44	8.20	CBX25UH-036		7044513
14HPX-036-230	34,600	15.00	12.50	34,000	21,000	3.58	2.52	8.50	CBX25UHV-036		7044409
14HPX-036-230	34,800	15.20	12.50	32,800	20,400	3.72	2.56	8.70	CBX27UH-036		7044407
14HPX-036-230	36,000	16.00	13.50	33,000	17,300	3.98	2.34	8.50	CBX27UH-042		7044408
14HPX-036-230	34,600	14.50	11.70	33,400	20,800	3.62	2.48	8.50	CBX32M-036		7044752
14HPX-036-230	34,400	14.50	11.70	33,200	20,800	3.60	2.48	8.50	CBX32M-042		7044753
14HPX-036-230	34,800	14.70	12.00	33,200	20,800	3.64	2.52	8.70	CBX32MV-036		7044743
14HPX-036-230	35,400	15.50	13.00	31,800	20,800	3.76	2.62	9.20	CBX32MV-048		7044744
14HPX-036-230	34,800	14.70	12.20	33,200	20,600	3.68	2.52	8.70	CBX40UHV-036		7044745
14HPX-036-230	35,200	15.20	12.70	32,000	20,800	3.74	2.58	9.00	CBX40UHV-042		7044734
14HPX-036-230	35,400	15.50	13.00	31,800	20,800	3.78	2.62	9.20	CBX40UHV-048		7044735
14HPX-036-230	35,200	15.70	13.20	32,000	20,200	3.68	2.54	9.00	CH33-43B	EL180UH070E36B	7044504
14HPX-036-230	35,600	15.70	13.20	32,200	20,400	3.72	2.54	9.00	CH33-43B	EL180UH090E48B	7044480
14HPX-036-230	35,400	14.70	12.50	32,800	21,000	3.60	2.48	8.50	CH33-43B	EL195UH045XE36B	7044699
14HPX-036-230	35,200	15.20	12.70	32,200	20,600	3.62	2.50	8.70	CH33-43B	EL195UH070XE36B	7044694
14HPX-036-230	35,400	14.70	12.50	32,800	21,000	3.60	2.48	8.50	CH33-43B	EL296UH045XE36B	7044560
14HPX-036-230	35,400	15.20	12.70	32,600	20,800	3.66	2.50	8.70	CH33-43B	EL296UH045XV36B	7044469
14HPX-036-230	35,200	15.20	12.70	32,200	20,600	3.62	2.50	8.70	CH33-43B	EL296UH070XE36B	7044556
14HPX-036-230	35,600	15.20	12.70	32,600	20,800	3.66	2.52	8.70	CH33-43B	EL296UH070XV36B	7044461
14HPX-036-230	35,600	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-43B	SL280UH090V36B	7044574
14HPX-036-230	35,600	15.70	13.20	32,400	20,600	3.72	2.56	9.00	CH33-43B	SL280UH090V48B	7044736
14HPX-036-230	35,600	15.70	13.20	32,400	20,600	3.72	2.56	9.00	CH33-43B	SL280UH090XV48B	8133615
14HPX-036-230	35,600	15.20	12.70	32,600	20,800	3.66	2.52	8.70	CH33-43B	SLP98UH070XV36B	7044665
14HPX-036-230	35,200	14.50	12.20	32,800	21,000	3.52	2.42	8.50	CH33-43B		7044398
14HPX-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	EL180UH090E60C	7044498
14HPX-036-230	35,200	15.70	13.20	32,400	20,400	3.48	2.46	8.50	CH33-43C	EL180UH110E60C	7044510
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL195UH090XE48C	7044621
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.46	8.50	CH33-43C	EL195UH110XE60C	7044608
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL296UH090XE48C	7044549
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL296UH090XV36C	7044441
14HPX-036-230	35,000	15.50	13.20	32,400	20,400	3.46	2.44	8.50	CH33-43C	EL296UH090XV48C	7044443
14HPX-036-230	35,600	15.50	13.00	32,800	20,800	3.52	2.48	8.50	CH33-43C	EL296UH090XV60C	7044432
14HPX-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.46	8.50	CH33-43C	EL296UH110XE60C	7044524
14HPX-036-230	35,200	15.70	13.20	32,400	20,600	3.48	2.48	8.50	CH33-43C	EL296UH110XV48C	7044527
14HPX-036-230	35,600	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	EL296UH110XV60C	7044411
14HPX-036-230	35,600	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-43C	SL280UH090V60C	7044406
14HPX-036-230	35,600	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-43C	SL280UH090XV60C	8133638
14HPX-036-230	35,400	15.10	13.00	32,800	20,600	3.52	2.46	8.20	CH33-43C	SL280UH110V60C	7044737
14HPX-036-230	35,400	15.10	13.00	32,800	20,600	3.52	2.46	8.20	CH33-43C	SL280UH110XV60C	8133691
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	SLP98UH090XV36C	7044666
14HPX-036-230	35,000	15.50	13.20	32,400	20,400	3.46	2.44	8.50	CH33-43C	SLP98UH090XV48C	7044667
14HPX-036-230	35,600	15.50	13.00	32,800	20,800	3.52	2.48	8.50	CH33-43C	SLP98UH090XV60C	7044656
14HPX-036-230	35,600	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	SLP98UH110XV60C	7044657
14HPX-036-230	34,000	15.20	12.70	32,400	20,400	3.38	2.46	8.20	CH33-44/48	EL180UH070E36B	7044501
14HPX-036-230	34,200	15.20	12.70	32,800	20,600	3.42	2.48	8.20	CH33-44/48	EL180UH090E48B	7044476
14HPX-036-230	34,000	14.70	12.50	32,800	20,800	3.36	2.44	8.20	CH33-44/48	EL195UH070XE36B	7044695
14HPX-036-230	34,200	14.50	12.20	33,000	21,000	3.36	2.44	8.20	CH33-44/48	EL296UH045XV36B	7044466
14HPX-036-230	34,000	14.70	12.50	32,800	20,800	3.36	2.44	8.20	CH33-44/48	EL296UH070XE36B	7044548
14HPX-036-230	34,200	14.70	12.50	33,000	21,000	3.38	2.46	8.20	CH33-44/48	EL296UH070XV36B	7044460
14HPX-036-230	34,400	15.20	12.70	32,800	20,600	3.46	2.48	8.20	CH33-44/48	SL280UH090V36B	7044575
14HPX-036-230	34,400	15.00	12.70	32,800	20,800	3.42	2.48	8.20	CH33-44/48	SL280UH090V48B	7044738
14HPX-036-230	34,400	15.00	12.70	32,800	20,800	3.42	2.48	8.20	CH33-44/48	SL280UH090XV48B	8133616
14HPX-036-230	34,200	14.70	12.50	33,000	21,000	3.38	2.46	8.20	CH33-44/48	SLP98UH070XV36B	7044658
14HPX-036-230	35,000	15.50	13.00	32,600	20,600	3.46	2.44	8.20	CH33-48	EL296UH090XV36C	7044456
14HPX-036-230	34,800	15.50	13.00	32,400	20,400	3.44	2.44	8.50	CH33-48	EL296UH090XV48C	7044436
14HPX-036-230	35,400	15.20	13.00	32,800	20,800	3.52	2.46	8.50	CH33-48	EL296UH090XV60C	7044433
14HPX-036-230	35,000	15.50	13.20	32,400	20,600	3.46	2.48	8.50	CH33-48	EL296UH110XV48C	7044520
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.52	2.46	8.50	CH33-48	EL296UH110XV60C	7044413
14HPX-036-230	35,400	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-48	SL280UH090V60C	7044739
14HPX-036-230	35,400	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-48	SL280UH090XV60C	8133648
14HPX-036-230	35,200	15.10	12.50	32,600	20,600	3.48	2.44	8.20	CH33-48	SL280UH110V60C	7044757
14HPX-036-230	35,200	15.10	12.50	32,600	20,600	3.48	2.44	8.20	CH33-48	SL280UH110XV60C	8133702
14HPX-036-230	35,000	15.50	13.00	32,600	20,600	3.46	2.44	8.20	CH33-48	SLP98UH090XV36C	7044674
14HPX-036-230	34,800	15.50	13.00	32,400	20,400	3.44	2.44	8.50	CH33-48	SLP98UH090XV48C	7044675
14HPX-036-230	35,400	15.20	13.00	32,800	20,800	3.52	2.46	8.50	CH33-48	SLP98UH090XV60C	7044676
14HPX-036-230	35,200	15.50	13.20	32,600	20,600	3.52	2.46	8.50	CH33-48	SLP98UH110XV60C	7044677
14HPX-036-230	35,200	15.70	13.20	31,800	20,400	3.76	2.58	9.00	CH33-49	EL180UH090E60C	7044487
14HPX-036-230	35,000	15.70	13.20	31,600	20,200	3.72	2.56	9.00	CH33-49	EL180UH110E60C	7044515
14HPX-036-230	34,800	15.50	13.00	31,800	20,400	3.70	2.56	8.50	CH33-49	EL195UH090XE48C	7044622
14HPX-036-230	35,200	15.70	13.20	31,800	20,400	3.74	2.56	9.00	CH33-49	EL195UH110XE60C	7044609
14HPX-036-230	34,800	15.50	13.00	31,800	20,400	3.70	2.56	8.50	CH33-49	EL296UH090XE48C	7044563
14HPX-036-230	35,000	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-49	EL296UH090XV36C	7044454
14HPX-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-49	EL296UH090XV48C	7044434
14HPX-036-230	35,400	15.50	13.00	32,400	20,600	3.78	2.56	9.00	CH33-49	EL296UH090XV60C	7044429
14HPX-036-230	35,200	15.70	13.20	31,800	20,400	3.74	2.56	9.00	CH33-49	EL296UH110XE60C	7044537
14HPX-036-230	35,000	15.70	13.20	32,000	20,400	3.76	2.58	9.00	CH33-49	EL296UH110XV48C	7044525
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-036-230	35,400	15.70	13.20	32,200	20,400	3.78	2.58	9.00	CH33-49	EL296UH110XV60C	7044412
14HPX-036-230	35,400	15.10	13.00	32,200	20,400	3.80	2.58	9.00	CH33-49	SL280UH090V60C	7044728
14HPX-036-230	35,400	15.10	13.00	32,200	20,400	3.80	2.58	9.00	CH33-49	SL280UH090XV60C	8133644
14HPX-036-230	35,200	15.10	13.00	32,200	20,600	3.74	2.58	9.00	CH33-49	SL280UH110V60C	7044729
14HPX-036-230	35,200	15.10	13.00	32,200	20,600	3.74	2.58	9.00	CH33-49	SL280UH110XV60C	8133688
14HPX-036-230	35,000	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-49	SLP98UH090XV36C	7044659
14HPX-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-49	SLP98UH090XV48C	7044660
14HPX-036-230	35,400	15.50	13.00	32,400	20,600	3.78	2.56	9.00	CH33-49	SLP98UH090XV60C	7044661
14HPX-036-230	35,400	15.70	13.20	32,200	20,400	3.78	2.58	9.00	CH33-49	SLP98UH110XV60C	7044650
14HPX-036-230	34,400	14.20	12.00	32,800	21,000	3.52	2.42	8.50	CH33-49		7044401
14HPX-036-230	35,000	15.70	13.20	31,600	20,400	3.70	2.56	9.00	CH33-50/60C	EL180UH090E60C	7044471
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.66	2.54	9.00	CH33-50/60C	EL180UH110E60C	7044506
14HPX-036-230	34,800	15.50	13.00	31,600	20,400	3.66	2.54	9.00	CH33-50/60C	EL195UH090XE48C	7044623
14HPX-036-230	35,000	15.70	13.20	31,800	20,400	3.72	2.56	9.00	CH33-50/60C	EL195UH110XE60C	7044610
14HPX-036-230	34,800	15.50	13.00	31,600	20,400	3.66	2.54	9.00	CH33-50/60C	EL296UH090XE48C	7044530
14HPX-036-230	34,800	15.50	13.00	32,000	20,400	3.70	2.54	9.00	CH33-50/60C	EL296UH090XV36C	7044449
14HPX-036-230	34,600	15.70	13.00	31,800	20,400	3.68	2.56	9.00	CH33-50/60C	EL296UH090XV48C	7044444
14HPX-036-230	35,400	15.50	13.00	32,400	20,600	3.76	2.56	9.00	CH33-50/60C	EL296UH090XV60C	7044423
14HPX-036-230	35,000	15.70	13.20	31,800	20,400	3.72	2.56	9.00	CH33-50/60C	EL296UH110XE60C	7044545
14HPX-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-50/60C	EL296UH110XV48C	7044521
14HPX-036-230	35,200	15.70	13.20	32,200	20,400	3.76	2.56	9.00	CH33-50/60C	EL296UH110XV60C	7044418
14HPX-036-230	35,400	15.10	13.00	32,200	20,400	3.78	2.58	9.00	CH33-50/60C	SL280UH090V60C	7044730
14HPX-036-230	35,400	15.10	13.00	32,200	20,400	3.78	2.58	9.00	CH33-50/60C	SL280UH090XV60C	8133646
14HPX-036-230	35,000	15.50	12.50	32,200	20,400	3.74	2.54	8.50	CH33-50/60C	SL280UH110V60C	7044731
14HPX-036-230	35,000	15.50	12.50	32,200	20,400	3.74	2.54	8.50	CH33-50/60C	SL280UH110XV60C	8133690
14HPX-036-230	34,800	15.50	13.00	32,000	20,400	3.70	2.54	9.00	CH33-50/60C	SLP98UH090XV36C	7044651
14HPX-036-230	34,600	15.70	13.00	31,800	20,400	3.68	2.56	9.00	CH33-50/60C	SLP98UH090XV48C	7044652
14HPX-036-230	35,400	15.50	13.00	32,400	20,600	3.76	2.56	9.00	CH33-50/60C	SLP98UH090XV60C	7044653
14HPX-036-230	35,200	15.70	13.20	32,200	20,400	3.76	2.56	9.00	CH33-50/60C	SLP98UH110XV60C	7044654
14HPX-036-230	34,200	14.20	12.00	32,600	21,000	3.48	2.40	8.20	CH33-50/60C		7044402
14HPX-036-230	35,200	15.70	13.20	33,200	20,800	3.52	2.48	8.50	CR33-48	EL180DF070E36B	7044494
14HPX-036-230	35,200	15.50	13.00	33,400	21,000	3.54	2.50	8.50	CR33-48	EL180DF090E48B	7044484
14HPX-036-230	35,800	15.70	13.20	33,400	21,000	3.58	2.52	8.70	CR33-48	EL180DF110E60C	7044488
14HPX-036-230	34,800	15.00	12.70	33,400	21,200	3.44	2.44	8.20	CR33-48	EL195DF045XE36B	7044714
14HPX-036-230	35,200	15.20	13.00	33,400	21,000	3.50	2.46	8.50	CR33-48	EL195DF070XE48B	7044715
14HPX-036-230	35,200	15.20	12.70	33,400	21,000	3.48	2.46	8.50	CR33-48	EL195DF090XE48C	7044704
14HPX-036-230	35,600	15.50	13.00	33,600	21,000	3.58	2.50	8.50	CR33-48	EL195DF110XE60C	7044706
14HPX-036-230	34,800	15.00	12.70	33,400	21,200	3.44	2.44	8.20	CR33-48	EL296DF045XE36B	7044566
14HPX-036-230	35,200	15.00	12.70	33,600	21,200	3.46	2.44	8.20	CR33-48	EL296DF045XV36B	7505743
14HPX-036-230	35,200	15.20	13.00	33,400	21,000	3.50	2.46	8.50	CR33-48	EL296DF070XE48B	7044568
14HPX-036-230	35,200	15.00	12.50	33,800	21,200	3.48	2.42	8.20	CR33-48	EL296DF070XV48B	7487529
14HPX-036-230	35,600	15.50	13.00	33,600	21,000	3.56	2.48	8.50	CR33-48	EL296DF090V60C	7044722
14HPX-036-230	35,200	15.20	12.70	33,400	21,000	3.48	2.46	8.50	CR33-48	EL296DF090XE48C	7044567
14HPX-036-230	35,600	15.50	13.00	33,600	21,200	3.56	2.50	8.50	CR33-48	EL296DF110V60C	7044723
14HPX-036-230	35,600	15.50	13.00	33,600	21,000	3.58	2.50	8.50	CR33-48	EL296DF110XE60C	7044570
14HPX-036-230	35,200	15.50	13.00	33,400	21,000	3.52	2.48	8.50	CR33-48	SL280DF090V48B	7044578
14HPX-036-230	35,800	15.70	13.00	33,600	21,000	3.62	2.52	8.50	CR33-48	SL280DF090V60C	7044724
14HPX-036-230	35,600	15.10	13.00	33,400	21,000	3.58	2.52	8.50	CR33-48	SL280DF110V60C	7044725
14HPX-036-230	35,400	15.20	12.70	33,600	21,200	3.50	2.46	8.50	CR33-48	SLP98DF070XV36B	7044655
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-036-230	35,400	15.50	13.00	33,400	21,000	3.52	2.46	8.50	CR33-48	SLP98DF090XV36C	7044644
14HPX-036-230	35,400	15.50	13.00	33,400	21,000	3.54	2.48	8.50	CR33-48	SLP98DF090XV48C	7044645
14HPX-036-230	35,600	15.50	13.00	33,600	21,000	3.56	2.48	8.50	CR33-48	SLP98DF090XV60C	7044646
14HPX-036-230	35,600	15.50	13.00	33,600	21,200	3.56	2.50	8.50	CR33-48	SLP98DF110XV60C	7044647
14HPX-036-230	34,800	14.20	12.00	34,000	21,600	3.34	2.36	8.20	CR33-48		7044391
14HPX-036-230	36,000	16.00	13.50	32,800	20,400	3.92	2.64	9.00	CR33-50/60	EL180DF110E60C	7044485
14HPX-036-230	35,600	15.50	13.20	32,800	20,600	3.80	2.60	8.70	CR33-50/60	EL195DF090XE48C	7044705
14HPX-036-230	35,800	15.70	13.20	32,800	20,600	3.88	2.64	9.00	CR33-50/60	EL195DF110XE60C	7044707
14HPX-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	EL296DF090V60C	7044726
14HPX-036-230	35,600	15.50	13.20	32,800	20,600	3.80	2.60	8.70	CR33-50/60	EL296DF090XE48C	7044571
14HPX-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	EL296DF110V60C	7044712
14HPX-036-230	35,800	15.70	13.20	32,800	20,600	3.88	2.64	9.00	CR33-50/60	EL296DF110XE60C	7044577
14HPX-036-230	36,600	15.10	13.00	34,000	21,200	3.82	2.62	9.00	CR33-50/60	SL280DF090V60C	7044727
14HPX-036-230	36,400	15.10	13.00	33,800	21,000	3.80	2.60	8.50	CR33-50/60	SL280DF110V60C	7044740
14HPX-036-230	36,200	15.70	13.20	33,800	21,200	3.72	2.56	8.70	CR33-50/60	SLP98DF090XV36C	7044648
14HPX-036-230	36,200	15.70	13.20	33,800	21,200	3.74	2.58	8.70	CR33-50/60	SLP98DF090XV48C	7044649
14HPX-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	SLP98DF090XV60C	7044638
14HPX-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	SLP98DF110XV60C	7044639
14HPX-036-230	35,200	14.20	12.20	33,400	21,200	3.62	2.48	8.50	CR33-50/60		7044392
14HPX-036-230	34,200	15.20	12.70	32,600	20,800	3.44	2.44	8.20	CX34-38	CBWMV-24B-040	7044626
14HPX-036-230	34,200	15.20	12.70	32,600	20,800	3.44	2.42	8.20	CX34-38	CBWMV-36B-070	7044629
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL180UH045E36A	7044489
14HPX-036-230	34,200	15.70	13.00	32,400	20,400	3.48	2.44	8.50	CX34-38	EL180UH070E36B	7044495
14HPX-036-230	34,600	15.50	13.00	32,600	20,600	3.52	2.46	8.50	CX34-38	EL180UH090E48B	7044493
14HPX-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	CX34-38	EL195UH045XE36B	7044700
14HPX-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	CX34-38	EL195UH070XE36B	7044696
14HPX-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	CX34-38	EL296UH045XE36B	7044553
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL296UH045XV36B	7044475
14HPX-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	CX34-38	EL296UH070XE36B	7044562
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL296UH070XV36B	7044458
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	CX34-38	SL280UH070V36A	7044580
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	CX34-38	SL280UH070XV36A	8133567
14HPX-036-230	34,400	15.70	13.00	32,600	20,600	3.50	2.46	8.20	CX34-38	SL280UH090V36B	7044583
14HPX-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	CX34-38	SL280UH090V48B	7044716
14HPX-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	CX34-38	SL280UH090XV48B	8133610
14HPX-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	SLP98UH070XV36B	7044640
14HPX-036-230	35,200	15.20	13.00	32,600	20,400	3.44	2.46	8.20	CX34-43	CBWMV-24B-040	7044591
14HPX-036-230	35,200	15.20	13.00	32,600	20,400	3.42	2.46	8.20	CX34-43	CBWMV-36B-070	7044605
14HPX-036-230	35,200	15.50	13.00	32,600	20,400	3.46	2.48	8.20	CX34-43	CBWMV-36C-090	7044596
14HPX-036-230	35,200	15.70	13.20	32,400	20,200	3.46	2.50	8.50	CX34-43	EL180UH070E36B	7044503
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL180UH090E48B	7044479
14HPX-036-230	35,600	15.70	13.20	32,600	20,200	3.52	2.50	8.20	CX34-43	EL180UH090E60C	7044472
14HPX-036-230	35,200	15.70	13.20	32,400	20,200	3.48	2.50	8.50	CX34-43	EL180UH110E60C	7044509
14HPX-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	CX34-43	EL195UH045XE36B	7044701
14HPX-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	CX34-43	EL195UH070XE36B	7044697
14HPX-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	CX34-43	EL195UH090XE48C	7044624
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL195UH110XE60C	7044611
14HPX-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	CX34-43	EL296UH045XE36B	7044540
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.46	8.20	CX34-43	EL296UH045XV36B	7044467
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	CX34-43	EL296UH070XE36B	7044541
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	CX34-43	EL296UH070XV36B	7044459
14HPX-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	CX34-43	EL296UH090XE48C	7044535
14HPX-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	CX34-43	EL296UH090XV36C	7044447
14HPX-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	EL296UH090XV48C	7044589
14HPX-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	CX34-43	EL296UH090XV60C	7044430
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL296UH110XE60C	7044555
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	CX34-43	EL296UH110XV48C	7044523
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	CX34-43	EL296UH110XV60C	7044416
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	CX34-43	SL280UH090V36B	7044582
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SL280UH090V48B	7044717
14HPX-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	CX34-43	SL280UH090V60C	7044746
14HPX-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SL280UH090XV48B	8133611
14HPX-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	CX34-43	SL280UH090XV60C	8133651
14HPX-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	CX34-43	SL280UH110V60C	7044747
14HPX-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	CX34-43	SL280UH110XV60C	8133695
14HPX-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	CX34-43	SLP98UH070XV36B	7044641
14HPX-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	CX34-43	SLP98UH090XV36C	7044642
14HPX-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SLP98UH090XV48C	7044643
14HPX-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	CX34-43	SLP98UH090XV60C	7044632
14HPX-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	CX34-43	SLP98UH110XV60C	7044633
14HPX-036-230	34,000	15.00	12.70	32,400	20,600	3.34	2.36	8.20	CX34-44/48	CBWMV-24B-040	7044600
14HPX-036-230	33,800	15.20	12.70	32,400	20,600	3.34	2.38	8.20	CX34-44/48	CBWMV-36C-090	7044598
14HPX-036-230	33,800	15.50	13.00	32,200	20,400	3.36	2.38	8.20	CX34-44/48	EL180UH070E36B	7044486
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL180UH090E48B	7044490
14HPX-036-230	34,200	15.50	13.00	32,400	20,400	3.40	2.38	8.20	CX34-44/48	EL180UH090E60C	7044492
14HPX-036-230	34,000	15.50	13.00	32,200	20,400	3.36	2.38	8.20	CX34-44/48	EL180UH110E60C	7044517
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL195UH090XE48C	7044625
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL195UH110XE60C	7044612
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL296UH090XE48C	7044536
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL296UH090XV36C	7044440
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	CX34-44/48	EL296UH090XV48C	7044428
14HPX-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	CX34-44/48	EL296UH090XV60C	7044426
14HPX-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL296UH110XE60C	7044551
14HPX-036-230	34,200	15.50	13.00	32,200	20,400	3.38	2.38	8.20	CX34-44/48	EL296UH110XV48C	7044519
14HPX-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	CX34-44/48	EL296UH110XV60C	7044415
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.36	2.38	8.20	CX34-44/48	SL280UH090V36B	7044581
14HPX-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	CX34-44/48	SL280UH090V48B	7044718
14HPX-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SL280UH090V60C	7044711
14HPX-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	CX34-44/48	SL280UH090XV48B	8133613
14HPX-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SL280UH090XV60C	8133641
14HPX-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	CX34-44/48	SL280UH110V60C	7044719
14HPX-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	CX34-44/48	SL280UH110XV60C	8133684
14HPX-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	SLP98UH090XV36C	7044635
14HPX-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	CX34-44/48	SLP98UH090XV48C	7044636
14HPX-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	CX34-44/48	SLP98UH090XV60C	7044588
14HPX-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SLP98UH110XV60C	7044637
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.56	2.48	8.70	CX34-49	CBWMV-36C-090	7044627
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL180UH090E60C	7044478
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.62	2.50	8.70	CX34-49	EL180UH110E60C	7044516
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	CX34-49	EL195UH090XE48C	7044614
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL195UH110XE60C	7044613
14HPX-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	CX34-49	EL296UH090XE48C	7044544
14HPX-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	CX34-49	EL296UH090XV36C	7044451
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	CX34-49	EL296UH090XV48C	7044435
14HPX-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	CX34-49	EL296UH090XV60C	7044427
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL296UH110XE60C	7044552
14HPX-036-230	35,000	15.70	13.20	31,400	20,200	3.60	2.50	8.70	CX34-49	EL296UH110XV48C	7044529
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL296UH110XV60C	7044421
14HPX-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	CX34-49	SL280UH090V60C	7044720
14HPX-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	CX34-49	SL280UH090XV60C	8133643
14HPX-036-230	35,200	15.50	13.00	31,600	20,400	3.62	2.50	8.50	CX34-49	SL280UH110V60C	7044721
14HPX-036-230	35,200	15.50	13.00	31,600	20,400	3.62	2.50	8.50	CX34-49	SL280UH110XV60C	8133686
14HPX-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	CX34-49	SLP98UH090XV36C	7044593
14HPX-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	CX34-49	SLP98UH090XV48C	7044594
14HPX-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	CX34-49	SLP98UH090XV60C	7044595
14HPX-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	SLP98UH110XV60C	7044584
14HPX-036-230	34,400	14.20	12.00	32,200	21,000	3.40	2.36	8.20	CX34-49		7044388
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.54	2.48	8.70	CX34-50/60C	CBWMV-36C-090	7044601
14HPX-036-230	34,600	15.50	13.00	31,400	20,200	3.60	2.50	8.70	CX34-50/60C	EL180UH090E60C	7044481
14HPX-036-230	34,200	15.50	13.00	31,200	20,200	3.56	2.50	8.70	CX34-50/60C	EL180UH110E60C	7044514
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL195UH090XE48C	7044615
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	CX34-50/60C	EL195UH110XE60C	7044602
14HPX-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL296UH090XE48C	7044554
14HPX-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL296UH090XV36C	7044455
14HPX-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	CX34-50/60C	EL296UH090XV48C	7044442
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	CX34-50/60C	EL296UH110XE60C	7044539
14HPX-036-230	34,400	15.50	13.00	31,400	20,200	3.58	2.50	8.70	CX34-50/60C	EL296UH110XV48C	7044518
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	CX34-50/60C	EL296UH110XV60C	7044420
14HPX-036-230	34,800	15.50	12.50	31,600	20,400	3.64	2.52	8.50	CX34-50/60C	SL280UH090V60C	7044403
14HPX-036-230	34,800	15.50	12.50	31,600	20,400	3.64	2.52	8.50	CX34-50/60C	SL280UH090XV60C	8133636
14HPX-036-230	34,600	15.20	12.50	31,600	20,400	3.58	2.50	8.50	CX34-50/60C	SL280UH110V60C	7044404
14HPX-036-230	34,600	15.20	12.50	31,600	20,400	3.58	2.50	8.50	CX34-50/60C	SL280UH110XV60C	8133683
14HPX-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	SLP98UH090XV36C	7044690
14HPX-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	CX34-50/60C	SLP98UH090XV48C	7044662
14HPX-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	CX34-50/60C	SLP98UH110XV60C	7044585
14HPX-036-230	33,800	14.00	11.70	32,000	21,000	3.34	2.36	8.20	CX34-50/60C		7044396
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	C33-49	CBWMV-36C-090	7044966
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	C33-49	CBWMV-60C-100	7044938
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	C33-49	EL180UH090E60C	7044797
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	EL180UH110E60C	7044814
14HPX-042-230	43,500	15.20	13.00	41,500	26,600	3.66	2.58	8.50	C33-49	EL195UH090XE48C	7045004
14HPX-042-230	44,000	15.20	13.00	42,000	27,000	3.74	2.62	8.50	C33-49	EL195UH110XE60C	7044961
14HPX-042-230	43,500	15.20	13.00	41,500	26,600	3.66	2.58	8.50	C33-49	EL296UH090XE48C	7044838
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	C33-49	EL296UH090XV36C	7044854
14HPX-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	EL296UH090XV48C	7044869
14HPX-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	C33-49	EL296UH090XV60C	7044898
14HPX-042-230	44,000	15.20	13.00	42,000	27,000	3.74	2.62	8.50	C33-49	EL296UH110XE60C	7044839
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	EL296UH110XV48C	7044893
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	EL296UH110XV60C	7044903
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	C33-49	SL280UH090V60C	7044779
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	C33-49	SL280UH090XV60C	8133656
14HPX-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	C33-49	SL280UH110V60C	7044780
14HPX-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	C33-49	SL280UH110XV60C	8133703
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	C33-49	SLP98UH090XV36C	7045007
14HPX-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	SLP98UH090XV48C	7044996
14HPX-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	C33-49	SLP98UH090XV60C	7045001
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	SLP98UH110XV60C	7044990
14HPX-042-230	43,500	14.50	12.20	42,000	27,400	3.42	2.40	8.20	C33-49		7044759
14HPX-042-230	42,500	15.00	12.70	41,500	26,200	3.82	2.66	9.20	C33-60D	EL180UH135E60D	7044798
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.60	2.50	8.70	C33-60D	EL195UH135XE60D	7044957
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.60	2.50	8.70	C33-60D	EL296UH135XE60D	7044832
14HPX-042-230	44,000	15.70	13.20	42,000	26,800	3.66	2.54	8.70	C33-60D	EL296UH135XV60D	7044882
14HPX-042-230	44,000	15.70	13.50	41,500	26,600	3.64	2.54	8.70	C33-60D	SL280UH135V60D	7045033
14HPX-042-230	44,000	15.70	13.20	41,500	26,800	3.64	2.56	8.70	C33-60D	SLP98UH135XV60D	7044995
14HPX-042-230	43,000	14.50	12.20	42,500	27,400	3.46	2.42	8.20	C33-60D		7044761
14HPX-042-230	43,500	15.70	13.20	42,500	26,800	3.58	2.60	8.70	C33-62C	CBWMV-36C-090	7044946
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	C33-62C	CBWMV-60C-100	7044947
14HPX-042-230	43,000	15.20	13.00	41,500	26,400	3.92	2.74	9.50	C33-62C	EL180UH090E60C	7044794
14HPX-042-230	43,000	15.20	13.00	41,500	26,400	3.90	2.74	9.50	C33-62C	EL180UH110E60C	7044807
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.56	2.58	8.70	C33-62C	EL195UH090XE48C	7045006
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.64	2.60	8.70	C33-62C	EL195UH110XE60C	7044963
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.56	2.58	8.70	C33-62C	EL296UH090XE48C	7044848
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	C33-62C	EL296UH090XV36C	7044909
14HPX-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	C33-62C	EL296UH090XV48C	7044877
14HPX-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	C33-62C	EL296UH090XV60C	7044864
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.64	2.60	8.70	C33-62C	EL296UH110XE60C	7044849
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	C33-62C	EL296UH110XV48C	7044846
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	C33-62C	EL296UH110XV60C	7044861
14HPX-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	C33-62C	SL280UH090V60C	7044781
14HPX-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	C33-62C	SL280UH090XV60C	8133658
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	C33-62C	SL280UH110V60C	7044782
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	C33-62C	SL280UH110XV60C	8133705
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	C33-62C	SLP98UH090XV36C	7044997
14HPX-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	C33-62C	SLP98UH090XV48C	7044998
14HPX-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	C33-62C	SLP98UH090XV60C	7044999
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	C33-62C	SLP98UH110XV60C	7045000
14HPX-042-230	43,000	14.70	12.20	43,000	27,600	3.44	2.50	8.50	C33-62C		7044758
14HPX-042-230	43,000	15.20	13.00	41,500	26,200	3.84	2.68	9.20	C33-62D	EL180UH135E60D	7044799
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.64	2.50	8.70	C33-62D	EL195UH135XE60D	7044958
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.64	2.50	8.70	C33-62D	EL296UH135XE60D	7044837
14HPX-042-230	43,500	15.50	13.00	42,000	27,000	3.72	2.56	8.70	C33-62D	EL296UH135XV60D	7044908
14HPX-042-230	43,500	15.70	13.20	41,500	26,800	3.70	2.56	8.70	C33-62D	SL280UH135V60D	7044783
14HPX-042-230	43,500	15.50	13.20	41,500	26,800	3.70	2.56	8.70	C33-62D	SLP98UH135XV60D	7044984
14HPX-042-230	43,000	14.20	12.20	42,500	27,600	3.52	2.44	8.50	C33-62D		7044762
14HPX-042-230	42,500	14.00	12.00	45,500	28,200	3.66	2.58	8.20	CBX25UH-042		7044819
14HPX-042-230	42,000	15.50	13.00	44,500	27,400	3.86	2.68	8.50	CBX25UHV-042		7044785
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
14HPX-042-230	43,500	15.50	13.00	43,500	27,400	3.70	2.62	9.00	CBX27UH-042		7045034
14HPX-042-230	43,000	15.00	12.50	43,000	27,200	3.68	2.62	8.50	CBX27UH-048		7044914
14HPX-042-230	43,000	14.50	12.50	44,000	27,800	3.58	2.54	8.70	CBX32M-048		7045035
14HPX-042-230	43,500	15.50	13.00	43,500	27,400	3.68	2.62	8.70	CBX32MV-048		7045036
14HPX-042-230	43,000	15.20	12.70	43,500	27,400	3.64	2.60	8.70	CBX40UHV-042		7045037
14HPX-042-230	43,500	15.50	13.00	43,500	27,400	3.68	2.62	8.70	CBX40UHV-048		7045026
14HPX-042-230	44,000	15.70	13.20	42,500	27,400	3.90	2.68	9.20	CH23-68	EL180UH090E60C	7044787
14HPX-042-230	44,000	15.50	13.20	42,500	27,400	3.90	2.66	9.20	CH23-68	EL180UH110E60C	7044812
14HPX-042-230	44,000	15.70	13.20	42,500	27,400	3.92	2.68	9.20	CH23-68	EL180UH135E60D	7044806
14HPX-042-230	43,500	15.20	13.00	42,500	27,400	3.84	2.64	9.20	CH23-68	EL195UH090XE48C	7044968
14HPX-042-230	44,000	15.20	13.00	42,500	27,600	3.88	2.66	9.20	CH23-68	EL195UH110XE60C	7044964
14HPX-042-230	44,000	15.20	13.00	42,500	27,600	3.86	2.64	9.20	CH23-68	EL195UH135XE60D	7044959
14HPX-042-230	43,500	15.20	13.00	42,500	27,400	3.84	2.64	9.20	CH23-68	EL296UH090XE48C	7044840
14HPX-042-230	44,000	15.20	13.00	42,500	27,600	3.88	2.66	9.20	CH23-68	EL296UH110XE60C	7044841
14HPX-042-230	44,000	15.20	13.00	42,500	27,600	3.86	2.64	9.20	CH23-68	EL296UH135XE60D	7044850
14HPX-042-230	44,000	15.70	13.20	42,500	27,400	3.94	2.70	9.50	CH23-68	EL296UH135XV60D	7044888
14HPX-042-230	44,000	16.00	13.00	42,500	27,200	3.98	2.70	9.50	CH23-68	SL280UH135V60D	7045027
14HPX-042-230	44,000	15.70	13.20	42,500	27,400	3.96	2.72	9.50	CH23-68	SLP98UH135XV60D	7044985
14HPX-042-230	43,500	14.50	12.20	43,000	28,000	3.72	2.56	9.00	CH23-68		7044763
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.56	2.52	8.70	CH33-43B	EL180UH090E48B	7044792
14HPX-042-230	43,500	14.70	12.70	42,500	27,400	3.48	2.50	8.50	CH33-43B	EL296UH045XV36B	7044883
14HPX-042-230	43,500	14.70	12.50	42,500	27,400	3.48	2.48	8.50	CH33-43B	EL296UH070XV36B	7044904
14HPX-042-230	44,000	15.50	13.00	42,500	27,200	3.60	2.56	8.70	CH33-43B	SL280UH090V36B	7044916
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.60	2.54	8.70	CH33-43B	SL280UH090V48B	7045028
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.60	2.54	8.70	CH33-43B	SL280UH090XV48B	8133621
14HPX-042-230	43,500	14.70	12.50	42,500	27,400	3.48	2.48	8.50	CH33-43B	SLP98UH070XV36B	7044986
14HPX-042-230	43,500	14.50	12.20	43,000	27,600	3.48	2.46	8.50	CH33-43B		7044773
14HPX-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.48	8.20	CH33-43C	EL180UH090E60C	7044795
14HPX-042-230	43,000	15.20	13.00	42,000	26,800	3.40	2.48	8.20	CH33-43C	EL180UH110E60C	7044821
14HPX-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-43C	EL195UH090XE48C	7044969
14HPX-042-230	43,000	15.00	12.70	42,500	27,000	3.44	2.48	8.20	CH33-43C	EL195UH110XE60C	7044965
14HPX-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-43C	EL296UH090XE48C	7044844
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.40	2.46	8.20	CH33-43C	EL296UH090XV36C	7044910
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	EL296UH090XV48C	7044880
14HPX-042-230	43,000	15.20	12.70	42,500	27,000	3.44	2.50	8.20	CH33-43C	EL296UH090XV60C	7044865
14HPX-042-230	43,000	15.00	12.70	42,500	27,000	3.44	2.48	8.20	CH33-43C	EL296UH110XE60C	7044845
14HPX-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.48	8.20	CH33-43C	EL296UH110XV48C	7044847
14HPX-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.50	8.20	CH33-43C	EL296UH110XV60C	7044862
14HPX-042-230	43,000	15.50	13.00	42,500	26,800	3.50	2.52	8.50	CH33-43C	SL280UH090V60C	7045029
14HPX-042-230	43,000	15.50	13.00	42,500	26,800	3.50	2.52	8.50	CH33-43C	SL280UH090XV60C	8133668
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SL280UH110V60C	7045030
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SL280UH110XV60C	8133714
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.40	2.46	8.20	CH33-43C	SLP98UH090XV36C	7044987
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SLP98UH090XV48C	7044988
14HPX-042-230	43,000	15.20	12.70	42,500	27,000	3.44	2.50	8.20	CH33-43C	SLP98UH090XV60C	7044989
14HPX-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.50	8.20	CH33-43C	SLP98UH110XV60C	7044978
14HPX-042-230	42,000	14.70	12.50	42,500	27,000	3.46	2.48	8.50	CH33-44/48	EL180UH090E48B	7044790
14HPX-042-230	41,500	14.20	12.20	42,500	27,200	3.38	2.46	8.20	CH33-44/48	EL296UH045XV36B	7044886
14HPX-042-230	41,500	14.20	12.20	42,500	27,200	3.36	2.46	8.20	CH33-44/48	EL296UH070XV36B	7044870
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-042-230	42,000	14.70	12.70	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090V36B	7044915
14HPX-042-230	42,000	14.70	12.50	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090V48B	7045031
14HPX-042-230	42,000	14.70	12.50	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090XV48B	8133623
14HPX-042-230	41,500	14.20	12.20	42,500	27,200	3.36	2.46	8.20	CH33-44/48	SLP98UH070XV36B	7044979
14HPX-042-230	41,500	14.00	11.70	43,000	27,600	3.36	2.44	8.20	CH33-44/48		7044775
14HPX-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-48	EL180UH090E60C	7044793
14HPX-042-230	42,000	15.00	12.70	42,000	26,800	3.32	2.44	8.20	CH33-48	EL180UH110E60C	7044813
14HPX-042-230	42,000	14.70	12.50	42,500	26,800	3.34	2.42	8.20	CH33-48	EL296UH090XV36C	7044852
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	EL296UH090XV48C	7044867
14HPX-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.46	8.20	CH33-48	EL296UH090XV60C	7044896
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.40	2.44	8.20	CH33-48	EL296UH110XV48C	7044891
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	EL296UH110XV60C	7044881
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.46	8.20	CH33-48	SL280UH090V60C	7045020
14HPX-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.46	8.20	CH33-48	SL280UH090XV60C	8133663
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	SL280UH110V60C	7045021
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	SL280UH110XV60C	8133681
14HPX-042-230	42,000	14.70	12.50	42,500	26,800	3.34	2.42	8.20	CH33-48	SLP98UH090XV36C	7044980
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	SLP98UH090XV48C	7044981
14HPX-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.46	8.20	CH33-48	SLP98UH090XV60C	7044982
14HPX-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48	SLP98UH110XV60C	7044983
14HPX-042-230	42,000	14.70	12.50	42,000	26,800	3.28	2.42	8.20	CH33-48C	EL195UH090XE48C	7044970
14HPX-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.44	8.20	CH33-48C	EL195UH110XE60C	7044954
14HPX-042-230	42,000	14.70	12.50	42,000	26,800	3.28	2.42	8.20	CH33-48C	EL296UH090XE48C	7044829
14HPX-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.44	8.20	CH33-48C	EL296UH110XE60C	7044830
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	EL180UH090E60C	7044796
14HPX-042-230	43,000	15.20	13.00	42,000	26,800	3.60	2.50	8.70	CH33-49	EL180UH110E60C	7044811
14HPX-042-230	43,000	15.00	12.70	42,000	26,800	3.56	2.48	8.50	CH33-49	EL195UH090XE48C	7044971
14HPX-042-230	43,500	15.20	12.70	42,500	27,000	3.64	2.50	8.70	CH33-49	EL195UH110XE60C	7044955
14HPX-042-230	43,000	15.00	12.70	42,000	26,800	3.56	2.48	8.50	CH33-49	EL296UH090XE48C	7044823
14HPX-042-230	43,500	15.20	13.00	42,000	27,000	3.58	2.52	8.70	CH33-49	EL296UH090XV36C	7044863
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	EL296UH090XV48C	7044866
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.66	2.56	8.70	CH33-49	EL296UH090XV60C	7044895
14HPX-042-230	43,500	15.20	12.70	42,500	27,000	3.64	2.50	8.70	CH33-49	EL296UH110XE60C	7044824
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	EL296UH110XV48C	7044890
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	EL296UH110XV60C	7044900
14HPX-042-230	44,000	15.50	13.20	42,000	27,000	3.66	2.56	8.70	CH33-49	SL280UH090V60C	7045022
14HPX-042-230	44,000	15.50	13.20	42,000	27,000	3.66	2.56	8.70	CH33-49	SL280UH090XV60C	8133664
14HPX-042-230	43,500	15.20	13.00	42,000	27,000	3.62	2.54	8.70	CH33-49	SL280UH110V60C	7045023
14HPX-042-230	43,500	15.20	13.00	42,000	27,000	3.62	2.54	8.70	CH33-49	SL280UH110XV60C	8133711
14HPX-042-230	43,500	15.20	13.00	42,000	27,000	3.58	2.52	8.70	CH33-49	SLP98UH090XV36C	7044972
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	SLP98UH090XV48C	7044973
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.66	2.56	8.70	CH33-49	SLP98UH090XV60C	7044974
14HPX-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	SLP98UH110XV60C	7044975
14HPX-042-230	43,000	14.20	12.20	42,500	27,400	3.50	2.44	8.50	CH33-49		7044777
14HPX-042-230	43,000	15.20	12.70	42,000	26,800	3.60	2.50	8.70	CH33-50/60C	EL180UH090E60C	7044791
14HPX-042-230	43,000	15.20	13.00	42,000	26,800	3.58	2.50	8.50	CH33-50/60C	EL180UH110E60C	7044810
14HPX-042-230	43,000	15.00	12.70	42,000	26,800	3.54	2.48	8.50	CH33-50/60C	EL195UH090XE48C	7044960
14HPX-042-230	43,500	15.00	12.70	42,000	27,000	3.58	2.50	8.50	CH33-50/60C	EL195UH110XE60C	7044956
14HPX-042-230	43,000	15.00	12.70	42,000	26,800	3.54	2.48	8.50	CH33-50/60C	EL296UH090XE48C	7044816
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
14HPX-042-230	43,000	15.20	12.70	42,500	27,200	3.50	2.48	8.50	CH33-50/60C	EL296UH090XV36C	7044917
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	EL296UH090XV48C	7044885
14HPX-042-230	43,500	15.20	12.70	42,500	27,400	3.54	2.52	8.50	CH33-50/60C	EL296UH090XV60C	7044871
14HPX-042-230	43,500	15.00	12.70	42,000	27,000	3.58	2.50	8.50	CH33-50/60C	EL296UH110XE60C	7044817
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	EL296UH110XV48C	7044853
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	EL296UH110XV60C	7044868
14HPX-042-230	43,500	15.50	13.00	42,500	27,200	3.58	2.54	8.70	CH33-50/60C	SL280UH090V60C	7045024
14HPX-042-230	43,500	15.50	13.00	42,500	27,200	3.58	2.54	8.70	CH33-50/60C	SL280UH090XV60C	8133666
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SL280UH110V60C	7045025
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SL280UH110XV60C	8133712
14HPX-042-230	43,000	15.20	12.70	42,500	27,200	3.50	2.48	8.50	CH33-50/60C	SLP98UH090XV36C	7044976
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SLP98UH090XV48C	7044939
14HPX-042-230	43,500	15.20	12.70	42,500	27,400	3.54	2.52	8.50	CH33-50/60C	SLP98UH090XV60C	7044940
14HPX-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	SLP98UH110XV60C	7044941
14HPX-042-230	43,000	14.20	12.20	43,000	27,800	3.40	2.42	8.20	CH33-50/60C		7044778
14HPX-042-230	44,500	15.70	13.20	42,500	27,000	3.56	2.52	8.50	CH33-60D	EL180UH135E60D	7044805
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.50	2.50	8.50	CH33-60D	EL195UH135XE60D	7044948
14HPX-042-230	44,000	15.20	13.00	42,500	27,200	3.50	2.50	8.50	CH33-60D	EL296UH135XE60D	7044842
14HPX-042-230	44,500	15.70	13.20	42,500	27,000	3.58	2.54	8.70	CH33-60D	EL296UH135XV60D	7044901
14HPX-042-230	44,000	16.00	13.00	42,000	26,800	3.54	2.54	8.50	CH33-60D	SL280UH135V60D	7045014
14HPX-042-230	44,000	15.70	13.20	42,500	26,800	3.58	2.52	8.70	CH33-60D	SLP98UH135XV60D	7044930
14HPX-042-230	43,500	14.50	12.20	43,000	27,600	3.36	2.42	8.20	CH33-60D		7044767
14HPX-042-230	42,500	15.00	12.70	41,500	26,200	3.78	2.66	9.20	CH33-62D	EL180UH135E60D	7044809
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.72	2.62	8.70	CH33-62D	EL195UH135XE60D	7044942
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.72	2.62	8.70	CH33-62D	EL296UH135XE60D	7044843
14HPX-042-230	43,500	15.50	13.00	42,000	26,800	3.64	2.54	8.70	CH33-62D	EL296UH135XV60D	7044906
14HPX-042-230	43,500	15.70	13.20	41,500	26,600	3.60	2.54	8.70	CH33-62D	SL280UH135V60D	7045015
14HPX-042-230	43,500	15.70	13.20	42,000	26,800	3.64	2.54	8.70	CH33-62D	SLP98UH135XV60D	7044931
14HPX-042-230	43,000	14.20	12.20	42,500	27,400	3.42	2.40	8.20	CH33-62D		7044768
14HPX-042-230	44,500	15.50	13.20	43,000	27,000	3.76	2.62	9.00	CR33-50/60	EL180DF110E60C	7044803
14HPX-042-230	44,000	15.20	13.00	43,000	27,200	3.68	2.60	8.70	CR33-50/60	EL195DF090XE48C	7045002
14HPX-042-230	44,500	15.20	13.00	43,500	27,200	3.78	2.62	9.00	CR33-50/60	EL195DF110XE60C	7045003
14HPX-042-230	44,000	15.20	13.00	43,000	27,200	3.68	2.60	8.70	CR33-50/60	EL296DF090XE48C	7044822
14HPX-042-230	44,500	15.20	13.00	43,500	27,200	3.76	2.62	9.00	CR33-50/60	EL296DF090XV60C	7044887
14HPX-042-230	44,500	15.20	13.00	43,500	27,200	3.78	2.62	9.00	CR33-50/60	EL296DF110XE60C	7044827
14HPX-042-230	44,500	15.50	13.20	43,000	27,200	3.76	2.64	9.00	CR33-50/60	EL296DF110XV60C	7044873
14HPX-042-230	44,000	15.70	13.20	43,000	27,000	3.76	2.64	9.00	CR33-50/60	SL280DF090V60C	7045016
14HPX-042-230	44,500	15.70	13.20	43,000	27,000	3.78	2.66	9.00	CR33-50/60	SL280DF110V60C	7045017
14HPX-042-230	44,000	15.20	13.00	43,000	27,200	3.70	2.62	9.00	CR33-50/60	SLP98DF090XV36C	7044932
14HPX-042-230	44,500	15.20	13.00	43,000	27,200	3.72	2.62	9.00	CR33-50/60	SLP98DF090XV48C	7044933
14HPX-042-230	44,500	15.20	13.00	43,500	27,200	3.76	2.62	9.00	CR33-50/60	SLP98DF090XV60C	7044934
14HPX-042-230	44,500	15.50	13.20	43,000	27,200	3.76	2.64	9.00	CR33-50/60	SLP98DF110XV60C	7044935
14HPX-042-230	43,500	14.20	12.20	43,500	27,800	3.56	2.54	8.70	CR33-50/60		7044769
14HPX-042-230	43,500	14.20	12.20	43,500	27,800	3.56	2.54	8.70	CR33-60		7044770
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	CX34-49	CBWMV-36C-090	7044937
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	CX34-49	CBWMV-60C-100	7044967
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	CX34-49	EL180UH090E60C	7044786
14HPX-042-230	44,000	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	EL180UH110E60C	7044815
14HPX-042-230	43,500	15.20	13.00	41,500	26,600	3.54	2.44	8.50	CX34-49	EL195UH090XE48C	7044949
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-042-230	44,000	15.20	13.00	42,000	27,000	3.62	2.48	8.50	CX34-49	EL195UH110XE60C	7044952
14HPX-042-230	43,500	15.20	13.00	41,500	26,600	3.54	2.44	8.50	CX34-49	EL296UH090XE48C	7044825
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	CX34-49	EL296UH090XV36C	7044856
14HPX-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	EL296UH090XV48C	7044859
14HPX-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	CX34-49	EL296UH090XV60C	7044897
14HPX-042-230	44,000	15.20	13.00	42,000	27,000	3.62	2.48	8.50	CX34-49	EL296UH110XE60C	7044828
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	EL296UH110XV48C	7044892
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	EL296UH110XV60C	7044902
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	CX34-49	SL280UH090V60C	7045018
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	CX34-49	SL280UH090XV60C	8133661
14HPX-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	CX34-49	SL280UH110V60C	7045019
14HPX-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	CX34-49	SL280UH110XV60C	8133709
14HPX-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	CX34-49	SLP98UH090XV36C	7044924
14HPX-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	SLP98UH090XV48C	7044925
14HPX-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	CX34-49	SLP98UH090XV60C	7044926
14HPX-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	SLP98UH110XV60C	7044927
14HPX-042-230	43,500	14.50	12.20	42,000	27,400	3.42	2.40	8.20	CX34-49		7044771
14HPX-042-230	42,500	15.00	12.70	41,500	26,200	3.82	2.66	9.20	CX34-60D	EL180UH135E60D	7044800
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	8.70	CX34-60D	EL195UH135XE60D	7044945
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	8.70	CX34-60D	EL296UH135XE60D	7044826
14HPX-042-230	44,000	15.70	13.20	42,000	26,800	3.66	2.54	8.70	CX34-60D	EL296UH135XV60D	7044889
14HPX-042-230	44,000	15.70	13.50	41,500	26,600	3.64	2.54	8.70	CX34-60D	SL280UH135V60D	7045010
14HPX-042-230	44,000	15.70	13.20	41,500	26,800	3.64	2.56	8.70	CX34-60D	SLP98UH135XV60D	7044920
14HPX-042-230	43,000	14.50	12.20	42,500	27,400	3.46	2.42	8.20	CX34-60D		7044764
14HPX-042-230	43,500	15.70	13.20	42,500	26,800	3.58	2.60	8.70	CX34-62C	CBWMV-36C-090	7044936
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	CX34-62C	CBWMV-60C-100	7044977
14HPX-042-230	43,000	15.20	13.00	41,500	26,400	3.92	2.74	9.50	CX34-62C	EL180UH090E60C	7044802
14HPX-042-230	43,000	15.20	13.00	41,500	26,400	3.90	2.74	9.50	CX34-62C	EL180UH110E60C	7044808
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.86	2.70	8.70	CX34-62C	EL195UH090XE48C	7044951
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.94	2.72	8.70	CX34-62C	EL195UH110XE60C	7044944
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.86	2.70	8.70	CX34-62C	EL296UH090XE48C	7044833
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	CX34-62C	EL296UH090XV36C	7044884
14HPX-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	CX34-62C	EL296UH090XV48C	7044905
14HPX-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	CX34-62C	EL296UH090XV60C	7044894
14HPX-042-230	43,000	15.00	13.00	41,500	26,400	3.94	2.72	8.70	CX34-62C	EL296UH110XE60C	7044831
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	CX34-62C	EL296UH110XV48C	7044911
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	CX34-62C	EL296UH110XV60C	7044879
14HPX-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	CX34-62C	SL280UH090V60C	7045011
14HPX-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	CX34-62C	SL280UH090XV60C	8133659
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	CX34-62C	SL280UH110V60C	7045012
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	CX34-62C	SL280UH110XV60C	8133707
14HPX-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	CX34-62C	SLP98UH090XV36C	7044921
14HPX-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	CX34-62C	SLP98UH090XV48C	7044922
14HPX-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	CX34-62C	SLP98UH090XV60C	7044923
14HPX-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	CX34-62C	SLP98UH110XV60C	7044912
14HPX-042-230	43,000	14.70	12.20	43,000	27,600	3.44	2.50	8.50	CX34-62C		7044765
14HPX-042-230	43,000	15.20	13.00	41,500	26,200	3.84	2.68	9.20	CX34-62D	EL180UH135E60D	7044801
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.76	2.64	8.70	CX34-62D	EL195UH135XE60D	7044943
14HPX-042-230	42,500	14.70	12.70	41,500	26,400	3.76	2.64	8.70	CX34-62D	EL296UH135XE60D	7044834
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-042-230	43,500	15.50	13.00	42,000	27,000	3.72	2.56	8.70	CX34-62D	EL296UH135XV60D	7044875
14HPX-042-230	43,500	15.70	13.20	41,500	26,800	3.70	2.56	8.70	CX34-62D	SL280UH135V60D	7045013
14HPX-042-230	43,500	15.50	13.20	41,500	26,800	3.70	2.56	8.70	CX34-62D	SLP98UH135XV60D	7044913
14HPX-042-230	43,000	14.20	12.20	42,500	27,600	3.52	2.44	8.50	CX34-62D		7044766
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.42	2.50	8.50	C33-49	CBWMV-60C-100	7045159
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	C33-49	CBWMV-60C-120	7045162
14HPX-048-230	49,000	15.00	12.70	45,500	30,000	3.38	2.54	8.70	C33-49	EL180UH090E60C	7045113
14HPX-048-230	48,500	14.70	12.70	45,500	30,000	3.36	2.52	8.50	C33-49	EL180UH110E60C	7045115
14HPX-048-230	49,000	14.70	12.70	46,000	30,200	3.38	2.52	8.50	C33-49	EL195UH090XE48C	7045192
14HPX-048-230	49,000	14.50	12.70	46,000	30,200	3.40	2.54	8.50	C33-49	EL195UH110XE60C	7045207
14HPX-048-230	49,000	14.70	12.70	46,000	30,200	3.38	2.52	8.50	C33-49	EL296UH090XE48C	7045156
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	C33-49	EL296UH090XV48C	7045103
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH090XV60C	7045107
14HPX-048-230	49,000	14.50	12.70	46,000	30,200	3.40	2.54	8.50	C33-49	EL296UH110XE60C	7045144
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH110XV48C	7045136
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH110XV60C	7045102
14HPX-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	C33-49	SL280UH090V60C	7045084
14HPX-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	C33-49	SL280UH090XV60C	8133671
14HPX-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	C33-49	SL280UH110V60C	7045085
14HPX-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	C33-49	SL280UH110XV60C	8133718
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	C33-49	SLP98UH090XV48C	7045186
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	SLP98UH090XV60C	7045175
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	SLP98UH110XV60C	7045176
14HPX-048-230	49,000	14.00	12.20	46,500	30,400	3.32	2.44	8.20	C33-49		7045068
14HPX-048-230	47,500	14.70	12.50	47,500	31,000	3.14	2.44	8.20	C33-60D	EL180UH135E60D	7045122
14HPX-048-230	49,000	14.50	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	CBWMV-60C-100	7045196
14HPX-048-230	48,500	14.50	12.50	46,500	30,400	3.60	2.62	9.00	C33-62C	CBWMV-60C-120	7045197
14HPX-048-230	48,500	15.00	12.70	46,000	30,400	3.60	2.66	9.00	C33-62C	EL180UH090E60C	7045112
14HPX-048-230	48,500	15.00	12.70	46,000	30,400	3.58	2.66	9.00	C33-62C	EL180UH110E60C	7045118
14HPX-048-230	48,500	14.70	12.50	46,500	30,600	3.58	2.64	9.00	C33-62C	EL195UH090XE48C	7045187
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	C33-62C	EL195UH110XE60C	7045208
14HPX-048-230	48,500	14.70	12.50	46,500	30,600	3.58	2.64	9.00	C33-62C	EL296UH090XE48C	7045155
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	EL296UH090XV48C	7045105
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	EL296UH090XV60C	7045097
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	C33-62C	EL296UH110XE60C	7045134
14HPX-048-230	48,500	14.70	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	EL296UH110XV48C	7045138
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	EL296UH110XV60C	7045101
14HPX-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	C33-62C	SL280UH090V60C	7045230
14HPX-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	C33-62C	SL280UH090XV60C	8133676
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	C33-62C	SL280UH110V60C	7045231
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	C33-62C	SL280UH110XV60C	8133723
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	SLP98UH090XV48C	7045178
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	SLP98UH090XV60C	7045179
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	SLP98UH110XV60C	7045180
14HPX-048-230	48,500	14.00	12.20	47,000	30,800	3.52	2.56	8.70	C33-62C		7045070
14HPX-048-230	48,000	14.70	12.50	46,000	30,400	3.52	2.60	8.70	C33-62D	EL180UH135E60D	7045131
14HPX-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	C33-62D	EL195UH135XE60D	7045202
14HPX-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	C33-62D	EL296UH135XE60D	7045141
14HPX-048-230	48,000	14.50	12.50	46,000	30,400	3.50	2.56	8.70	C33-62D	EL296UH135XV60D	7045087
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-048-230	48,000	14.50	12.50	46,000	30,200	3.52	2.56	8.70	C33-62D	SL280UH135V60D	7045232
14HPX-048-230	48,000	14.50	12.70	46,000	30,000	3.52	2.56	8.70	C33-62D	SLP98UH135XV60D	7045169
14HPX-048-230	49,000	14.00	12.00	47,000	30,200	3.44	2.56	8.20	CBX25UH-048		7045129
14HPX-048-230	48,500	14.00	12.00	47,000	30,400	3.40	2.54	8.20	CBX25UH-060		7045089
14HPX-048-230	48,000	15.00	12.50	46,500	29,800	3.52	2.62	8.50	CBX25UHV-048		7045090
14HPX-048-230	49,000	15.00	12.50	47,000	30,000	3.52	2.62	8.20	CBX25UHV-060		8703418
14HPX-048-230	49,500	15.00	12.70	47,500	30,600	3.62	2.70	9.20	CBX27UH-048		7045233
14HPX-048-230	49,500	15.20	12.70	43,500	29,800	3.52	2.66	9.00	CBX27UH-060		7045234
14HPX-048-230	49,500	14.70	12.50	48,000	30,800	3.60	2.68	9.00	CBX32M-048		7045223
14HPX-048-230	49,500	14.50	12.20	48,000	30,800	3.52	2.64	8.70	CBX32M-060		7045224
14HPX-048-230	49,000	15.00	12.70	47,500	30,600	3.60	2.70	9.00	CBX32MV-048		7045218
14HPX-048-230	49,500	14.70	12.50	48,000	30,600	3.54	2.64	8.70	CBX32MV-060		7045219
14HPX-048-230	49,000	14.70	12.50	46,000	30,200	3.46	2.58	8.70	CBX32MV-068		7045220
14HPX-048-230	49,000	15.00	12.70	47,500	30,600	3.62	2.70	9.00	CBX40UHV-048		7045221
14HPX-048-230	50,000	14.70	12.50	48,000	30,600	3.54	2.64	9.00	CBX40UHV-060		7045222
14HPX-048-230	50,500	15.20	13.20	46,500	31,000	3.66	2.74	9.20	CH23-68	EL180UH090E60C	7045110
14HPX-048-230	50,000	15.20	13.00	46,500	31,000	3.64	2.74	9.20	CH23-68	EL180UH110E60C	7045126
14HPX-048-230	50,500	15.20	13.00	47,000	31,000	3.72	2.76	9.20	CH23-68	EL180UH135E60D	7045124
14HPX-048-230	50,000	15.00	12.70	47,000	31,200	3.64	2.72	9.20	CH23-68	EL195UH090XE48C	7045191
14HPX-048-230	50,500	15.20	13.00	47,000	31,200	3.66	2.74	9.20	CH23-68	EL195UH110XE60C	7045209
14HPX-048-230	50,500	14.70	12.70	47,000	31,400	3.64	2.72	9.20	CH23-68	EL195UH135XE60D	7045203
14HPX-048-230	50,000	15.00	12.70	47,000	31,200	3.64	2.72	9.20	CH23-68	EL296UH090XE48C	7045154
14HPX-048-230	50,500	15.20	13.00	47,000	31,200	3.66	2.74	9.20	CH23-68	EL296UH110XE60C	7045142
14HPX-048-230	50,500	14.70	12.70	47,000	31,400	3.64	2.72	9.20	CH23-68	EL296UH135XE60D	7045133
14HPX-048-230	51,000	15.20	13.20	47,000	30,800	3.68	2.68	9.20	CH23-68	EL296UH135XV60D	7045094
14HPX-048-230	50,500	15.20	13.20	46,500	30,800	3.64	2.70	9.20	CH23-68	SL280UH135V60D	7045211
14HPX-048-230	50,500	15.20	13.20	46,500	30,600	3.64	2.68	9.20	CH23-68	SLP98UH135XV60D	7045163
14HPX-048-230	49,500	14.00	12.20	47,500	31,400	3.56	2.60	9.00	CH23-68		7045076
14HPX-048-230	48,500	14.70	12.70	45,500	29,800	3.32	2.54	8.50	CH33-50/60C	EL180UH090E60C	7045120
14HPX-048-230	49,000	14.20	12.20	46,500	30,200	3.38	2.52	8.50	CH33-50/60C	EL180UH110E60C	7045117
14HPX-048-230	48,000	14.20	12.20	45,500	29,800	3.28	2.50	8.20	CH33-50/60C	EL195UH090XE48C	7045188
14HPX-048-230	48,000	14.20	12.50	45,500	29,800	3.30	2.52	8.20	CH33-50/60C	EL195UH110XE60C	7045210
14HPX-048-230	48,000	14.20	12.20	45,500	29,800	3.28	2.50	8.20	CH33-50/60C	EL296UH090XE48C	7045152
14HPX-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	EL296UH090XV48C	7045106
14HPX-048-230	48,500	14.20	12.20	46,000	29,800	3.32	2.50	8.20	CH33-50/60C	EL296UH090XV60C	7045108
14HPX-048-230	48,000	14.20	12.50	45,500	29,800	3.30	2.52	8.20	CH33-50/60C	EL296UH110XE60C	7045150
14HPX-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.50	CH33-50/60C	EL296UH110XV48C	7045137
14HPX-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	EL296UH110XV60C	7045100
14HPX-048-230	48,500	14.50	12.50	46,000	29,600	3.38	2.52	8.50	CH33-50/60C	SL280UH090V60C	7045212
14HPX-048-230	48,500	14.50	12.50	46,000	29,600	3.38	2.52	8.50	CH33-50/60C	SL280UH090XV60C	8133673
14HPX-048-230	48,500	14.20	12.50	46,000	29,600	3.36	2.50	8.50	CH33-50/60C	SL280UH110V60C	7045213
14HPX-048-230	48,500	14.20	12.50	46,000	29,600	3.36	2.50	8.50	CH33-50/60C	SL280UH110XV60C	8133719
14HPX-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	SLP98UH090XV48C	7045164
14HPX-048-230	48,500	14.20	12.20	46,000	29,800	3.32	2.50	8.20	CH33-50/60C	SLP98UH090XV60C	7045165
14HPX-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	SLP98UH110XV60C	7045166
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.40	2.58	8.70	CH33-60D	EL180UH135E60D	7045123
14HPX-048-230	48,000	14.20	12.20	46,500	30,600	3.38	2.54	8.50	CH33-60D	EL195UH135XE60D	7045204
14HPX-048-230	48,000	14.20	12.20	46,500	30,600	3.38	2.54	8.50	CH33-60D	EL296UH135XE60D	7045135
14HPX-048-230	48,500	14.20	12.50	46,500	30,200	3.44	2.52	8.70	CH33-60D	EL296UH135XV60D	7045093
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High		Heat COP High		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
14HPX-048-230	48,500	14.50	12.70	46,000	30,000	3.40	2.52	8.70	CH33-60D	SL280UH135V60D	7045080
14HPX-048-230	48,000	14.50	12.50	46,000	30,000	3.40	2.54	8.50	CH33-60D	SLP98UH135XV60D	7045181
14HPX-048-230	48,500	15.00	12.70	46,000	30,200	3.44	2.58	8.70	CH33-62D	EL180UH135E60D	7045125
14HPX-048-230	48,000	14.70	12.20	46,000	30,400	3.36	2.54	8.70	CH33-62D	EL195UH135XE60D	7045193
14HPX-048-230	48,000	14.70	12.20	46,000	30,400	3.36	2.54	8.70	CH33-62D	EL296UH135XE60D	7045143
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.42	2.54	8.70	CH33-62D	EL296UH135XV60D	7045086
14HPX-048-230	48,500	14.70	12.70	46,000	30,000	3.44	2.54	8.70	CH33-62D	SL280UH135V60D	7045081
14HPX-048-230	48,000	14.70	12.70	45,500	30,000	3.40	2.54	8.70	CH33-62D	SLP98UH135XV60D	7045170
14HPX-048-230	48,000	14.00	12.00	46,500	30,600	3.32	2.46	8.50	CH33-62D		7045074
14HPX-048-230	49,500	15.00	12.70	48,500	31,200	3.50	2.66	9.00	CR33-50/60	EL180DF110E60C	7045109
14HPX-048-230	49,500	14.20	12.50	49,000	31,400	3.44	2.60	8.70	CR33-50/60	EL195DF090XE48C	7045205
14HPX-048-230	49,500	14.20	12.70	48,500	31,200	3.46	2.64	8.70	CR33-50/60	EL195DF110XE60C	7045206
14HPX-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.60	8.70	CR33-50/60	EL296DF090V60C	7045225
14HPX-048-230	49,500	14.20	12.50	49,000	31,400	3.44	2.60	8.70	CR33-50/60	EL296DF090XE48C	7045148
14HPX-048-230	49,500	14.20	12.70	48,500	31,200	3.42	2.58	8.70	CR33-50/60	EL296DF110V60C	7045226
14HPX-048-230	49,500	14.20	12.70	48,500	31,200	3.46	2.64	8.70	CR33-50/60	EL296DF110XE60C	7045140
14HPX-048-230	49,500	14.70	12.70	48,500	31,000	3.48	2.62	8.70	CR33-50/60	SL280DF090V60C	7045227
14HPX-048-230	49,500	14.70	13.00	48,500	31,000	3.52	2.64	8.70	CR33-50/60	SL280DF110V60C	7045228
14HPX-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.58	8.70	CR33-50/60	SLP98DF090XV48C	7045171
14HPX-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.60	8.70	CR33-50/60	SLP98DF090XV60C	7045172
14HPX-048-230	49,500	14.20	12.70	48,500	31,200	3.42	2.58	8.70	CR33-50/60	SLP98DF110XV60C	7045173
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.42	2.50	8.50	CX34-49	CBWMV-60C-100	7045161
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	CX34-49	CBWMV-60C-120	7045160
14HPX-048-230	49,000	15.00	12.70	45,500	30,000	3.38	2.54	8.70	CX34-49	EL180UH090E60C	7045111
14HPX-048-230	48,500	14.70	12.70	45,500	30,000	3.36	2.52	8.50	CX34-49	EL180UH110E60C	7045130
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.38	2.52	8.50	CX34-49	EL195UH090XE48C	7045189
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.54	8.50	CX34-49	EL195UH110XE60C	7045199
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.38	2.52	8.50	CX34-49	EL296UH090XE48C	7045151
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	CX34-49	EL296UH090XV48C	7045114
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH090XV60C	7045099
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.54	8.50	CX34-49	EL296UH110XE60C	7045145
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH110XV48C	7045127
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH110XV60C	7045092
14HPX-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	CX34-49	SL280UH090V60C	7045082
14HPX-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	CX34-49	SL280UH090XV60C	8133669
14HPX-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	CX34-49	SL280UH110V60C	7045083
14HPX-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	CX34-49	SL280UH110XV60C	8133716
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	CX34-49	SLP98UH090XV48C	7045183
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	SLP98UH090XV60C	7045184
14HPX-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	SLP98UH110XV60C	7045185
14HPX-048-230	49,000	14.00	12.20	46,500	30,400	3.32	2.44	8.20	CX34-49		7045067
14HPX-048-230	47,500	14.70	12.50	47,500	31,000	3.14	2.44	8.20	CX34-60D	EL180UH135E60D	7045121
14HPX-048-230	49,000	14.50	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	CBWMV-60C-100	7045198
14HPX-048-230	48,500	14.50	12.50	46,500	30,400	3.60	2.62	9.00	CX34-62C	CBWMV-60C-120	7045182
14HPX-048-230	48,500	15.00	12.70	46,000	30,400	3.60	2.66	9.00	CX34-62C	EL180UH090E60C	7045119
14HPX-048-230	48,500	15.00	12.70	46,000	30,400	3.58	2.66	9.00	CX34-62C	EL180UH110E60C	7045116
14HPX-048-230	48,500	14.50	12.50	46,500	30,400	3.58	2.64	9.00	CX34-62C	EL195UH090XE48C	7045190
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	CX34-62C	EL195UH110XE60C	7045200
14HPX-048-230	48,500	14.50	12.50	46,500	30,400	3.58	2.64	9.00	CX34-62C	EL296UH090XE48C	7045153
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	EL296UH090XV48C	7045104
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	EL296UH090XV60C	7045098
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	CX34-62C	EL296UH110XE60C	7045147
14HPX-048-230	48,500	14.70	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	EL296UH110XV48C	7045128
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	EL296UH110XV60C	7045091
14HPX-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	CX34-62C	SL280UH090V60C	7045214
14HPX-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	CX34-62C	SL280UH090XV60C	8133674
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	CX34-62C	SL280UH110V60C	7045215
14HPX-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	CX34-62C	SL280UH110XV60C	8133721
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	SLP98UH090XV48C	7045167
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	SLP98UH090XV60C	7045168
14HPX-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	SLP98UH110XV60C	7045157
14HPX-048-230	48,500	14.00	12.20	47,000	30,800	3.52	2.56	8.70	CX34-62C		7045079
14HPX-048-230	48,000	14.70	12.50	46,000	30,400	3.52	2.60	8.70	CX34-62D	EL180UH135E60D	7045132
14HPX-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	CX34-62D	EL195UH135XE60D	7045195
14HPX-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	CX34-62D	EL296UH135XE60D	7045146
14HPX-048-230	48,000	14.50	12.50	46,000	30,400	3.50	2.56	8.70	CX34-62D	EL296UH135XV60D	7045095
14HPX-048-230	48,000	14.50	12.50	46,000	30,200	3.52	2.56	8.70	CX34-62D	SL280UH135V60D	7045216
14HPX-048-230	48,000	14.50	12.70	46,000	30,000	3.52	2.56	8.70	CX34-62D	SLP98UH135XV60D	7045158
14HPX-060-230	57,500	14.50	12.00	54,000	35,000	3.28	2.36	8.20	C33-60D	EL180UH135E60D	7045423
14HPX-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	C33-60D	EL195UH135XE60D	7045455
14HPX-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	C33-60D	EL296UH135XE60D	7045437
14HPX-060-230	61,000	15.00	12.50	54,500	36,400	3.30	2.52	8.70	C33-62C	CBWMV-60C-100	7045450
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	CBWMV-60C-120	7045460
14HPX-060-230	60,500	15.20	12.50	54,500	36,200	3.28	2.52	8.70	C33-62C	EL180UH090E60C	7045418
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.50	8.50	C33-62C	EL180UH110E60C	7045432
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	C33-62C	EL195UH110XE60C	7045451
14HPX-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	C33-62C	EL296UH090XV60C	7045410
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	C33-62C	EL296UH110XE60C	7045441
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	EL296UH110XV60C	7045413
14HPX-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	C33-62C	SL280UH090V60C	7045400
14HPX-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	C33-62C	SL280UH090XV60C	8133678
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SL280UH110V60C	7045401
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SL280UH110XV60C	8133724
14HPX-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	C33-62C	SLP98UH090XV60C	7045474
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SLP98UH110XV60C	7045464
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C		7045391
14HPX-060-230	57,500	14.50	12.20	55,000	36,400	3.20	2.38	8.20	C33-62D	EL180UH135E60D	7045415
14HPX-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	C33-62D	EL195UH135XE60D	7045456
14HPX-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	C33-62D	EL296UH135XE60D	7045435
14HPX-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	C33-62D	EL296UH135XV60D	7045405
14HPX-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	C33-62D	SL280UH135V60D	7045482
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	C33-62D	SLP98UH135XV60D	7045465
14HPX-060-230	58,500	14.00	12.00	55,500	35,800	3.28	2.46	8.20	CBX25UH-060		7045428
14HPX-060-230	58,000	14.50	12.50	54,500	35,000	3.28	2.50	8.50	CBX25UHV-060		7045408
14HPX-060-230	59,000	15.00	12.50	56,000	36,000	3.52	2.62	8.50	CBX27UH-060		7045483
14HPX-060-230	59,000	14.50	12.00	56,500	37,200	3.22	2.50	8.50	CBX32M-060		7045484
14HPX-060-230	59,000	14.50	12.00	57,000	37,200	3.24	2.48	8.50	CBX32MV-060		7045476
14HPX-060-230	59,000	14.50	12.20	53,500	36,000	3.28	2.48	8.70	CBX32MV-068		7045477
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-060-230	59,000	14.50	12.00	57,000	37,200	3.24	2.48	8.50	CBX40UHV-060		7045402
14HPX-060-230	59,500	15.00	12.50	57,000	37,400	3.48	2.60	9.00	CH23-68	EL180UH090E60C	7045416
14HPX-060-230	59,500	14.70	12.50	57,000	37,400	3.46	2.58	9.00	CH23-68	EL180UH110E60C	7045431
14HPX-060-230	60,000	15.00	12.70	57,000	37,600	3.52	2.62	9.00	CH23-68	EL180UH135E60D	7045422
14HPX-060-230	59,500	15.00	12.50	57,000	37,400	3.50	2.60	9.00	CH23-68	EL195UH110XE60C	7045452
14HPX-060-230	60,000	14.70	12.20	57,500	37,800	3.48	2.58	9.00	CH23-68	EL195UH135XE60D	7045445
14HPX-060-230	59,500	15.00	12.50	57,000	37,400	3.50	2.60	9.00	CH23-68	EL296UH110XE60C	7045442
14HPX-060-230	60,000	14.70	12.20	57,500	37,800	3.48	2.58	9.00	CH23-68	EL296UH135XE60D	7045444
14HPX-060-230	60,000	14.70	12.50	57,500	37,800	3.50	2.60	9.00	CH23-68	EL296UH135XV60D	7045404
14HPX-060-230	60,000	14.70	12.50	57,500	37,800	3.50	2.60	9.00	CH23-68	SL280UH135V60D	7045403
14HPX-060-230	59,500	15.00	12.50	57,000	37,400	3.46	2.60	9.00	CH23-68	SLP98UH135XV60D	7045463
14HPX-060-230	59,500	14.20	12.20	57,500	38,000	3.42	2.56	8.70	CH23-68		7045390
14HPX-060-230	57,000	14.20	11.70	54,000	35,000	3.24	2.36	8.20	CH33-60D	EL180UH135E60D	7045429
14HPX-060-230	57,000	14.00	11.70	54,500	35,200	3.22	2.32	8.20	CH33-60D	EL195UH135XE60D	7045449
14HPX-060-230	57,000	14.00	11.70	54,500	35,200	3.22	2.32	8.20	CH33-60D	EL296UH135XE60D	7045427
14HPX-060-230	57,500	14.50	12.20	54,000	36,000	3.24	2.42	8.50	CH33-62D	EL180UH135E60D	7045426
14HPX-060-230	57,500	14.20	12.00	54,000	36,400	3.20	2.40	8.50	CH33-62D	EL195UH135XE60D	7045446
14HPX-060-230	57,500	14.20	12.00	54,000	36,400	3.20	2.40	8.50	CH33-62D	EL296UH135XE60D	7045433
14HPX-060-230	57,500	14.20	12.20	54,000	36,200	3.24	2.42	8.50	CH33-62D	EL296UH135XV60D	7045406
14HPX-060-230	57,500	14.20	12.20	54,000	36,200	3.22	2.42	8.50	CH33-62D	SL280UH135V60D	7045478
14HPX-060-230	57,500	14.50	12.20	54,000	36,200	3.22	2.42	8.50	CH33-62D	SLP98UH135XV60D	7045457
14HPX-060-230	57,000	14.00	11.70	54,000	36,400	3.16	2.38	8.20	CH33-62D		7045396
14HPX-060-230	59,000	14.70	12.20	58,000	37,800	3.16	2.46	8.20	CR33-50/60	EL180DF110E60C	7045420
14HPX-060-230	58,500	14.00	11.70	58,000	37,600	3.10	2.42	8.20	CR33-50/60	EL195DF110XE60C	7045462
14HPX-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	EL296DF090V60C	7045479
14HPX-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	EL296DF110V60C	7045480
14HPX-060-230	58,500	14.00	11.70	58,000	37,600	3.10	2.42	8.20	CR33-50/60	EL296DF110XE60C	7045440
14HPX-060-230	59,000	14.50	12.00	58,500	37,800	3.14	2.44	8.20	CR33-50/60	SL280DF090V60C	7045486
14HPX-060-230	59,000	14.70	12.20	58,000	37,800	3.12	2.44	8.20	CR33-50/60	SL280DF110V60C	7045475
14HPX-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	SLP98DF090XV60C	7045466
14HPX-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	SLP98DF110XV60C	7045467
14HPX-060-230	58,500	14.20	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60		7045393
14HPX-060-230	58,500	14.20	11.70	58,500	38,000	3.08	2.38	8.20	CR33-60		7045394
14HPX-060-230	57,500	14.50	12.00	54,000	35,000	3.28	2.36	8.20	CX34-60D	EL180UH135E60D	7045425
14HPX-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	CX34-60D	EL195UH135XE60D	7045447
14HPX-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	CX34-60D	EL296UH135XE60D	7045434
14HPX-060-230	61,000	15.00	12.50	54,500	36,400	3.30	2.52	8.70	CX34-62C	CBWMV-60C-100	7045439
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	CBWMV-60C-120	7045461
14HPX-060-230	60,500	15.20	12.50	54,500	36,200	3.28	2.52	8.70	CX34-62C	EL180UH090E60C	7045417
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.50	8.50	CX34-62C	EL180UH110E60C	7045421
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	CX34-62C	EL195UH110XE60C	7045454
14HPX-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	CX34-62C	EL296UH090XV60C	7045411
14HPX-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	CX34-62C	EL296UH110XE60C	7045438
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	EL296UH110XV60C	7045414
14HPX-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	CX34-62C	SL280UH090V60C	7045469
14HPX-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	CX34-62C	SL280UH090XV60C	8133679
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SL280UH110V60C	7045470
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SL280UH110XV60C	8133726
14HPX-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	CX34-62C	SLP98UH090XV60C	7045458
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES - ALL REGIONS**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SLP98UH110XV60C	7045468
14HPX-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C		7045395
14HPX-060-230	57,500	14.50	12.20	55,000	36,400	3.20	2.38	8.20	CX34-62D	EL180UH135E60D	7045424
14HPX-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	CX34-62D	EL195UH135XE60D	7045448
14HPX-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	CX34-62D	EL296UH135XE60D	7045436
14HPX-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	CX34-62D	EL296UH135XV60D	7045407
14HPX-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	CX34-62D	SL280UH135V60D	7045471
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459
14HPX-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	7045459

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.





PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-018-230A	18,000	16.00	13.00	17,500	11,100	3.80	2.56	8.50	C33-25A	EL180UH045E36A	7533486
XP14-018-230A	18,000	16.00	13.00	17,600	11,100	3.86	2.58	8.50	C33-31A	EL180UH045E36A	7533484
XP14-018-230A	18,000	14.00	12.00	17,800	11,800	3.52	2.48	8.20	CBX25UH-018		7533471
XP14-018-230A	18,000	15.00	12.50	17,600	11,600	3.64	2.54	8.50	CBX25UHV-018		7533472
XP14-018-230A	18,000	15.50	12.50	18,000	11,600	3.80	2.62	8.50	CBX25UHV-024		7533489
XP14-018-230A	18,000	16.00	13.00	17,500	11,100	3.92	2.62	8.50	CBX27UH-018		7533475
XP14-018-230A	18,000	16.00	13.00	17,500	11,100	3.96	2.64	8.50	CBX27UH-024		7533474
XP14-018-230A	18,000	15.50	12.50	17,700	11,100	3.84	2.56	8.50	CBX32MV-018/024		7533477
XP14-018-230A	18,000	16.00	13.00	17,700	11,300	3.90	2.62	8.50	CH33-25A	EL180UH045E36A	7533479
XP14-018-230A	18,000	14.00	12.00	18,000	11,700	3.56	2.42	8.20	CH33-25A		7533478
XP14-018-230A	18,000	14.00	11.50	18,000	11,700	3.56	2.42	8.20	CH33-25B		7533481
XP14-018-230A	18,000	16.00	13.00	18,000	11,400	4.06	2.66	8.50	CR33-30/36A	EL180DF045E36A	7533488
XP14-018-230A	18,000	16.00	13.00	17,500	11,100	3.80	2.56	8.50	CX34-25A	EL180UH045E36A	7533485
XP14-018-230A	18,000	16.00	13.00	17,600	11,100	3.86	2.58	8.50	CX34-31A	EL180UH045E36A	7533482
XP14-024-230	24,000	15.50	13.00	21,400	13,500	3.50	2.44	8.20	C33-25	EL180UH045E36A	5741752
XP14-024-230	24,800	16.00	13.50	21,600	13,500	3.68	2.52	8.50	C33-25	EL180UH070E36B	5742030
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	C33-25	EL195UH045XE36B	5431380
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	C33-25	EL195UH070XE36B	5431372
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	C33-25	EL296UH045XE36B	5650630
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	C33-25	EL296UH045XV36B	5562666
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	C33-25	EL296UH070XE36B	5650629
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-25	EL296UH070XV36B	5562673
XP14-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	C33-25	SL280UH070V36A	5532364
XP14-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	C33-25	SL280UH070XV36A	8133171
XP14-024-230	24,800	16.00	13.00	21,600	13,500	3.72	2.52	8.50	C33-25	SL280UH090V36B	5532458
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	C33-25	SL280UH090V48B	5431275
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	C33-25	SL280UH090XV48B	8133190
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-25	SLP98UH070XV36B	5431384
XP14-024-230	24,400	15.70	13.20	21,400	13,500	3.60	2.48	8.50	C33-31	EL180UH045E36A	5741754
XP14-024-230	24,800	16.00	13.50	21,600	13,500	3.70	2.52	8.50	C33-31	EL180UH070E36B	5742033
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	C33-31	EL195UH045XE36B	5431381
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	C33-31	EL195UH070XE36B	5431373
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	C33-31	EL296UH045XE36B	5650636
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	C33-31	EL296UH045XV36B	5562660
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	C33-31	EL296UH070XE36B	5650635
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	C33-31	EL296UH070XV36B	5562675
XP14-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH070V36A	5532366
XP14-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH070XV36A	8133173

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-024-230	24,800	15.10	13.50	21,600	13,500	3.74	2.54	8.50	C33-31	SL280UH090V36B	5532453
XP14-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	C33-31	SL280UH090V48B	5431282
XP14-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	C33-31	SL280UH090XV48B	8133191
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	C33-31	SLP98UH070XV36B	5431385
XP14-024-230	24,000	15.70	13.00	21,400	13,500	3.58	2.48	8.50	C33-36	EL180UH045E36A	5741758
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.52	8.50	C33-36	EL180UH070E36B	5742034
XP14-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	C33-36	EL195UH045XE36B	5431382
XP14-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	EL195UH070XE36B	5431374
XP14-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	C33-36	EL296UH045XE36B	5650639
XP14-024-230	24,400	15.70	13.20	21,600	13,600	3.68	2.52	8.50	C33-36	EL296UH045XV36B	5562663
XP14-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	EL296UH070XE36B	5650638
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	C33-36	EL296UH070XV36B	5562670
XP14-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	C33-36	EL296UH090XV36C	5562681
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	C33-36	SL280UH070V36A	5532368
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	C33-36	SL280UH070XV36A	8133175
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.74	2.54	8.50	C33-36	SL280UH090V36B	5532455
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	SL280UH090V48B	5431289
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.50	C33-36	SL280UH090XV48B	8133192
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	C33-36	SLP98UH070XV36B	5431386
XP14-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	C33-36	SLP98UH090XV36C	5431387
XP14-024-230	23,200	14.00	11.70	22,200	14,000	3.46	2.36	8.20	CBX25UH-024		5727003
XP14-024-230	23,200	14.00	11.70	22,200	14,100	3.48	2.38	8.20	CBX25UH-030		5796112
XP14-024-230	23,600	15.50	12.50	21,400	13,400	3.64	2.48	8.50	CBX25UHV-024		6970216
XP14-024-230	25,200	16.00	13.50	21,800	13,700	3.88	2.64	9.00	CBX27UH-024		5431298
XP14-024-230	25,000	16.00	13.50	21,800	13,600	3.96	2.66	9.00	CBX27UH-030		6482931
XP14-024-230	24,800	14.20	11.70	22,800	14,100	3.54	2.42	8.20	CBX32M-018/024		5431299
XP14-024-230	25,000	15.20	12.70	22,400	14,000	3.76	2.52	8.70	CBX32M-030		5431300
XP14-024-230	25,000	14.50	12.20	22,600	14,000	3.58	2.44	8.20	CBX32MV-018/024		5431301
XP14-024-230	24,800	15.20	12.70	22,200	14,000	3.72	2.52	8.70	CBX32MV-024/030		5431302
XP14-024-230	25,200	15.50	13.00	22,400	14,000	3.92	2.60	9.00	CBX32MV-036		5431303
XP14-024-230	24,800	15.20	12.70	22,200	14,000	3.82	2.58	8.70	CBX40UHV-024		5431304
XP14-024-230	24,800	15.50	13.00	22,200	13,900	3.82	2.58	8.70	CBX40UHV-030		5431305
XP14-024-230	25,200	15.50	13.00	22,400	14,000	3.92	2.60	9.00	CBX40UHV-036		6482929
XP14-024-230	24,200	15.70	13.20	21,400	13,500	3.60	2.48	8.50	CH23-41	EL180UH045E36A	5741756
XP14-024-230	24,600	15.70	13.20	21,600	13,500	3.70	2.50	8.50	CH23-41	EL296UH045XV36B	5562662
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CH23-41	EL296UH070XV36B	5562672
XP14-024-230	24,800	16.00	13.00	21,600	13,500	3.74	2.54	8.50	CH23-41	SL280UH090V36B	5532454
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CH23-41	SL280UH090V48B	5431310
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CH23-41	SL280UH090XV48B	8133193
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CH23-41	SLP98UH070XV36B	5431389
XP14-024-230	24,400	15.70	13.20	21,600	13,500	3.64	2.48	8.50	CH33-25A	EL180UH045E36A	5741760
XP14-024-230	24,800	15.70	13.00	21,800	13,700	3.72	2.52	8.50	CH33-25A	SL280UH070V36A	5532370

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-024-230	24,800	15.70	13.00	21,800	13,700	3.72	2.52	8.50	CH33-25A	SL280UH070XV36A	8133176
XP14-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	EL180UH070E36B	5742031
XP14-024-230	24,000	15.50	13.00	21,600	13,500	3.60	2.46	8.50	CH33-25B	EL195UH045XE36B	5431365
XP14-024-230	24,400	15.50	13.00	21,800	13,600	3.68	2.50	8.50	CH33-25B	EL195UH070XE36B	5431376
XP14-024-230	24,000	15.50	13.00	21,600	13,500	3.60	2.46	8.50	CH33-25B	EL296UH045XE36B	5650634
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.72	2.54	8.70	CH33-25B	EL296UH045XV36B	5562665
XP14-024-230	24,400	15.50	13.00	21,800	13,600	3.68	2.50	8.50	CH33-25B	EL296UH070XE36B	5650627
XP14-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	EL296UH070XV36B	5562674
XP14-024-230	24,600	15.10	13.00	21,600	13,500	3.78	2.56	8.50	CH33-25B	SL280UH090V36B	5532457
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.66	2.50	8.50	CH33-25B	SL280UH090V48B	5431317
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.66	2.50	8.50	CH33-25B	SL280UH090XV48B	8133194
XP14-024-230	24,600	16.00	13.00	21,600	13,600	3.74	2.54	8.50	CH33-25B	SLP98UH070XV36B	5431390
XP14-024-230	24,400	15.70	13.20	21,600	13,600	3.66	2.52	8.50	CH33-31A	EL180UH045E36A	5741757
XP14-024-230	25,200	16.00	13.00	22,000	13,700	3.86	2.58	8.50	CH33-31A	SL280UH070V36A	5532371
XP14-024-230	25,200	16.00	13.00	22,000	13,700	3.86	2.58	8.50	CH33-31A	SL280UH070XV36A	8133177
XP14-024-230	24,400	14.20	12.00	22,400	14,200	3.54	2.40	8.20	CH33-31A		5431261
XP14-024-230	23,800	15.20	12.70	21,400	13,500	3.50	2.42	8.20	CH33-36A	EL180UH045E36A	5741755
XP14-024-230	24,600	15.10	13.00	21,800	13,600	3.68	2.48	8.50	CH33-36A	SL280UH070V36A	5532367
XP14-024-230	24,600	15.10	13.00	21,800	13,600	3.68	2.48	8.50	CH33-36A	SL280UH070XV36A	8133174
XP14-024-230	24,600	16.00	13.50	21,800	13,500	3.84	2.58	8.50	CH33-36C	EL296UH090XV36C	5562680
XP14-024-230	24,600	16.00	13.50	21,800	13,500	3.84	2.58	8.50	CH33-36C	SLP98UH090XV36C	5431391
XP14-024-230	24,000	14.00	11.70	22,400	14,200	3.50	2.38	8.20	CH33-36C		5431263
XP14-024-230	24,800	15.70	13.20	22,000	13,600	3.76	2.54	8.70	CR33-30/36	EL180DF045E36A	5741528
XP14-024-230	25,400	16.00	13.50	22,200	13,600	3.92	2.60	9.00	CR33-30/36	EL180DF070E36B	5741558
XP14-024-230	25,200	16.00	13.00	22,200	13,600	3.84	2.56	8.50	CR33-30/36	EL195DF045XE36B	5431378
XP14-024-230	25,400	16.00	13.50	22,200	13,600	3.90	2.60	9.00	CR33-30/36	EL195DF070XE48B	5431379
XP14-024-230	25,200	16.00	13.00	22,200	13,600	3.84	2.56	8.50	CR33-30/36	EL296DF045XE36B	5650618
XP14-024-230	25,200	16.00	13.50	22,200	13,600	3.86	2.58	8.50	CR33-30/36	EL296DF045XV36B	5562658
XP14-024-230	25,400	16.00	13.50	22,200	13,600	3.90	2.60	9.00	CR33-30/36	EL296DF070XE48B	5650624
XP14-024-230	25,600	15.70	13.20	22,400	13,800	3.88	2.58	8.70	CR33-30/36	EL296DF070XV48B	5562659
XP14-024-230	25,200	15.70	13.00	22,200	13,700	3.82	2.56	8.50	CR33-30/36	SL280DF070V36A	5431324
XP14-024-230	25,600	15.10	13.50	22,200	13,700	3.94	2.62	9.00	CR33-30/36	SL280DF090V48B	5532330
XP14-024-230	25,400	16.00	13.50	22,200	13,600	3.92	2.60	9.00	CR33-30/36	SLP98DF070XV36B	5431392
XP14-024-230	25,400	16.00	13.50	22,200	13,600	3.94	2.62	9.00	CR33-30/36	SLP98DF090XV36C	5431393
XP14-024-230	24,800	14.20	12.20	22,600	14,200	3.54	2.40	8.20	CR33-30/36		5431264
XP14-024-230	24,000	15.50	13.00	21,400	13,500	3.50	2.44	8.20	CX34-25	EL180UH045E36A	5741753
XP14-024-230	24,800	16.00	13.50	21,600	13,500	3.68	2.52	8.50	CX34-25	EL180UH070E36B	5742032
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	CX34-25	EL195UH045XE36B	5431368
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	CX34-25	EL195UH070XE36B	5431360
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.52	2.44	8.20	CX34-25	EL296UH045XE36B	5650626
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.66	2.50	8.50	CX34-25	EL296UH045XV36B	5562661
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.60	2.48	8.50	CX34-25	EL296UH070XE36B	5650625

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-25	EL296UH070XV36B	5562676
XP14-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	CX34-25	SL280UH070V36A	5532365
XP14-024-230	24,800	15.70	13.00	21,800	13,600	3.68	2.48	8.20	CX34-25	SL280UH070XV36A	8133172
XP14-024-230	24,800	16.00	13.00	21,600	13,500	3.72	2.52	8.50	CX34-25	SL280UH090V36B	5532462
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	CX34-25	SL280UH090V48B	5431335
XP14-024-230	24,400	15.10	13.00	21,600	13,600	3.60	2.48	8.20	CX34-25	SL280UH090XV48B	8133195
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-25	SLP98UH070XV36B	5431394
XP14-024-230	24,400	15.70	13.20	21,400	13,500	3.60	2.48	8.50	CX34-31	EL180UH045E36A	5741761
XP14-024-230	24,800	16.00	13.50	21,600	13,500	3.70	2.52	8.50	CX34-31	EL180UH070E36B	5742038
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	CX34-31	EL195UH045XE36B	5431369
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	CX34-31	EL195UH070XE36B	5431361
XP14-024-230	24,200	15.50	13.00	21,400	13,500	3.54	2.44	8.20	CX34-31	EL296UH045XE36B	5650620
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.68	2.50	8.50	CX34-31	EL296UH045XV36B	5562667
XP14-024-230	24,600	15.70	13.20	21,600	13,600	3.62	2.48	8.50	CX34-31	EL296UH070XE36B	5650619
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-31	EL296UH070XV36B	5562679
XP14-024-230	24,800	15.10	13.00	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH070V36A	5532372
XP14-024-230	24,800	15.10	13.00	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH070XV36A	8133178
XP14-024-230	24,800	16.00	13.50	21,600	13,500	3.74	2.54	8.50	CX34-31	SL280UH090V36B	5532461
XP14-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CX34-31	SL280UH090V48B	5431342
XP14-024-230	24,600	15.10	13.00	21,600	13,600	3.62	2.48	8.20	CX34-31	SL280UH090XV48B	8133196
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-31	SLP98UH070XV36B	5431395
XP14-024-230	24,000	15.70	13.00	21,400	13,500	3.58	2.48	8.50	CX34-36	EL180UH045E36A	5741762
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.52	8.50	CX34-36	EL180UH070E36B	5742036
XP14-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	CX34-36	EL195UH045XE36B	5431370
XP14-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	CX34-36	EL195UH070XE36B	5431362
XP14-024-230	23,800	15.50	12.70	21,400	13,500	3.54	2.44	8.20	CX34-36	EL296UH045XE36B	5650617
XP14-024-230	24,400	15.70	13.20	21,600	13,600	3.68	2.52	8.50	CX34-36	EL296UH045XV36B	5562668
XP14-024-230	24,200	15.50	13.00	21,600	13,600	3.62	2.48	8.50	CX34-36	EL296UH070XE36B	5650616
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CX34-36	EL296UH070XV36B	5562677
XP14-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	CX34-36	EL296UH090XV36C	5562682
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	CX34-36	SL280UH070V36A	5532373
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.72	2.54	8.50	CX34-36	SL280UH070XV36A	8133179
XP14-024-230	24,600	16.00	13.00	21,600	13,500	3.74	2.54	8.50	CX34-36	SL280UH090V36B	5532459
XP14-024-230	24,400	15.10	12.50	21,600	13,600	3.62	2.48	8.20	CX34-36	SL280UH090V48B	5431349
XP14-024-230	24,400	15.10	12.50	21,600	13,600	3.62	2.48	8.20	CX34-36	SL280UH090XV48B	8133197
XP14-024-230	24,400	16.00	13.00	21,600	13,500	3.70	2.50	8.50	CX34-36	SLP98UH070XV36B	5431396
XP14-024-230	24,400	16.00	13.00	21,400	13,500	3.68	2.52	8.50	CX34-36	SLP98UH090XV36C	5431397
XP14-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-31	EL180UH045E36A	5741769
XP14-030-230	30,000	15.70	13.50	25,600	16,400	3.64	2.52	8.50	C33-31	EL180UH070E36B	5742043
XP14-030-230	30,200	15.70	13.50	25,600	16,500	3.66	2.56	8.70	C33-31	EL180UH090E48B	5742360
XP14-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL195UH045XE36B	5431577
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL195UH070XE36B	5431607

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL296UH045XE36B	5650647
XP14-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	C33-31	EL296UH045XV36B	5562690
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	C33-31	EL296UH070XE36B	5650662
XP14-030-230	29,800	15.50	13.20	25,600	16,500	3.60	2.52	8.50	C33-31	EL296UH070XV36B	5562706
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	C33-31	SL280UH070V36A	5532379
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	C33-31	SL280UH070XV36A	8133184
XP14-030-230	30,000	15.70	13.50	25,400	16,400	3.62	2.54	8.50	C33-31	SL280UH090V36B	5532473
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	C33-31	SL280UH090V48B	5431559
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	C33-31	SL280UH090XV48B	8133213
XP14-030-230	30,000	15.20	13.20	25,600	16,600	3.62	2.52	8.50	C33-31	SLP98UH070XV36B	5431643
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	EL180UH070E36B	5742054
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	C33-36	EL180UH090E48B	5742365
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-36	EL195UH045XE36B	5431578
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-36	EL195UH070XE36B	5431608
XP14-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	C33-36	EL195UH090XE48C	5431584
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-36	EL296UH045XE36B	5650664
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	C33-36	EL296UH045XV36B	5562694
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-36	EL296UH070XE36B	5650656
XP14-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	C33-36	EL296UH070XV36B	5562712
XP14-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	C33-36	EL296UH090XE48C	5650653
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	EL296UH090XV36C	5767217
XP14-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	C33-36	SL280UH070V36A	5532380
XP14-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	C33-36	SL280UH070XV36A	8133185
XP14-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	C33-36	SL280UH090V36B	5532478
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-36	SL280UH090V48B	5431482
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-36	SL280UH090XV48B	8133204
XP14-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-36	SLP98UH070XV36B	5431624
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-36	SLP98UH090XV36C	5431625
XP14-030-230	29,600	15.20	13.20	25,600	16,600	3.66	2.54	8.70	C33-36	SLP98UH090XV48C	5431626
XP14-030-230	30,800	15.50	13.50	25,800	16,600	3.66	2.54	8.50	C33-38	EL180UH045E36A	5741770
XP14-030-230	30,800	15.70	13.70	25,600	16,400	3.70	2.54	8.70	C33-38	EL180UH070E36B	5742048
XP14-030-230	31,000	15.70	13.70	25,600	16,500	3.72	2.58	8.70	C33-38	EL180UH090E48B	5742373
XP14-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	C33-38	EL195UH045XE36B	5431592
XP14-030-230	31,000	15.50	13.20	26,000	16,800	3.70	2.54	8.70	C33-38	EL195UH070XE36B	5431564
XP14-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	C33-38	EL296UH045XE36B	5650654
XP14-030-230	30,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	C33-38	EL296UH045XV36B	5562686
XP14-030-230	31,000	15.50	13.20	26,000	16,800	3.70	2.54	8.70	C33-38	EL296UH070XE36B	5650674
XP14-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	C33-38	EL296UH070XV36B	5562703
XP14-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	C33-38	SL280UH070V36A	5532377
XP14-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	C33-38	SL280UH070XV36A	8133182
XP14-030-230	30,800	15.70	13.70	25,400	16,400	3.68	2.56	8.70	C33-38	SL280UH090V36B	5532466
XP14-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	C33-38	SL280UH090V48B	5431426

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	C33-38	SL280UH090XV48B	8133198
XP14-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	C33-38	SLP98UH070XV36B	5431613
XP14-030-230	30,400	14.00	12.20	26,200	17,200	3.44	2.40	8.20	C33-38		5431410
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	C33-42	EL180UH070E36B	5742045
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	C33-42	EL180UH090E48B	5742371
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-42	EL195UH045XE36B	5431593
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-42	EL195UH070XE36B	5431565
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	C33-42	EL296UH045XE36B	5650649
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	C33-42	EL296UH045XV36B	5562695
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	C33-42	EL296UH070XE36B	5650668
XP14-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	C33-42	EL296UH070XV36B	5562704
XP14-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	C33-42	SL280UH090V36B	5532467
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-42	SL280UH090V48B	5431437
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	C33-42	SL280UH090XV48B	8133199
XP14-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	C33-42	SLP98UH070XV36B	5431615
XP14-030-230	30,400	15.70	13.70	25,600	16,400	3.66	2.54	8.70	C33-43	EL180UH070E36B	5742041
XP14-030-230	30,600	16.00	13.50	25,800	16,500	3.72	2.56	8.50	C33-43	EL180UH090E48B	5742364
XP14-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	C33-43	EL195UH045XE36B	5431594
XP14-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	C33-43	EL195UH070XE36B	5431566
XP14-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	C33-43	EL195UH090XE48C	5431585
XP14-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	C33-43	EL296UH045XE36B	5650666
XP14-030-230	30,200	15.50	13.20	25,800	16,600	3.62	2.50	8.50	C33-43	EL296UH045XV36B	5562687
XP14-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	C33-43	EL296UH070XE36B	5650640
XP14-030-230	30,200	15.70	13.50	25,600	16,500	3.64	2.54	8.50	C33-43	EL296UH070XV36B	5562701
XP14-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	C33-43	EL296UH090XE48C	5650648
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	C33-43	EL296UH090XV36C	5562719
XP14-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	C33-43	EL296UH090XV48C	5562726
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.68	2.56	8.50	C33-43	SL280UH090V36B	5532465
XP14-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	C33-43	SL280UH090V48B	5431471
XP14-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	C33-43	SL280UH090XV48B	8133203
XP14-030-230	30,400	15.70	13.50	25,800	16,600	3.66	2.54	8.50	C33-43	SLP98UH070XV36B	5431620
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	C33-43	SLP98UH090XV36C	5431621
XP14-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	C33-43	SLP98UH090XV48C	5431622
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	EL180UH070E36B	5742039
XP14-030-230	29,800	15.50	13.20	25,400	16,400	3.58	2.50	8.50	C33-48	EL180UH090E48B	5742362
XP14-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	C33-48	EL195UH045XE36B	5431595
XP14-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	C33-48	EL195UH070XE36B	5431567
XP14-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-48	EL195UH090XE48C	5431586
XP14-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	C33-48	EL296UH045XE36B	5650683
XP14-030-230	29,600	15.00	13.00	25,600	16,500	3.50	2.44	8.20	C33-48	EL296UH045XV36B	5562691
XP14-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	C33-48	EL296UH070XE36B	5650657
XP14-030-230	29,600	15.20	13.20	25,400	16,400	3.52	2.46	8.20	C33-48	EL296UH070XV36B	5562714

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	C33-48	EL296UH090XE48C	5650665
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	EL296UH090XV36C	5562717
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.60	2.50	8.50	C33-48	EL296UH090XV48C	5562725
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.56	2.48	8.20	C33-48	SL280UH090V36B	5532463
XP14-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	C33-48	SL280UH090V48B	5431489
XP14-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	C33-48	SL280UH090XV48B	8133205
XP14-030-230	29,600	15.20	13.00	25,600	16,500	3.54	2.48	8.20	C33-48	SLP98UH070XV36B	5431627
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	C33-48	SLP98UH090XV36C	5431636
XP14-030-230	28,200	14.00	12.00	26,200	17,100	3.64	2.52	8.20	CBX25UH-030		5727004
XP14-030-230	28,200	14.00	12.00	26,600	17,100	3.58	2.48	8.20	CBX25UH-036		5796508
XP14-030-230	28,600	15.00	12.50	25,600	16,400	3.66	2.54	8.50	CBX25UHV-030		6970217
XP14-030-230	30,000	15.00	13.00	26,400	16,800	3.88	2.66	9.00	CBX27UH-030		5431515
XP14-030-230	30,000	15.00	13.00	26,200	16,700	3.88	2.68	9.00	CBX27UH-036		5431516
XP14-030-230	29,200	14.50	12.50	26,200	16,900	3.68	2.56	8.70	CBX32M-030		5431517
XP14-030-230	30,000	14.50	12.00	26,800	17,300	3.74	2.58	8.70	CBX32M-036		5431518
XP14-030-230	29,200	14.20	12.20	26,400	17,100	3.68	2.54	8.70	CBX32MV-024/030		5431519
XP14-030-230	30,000	14.50	12.50	26,600	17,000	3.80	2.62	8.70	CBX32MV-036		5431520
XP14-030-230	30,000	14.50	12.50	26,600	17,000	3.78	2.60	8.70	CBX40UHV-030		5431521
XP14-030-230	30,000	15.00	12.50	26,400	16,900	3.80	2.62	8.70	CBX40UHV-036		5431522
XP14-030-230	29,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	CH23-41	EL180UH045E36A	5741768
XP14-030-230	29,800	15.50	13.50	25,600	16,400	3.70	2.54	8.70	CH23-41	EL180UH070E36B	5742050
XP14-030-230	29,800	15.70	13.50	25,600	16,400	3.72	2.56	8.70	CH23-41	EL180UH090E48B	5742368
XP14-030-230	29,600	15.00	13.00	25,800	16,600	3.62	2.50	8.50	CH23-41	EL195UH045XE36B	5431596
XP14-030-230	29,600	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CH23-41	EL195UH070XE36B	5431568
XP14-030-230	29,600	15.00	13.00	25,800	16,600	3.62	2.50	8.50	CH23-41	EL296UH045XE36B	5650678
XP14-030-230	29,400	15.20	13.20	25,600	16,400	3.62	2.50	8.50	CH23-41	EL296UH045XV36B	5562700
XP14-030-230	29,600	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CH23-41	EL296UH070XE36B	5650651
XP14-030-230	29,400	15.50	13.20	25,400	16,300	3.62	2.50	8.50	CH23-41	EL296UH070XV36B	5562713
XP14-030-230	29,400	15.70	13.50	25,400	16,300	3.68	2.56	8.50	CH23-41	SL280UH090V36B	5532475
XP14-030-230	29,800	15.50	13.20	25,600	16,400	3.68	2.54	8.70	CH23-41	SL280UH090V48B	5431529
XP14-030-230	29,800	15.50	13.20	25,600	16,400	3.68	2.54	8.70	CH23-41	SL280UH090XV48B	8133208
XP14-030-230	29,600	15.20	13.20	25,600	16,400	3.64	2.52	8.50	CH23-41	SLP98UH070XV36B	5431637
XP14-030-230	29,600	15.70	13.20	25,600	16,500	3.74	2.58	8.70	CH23-51	EL180UH070E36B	5742042
XP14-030-230	29,800	15.70	13.20	25,800	16,500	3.78	2.60	8.70	CH23-51	EL180UH090E48B	5742358
XP14-030-230	29,600	15.20	13.00	25,800	16,700	3.66	2.54	8.50	CH23-51	EL195UH045XE36B	5431597
XP14-030-230	29,600	15.00	12.70	26,000	16,700	3.66	2.52	8.50	CH23-51	EL195UH070XE36B	5431569
XP14-030-230	29,600	15.20	13.00	25,800	16,700	3.66	2.54	8.50	CH23-51	EL296UH045XE36B	5650672
XP14-030-230	29,600	15.00	12.70	26,000	16,700	3.66	2.52	8.50	CH23-51	EL296UH070XE36B	5650646
XP14-030-230	29,400	15.50	13.20	25,400	16,400	3.68	2.58	8.70	CH23-51	EL296UH090XV36C	5562721
XP14-030-230	29,800	15.70	13.50	25,800	16,500	3.80	2.60	8.70	CH23-51	EL296UH090XV48C	5562727
XP14-030-230	29,400	15.50	13.20	25,400	16,400	3.68	2.58	8.70	CH23-51	SLP98UH090XV36C	5431614
XP14-030-230	29,800	15.20	13.00	26,000	16,800	3.72	2.60	8.70	CH33-31A	EL180UH045E36A	5741765

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	30,000	15.20	13.20	26,000	16,700	3.74	2.60	8.70	CH33-31A	SL280UH070V36A	5532375
XP14-030-230	30,000	15.20	13.20	26,000	16,700	3.74	2.60	8.70	CH33-31A	SL280UH070XV36A	8133180
XP14-030-230	29,600	14.00	12.20	26,600	17,300	3.54	2.46	8.20	CH33-31A		5431403
XP14-030-230	30,400	15.70	13.50	25,800	16,500	3.72	2.56	8.70	CH33-31B	EL180UH070E36B	5742047
XP14-030-230	30,400	15.70	13.70	25,600	16,500	3.72	2.58	8.70	CH33-31B	EL180UH090E48B	5742359
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.64	2.52	8.50	CH33-31B	EL195UH045XE36B	5431598
XP14-030-230	30,400	15.50	13.20	26,000	16,800	3.68	2.54	8.70	CH33-31B	EL195UH070XE36B	5431570
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.64	2.52	8.50	CH33-31B	EL296UH045XE36B	5650644
XP14-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.52	8.50	CH33-31B	EL296UH045XV36B	5562688
XP14-030-230	30,400	15.50	13.20	26,000	16,800	3.68	2.54	8.70	CH33-31B	EL296UH070XE36B	5650663
XP14-030-230	30,000	15.70	13.20	25,600	16,500	3.66	2.54	8.50	CH33-31B	EL296UH070XV36B	5562711
XP14-030-230	30,200	15.70	13.70	25,600	16,400	3.70	2.56	8.70	CH33-31B	SL280UH090V36B	5532468
XP14-030-230	30,400	15.70	13.50	25,800	16,600	3.72	2.58	8.70	CH33-31B	SL280UH090V48B	5431445
XP14-030-230	30,400	15.70	13.50	25,800	16,600	3.72	2.58	8.70	CH33-31B	SL280UH090XV48B	8133200
XP14-030-230	30,200	15.50	13.20	25,800	16,600	3.68	2.54	8.70	CH33-31B	SLP98UH070XV36B	5431617
XP14-030-230	29,800	14.00	12.20	26,400	17,200	3.46	2.40	8.20	CH33-31B		5431404
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.52	2.48	8.20	CH33-36A	EL180UH045E36A	5741766
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.54	2.50	8.20	CH33-36A	SL280UH070V36A	5532378
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.54	2.50	8.20	CH33-36A	SL280UH070XV36A	8133183
XP14-030-230	29,600	15.20	13.20	25,600	16,500	3.66	2.54	8.50	CH33-36B	EL180UH070E36B	5742044
XP14-030-230	29,400	15.20	13.20	25,600	16,400	3.66	2.54	8.70	CH33-36B	EL180UH090E48B	5742361
XP14-030-230	29,400	14.70	12.70	25,800	16,600	3.60	2.50	8.50	CH33-36B	EL195UH045XE36B	5431599
XP14-030-230	29,600	15.00	12.70	26,000	16,700	3.64	2.50	8.50	CH33-36B	EL195UH070XE36B	5431571
XP14-030-230	29,400	14.70	12.70	25,800	16,600	3.60	2.50	8.50	CH33-36B	EL296UH045XE36B	5650661
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.56	2.50	8.50	CH33-36B	EL296UH045XV36B	5562692
XP14-030-230	29,600	15.00	12.70	26,000	16,700	3.64	2.50	8.50	CH33-36B	EL296UH070XE36B	5650680
XP14-030-230	29,200	15.20	13.00	25,600	16,400	3.62	2.50	8.50	CH33-36B	EL296UH070XV36B	5562715
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.54	8.50	CH33-36B	SL280UH090V36B	5532469
XP14-030-230	29,600	15.20	13.20	25,600	16,500	3.64	2.54	8.50	CH33-36B	SL280UH090V48B	5431468
XP14-030-230	29,600	15.20	13.20	25,600	16,500	3.64	2.54	8.50	CH33-36B	SL280UH090XV48B	8133202
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.62	2.52	8.50	CH33-36B	SLP98UH070XV36B	5431618
XP14-030-230	29,800	15.20	13.00	26,000	16,700	3.70	2.54	8.70	CH33-36C	EL195UH090XE48C	5431587
XP14-030-230	29,800	15.20	13.00	26,000	16,700	3.70	2.54	8.70	CH33-36C	EL296UH090XE48C	5650682
XP14-030-230	29,400	15.50	13.20	25,600	16,500	3.72	2.58	8.70	CH33-36C	EL296UH090XV36C	5562723
XP14-030-230	30,000	15.50	13.20	26,000	16,700	3.80	2.62	8.70	CH33-36C	EL296UH090XV48C	5562728
XP14-030-230	29,400	15.50	13.20	25,600	16,500	3.72	2.58	8.70	CH33-36C	SLP98UH090XV36C	5431619
XP14-030-230	30,000	15.50	13.20	26,000	16,700	3.80	2.62	8.70	CH33-36C	SLP98UH090XV48C	5431623
XP14-030-230	30,000	15.70	13.20	25,600	16,500	3.66	2.54	8.50	CH33-42	EL180UH070E36B	5742049
XP14-030-230	30,000	15.70	13.50	25,600	16,500	3.68	2.56	8.70	CH33-42	EL180UH090E48B	5742367
XP14-030-230	30,000	15.20	13.20	25,800	16,600	3.60	2.50	8.50	CH33-42	EL195UH045XE36B	5431600
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.62	2.52	8.50	CH33-42	EL195UH070XE36B	5431572
XP14-030-230	30,000	15.20	13.20	25,800	16,600	3.60	2.50	8.50	CH33-42	EL296UH045XE36B	5650655

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	CH33-42	EL296UH045XV36B	5562697
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.62	2.52	8.50	CH33-42	EL296UH070XE36B	5650675
XP14-030-230	29,800	15.50	13.20	25,600	16,400	3.62	2.50	8.50	CH33-42	EL296UH070XV36B	5562708
XP14-030-230	29,800	15.70	13.50	25,400	16,400	3.64	2.54	8.50	CH33-42	SL280UH090V36B	5532474
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.70	CH33-42	SL280UH090V48B	5431496
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.70	CH33-42	SL280UH090XV48B	8133206
XP14-030-230	30,000	15.50	13.20	25,600	16,600	3.62	2.54	8.50	CH33-42	SLP98UH070XV36B	5431628
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.72	2.58	8.50	CH33-43	EL296UH090XV36C	5562718
XP14-030-230	31,000	16.00	14.00	25,800	16,500	3.80	2.60	8.50	CH33-43	EL296UH090XV48C	5562724
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.72	2.58	8.50	CH33-43	SLP98UH090XV36C	5431629
XP14-030-230	31,000	16.00	14.00	25,800	16,500	3.80	2.60	8.50	CH33-43	SLP98UH090XV48C	5431630
XP14-030-230	30,000	14.20	12.20	26,400	17,200	3.46	2.40	8.20	CH33-43		5431412
XP14-030-230	31,000	15.70	13.70	26,000	16,700	3.74	2.56	8.70	CH33-43C	EL195UH090XE48C	5431588
XP14-030-230	31,000	15.70	13.70	26,000	16,700	3.74	2.56	8.70	CH33-43C	EL296UH090XE48C	5650677
XP14-030-230	29,800	15.00	13.00	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL180DF045E36A	5741529
XP14-030-230	29,800	15.50	13.20	26,800	17,100	3.84	2.64	9.00	CR33-30/36	EL180DF070E36B	5741559
XP14-030-230	29,800	15.50	13.20	26,800	17,100	3.82	2.64	9.00	CR33-30/36	EL180DF090E48B	5741583
XP14-030-230	29,600	15.00	12.70	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL195DF045XE36B	5431574
XP14-030-230	30,000	15.20	13.20	27,000	17,300	3.82	2.64	9.00	CR33-30/36	EL195DF070XE48B	5431575
XP14-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	EL195DF090XE48C	5431576
XP14-030-230	29,600	15.00	12.70	27,000	17,300	3.76	2.60	8.70	CR33-30/36	EL296DF045XE36B	5650641
XP14-030-230	29,600	15.20	13.20	26,800	17,100	3.76	2.60	8.70	CR33-30/36	EL296DF045XV36B	5562683
XP14-030-230	30,000	15.20	13.20	27,000	17,300	3.82	2.64	9.00	CR33-30/36	EL296DF070XE48B	5650658
XP14-030-230	29,600	15.00	13.00	26,800	17,200	3.72	2.58	8.70	CR33-30/36	EL296DF070XV48B	5562684
XP14-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	EL296DF090XE48C	5650652
XP14-030-230	29,600	15.20	13.00	26,800	17,200	3.76	2.60	8.70	CR33-30/36	SL280DF070V36A	5431500
XP14-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	SL280DF090V48B	5532331
XP14-030-230	29,600	15.20	13.00	26,800	17,200	3.76	2.60	8.70	CR33-30/36	SLP98DF070XV36B	5431631
XP14-030-230	29,800	15.50	13.20	26,800	17,100	3.82	2.64	9.00	CR33-30/36	SLP98DF090XV36C	5431632
XP14-030-230	29,600	15.20	13.20	26,800	17,100	3.80	2.62	8.70	CR33-30/36	SLP98DF090XV48C	5431633
XP14-030-230	30,000	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-31	EL180UH045E36A	5741764
XP14-030-230	30,000	15.70	13.50	25,600	16,400	3.64	2.52	8.50	CX34-31	EL180UH070E36B	5742040
XP14-030-230	30,200	15.70	13.50	25,600	16,500	3.66	2.56	8.70	CX34-31	EL180UH090E48B	5742363
XP14-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL195UH045XE36B	5431601
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL195UH070XE36B	5431573
XP14-030-230	30,000	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL296UH045XE36B	5650650
XP14-030-230	29,800	15.20	13.00	25,600	16,600	3.56	2.50	8.50	CX34-31	EL296UH045XV36B	5562696
XP14-030-230	30,200	15.20	13.20	25,800	16,700	3.60	2.50	8.50	CX34-31	EL296UH070XE36B	5650669
XP14-030-230	29,800	15.50	13.20	25,600	16,500	3.60	2.52	8.50	CX34-31	EL296UH070XV36B	5562705
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	CX34-31	SL280UH070V36A	5532376
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.62	2.52	8.50	CX34-31	SL280UH070XV36A	8133181
XP14-030-230	30,000	15.70	13.50	25,400	16,400	3.62	2.54	8.50	CX34-31	SL280UH090V36B	5532464

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	CX34-31	SL280UH090V48B	5431513
XP14-030-230	30,200	15.50	13.50	25,800	16,500	3.68	2.54	8.50	CX34-31	SL280UH090XV48B	8133207
XP14-030-230	30,000	15.20	13.20	25,600	16,600	3.62	2.52	8.50	CX34-31	SLP98UH070XV36B	5431634
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	EL180UH070E36B	5742052
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	CX34-36	EL180UH090E48B	5742366
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-36	EL195UH045XE36B	5431602
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-36	EL195UH070XE36B	5431579
XP14-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	CX34-36	EL195UH090XE48C	5431589
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-36	EL296UH045XE36B	5650667
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	CX34-36	EL296UH045XV36B	5562698
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-36	EL296UH070XE36B	5650681
XP14-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	CX34-36	EL296UH070XV36B	5562709
XP14-030-230	29,600	15.20	13.00	25,800	16,600	3.68	2.52	8.70	CX34-36	EL296UH090XE48C	5650671
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	EL296UH090XV36C	5767219
XP14-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	CX34-36	SL280UH070V36A	5532381
XP14-030-230	29,200	15.20	13.00	25,400	16,500	3.60	2.52	8.50	CX34-36	SL280UH070XV36A	8133186
XP14-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	CX34-36	SL280UH090V36B	5532471
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-36	SL280UH090V48B	5431535
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-36	SL280UH090XV48B	8133209
XP14-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-36	SLP98UH070XV36B	5431638
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-36	SLP98UH090XV36C	5431639
XP14-030-230	29,600	15.20	13.20	25,600	16,600	3.66	2.54	8.70	CX34-36	SLP98UH090XV48C	5431640
XP14-030-230	30,800	15.50	13.50	25,800	16,600	3.66	2.54	8.50	CX34-38	EL180UH045E36A	5741767
XP14-030-230	30,800	15.70	13.70	25,600	16,400	3.70	2.54	8.70	CX34-38	EL180UH070E36B	5742051
XP14-030-230	31,000	15.70	13.70	25,600	16,500	3.72	2.58	8.70	CX34-38	EL180UH090E48B	5742369
XP14-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	CX34-38	EL195UH045XE36B	5431603
XP14-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	CX34-38	EL195UH070XE36B	5431580
XP14-030-230	30,800	15.20	13.20	25,800	16,700	3.64	2.54	8.50	CX34-38	EL296UH045XE36B	5650684
XP14-030-230	30,800	15.20	13.20	25,800	16,600	3.64	2.52	8.50	CX34-38	EL296UH045XV36B	5562699
XP14-030-230	30,600	15.50	13.20	25,600	16,500	3.70	2.54	8.50	CX34-38	EL296UH070XE36B	5650676
XP14-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	CX34-38	EL296UH070XV36B	5562710
XP14-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	CX34-38	SL280UH070V36A	5532382
XP14-030-230	30,800	15.70	13.50	25,600	16,500	3.68	2.54	8.70	CX34-38	SL280UH070XV36A	8133187
XP14-030-230	30,800	15.70	13.70	25,400	16,400	3.68	2.56	8.70	CX34-38	SL280UH090V36B	5532476
XP14-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	CX34-38	SL280UH090V48B	5431545
XP14-030-230	31,000	15.70	13.70	25,600	16,600	3.70	2.58	8.70	CX34-38	SL280UH090XV48B	8133210
XP14-030-230	30,600	15.70	13.50	25,600	16,500	3.66	2.54	8.50	CX34-38	SLP98UH070XV36B	5431641
XP14-030-230	30,400	14.00	12.20	26,200	17,200	3.44	2.40	8.20	CX34-38		5431417
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.62	2.52	8.50	CX34-42	EL180UH070E36B	5742055
XP14-030-230	29,200	15.20	13.20	25,400	16,400	3.64	2.52	8.50	CX34-42	EL180UH090E48B	5742370
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-42	EL195UH045XE36B	5431604
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-42	EL195UH070XE36B	5431581

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	29,200	14.70	12.70	25,600	16,600	3.58	2.48	8.50	CX34-42	EL296UH045XE36B	5650679
XP14-030-230	29,000	14.70	12.70	25,600	16,600	3.56	2.48	8.20	CX34-42	EL296UH045XV36B	5562693
XP14-030-230	29,400	15.00	12.70	25,800	16,700	3.60	2.50	8.50	CX34-42	EL296UH070XE36B	5650670
XP14-030-230	29,000	15.20	13.00	25,400	16,400	3.58	2.50	8.50	CX34-42	EL296UH070XV36B	5562716
XP14-030-230	29,200	15.20	13.20	25,400	16,300	3.62	2.52	8.50	CX34-42	SL280UH090V36B	5532472
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-42	SL280UH090V48B	5431551
XP14-030-230	29,400	15.20	13.00	25,600	16,500	3.64	2.52	8.50	CX34-42	SL280UH090XV48B	8133211
XP14-030-230	29,200	15.00	13.00	25,600	16,500	3.60	2.50	8.50	CX34-42	SLP98UH070XV36B	5431642
XP14-030-230	30,400	15.70	13.70	25,600	16,400	3.66	2.54	8.70	CX34-43	EL180UH070E36B	5742053
XP14-030-230	30,600	16.00	13.50	25,800	16,500	3.72	2.56	8.50	CX34-43	EL180UH090E48B	5742374
XP14-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	CX34-43	EL195UH045XE36B	5431605
XP14-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	CX34-43	EL195UH070XE36B	5431582
XP14-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	CX34-43	EL195UH090XE48C	5431590
XP14-030-230	30,400	15.50	13.20	25,800	16,700	3.62	2.52	8.50	CX34-43	EL296UH045XE36B	5650673
XP14-030-230	30,200	15.50	13.20	25,800	16,600	3.62	2.50	8.50	CX34-43	EL296UH045XV36B	5562689
XP14-030-230	30,600	15.50	13.20	26,000	16,700	3.66	2.52	8.50	CX34-43	EL296UH070XE36B	5650642
XP14-030-230	30,200	15.70	13.50	25,600	16,500	3.64	2.54	8.50	CX34-43	EL296UH070XV36B	5562707
XP14-030-230	30,800	15.70	13.50	26,000	16,700	3.70	2.56	8.70	CX34-43	EL296UH090XE48C	5650643
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	CX34-43	EL296UH090XV36C	5562722
XP14-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	CX34-43	EL296UH090XV48C	5562730
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.68	2.56	8.50	CX34-43	SL280UH090V36B	5532477
XP14-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	CX34-43	SL280UH090V48B	5431557
XP14-030-230	30,600	15.70	13.50	25,800	16,600	3.70	2.56	8.70	CX34-43	SL280UH090XV48B	8133212
XP14-030-230	30,400	15.70	13.50	25,800	16,600	3.66	2.54	8.50	CX34-43	SLP98UH070XV36B	5431610
XP14-030-230	30,400	16.00	13.50	25,600	16,400	3.70	2.56	8.50	CX34-43	SLP98UH090XV36C	5431611
XP14-030-230	30,800	16.00	13.50	25,800	16,500	3.76	2.60	8.50	CX34-43	SLP98UH090XV48C	5431612
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	EL180UH070E36B	5742046
XP14-030-230	29,800	15.50	13.20	25,400	16,400	3.58	2.50	8.50	CX34-44/48	EL180UH090E48B	5742372
XP14-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	CX34-44/48	EL195UH045XE36B	5431606
XP14-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	CX34-44/48	EL195UH070XE36B	5431583
XP14-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-44/48	EL195UH090XE48C	5431591
XP14-030-230	29,600	15.00	13.00	25,600	16,600	3.50	2.46	8.20	CX34-44/48	EL296UH045XE36B	5650645
XP14-030-230	29,600	15.00	13.00	25,600	16,500	3.50	2.44	8.20	CX34-44/48	EL296UH045XV36B	5562685
XP14-030-230	30,000	15.00	13.00	25,800	16,600	3.56	2.46	8.20	CX34-44/48	EL296UH070XE36B	5650659
XP14-030-230	29,600	15.20	13.20	25,400	16,400	3.52	2.46	8.20	CX34-44/48	EL296UH070XV36B	5562702
XP14-030-230	30,200	15.20	13.20	25,800	16,600	3.62	2.50	8.50	CX34-44/48	EL296UH090XE48C	5650660
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	EL296UH090XV36C	5562720
XP14-030-230	30,000	15.50	13.20	25,600	16,500	3.60	2.50	8.50	CX34-44/48	EL296UH090XV48C	5562729
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.56	2.48	8.20	CX34-44/48	SL280UH090V36B	5532470
XP14-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	CX34-44/48	SL280UH090V48B	5431451
XP14-030-230	29,800	15.20	13.20	25,600	16,400	3.58	2.48	8.50	CX34-44/48	SL280UH090XV48B	8133201
XP14-030-230	29,600	15.20	13.00	25,600	16,500	3.54	2.48	8.20	CX34-44/48	SLP98UH070XV36B	5431616

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-030-230	29,600	15.50	13.20	25,400	16,300	3.54	2.48	8.20	CX34-44/48	SLP98UH090XV36C	5431635
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL180UH045E36A	5741773
XP14-036-230	34,200	15.70	13.00	32,400	20,400	3.48	2.44	8.50	C33-38	EL180UH070E36B	5742064
XP14-036-230	34,600	15.50	13.00	32,600	20,600	3.52	2.46	8.50	C33-38	EL180UH090E48B	5742386
XP14-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	C33-38	EL195UH045XE36B	5432185
XP14-036-230	34,000	15.20	12.50	32,600	20,800	3.42	2.42	8.20	C33-38	EL195UH070XE36B	5432193
XP14-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	C33-38	EL296UH045XE36B	5650736
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL296UH045XV36B	5562742
XP14-036-230	34,000	15.20	12.50	32,600	20,800	3.42	2.42	8.20	C33-38	EL296UH070XE36B	5650749
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	EL296UH070XV36B	5562750
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	C33-38	SL280UH070V36A	5532383
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	C33-38	SL280UH070XV36A	8133188
XP14-036-230	34,400	15.70	13.00	32,600	20,600	3.50	2.46	8.20	C33-38	SL280UH090V36B	5532479
XP14-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	C33-38	SL280UH090V48B	5431983
XP14-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	C33-38	SL280UH090XV48B	8133214
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	C33-38	SLP98UH070XV36B	5432205
XP14-036-230	35,200	15.70	13.20	32,400	20,200	3.46	2.50	8.50	C33-43	EL180UH070E36B	5742065
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL180UH090E48B	5742385
XP14-036-230	35,600	15.70	13.20	32,600	20,200	3.52	2.50	8.20	C33-43	EL180UH090E60C	5740234
XP14-036-230	35,200	15.70	13.20	32,400	20,200	3.48	2.50	8.50	C33-43	EL180UH110E60C	5740695
XP14-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	C33-43	EL195UH045XE36B	5432186
XP14-036-230	35,000	15.20	12.70	32,600	20,400	3.40	2.44	8.20	C33-43	EL195UH070XE36B	5432194
XP14-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	C33-43	EL195UH090XE48C	5432164
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL195UH110XE60C	5432175
XP14-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	C33-43	EL296UH045XE36B	5650758
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.46	8.20	C33-43	EL296UH045XV36B	5562737
XP14-036-230	35,000	15.20	12.70	32,600	20,400	3.40	2.44	8.20	C33-43	EL296UH070XE36B	5650759
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	C33-43	EL296UH070XV36B	5562747
XP14-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	C33-43	EL296UH090XE48C	5650742
XP14-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	C33-43	EL296UH090XV36C	5562754
XP14-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	EL296UH090XV48C	5562774
XP14-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	C33-43	EL296UH090XV60C	5562777
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	C33-43	EL296UH110XE60C	5650746
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	C33-43	EL296UH110XV48C	5562792
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	C33-43	EL296UH110XV60C	5562801
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SL280UH090V36B	5532482
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SL280UH090V48B	5431993
XP14-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	C33-43	SL280UH090V60C	5431975
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SL280UH090XV48B	8133216
XP14-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	C33-43	SL280UH090XV60C	8133224
XP14-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	C33-43	SL280UH110V60C	5431976
XP14-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	C33-43	SL280UH110XV60C	8133251

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	C33-43	SLP98UH070XV36B	5432207
XP14-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	C33-43	SLP98UH090XV36C	5432201
XP14-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	C33-43	SLP98UH090XV48C	5432202
XP14-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	C33-43	SLP98UH090XV60C	5432203
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	C33-43	SLP98UH110XV60C	5432204
XP14-036-230	33,800	15.50	13.00	32,200	20,400	3.36	2.38	8.20	C33-48	EL180UH070E36B	5742066
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL180UH090E48B	5742383
XP14-036-230	34,200	15.50	13.00	32,400	20,400	3.40	2.38	8.20	C33-48	EL180UH090E60C	5740239
XP14-036-230	34,000	15.50	13.00	32,200	20,400	3.36	2.38	8.20	C33-48	EL180UH110E60C	5740692
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL195UH090XE48C	5432165
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL195UH110XE60C	5432176
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL296UH090XE48C	5650738
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	EL296UH090XV36C	5562755
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	C33-48	EL296UH090XV48C	5562765
XP14-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	C33-48	EL296UH090XV60C	5562788
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	C33-48	EL296UH110XE60C	5650731
XP14-036-230	34,200	15.50	13.00	32,200	20,400	3.38	2.38	8.20	C33-48	EL296UH110XV48C	5562789
XP14-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	C33-48	EL296UH110XV60C	5562802
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.36	2.38	8.20	C33-48	SL280UH090V36B	5532480
XP14-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	C33-48	SL280UH090V48B	5431987
XP14-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	C33-48	SL280UH090V60C	5432151
XP14-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	C33-48	SL280UH090XV48B	8133215
XP14-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	C33-48	SL280UH090XV60C	8133234
XP14-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	C33-48	SL280UH110V60C	5432005
XP14-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	C33-48	SL280UH110XV60C	8133252
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	C33-48	SLP98UH090XV36C	5432208
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	C33-48	SLP98UH090XV48C	5432209
XP14-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	C33-48	SLP98UH090XV60C	5432262
XP14-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	C33-48	SLP98UH110XV60C	5432210
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL180UH090E60C	5740240
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.62	2.50	8.70	C33-49	EL180UH110E60C	5740693
XP14-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	C33-49	EL195UH090XE48C	5432166
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL195UH110XE60C	5432177
XP14-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	C33-49	EL296UH090XE48C	5650768
XP14-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	C33-49	EL296UH090XV36C	5562753
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	C33-49	EL296UH090XV48C	5562767
XP14-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	C33-49	EL296UH090XV60C	5562778
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL296UH110XE60C	5650735
XP14-036-230	35,000	15.70	13.20	31,400	20,200	3.60	2.50	8.70	C33-49	EL296UH110XV48C	5562790
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	EL296UH110XV60C	5562803
XP14-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	C33-49	SL280UH090V60C	5432013
XP14-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	C33-49	SL280UH090XV60C	8133225

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	C33-49	SL280UH110V60C	5432014
XP14-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	C33-49	SL280UH110XV60C	8133253
XP14-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	C33-49	SLP98UH090XV36C	5432211
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	C33-49	SLP98UH090XV48C	5432212
XP14-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	C33-49	SLP98UH090XV60C	5432213
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	C33-49	SLP98UH110XV60C	5432214
XP14-036-230	34,400	14.20	12.00	32,200	21,000	3.40	2.36	8.20	C33-49		5431957
XP14-036-230	34,600	15.50	13.00	31,400	20,200	3.60	2.50	8.70	C33-50/60C	EL180UH090E60C	5740241
XP14-036-230	34,200	15.50	13.00	31,200	20,200	3.56	2.50	8.70	C33-50/60C	EL180UH110E60C	5740694
XP14-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL195UH090XE48C	5432167
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	C33-50/60C	EL195UH110XE60C	5432178
XP14-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL296UH090XE48C	5650745
XP14-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	EL296UH090XV36C	5562756
XP14-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	C33-50/60C	EL296UH090XV48C	5562766
XP14-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	C33-50/60C	EL296UH090XV60C	5562784
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	C33-50/60C	EL296UH110XE60C	5650752
XP14-036-230	34,400	15.50	13.00	31,400	20,200	3.58	2.50	8.70	C33-50/60C	EL296UH110XV48C	5562791
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	C33-50/60C	EL296UH110XV60C	5562804
XP14-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	C33-50/60C	SL280UH090V60C	5432021
XP14-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	C33-50/60C	SL280UH090XV60C	8133226
XP14-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	C33-50/60C	SL280UH110V60C	5432022
XP14-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	C33-50/60C	SL280UH110XV60C	8133254
XP14-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	C33-50/60C	SLP98UH090XV36C	5432215
XP14-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	C33-50/60C	SLP98UH090XV48C	5432216
XP14-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	C33-50/60C	SLP98UH090XV60C	5432263
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	C33-50/60C	SLP98UH110XV60C	5432217
XP14-036-230	33,800	14.00	11.70	32,000	21,000	3.34	2.36	8.20	C33-50/60C		5431958
XP14-036-230	34,600	14.00	12.00	34,600	21,400	3.50	2.44	8.20	CBX25UH-036		6991376
XP14-036-230	34,600	15.00	12.50	34,000	21,000	3.58	2.52	8.50	CBX25UHV-036		7498492
XP14-036-230	34,800	15.20	12.50	32,800	20,400	3.72	2.56	8.70	CBX27UH-036		5432024
XP14-036-230	36,000	16.00	13.50	33,000	17,300	3.98	2.34	8.50	CBX27UH-042		5432025
XP14-036-230	34,600	14.50	11.70	33,400	20,800	3.62	2.48	8.50	CBX32M-036		5432026
XP14-036-230	34,400	14.50	11.70	33,200	20,800	3.60	2.48	8.50	CBX32M-042		5432027
XP14-036-230	34,800	14.70	12.00	33,200	20,800	3.64	2.52	8.70	CBX32MV-036		5432028
XP14-036-230	35,400	15.50	13.00	31,800	20,800	3.76	2.62	9.20	CBX32MV-048		5432029
XP14-036-230	34,800	14.70	12.20	33,200	20,600	3.68	2.52	8.70	CBX40UHV-036		5432048
XP14-036-230	35,200	15.20	12.70	32,000	20,800	3.74	2.58	9.00	CBX40UHV-042		5432049
XP14-036-230	35,400	15.50	13.00	31,800	20,800	3.78	2.62	9.20	CBX40UHV-048		5432050
XP14-036-230	35,200	15.70	13.20	32,000	20,200	3.68	2.54	9.00	CH33-43B	EL180UH070E36B	5742069
XP14-036-230	35,600	15.70	13.20	32,200	20,400	3.72	2.54	9.00	CH33-43B	EL180UH090E48B	5742387
XP14-036-230	35,400	14.70	12.50	32,800	21,000	3.60	2.48	8.50	CH33-43B	EL195UH045XE36B	5432188
XP14-036-230	35,200	15.20	12.70	32,200	20,600	3.62	2.50	8.70	CH33-43B	EL195UH070XE36B	5432159

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,400	14.70	12.50	32,800	21,000	3.60	2.48	8.50	CH33-43B	EL296UH045XE36B	5650756
XP14-036-230	35,400	15.20	12.70	32,600	20,800	3.66	2.50	8.70	CH33-43B	EL296UH045XV36B	5562743
XP14-036-230	35,200	15.20	12.70	32,200	20,600	3.62	2.50	8.70	CH33-43B	EL296UH070XE36B	5650744
XP14-036-230	35,600	15.20	12.70	32,600	20,800	3.66	2.52	8.70	CH33-43B	EL296UH070XV36B	5562752
XP14-036-230	35,600	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-43B	SL280UH090V36B	5532486
XP14-036-230	35,600	15.70	13.20	32,400	20,600	3.72	2.56	9.00	CH33-43B	SL280UH090V48B	5432056
XP14-036-230	35,600	15.70	13.20	32,400	20,600	3.72	2.56	9.00	CH33-43B	SL280UH090XV48B	8133218
XP14-036-230	35,600	15.20	12.70	32,600	20,800	3.66	2.52	8.70	CH33-43B	SLP98UH070XV36B	5432220
XP14-036-230	35,200	14.50	12.20	32,800	21,000	3.52	2.42	8.50	CH33-43B		5431960
XP14-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	EL180UH090E60C	5740235
XP14-036-230	35,200	15.70	13.20	32,400	20,400	3.48	2.46	8.50	CH33-43C	EL180UH110E60C	5740702
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL195UH090XE48C	5432168
XP14-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.46	8.50	CH33-43C	EL195UH110XE60C	5432179
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL296UH090XE48C	5650730
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	EL296UH090XV36C	5562758
XP14-036-230	35,000	15.50	13.20	32,400	20,400	3.46	2.44	8.50	CH33-43C	EL296UH090XV48C	5562768
XP14-036-230	35,600	15.50	13.00	32,800	20,800	3.52	2.48	8.50	CH33-43C	EL296UH090XV60C	5562783
XP14-036-230	35,400	15.70	13.20	32,600	20,600	3.52	2.46	8.50	CH33-43C	EL296UH110XE60C	5650762
XP14-036-230	35,200	15.70	13.20	32,400	20,600	3.48	2.48	8.50	CH33-43C	EL296UH110XV48C	5562799
XP14-036-230	35,600	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	EL296UH110XV60C	5562806
XP14-036-230	35,600	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-43C	SL280UH090V60C	5432064
XP14-036-230	35,600	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-43C	SL280UH090XV60C	8133228
XP14-036-230	35,400	15.10	13.00	32,800	20,600	3.52	2.46	8.20	CH33-43C	SL280UH110V60C	5432065
XP14-036-230	35,400	15.10	13.00	32,800	20,600	3.52	2.46	8.20	CH33-43C	SL280UH110XV60C	8133256
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.48	2.46	8.20	CH33-43C	SLP98UH090XV36C	5432221
XP14-036-230	35,000	15.50	13.20	32,400	20,400	3.46	2.44	8.50	CH33-43C	SLP98UH090XV48C	5432222
XP14-036-230	35,600	15.50	13.00	32,800	20,800	3.52	2.48	8.50	CH33-43C	SLP98UH090XV60C	5432223
XP14-036-230	35,600	15.70	13.20	32,600	20,600	3.52	2.48	8.50	CH33-43C	SLP98UH110XV60C	5432224
XP14-036-230	34,000	15.20	12.70	32,400	20,400	3.38	2.46	8.20	CH33-44/48	EL180UH070E36B	5742071
XP14-036-230	34,200	15.20	12.70	32,800	20,600	3.42	2.48	8.20	CH33-44/48	EL180UH090E48B	5742390
XP14-036-230	34,000	14.70	12.50	32,800	20,800	3.36	2.44	8.20	CH33-44/48	EL195UH070XE36B	5432160
XP14-036-230	34,200	14.50	12.20	33,000	21,000	3.36	2.44	8.20	CH33-44/48	EL296UH045XV36B	5562740
XP14-036-230	34,000	14.70	12.50	32,800	20,800	3.36	2.44	8.20	CH33-44/48	EL296UH070XE36B	5650729
XP14-036-230	34,200	14.70	12.50	33,000	21,000	3.38	2.46	8.20	CH33-44/48	EL296UH070XV36B	5562751
XP14-036-230	34,400	15.20	12.70	32,800	20,600	3.46	2.48	8.20	CH33-44/48	SL280UH090V36B	5532483
XP14-036-230	34,400	15.00	12.70	32,800	20,800	3.42	2.48	8.20	CH33-44/48	SL280UH090V48B	5432071
XP14-036-230	34,400	15.00	12.70	32,800	20,800	3.42	2.48	8.20	CH33-44/48	SL280UH090XV48B	8133219
XP14-036-230	34,200	14.70	12.50	33,000	21,000	3.38	2.46	8.20	CH33-44/48	SLP98UH070XV36B	5432225
XP14-036-230	35,000	15.50	13.00	32,600	20,600	3.46	2.44	8.20	CH33-48	EL296UH090XV36C	5562759
XP14-036-230	34,800	15.50	13.00	32,400	20,400	3.44	2.44	8.50	CH33-48	EL296UH090XV48C	5562769
XP14-036-230	35,400	15.20	13.00	32,800	20,800	3.52	2.46	8.50	CH33-48	EL296UH090XV60C	5562779
XP14-036-230	35,000	15.50	13.20	32,400	20,600	3.46	2.48	8.50	CH33-48	EL296UH110XV48C	5562795

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.52	2.46	8.50	CH33-48	EL296UH110XV60C	5562811
XP14-036-230	35,400	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-48	SL280UH090V60C	5432077
XP14-036-230	35,400	15.10	13.00	32,600	20,600	3.54	2.48	8.20	CH33-48	SL280UH090XV60C	8133229
XP14-036-230	35,200	15.10	12.50	32,600	20,600	3.48	2.44	8.20	CH33-48	SL280UH110V60C	5432078
XP14-036-230	35,200	15.10	12.50	32,600	20,600	3.48	2.44	8.20	CH33-48	SL280UH110XV60C	8133257
XP14-036-230	35,000	15.50	13.00	32,600	20,600	3.46	2.44	8.20	CH33-48	SLP98UH090XV36C	5432226
XP14-036-230	34,800	15.50	13.00	32,400	20,400	3.44	2.44	8.50	CH33-48	SLP98UH090XV48C	5432227
XP14-036-230	35,400	15.20	13.00	32,800	20,800	3.52	2.46	8.50	CH33-48	SLP98UH090XV60C	5432228
XP14-036-230	35,200	15.50	13.20	32,600	20,600	3.52	2.46	8.50	CH33-48	SLP98UH110XV60C	5432229
XP14-036-230	35,200	15.70	13.20	31,800	20,400	3.76	2.58	9.00	CH33-49	EL180UH090E60C	5740244
XP14-036-230	35,000	15.70	13.20	31,600	20,200	3.72	2.56	9.00	CH33-49	EL180UH110E60C	5740697
XP14-036-230	34,800	15.50	13.00	31,800	20,400	3.70	2.56	8.50	CH33-49	EL195UH090XE48C	5432169
XP14-036-230	35,200	15.70	13.20	31,800	20,400	3.74	2.56	9.00	CH33-49	EL195UH110XE60C	5432180
XP14-036-230	34,800	15.50	13.00	31,800	20,400	3.70	2.56	8.50	CH33-49	EL296UH090XE48C	5650734
XP14-036-230	35,000	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-49	EL296UH090XV36C	5562763
XP14-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-49	EL296UH090XV48C	5562772
XP14-036-230	35,400	15.50	13.00	32,400	20,600	3.78	2.56	9.00	CH33-49	EL296UH090XV60C	5562782
XP14-036-230	35,200	15.70	13.20	31,800	20,400	3.74	2.56	9.00	CH33-49	EL296UH110XE60C	5650755
XP14-036-230	35,000	15.70	13.20	32,000	20,400	3.76	2.58	9.00	CH33-49	EL296UH110XV48C	5562793
XP14-036-230	35,400	15.70	13.20	32,200	20,400	3.78	2.58	9.00	CH33-49	EL296UH110XV60C	5562808
XP14-036-230	35,400	15.10	13.00	32,200	20,400	3.80	2.58	9.00	CH33-49	SL280UH090V60C	5432086
XP14-036-230	35,400	15.10	13.00	32,200	20,400	3.80	2.58	9.00	CH33-49	SL280UH090XV60C	8133230
XP14-036-230	35,200	15.10	13.00	32,200	20,600	3.74	2.58	9.00	CH33-49	SL280UH110V60C	5432087
XP14-036-230	35,200	15.10	13.00	32,200	20,600	3.74	2.58	9.00	CH33-49	SL280UH110XV60C	8133258
XP14-036-230	35,000	15.70	13.20	32,200	20,400	3.74	2.56	9.00	CH33-49	SLP98UH090XV36C	5432230
XP14-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-49	SLP98UH090XV48C	5432231
XP14-036-230	35,400	15.50	13.00	32,400	20,600	3.78	2.56	9.00	CH33-49	SLP98UH090XV60C	5432232
XP14-036-230	35,400	15.70	13.20	32,200	20,400	3.78	2.58	9.00	CH33-49	SLP98UH110XV60C	5432233
XP14-036-230	34,400	14.20	12.00	32,800	21,000	3.52	2.42	8.50	CH33-49		5431964
XP14-036-230	35,000	15.70	13.20	31,600	20,400	3.70	2.56	9.00	CH33-50/60C	EL180UH090E60C	5740236
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.66	2.54	9.00	CH33-50/60C	EL180UH110E60C	5740696
XP14-036-230	34,800	15.50	13.00	31,600	20,400	3.66	2.54	9.00	CH33-50/60C	EL195UH090XE48C	5432170
XP14-036-230	35,000	15.70	13.20	31,800	20,400	3.72	2.56	9.00	CH33-50/60C	EL195UH110XE60C	5432181
XP14-036-230	34,800	15.50	13.00	31,600	20,400	3.66	2.54	9.00	CH33-50/60C	EL296UH090XE48C	5650751
XP14-036-230	34,800	15.50	13.00	32,000	20,400	3.70	2.54	9.00	CH33-50/60C	EL296UH090XV36C	5562760
XP14-036-230	34,600	15.70	13.00	31,800	20,400	3.68	2.56	9.00	CH33-50/60C	EL296UH090XV48C	5562770
XP14-036-230	35,400	15.50	13.00	32,400	20,600	3.76	2.56	9.00	CH33-50/60C	EL296UH090XV60C	5562780
XP14-036-230	35,000	15.70	13.20	31,800	20,400	3.72	2.56	9.00	CH33-50/60C	EL296UH110XE60C	5650740
XP14-036-230	34,800	15.70	13.20	32,000	20,400	3.72	2.56	9.00	CH33-50/60C	EL296UH110XV48C	5562796
XP14-036-230	35,200	15.70	13.20	32,200	20,400	3.76	2.56	9.00	CH33-50/60C	EL296UH110XV60C	5562812
XP14-036-230	35,400	15.10	13.00	32,200	20,400	3.78	2.58	9.00	CH33-50/60C	SL280UH090V60C	5432095
XP14-036-230	35,400	15.10	13.00	32,200	20,400	3.78	2.58	9.00	CH33-50/60C	SL280UH090XV60C	8133231

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,000	15.50	12.50	32,200	20,400	3.74	2.54	8.50	CH33-50/60C	SL280UH110V60C	5432096
XP14-036-230	35,000	15.50	12.50	32,200	20,400	3.74	2.54	8.50	CH33-50/60C	SL280UH110XV60C	8133259
XP14-036-230	34,800	15.50	13.00	32,000	20,400	3.70	2.54	9.00	CH33-50/60C	SLP98UH090XV36C	5432234
XP14-036-230	34,600	15.70	13.00	31,800	20,400	3.68	2.56	9.00	CH33-50/60C	SLP98UH090XV48C	5432235
XP14-036-230	35,400	15.50	13.00	32,400	20,600	3.76	2.56	9.00	CH33-50/60C	SLP98UH090XV60C	5432236
XP14-036-230	35,200	15.70	13.20	32,200	20,400	3.76	2.56	9.00	CH33-50/60C	SLP98UH110XV60C	5432237
XP14-036-230	34,200	14.20	12.00	32,600	21,000	3.48	2.40	8.20	CH33-50/60C		5431965
XP14-036-230	35,200	15.70	13.20	33,200	20,800	3.52	2.48	8.50	CR33-48	EL180DF070E36B	5741561
XP14-036-230	35,200	15.50	13.00	33,400	21,000	3.54	2.50	8.50	CR33-48	EL180DF090E48B	5741585
XP14-036-230	35,800	15.70	13.20	33,400	21,000	3.58	2.52	8.70	CR33-48	EL180DF110E60C	5741635
XP14-036-230	34,800	15.00	12.70	33,400	21,200	3.44	2.44	8.20	CR33-48	EL195DF045XE36B	5432156
XP14-036-230	35,200	15.20	13.00	33,400	21,000	3.50	2.46	8.50	CR33-48	EL195DF070XE48B	5432157
XP14-036-230	35,200	15.20	12.70	33,400	21,000	3.48	2.46	8.50	CR33-48	EL195DF090XE48C	5432158
XP14-036-230	35,600	15.50	13.00	33,600	21,000	3.58	2.50	8.50	CR33-48	EL195DF110XE60C	5432183
XP14-036-230	34,800	15.00	12.70	33,400	21,200	3.44	2.44	8.20	CR33-48	EL296DF045XE36B	5650741
XP14-036-230	35,200	15.00	12.70	33,600	21,200	3.46	2.44	8.20	CR33-48	EL296DF045XV36B	5562731
XP14-036-230	35,200	15.20	13.00	33,400	21,000	3.50	2.46	8.50	CR33-48	EL296DF070XE48B	5650737
XP14-036-230	35,200	15.00	12.50	33,800	21,200	3.48	2.42	8.20	CR33-48	EL296DF070XV48B	5562732
XP14-036-230	35,200	15.20	12.70	33,400	21,000	3.48	2.46	8.50	CR33-48	EL296DF090XE48C	5650767
XP14-036-230	35,600	15.50	13.00	33,600	21,000	3.56	2.48	8.50	CR33-48	EL296DF090XV60C	5562733
XP14-036-230	35,600	15.50	13.00	33,600	21,000	3.58	2.50	8.50	CR33-48	EL296DF110XE60C	5650747
XP14-036-230	35,600	15.50	13.00	33,600	21,200	3.56	2.50	8.50	CR33-48	EL296DF110XV60C	5562736
XP14-036-230	35,200	15.50	13.00	33,400	21,000	3.52	2.48	8.50	CR33-48	SL280DF090V48B	5532332
XP14-036-230	35,800	15.70	13.00	33,600	21,000	3.62	2.52	8.50	CR33-48	SL280DF090V60C	5432117
XP14-036-230	35,600	15.10	13.00	33,400	21,000	3.58	2.52	8.50	CR33-48	SL280DF110V60C	5432118
XP14-036-230	35,400	15.20	12.70	33,600	21,200	3.50	2.46	8.50	CR33-48	SLP98DF070XV36B	5432238
XP14-036-230	35,400	15.50	13.00	33,400	21,000	3.52	2.46	8.50	CR33-48	SLP98DF090XV36C	5432243
XP14-036-230	35,400	15.50	13.00	33,400	21,000	3.54	2.48	8.50	CR33-48	SLP98DF090XV48C	5432244
XP14-036-230	35,600	15.50	13.00	33,600	21,000	3.56	2.48	8.50	CR33-48	SLP98DF090XV60C	5432245
XP14-036-230	35,600	15.50	13.00	33,600	21,200	3.56	2.50	8.50	CR33-48	SLP98DF110XV60C	5432246
XP14-036-230	34,800	14.20	12.00	34,000	21,600	3.34	2.36	8.20	CR33-48		5431966
XP14-036-230	36,000	16.00	13.50	32,800	20,400	3.92	2.64	9.00	CR33-50/60	EL180DF110E60C	5741634
XP14-036-230	35,600	15.50	13.20	32,800	20,600	3.80	2.60	8.70	CR33-50/60	EL195DF090XE48C	5432182
XP14-036-230	35,800	15.70	13.20	32,800	20,600	3.88	2.64	9.00	CR33-50/60	EL195DF110XE60C	5432184
XP14-036-230	35,600	15.50	13.20	32,800	20,600	3.80	2.60	8.70	CR33-50/60	EL296DF090XE48C	5650770
XP14-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	EL296DF090XV60C	5562734
XP14-036-230	35,800	15.70	13.20	32,800	20,600	3.88	2.64	9.00	CR33-50/60	EL296DF110XE60C	5650732
XP14-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	EL296DF110XV60C	5562735
XP14-036-230	36,600	15.10	13.00	34,000	21,200	3.82	2.62	9.00	CR33-50/60	SL280DF090V60C	5432122
XP14-036-230	36,400	15.10	13.00	33,800	21,000	3.80	2.60	8.50	CR33-50/60	SL280DF110V60C	5432123
XP14-036-230	36,200	15.70	13.20	33,800	21,200	3.72	2.56	8.70	CR33-50/60	SLP98DF090XV36C	5432247
XP14-036-230	36,200	15.70	13.20	33,800	21,200	3.74	2.58	8.70	CR33-50/60	SLP98DF090XV48C	5432248

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	SLP98DF090XV60C	5432249
XP14-036-230	36,400	15.70	13.20	34,000	21,200	3.76	2.58	9.00	CR33-50/60	SLP98DF110XV60C	5432250
XP14-036-230	35,200	14.20	12.20	33,400	21,200	3.62	2.48	8.50	CR33-50/60		5431968
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL180UH045E36A	5741774
XP14-036-230	34,200	15.70	13.00	32,400	20,400	3.48	2.44	8.50	CX34-38	EL180UH070E36B	5742070
XP14-036-230	34,600	15.50	13.00	32,600	20,600	3.52	2.46	8.50	CX34-38	EL180UH090E48B	5742389
XP14-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	CX34-38	EL195UH045XE36B	5432190
XP14-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	CX34-38	EL195UH070XE36B	5432161
XP14-036-230	33,800	15.00	12.50	32,600	20,600	3.36	2.38	8.20	CX34-38	EL296UH045XE36B	5650771
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL296UH045XV36B	5562744
XP14-036-230	34,000	15.00	12.50	32,600	20,800	3.42	2.42	8.20	CX34-38	EL296UH070XE36B	5650733
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	EL296UH070XV36B	5562749
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	CX34-38	SL280UH070V36A	5532384
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.42	2.40	8.20	CX34-38	SL280UH070XV36A	8133189
XP14-036-230	34,400	15.70	13.00	32,600	20,600	3.50	2.46	8.20	CX34-38	SL280UH090V36B	5532484
XP14-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	CX34-38	SL280UH090V48B	5432131
XP14-036-230	34,400	15.50	13.00	32,600	20,600	3.50	2.44	8.20	CX34-38	SL280UH090XV48B	8133221
XP14-036-230	34,200	15.00	12.50	32,800	20,800	3.44	2.40	8.20	CX34-38	SLP98UH070XV36B	5432251
XP14-036-230	35,200	15.70	13.20	32,400	20,200	3.46	2.50	8.50	CX34-43	EL180UH070E36B	5742067
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL180UH090E48B	5742384
XP14-036-230	35,600	15.70	13.20	32,600	20,200	3.52	2.50	8.20	CX34-43	EL180UH090E60C	5740245
XP14-036-230	35,200	15.70	13.20	32,400	20,200	3.48	2.50	8.50	CX34-43	EL180UH110E60C	5740698
XP14-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	CX34-43	EL195UH045XE36B	5432191
XP14-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	CX34-43	EL195UH070XE36B	5432162
XP14-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	CX34-43	EL195UH090XE48C	5432171
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL195UH110XE60C	5432196
XP14-036-230	34,800	15.00	12.70	32,400	20,400	3.34	2.42	8.20	CX34-43	EL296UH045XE36B	5650753
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.46	8.20	CX34-43	EL296UH045XV36B	5562738
XP14-036-230	35,000	15.00	12.70	32,600	20,400	3.40	2.44	8.20	CX34-43	EL296UH070XE36B	5650750
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	CX34-43	EL296UH070XV36B	5562746
XP14-036-230	35,200	15.50	13.20	32,600	20,400	3.48	2.48	8.20	CX34-43	EL296UH090XE48C	5650761
XP14-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	CX34-43	EL296UH090XV36C	5562762
XP14-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	EL296UH090XV48C	5562771
XP14-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	CX34-43	EL296UH090XV60C	5562781
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.50	8.20	CX34-43	EL296UH110XE60C	5650757
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	CX34-43	EL296UH110XV48C	5562800
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	CX34-43	EL296UH110XV60C	5562807
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.48	2.48	8.50	CX34-43	SL280UH090V36B	5532481
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SL280UH090V48B	5432035
XP14-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	CX34-43	SL280UH090V60C	5432046
XP14-036-230	35,400	15.70	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SL280UH090XV48B	8133217
XP14-036-230	35,800	15.10	13.00	32,600	20,400	3.54	2.52	8.20	CX34-43	SL280UH090XV60C	8133227

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	CX34-43	SL280UH110V60C	5432047
XP14-036-230	35,600	15.10	13.00	32,600	20,400	3.50	2.48	8.20	CX34-43	SL280UH110XV60C	8133255
XP14-036-230	35,200	15.00	12.70	32,800	20,600	3.42	2.44	8.20	CX34-43	SLP98UH070XV36B	5432218
XP14-036-230	35,400	15.50	13.20	32,600	20,400	3.46	2.50	8.20	CX34-43	SLP98UH090XV36C	5432219
XP14-036-230	35,000	15.50	13.20	32,400	20,200	3.46	2.48	8.50	CX34-43	SLP98UH090XV48C	5432239
XP14-036-230	35,800	15.50	13.20	32,800	20,600	3.52	2.50	8.50	CX34-43	SLP98UH090XV60C	5432240
XP14-036-230	35,600	15.70	13.20	32,600	20,400	3.52	2.52	8.50	CX34-43	SLP98UH110XV60C	5432241
XP14-036-230	33,800	15.50	13.00	32,200	20,400	3.36	2.38	8.20	CX34-44/48	EL180UH070E36B	5742068
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL180UH090E48B	5742388
XP14-036-230	34,200	15.50	13.00	32,400	20,400	3.40	2.38	8.20	CX34-44/48	EL180UH090E60C	5740238
XP14-036-230	34,000	15.50	13.00	32,200	20,400	3.36	2.38	8.20	CX34-44/48	EL180UH110E60C	5740699
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL195UH090XE48C	5432172
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL195UH110XE60C	5432197
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL296UH090XE48C	5650743
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	EL296UH090XV36C	5562757
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	CX34-44/48	EL296UH090XV48C	5562775
XP14-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	CX34-44/48	EL296UH090XV60C	5562785
XP14-036-230	34,200	15.50	12.70	32,400	20,600	3.40	2.40	8.20	CX34-44/48	EL296UH110XE60C	5650766
XP14-036-230	34,200	15.50	13.00	32,200	20,400	3.38	2.38	8.20	CX34-44/48	EL296UH110XV48C	5562794
XP14-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	CX34-44/48	EL296UH110XV60C	5562805
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.36	2.38	8.20	CX34-44/48	SL280UH090V36B	5532485
XP14-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	CX34-44/48	SL280UH090V48B	5432109
XP14-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SL280UH090V60C	5432154
XP14-036-230	34,000	15.20	12.70	32,200	20,400	3.36	2.36	8.20	CX34-44/48	SL280UH090XV48B	8133220
XP14-036-230	34,400	15.10	12.50	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SL280UH090XV60C	8133235
XP14-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	CX34-44/48	SL280UH110V60C	5432132
XP14-036-230	34,200	15.10	12.50	32,400	20,600	3.38	2.38	8.20	CX34-44/48	SL280UH110XV60C	8133260
XP14-036-230	34,000	15.20	12.70	32,400	20,600	3.36	2.38	8.20	CX34-44/48	SLP98UH090XV36C	5432252
XP14-036-230	34,000	15.50	12.70	32,200	20,400	3.34	2.36	8.20	CX34-44/48	SLP98UH090XV48C	5432253
XP14-036-230	34,400	15.20	12.70	32,600	20,800	3.42	2.40	8.20	CX34-44/48	SLP98UH090XV60C	5432264
XP14-036-230	34,400	15.50	13.00	32,400	20,600	3.42	2.40	8.20	CX34-44/48	SLP98UH110XV60C	5432254
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL180UH090E60C	5740242
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.62	2.50	8.70	CX34-49	EL180UH110E60C	5740700
XP14-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	CX34-49	EL195UH090XE48C	5432173
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL195UH110XE60C	5432198
XP14-036-230	34,800	15.50	13.00	31,400	20,400	3.58	2.50	8.70	CX34-49	EL296UH090XE48C	5650739
XP14-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	CX34-49	EL296UH090XV36C	5562761
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	CX34-49	EL296UH090XV48C	5562776
XP14-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	CX34-49	EL296UH090XV60C	5562786
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL296UH110XE60C	5650772
XP14-036-230	35,000	15.70	13.20	31,400	20,200	3.60	2.50	8.70	CX34-49	EL296UH110XV48C	5562797
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	EL296UH110XV60C	5562809

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	CX34-49	SL280UH090V60C	5432140
XP14-036-230	35,400	15.10	13.00	31,600	20,400	3.66	2.52	8.50	CX34-49	SL280UH090XV60C	8133232
XP14-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	CX34-49	SL280UH110V60C	5432141
XP14-036-230	35,200	15.10	13.00	31,600	20,400	3.62	2.50	8.50	CX34-49	SL280UH110XV60C	8133261
XP14-036-230	35,000	15.50	13.20	31,600	20,400	3.60	2.50	8.70	CX34-49	SLP98UH090XV36C	5432255
XP14-036-230	34,800	15.70	13.20	31,400	20,200	3.58	2.48	8.70	CX34-49	SLP98UH090XV48C	5432256
XP14-036-230	35,400	15.50	13.00	31,800	20,600	3.64	2.52	8.70	CX34-49	SLP98UH090XV60C	5432257
XP14-036-230	35,200	15.70	13.20	31,600	20,400	3.64	2.52	8.70	CX34-49	SLP98UH110XV60C	5432258
XP14-036-230	34,400	14.20	12.00	32,200	21,000	3.40	2.36	8.20	CX34-49		5431971
XP14-036-230	34,600	15.50	13.00	31,400	20,200	3.60	2.50	8.70	CX34-50/60C	EL180UH090E60C	5740243
XP14-036-230	34,200	15.50	13.00	31,200	20,200	3.56	2.50	8.70	CX34-50/60C	EL180UH110E60C	5740701
XP14-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL195UH090XE48C	5432174
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	CX34-50/60C	EL195UH110XE60C	5432199
XP14-036-230	34,200	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL296UH090XE48C	5650769
XP14-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	EL296UH090XV36C	5562764
XP14-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	CX34-50/60C	EL296UH090XV48C	5562773
XP14-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	CX34-50/60C	EL296UH090XV60C	5562787
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.60	2.50	8.70	CX34-50/60C	EL296UH110XE60C	5650754
XP14-036-230	34,400	15.50	13.00	31,400	20,200	3.58	2.50	8.70	CX34-50/60C	EL296UH110XV48C	5562798
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	CX34-50/60C	EL296UH110XV60C	5562810
XP14-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	CX34-50/60C	SL280UH090V60C	5432148
XP14-036-230	34,800	15.10	12.50	31,600	20,400	3.64	2.52	8.50	CX34-50/60C	SL280UH090XV60C	8133233
XP14-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	CX34-50/60C	SL280UH110V60C	5432149
XP14-036-230	34,600	15.10	12.50	31,600	20,400	3.58	2.50	8.50	CX34-50/60C	SL280UH110XV60C	8133262
XP14-036-230	34,400	15.20	12.70	31,400	20,400	3.56	2.50	8.70	CX34-50/60C	SLP98UH090XV36C	5432259
XP14-036-230	34,200	15.20	13.00	31,200	20,200	3.54	2.48	8.70	CX34-50/60C	SLP98UH090XV48C	5432260
XP14-036-230	34,800	15.20	12.70	31,800	20,600	3.60	2.50	8.70	CX34-50/60C	SLP98UH090XV60C	5432265
XP14-036-230	34,600	15.50	13.00	31,600	20,400	3.62	2.52	8.70	CX34-50/60C	SLP98UH110XV60C	5432261
XP14-036-230	33,800	14.00	11.70	32,000	21,000	3.34	2.36	8.20	CX34-50/60C		5431972
XP14-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	C33-49	EL180UH090E60C	5740246
XP14-042-230	44,000	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	EL180UH110E60C	5740704
XP14-042-230	42,000	14.70	12.70	41,000	26,000	3.66	2.58	9.00	C33-49	EL195UH090XE48C	5432423
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	9.00	C33-49	EL195UH110XE60C	5432434
XP14-042-230	42,000	14.70	12.70	41,000	26,000	3.66	2.58	9.00	C33-49	EL296UH090XE48C	5650773
XP14-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	C33-49	EL296UH090XV36C	5562819
XP14-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	EL296UH090XV48C	5562831
XP14-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	C33-49	EL296UH090XV60C	5562841
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	9.00	C33-49	EL296UH110XE60C	5650798
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	EL296UH110XV48C	5562851
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	EL296UH110XV60C	5562866
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	C33-49	SL280UH090V60C	5432301
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	C33-49	SL280UH090XV60C	8133236

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	C33-49	SL280UH110V60C	5432302
XP14-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	C33-49	SL280UH110XV60C	8133263
XP14-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	C33-49	SLP98UH090XV36C	5432467
XP14-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	C33-49	SLP98UH090XV48C	5432468
XP14-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	C33-49	SLP98UH090XV60C	5432469
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	C33-49	SLP98UH110XV60C	5432470
XP14-042-230	43,500	14.50	12.20	42,000	27,400	3.42	2.40	8.20	C33-49		5432267
XP14-042-230	41,000	14.50	12.20	41,000	26,000	3.58	2.54	8.70	C33-50/60C	EL195UH090XE48C	5432424
XP14-042-230	42,000	14.50	12.50	41,500	26,200	3.66	2.56	8.70	C33-50/60C	EL195UH110XE60C	5432435
XP14-042-230	41,000	14.50	12.20	41,000	26,000	3.58	2.54	8.70	C33-50/60C	EL296UH090XE48C	5650781
XP14-042-230	42,000	14.50	12.50	41,500	26,200	3.66	2.56	8.70	C33-50/60C	EL296UH110XE60C	5650786
XP14-042-230	44,000	15.70	13.20	42,000	26,800	3.66	2.54	8.70	C33-50/60C	EL296UH135XV60D	5562869
XP14-042-230	42,500	15.00	12.70	41,500	26,200	3.82	2.66	9.20	C33-60D	EL180UH135E60D	5741086
XP14-042-230	44,000	15.20	13.00	42,000	27,000	3.60	2.50	8.70	C33-60D	EL195UH135XE60D	5432445
XP14-042-230	44,000	15.20	13.00	42,000	27,000	3.60	2.50	8.70	C33-60D	EL296UH135XE60D	5650796
XP14-042-230	44,000	15.70	13.50	41,500	26,600	3.64	2.54	8.70	C33-60D	SL280UH135V60D	5432313
XP14-042-230	44,000	15.70	13.20	41,500	26,800	3.64	2.56	8.70	C33-60D	SLP98UH135XV60D	5432475
XP14-042-230	43,000	14.50	12.20	42,500	27,400	3.46	2.42	8.20	C33-60D		5432269
XP14-042-230	43,000	15.20	13.00	41,500	26,400	3.92	2.74	9.50	C33-62C	EL180UH090E60C	5740250
XP14-042-230	43,000	15.20	13.00	41,500	26,400	3.90	2.74	9.50	C33-62C	EL180UH110E60C	5740709
XP14-042-230	43,500	15.50	13.00	42,500	27,000	3.56	2.58	8.70	C33-62C	EL195UH090XE48C	5432425
XP14-042-230	44,000	15.50	13.00	43,000	27,200	3.64	2.60	8.70	C33-62C	EL195UH110XE60C	5432436
XP14-042-230	43,500	15.50	13.00	42,500	27,000	3.56	2.58	8.70	C33-62C	EL296UH090XE48C	5650789
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	C33-62C	EL296UH090XV36C	5562828
XP14-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	C33-62C	EL296UH090XV48C	5562829
XP14-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	C33-62C	EL296UH090XV60C	5562840
XP14-042-230	44,000	15.50	13.00	43,000	27,200	3.64	2.60	8.70	C33-62C	EL296UH110XE60C	5650802
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	C33-62C	EL296UH110XV48C	5562850
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	C33-62C	EL296UH110XV60C	5562861
XP14-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	C33-62C	SL280UH090V60C	5432319
XP14-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	C33-62C	SL280UH090XV60C	8133237
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	C33-62C	SL280UH110V60C	5432320
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	C33-62C	SL280UH110XV60C	8133264
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	C33-62C	SLP98UH090XV36C	5432453
XP14-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	C33-62C	SLP98UH090XV48C	5432454
XP14-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	C33-62C	SLP98UH090XV60C	5432455
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	C33-62C	SLP98UH110XV60C	5432456
XP14-042-230	43,000	14.70	12.20	43,000	27,600	3.44	2.50	8.50	C33-62C		5432270
XP14-042-230	43,000	15.20	13.00	41,500	26,200	3.84	2.68	9.20	C33-62D	EL180UH135E60D	5741083
XP14-042-230	43,500	15.00	13.00	42,000	27,000	3.64	2.50	8.70	C33-62D	EL195UH135XE60D	5432446
XP14-042-230	43,500	15.00	13.00	42,000	27,000	3.64	2.50	8.70	C33-62D	EL296UH135XE60D	5650777
XP14-042-230	43,500	15.50	13.00	42,000	27,000	3.72	2.56	8.70	C33-62D	EL296UH135XV60D	5562870

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	43,500	15.70	13.20	41,500	26,800	3.70	2.56	8.70	C33-62D	SL280UH135V60D	5432322
XP14-042-230	43,500	15.50	13.20	41,500	26,800	3.70	2.56	8.70	C33-62D	SLP98UH135XV60D	5432457
XP14-042-230	43,000	14.20	12.20	42,500	27,600	3.52	2.44	8.50	C33-62D		5432271
XP14-042-230	42,500	14.00	12.00	45,500	28,200	3.66	2.58	8.20	CBX25UH-042		5727006
XP14-042-230	42,000	15.50	13.00	44,500	27,400	3.86	2.68	8.50	CBX25UHV-042		6970219
XP14-042-230	43,500	15.50	13.00	43,500	27,400	3.70	2.62	9.00	CBX27UH-042		5432324
XP14-042-230	43,000	15.00	12.50	43,000	27,200	3.68	2.62	8.50	CBX27UH-048		5491435
XP14-042-230	43,000	14.50	12.50	44,000	27,800	3.58	2.54	8.70	CBX32M-048		5432325
XP14-042-230	43,500	15.50	13.00	43,500	27,400	3.68	2.62	8.70	CBX32MV-048		5432326
XP14-042-230	43,000	15.20	12.70	43,500	27,400	3.64	2.60	8.70	CBX40UHV-042		5432327
XP14-042-230	43,500	15.50	13.00	43,500	27,400	3.68	2.62	8.70	CBX40UHV-048		5432328
XP14-042-230	44,000	15.70	13.20	42,500	27,400	3.90	2.68	9.20	CH23-68	EL180UH090E60C	5740255
XP14-042-230	44,000	15.50	13.20	42,500	27,400	3.90	2.66	9.20	CH23-68	EL180UH110E60C	5740703
XP14-042-230	44,000	15.70	13.20	42,500	27,400	3.92	2.68	9.20	CH23-68	EL180UH135E60D	5741082
XP14-042-230	43,500	15.20	13.00	42,500	27,400	3.84	2.64	9.20	CH23-68	EL195UH090XE48C	5432426
XP14-042-230	44,000	15.20	13.00	42,500	27,600	3.88	2.66	9.20	CH23-68	EL195UH110XE60C	5432437
XP14-042-230	44,000	15.20	13.00	42,500	27,600	3.86	2.64	9.20	CH23-68	EL195UH135XE60D	5432447
XP14-042-230	43,500	15.20	13.00	42,500	27,400	3.84	2.64	9.20	CH23-68	EL296UH090XE48C	5650797
XP14-042-230	44,000	15.20	13.00	42,500	27,600	3.88	2.66	9.20	CH23-68	EL296UH110XE60C	5650795
XP14-042-230	44,000	15.20	13.00	42,500	27,600	3.86	2.64	9.20	CH23-68	EL296UH135XE60D	5650780
XP14-042-230	44,000	15.70	13.20	42,500	27,400	3.94	2.70	9.50	CH23-68	EL296UH135XV60D	5562871
XP14-042-230	44,000	16.00	13.00	42,500	27,200	3.98	2.70	9.50	CH23-68	SL280UH135V60D	5432333
XP14-042-230	44,000	15.70	13.20	42,500	27,400	3.96	2.72	9.50	CH23-68	SLP98UH135XV60D	5432458
XP14-042-230	43,500	14.50	12.20	43,000	28,000	3.72	2.56	9.00	CH23-68		5432272
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.56	2.52	8.70	CH33-43B	EL180UH090E48B	5742391
XP14-042-230	43,500	14.70	12.70	42,500	27,400	3.48	2.50	8.50	CH33-43B	EL296UH045XV36B	5562816
XP14-042-230	43,500	14.70	12.50	42,500	27,400	3.48	2.48	8.50	CH33-43B	EL296UH070XV36B	5562818
XP14-042-230	44,000	15.50	13.00	42,500	27,200	3.60	2.56	8.70	CH33-43B	SL280UH090V36B	5532488
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.60	2.54	8.70	CH33-43B	SL280UH090V48B	5432288
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.60	2.54	8.70	CH33-43B	SL280UH090XV48B	8133222
XP14-042-230	43,500	14.70	12.50	42,500	27,400	3.48	2.48	8.50	CH33-43B	SLP98UH070XV36B	5432466
XP14-042-230	43,500	14.50	12.20	43,000	27,600	3.48	2.46	8.50	CH33-43B		5432266
XP14-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.48	8.20	CH33-43C	EL180UH090E60C	5740248
XP14-042-230	43,000	15.20	13.00	42,000	26,800	3.40	2.48	8.20	CH33-43C	EL180UH110E60C	5740712
XP14-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-43C	EL195UH090XE48C	5432427
XP14-042-230	43,000	15.00	12.70	42,500	27,000	3.44	2.48	8.20	CH33-43C	EL195UH110XE60C	5432438
XP14-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-43C	EL296UH090XE48C	5650785
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.40	2.46	8.20	CH33-43C	EL296UH090XV36C	5562820
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	EL296UH090XV48C	5562836
XP14-042-230	43,000	15.20	12.70	42,500	27,000	3.44	2.50	8.20	CH33-43C	EL296UH090XV60C	5562839
XP14-042-230	43,000	15.00	12.70	42,500	27,000	3.44	2.48	8.20	CH33-43C	EL296UH110XE60C	5650776
XP14-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.48	8.20	CH33-43C	EL296UH110XV48C	5562849

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.50	8.20	CH33-43C	EL296UH110XV60C	5562860
XP14-042-230	43,000	15.50	13.00	42,500	26,800	3.50	2.52	8.50	CH33-43C	SL280UH090V60C	5432339
XP14-042-230	43,000	15.50	13.00	42,500	26,800	3.50	2.52	8.50	CH33-43C	SL280UH090XV60C	8133238
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SL280UH110V60C	5432340
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SL280UH110XV60C	8133265
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.40	2.46	8.20	CH33-43C	SLP98UH090XV36C	5432459
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.48	8.20	CH33-43C	SLP98UH090XV48C	5432460
XP14-042-230	43,000	15.20	12.70	42,500	27,000	3.44	2.50	8.20	CH33-43C	SLP98UH090XV60C	5432461
XP14-042-230	43,000	15.20	13.00	42,500	26,800	3.44	2.50	8.20	CH33-43C	SLP98UH110XV60C	5432462
XP14-042-230	42,000	14.70	12.50	42,500	27,000	3.46	2.48	8.50	CH33-44/48	EL180UH090E48B	5742392
XP14-042-230	41,500	14.20	12.20	42,500	27,200	3.38	2.46	8.20	CH33-44/48	EL296UH045XV36B	5562815
XP14-042-230	41,500	14.20	12.20	42,500	27,200	3.36	2.46	8.20	CH33-44/48	EL296UH070XV36B	5562817
XP14-042-230	42,000	14.70	12.70	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090V36B	5532487
XP14-042-230	42,000	14.70	12.50	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090V48B	5432345
XP14-042-230	42,000	14.70	12.50	42,500	27,000	3.48	2.52	8.50	CH33-44/48	SL280UH090XV48B	8133223
XP14-042-230	41,500	14.20	12.20	42,500	27,200	3.36	2.46	8.20	CH33-44/48	SLP98UH070XV36B	5432465
XP14-042-230	41,500	14.00	11.70	43,000	27,600	3.36	2.44	8.20	CH33-44/48		5432276
XP14-042-230	42,500	15.00	12.70	42,000	26,800	3.34	2.44	8.20	CH33-48C	EL180UH090E60C	5740256
XP14-042-230	42,000	15.00	12.70	42,000	26,800	3.32	2.44	8.20	CH33-48C	EL180UH110E60C	5740710
XP14-042-230	42,000	14.70	12.50	42,000	26,800	3.28	2.42	8.20	CH33-48C	EL195UH090XE48C	5432428
XP14-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.44	8.20	CH33-48C	EL195UH110XE60C	5432439
XP14-042-230	42,000	14.70	12.50	42,000	26,800	3.28	2.42	8.20	CH33-48C	EL296UH090XE48C	5650801
XP14-042-230	42,000	14.70	12.50	42,500	26,800	3.34	2.42	8.20	CH33-48C	EL296UH090XV36C	5562822
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	EL296UH090XV48C	5562832
XP14-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.46	8.20	CH33-48C	EL296UH090XV60C	5562844
XP14-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.44	8.20	CH33-48C	EL296UH110XE60C	5650779
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.40	2.44	8.20	CH33-48C	EL296UH110XV48C	5562856
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	EL296UH110XV60C	5562863
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.46	8.20	CH33-48C	SL280UH090V60C	5432358
XP14-042-230	42,500	15.20	12.70	42,500	26,800	3.42	2.46	8.20	CH33-48C	SL280UH090XV60C	8133239
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	SL280UH110V60C	5432359
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	SL280UH110XV60C	8133266
XP14-042-230	42,000	14.70	12.50	42,500	26,800	3.34	2.42	8.20	CH33-48C	SLP98UH090XV36C	5432476
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	SLP98UH090XV48C	5432477
XP14-042-230	42,500	14.70	12.50	42,500	27,000	3.38	2.46	8.20	CH33-48C	SLP98UH090XV60C	5432478
XP14-042-230	42,500	15.00	12.70	42,500	26,800	3.38	2.44	8.20	CH33-48C	SLP98UH110XV60C	5432479
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	EL180UH090E60C	5740251
XP14-042-230	43,000	15.20	13.00	42,000	26,800	3.60	2.50	8.70	CH33-49	EL180UH110E60C	5740706
XP14-042-230	43,000	15.00	12.70	42,000	26,800	3.56	2.48	8.50	CH33-49	EL195UH090XE48C	5432429
XP14-042-230	43,500	15.20	12.70	42,500	27,000	3.64	2.50	8.70	CH33-49	EL195UH110XE60C	5432440
XP14-042-230	43,000	15.00	12.70	42,000	26,800	3.56	2.48	8.50	CH33-49	EL296UH090XE48C	5650794
XP14-042-230	43,500	15.20	13.00	42,000	27,000	3.58	2.52	8.70	CH33-49	EL296UH090XV36C	5562824

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	EL296UH090XV48C	5562834
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.66	2.56	8.70	CH33-49	EL296UH090XV60C	5562847
XP14-042-230	43,500	15.20	12.70	42,500	27,000	3.64	2.50	8.70	CH33-49	EL296UH110XE60C	5650783
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	EL296UH110XV48C	5562853
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	EL296UH110XV60C	5562867
XP14-042-230	44,000	15.50	13.20	42,000	27,000	3.66	2.56	8.70	CH33-49	SL280UH090V60C	5432367
XP14-042-230	44,000	15.50	13.20	42,000	27,000	3.66	2.56	8.70	CH33-49	SL280UH090XV60C	8133240
XP14-042-230	43,500	15.20	13.00	42,000	27,000	3.62	2.54	8.70	CH33-49	SL280UH110V60C	5432368
XP14-042-230	43,500	15.20	13.00	42,000	27,000	3.62	2.54	8.70	CH33-49	SL280UH110XV60C	8133267
XP14-042-230	43,500	15.20	13.00	42,000	27,000	3.58	2.52	8.70	CH33-49	SLP98UH090XV36C	5432480
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.62	2.52	8.70	CH33-49	SLP98UH090XV48C	5432481
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.66	2.56	8.70	CH33-49	SLP98UH090XV60C	5432482
XP14-042-230	43,500	15.20	13.00	42,000	26,800	3.64	2.52	8.70	CH33-49	SLP98UH110XV60C	5432483
XP14-042-230	43,000	14.20	12.20	42,500	27,400	3.50	2.44	8.50	CH33-49		5432278
XP14-042-230	43,000	15.20	12.70	42,000	26,800	3.60	2.50	8.70	CH33-50/60C	EL180UH090E60C	5740249
XP14-042-230	43,000	15.20	13.00	42,000	26,800	3.58	2.50	8.50	CH33-50/60C	EL180UH110E60C	5740708
XP14-042-230	43,000	15.00	12.70	42,000	26,800	3.54	2.48	8.50	CH33-50/60C	EL195UH090XE48C	5432430
XP14-042-230	43,500	15.00	12.70	42,000	27,000	3.58	2.50	8.50	CH33-50/60C	EL195UH110XE60C	5432441
XP14-042-230	43,000	15.00	12.70	42,000	26,800	3.54	2.48	8.50	CH33-50/60C	EL296UH090XE48C	5650775
XP14-042-230	43,000	15.20	12.70	42,500	27,200	3.50	2.48	8.50	CH33-50/60C	EL296UH090XV36C	5562827
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	EL296UH090XV48C	5562837
XP14-042-230	43,500	15.20	12.70	42,500	27,400	3.54	2.52	8.50	CH33-50/60C	EL296UH090XV60C	5562843
XP14-042-230	43,500	15.00	12.70	42,000	27,000	3.58	2.50	8.50	CH33-50/60C	EL296UH110XE60C	5650791
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	EL296UH110XV48C	5562858
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	EL296UH110XV60C	5562865
XP14-042-230	43,500	15.50	13.00	42,500	27,200	3.58	2.54	8.70	CH33-50/60C	SL280UH090V60C	5432376
XP14-042-230	43,500	15.50	13.00	42,500	27,200	3.58	2.54	8.70	CH33-50/60C	SL280UH090XV60C	8133241
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SL280UH110V60C	5432377
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SL280UH110XV60C	8133268
XP14-042-230	43,000	15.20	12.70	42,500	27,200	3.50	2.48	8.50	CH33-50/60C	SLP98UH090XV36C	5432484
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.52	2.50	8.50	CH33-50/60C	SLP98UH090XV48C	5432485
XP14-042-230	43,500	15.20	12.70	42,500	27,400	3.54	2.52	8.50	CH33-50/60C	SLP98UH090XV60C	5432486
XP14-042-230	43,500	15.20	13.00	42,500	27,200	3.54	2.50	8.50	CH33-50/60C	SLP98UH110XV60C	5432487
XP14-042-230	43,000	14.20	12.20	43,000	27,800	3.40	2.42	8.20	CH33-50/60C		5432279
XP14-042-230	44,500	15.70	13.20	42,500	27,000	3.56	2.52	8.50	CH33-60D	EL180UH135E60D	5741084
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.50	2.50	8.50	CH33-60D	EL195UH135XE60D	5432448
XP14-042-230	44,000	15.20	13.00	42,500	27,200	3.50	2.50	8.50	CH33-60D	EL296UH135XE60D	5650784
XP14-042-230	44,500	15.70	13.20	42,500	27,000	3.58	2.54	8.70	CH33-60D	EL296UH135XV60D	5562875
XP14-042-230	44,000	16.00	13.00	42,000	26,800	3.54	2.54	8.50	CH33-60D	SL280UH135V60D	5432348
XP14-042-230	44,000	15.70	13.20	42,500	26,800	3.58	2.52	8.70	CH33-60D	SLP98UH135XV60D	5432463
XP14-042-230	43,500	14.50	12.20	43,000	27,600	3.36	2.42	8.20	CH33-60D		5432274
XP14-042-230	42,500	15.00	12.70	41,500	26,200	3.78	2.66	9.20	CH33-62D	EL180UH135E60D	5741085

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.72	2.62	8.70	CH33-62D	EL195UH135XE60D	5432449
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.72	2.62	8.70	CH33-62D	EL296UH135XE60D	5650792
XP14-042-230	43,500	15.50	13.00	42,000	26,800	3.64	2.54	8.70	CH33-62D	EL296UH135XV60D	5562874
XP14-042-230	43,500	15.70	13.20	41,500	26,600	3.60	2.54	8.70	CH33-62D	SL280UH135V60D	5432350
XP14-042-230	43,500	15.70	13.20	42,000	26,800	3.64	2.54	8.70	CH33-62D	SLP98UH135XV60D	5432464
XP14-042-230	43,000	14.20	12.20	42,500	27,400	3.42	2.40	8.20	CH33-62D		5432275
XP14-042-230	44,500	15.50	13.20	43,000	27,000	3.76	2.62	9.00	CR33-50/60	EL180DF110E60C	5741636
XP14-042-230	44,000	15.20	13.00	43,000	27,200	3.68	2.60	8.70	CR33-50/60	EL195DF090XE48C	5432421
XP14-042-230	44,500	15.20	13.00	43,500	27,200	3.78	2.62	9.00	CR33-50/60	EL195DF110XE60C	5432422
XP14-042-230	44,000	15.20	13.00	43,000	27,200	3.68	2.60	8.70	CR33-50/60	EL296DF090XE48C	5650793
XP14-042-230	44,500	15.20	13.00	43,500	27,200	3.76	2.62	9.00	CR33-50/60	EL296DF090XV60C	5562813
XP14-042-230	44,500	15.20	13.00	43,500	27,200	3.78	2.62	9.00	CR33-50/60	EL296DF110XE60C	5650774
XP14-042-230	44,500	15.50	13.20	43,000	27,200	3.76	2.64	9.00	CR33-50/60	EL296DF110XV60C	5562814
XP14-042-230	44,000	15.70	13.20	43,000	27,000	3.76	2.64	9.00	CR33-50/60	SL280DF090V60C	5432381
XP14-042-230	44,500	15.70	13.20	43,000	27,000	3.78	2.66	9.00	CR33-50/60	SL280DF110V60C	5432382
XP14-042-230	44,000	15.20	13.00	43,000	27,200	3.70	2.62	9.00	CR33-50/60	SLP98DF090XV36C	5432488
XP14-042-230	44,500	15.20	13.00	43,000	27,200	3.72	2.62	9.00	CR33-50/60	SLP98DF090XV48C	5432489
XP14-042-230	44,500	15.20	13.00	43,500	27,200	3.76	2.62	9.00	CR33-50/60	SLP98DF090XV60C	5432490
XP14-042-230	44,500	15.50	13.20	43,000	27,200	3.76	2.64	9.00	CR33-50/60	SLP98DF110XV60C	5432491
XP14-042-230	43,500	14.20	12.20	43,500	27,800	3.56	2.54	8.70	CR33-50/60		5432280
XP14-042-230	43,500	14.20	12.20	43,500	27,800	3.56	2.54	8.70	CR33-60		5432281
XP14-042-230	44,000	15.50	13.20	41,500	26,600	3.60	2.48	8.50	CX34-49	EL180UH090E60C	5740257
XP14-042-230	44,000	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	EL180UH110E60C	5740711
XP14-042-230	43,500	15.20	13.00	41,500	26,600	3.54	2.44	8.50	CX34-49	EL195UH090XE48C	5432431
XP14-042-230	44,000	15.20	13.00	42,000	27,000	3.62	2.48	8.50	CX34-49	EL195UH110XE60C	5432442
XP14-042-230	43,500	15.20	13.00	41,500	26,600	3.54	2.44	8.50	CX34-49	EL296UH090XE48C	5650778
XP14-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	CX34-49	EL296UH090XV36C	5562823
XP14-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	EL296UH090XV48C	5562833
XP14-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	CX34-49	EL296UH090XV60C	5562845
XP14-042-230	44,000	15.20	13.00	42,000	27,000	3.62	2.48	8.50	CX34-49	EL296UH110XE60C	5650799
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	EL296UH110XV48C	5562857
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	EL296UH110XV60C	5562864
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	CX34-49	SL280UH090V60C	5432390
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.64	2.52	8.70	CX34-49	SL280UH090XV60C	8133242
XP14-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	CX34-49	SL280UH110V60C	5432391
XP14-042-230	44,000	15.50	13.20	41,500	26,800	3.58	2.48	8.50	CX34-49	SL280UH110XV60C	8133269
XP14-042-230	43,500	15.50	13.00	41,500	26,600	3.56	2.46	8.50	CX34-49	SLP98UH090XV36C	5432492
XP14-042-230	43,500	15.50	13.20	41,500	26,600	3.58	2.48	8.50	CX34-49	SLP98UH090XV48C	5432493
XP14-042-230	44,000	15.50	13.00	42,000	26,800	3.64	2.48	8.70	CX34-49	SLP98UH090XV60C	5432494
XP14-042-230	44,000	15.70	13.20	41,500	26,600	3.60	2.48	8.70	CX34-49	SLP98UH110XV60C	5432495
XP14-042-230	43,500	14.50	12.20	42,000	27,400	3.42	2.40	8.20	CX34-49		5432282
XP14-042-230	42,500	15.00	12.70	41,500	26,200	3.82	2.66	9.20	CX34-60D	EL180UH135E60D	5741087

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	8.70	CX34-60D	EL195UH135XE60D	5432450
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.74	2.62	8.70	CX34-60D	EL296UH135XE60D	5650800
XP14-042-230	44,000	15.70	13.20	42,000	26,800	3.66	2.54	8.70	CX34-60D	EL296UH135XV60D	5562873
XP14-042-230	44,000	15.70	13.50	41,500	26,600	3.64	2.54	8.70	CX34-60D	SL280UH135V60D	5432402
XP14-042-230	44,000	15.70	13.20	41,500	26,800	3.64	2.56	8.70	CX34-60D	SLP98UH135XV60D	5432500
XP14-042-230	43,000	14.50	12.20	42,500	27,400	3.46	2.42	8.20	CX34-60D		5432284
XP14-042-230	43,000	15.20	13.00	41,500	26,400	3.92	2.74	9.50	CX34-62C	EL180UH090E60C	5740254
XP14-042-230	43,000	15.20	13.00	41,500	26,400	3.90	2.74	9.50	CX34-62C	EL180UH110E60C	5740713
XP14-042-230	43,000	15.00	13.00	41,500	26,400	3.86	2.70	8.70	CX34-62C	EL195UH090XE48C	5432433
XP14-042-230	43,500	15.20	13.00	42,000	26,600	3.94	2.72	8.70	CX34-62C	EL195UH110XE60C	5432444
XP14-042-230	43,000	15.00	13.00	41,500	26,400	3.86	2.70	8.70	CX34-62C	EL296UH090XE48C	5650790
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	CX34-62C	EL296UH090XV36C	5562826
XP14-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	CX34-62C	EL296UH090XV48C	5562838
XP14-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	CX34-62C	EL296UH090XV60C	5562846
XP14-042-230	43,500	15.20	13.00	42,000	26,600	3.94	2.72	8.70	CX34-62C	EL296UH110XE60C	5650803
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.62	8.70	CX34-62C	EL296UH110XV48C	5562852
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	CX34-62C	EL296UH110XV60C	5562862
XP14-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	CX34-62C	SL280UH090V60C	5432408
XP14-042-230	44,000	16.00	13.00	42,500	26,800	3.68	2.64	8.50	CX34-62C	SL280UH090XV60C	8133243
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	CX34-62C	SL280UH110V60C	5432410
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.60	2.60	8.70	CX34-62C	SL280UH110XV60C	8133270
XP14-042-230	43,500	15.70	13.00	42,500	27,000	3.56	2.60	8.70	CX34-62C	SLP98UH090XV36C	5432502
XP14-042-230	43,500	15.70	13.20	42,500	27,000	3.60	2.62	8.70	CX34-62C	SLP98UH090XV48C	5432503
XP14-042-230	44,000	15.70	13.00	42,500	27,200	3.62	2.62	8.70	CX34-62C	SLP98UH090XV60C	5432504
XP14-042-230	44,000	15.70	13.20	42,500	27,000	3.62	2.64	8.70	CX34-62C	SLP98UH110XV60C	5432505
XP14-042-230	43,000	14.70	12.20	43,000	27,600	3.44	2.50	8.50	CX34-62C		5432286
XP14-042-230	43,000	15.20	13.00	41,500	26,200	3.84	2.68	9.20	CX34-62D	EL180UH135E60D	5741088
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.76	2.64	8.70	CX34-62D	EL195UH135XE60D	5432451
XP14-042-230	42,500	14.70	12.70	41,500	26,400	3.76	2.64	8.70	CX34-62D	EL296UH135XE60D	5650788
XP14-042-230	43,500	15.50	13.00	42,000	27,000	3.72	2.56	8.70	CX34-62D	EL296UH135XV60D	5562872
XP14-042-230	43,500	15.70	13.20	41,500	26,800	3.70	2.56	8.70	CX34-62D	SL280UH135V60D	5432409
XP14-042-230	43,500	15.50	13.20	41,500	26,800	3.70	2.56	8.70	CX34-62D	SLP98UH135XV60D	5432501
XP14-042-230	43,000	14.20	12.20	42,500	27,600	3.52	2.44	8.50	CX34-62D		5432285
XP14-048-230	49,000	15.00	12.70	45,500	30,000	3.38	2.54	8.70	C33-49	EL180UH090E60C	5740262
XP14-048-230	48,500	14.70	12.70	45,500	30,000	3.36	2.52	8.50	C33-49	EL180UH110E60C	5740717
XP14-048-230	49,000	14.70	12.70	46,000	30,200	3.38	2.52	8.50	C33-49	EL195UH090XE48C	5432600
XP14-048-230	49,000	14.70	12.70	46,000	30,200	3.40	2.54	8.50	C33-49	EL195UH110XE60C	5432606
XP14-048-230	49,000	14.70	12.70	46,000	30,200	3.38	2.52	8.50	C33-49	EL296UH090XE48C	5650806
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	C33-49	EL296UH090XV48C	5562879
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH090XV60C	5562883
XP14-048-230	49,000	14.70	12.70	46,000	30,200	3.40	2.54	8.50	C33-49	EL296UH110XE60C	5650807
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH110XV48C	5562891

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	EL296UH110XV60C	5562896
XP14-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	C33-49	SL280UH090V60C	5432563
XP14-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	C33-49	SL280UH090XV60C	8133245
XP14-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	C33-49	SL280UH110V60C	5432564
XP14-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	C33-49	SL280UH110XV60C	8133273
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	C33-49	SLP98UH090XV48C	5432634
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	SLP98UH090XV60C	5432635
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	C33-49	SLP98UH110XV60C	5432636
XP14-048-230	49,000	14.00	12.20	46,500	30,400	3.32	2.44	8.20	C33-49		5432513
XP14-048-230	47,500	14.70	12.50	47,500	31,000	3.14	2.44	8.20	C33-60D	EL180UH135E60D	5741090
XP14-048-230	48,500	15.00	12.70	46,000	30,400	3.60	2.66	9.00	C33-62C	EL180UH090E60C	5740259
XP14-048-230	48,500	15.00	12.70	46,000	30,400	3.58	2.66	9.00	C33-62C	EL180UH110E60C	5740716
XP14-048-230	48,500	14.70	12.50	46,500	30,600	3.58	2.64	9.00	C33-62C	EL195UH090XE48C	5432601
XP14-048-230	48,500	14.70	12.70	46,500	30,400	3.60	2.64	9.00	C33-62C	EL195UH110XE60C	5432607
XP14-048-230	48,500	14.70	12.50	46,500	30,600	3.58	2.64	9.00	C33-62C	EL296UH090XE48C	5650822
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	EL296UH090XV48C	5562882
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	EL296UH090XV60C	5562886
XP14-048-230	48,500	14.70	12.70	46,500	30,400	3.60	2.64	9.00	C33-62C	EL296UH110XE60C	5650812
XP14-048-230	48,500	14.70	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	EL296UH110XV48C	5562889
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	EL296UH110XV60C	5562895
XP14-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	C33-62C	SL280UH090V60C	5432584
XP14-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	C33-62C	SL280UH090XV60C	8133247
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	C33-62C	SL280UH110V60C	5432520
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	C33-62C	SL280UH110XV60C	8133271
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	SLP98UH090XV48C	5432620
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	C33-62C	SLP98UH090XV60C	5432621
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	C33-62C	SLP98UH110XV60C	5432622
XP14-048-230	48,500	14.00	12.20	47,000	30,800	3.52	2.56	8.70	C33-62C		5432506
XP14-048-230	48,000	14.70	12.50	46,000	30,400	3.52	2.60	8.70	C33-62D	EL180UH135E60D	5740949
XP14-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	C33-62D	EL195UH135XE60D	5432613
XP14-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	C33-62D	EL296UH135XE60D	5650816
XP14-048-230	48,000	14.50	12.50	46,000	30,400	3.50	2.56	8.70	C33-62D	EL296UH135XV60D	5562899
XP14-048-230	48,000	14.50	12.50	46,000	30,200	3.52	2.56	8.70	C33-62D	SL280UH135V60D	5432523
XP14-048-230	48,000	14.50	12.70	46,000	30,000	3.52	2.56	8.70	C33-62D	SLP98UH135XV60D	5432623
XP14-048-230	49,000	14.00	12.00	47,000	30,200	3.44	2.56	8.20	CBX25UH-048		5727007
XP14-048-230	48,500	14.00	12.00	47,000	30,400	3.40	2.54	8.20	CBX25UH-060		6623432
XP14-048-230	48,000	15.00	12.50	46,500	29,800	3.52	2.62	8.50	CBX25UHV-048		6970220
XP14-048-230	49,500	15.00	12.70	47,500	30,600	3.62	2.70	9.20	CBX27UH-048		5432528
XP14-048-230	49,500	15.20	12.70	43,500	29,800	3.52	2.66	9.00	CBX27UH-060		5432529
XP14-048-230	49,500	14.70	12.50	48,000	30,800	3.60	2.68	9.00	CBX32M-048		5432530
XP14-048-230	49,500	14.50	12.20	48,000	30,800	3.52	2.64	8.70	CBX32M-060		5432531
XP14-048-230	49,000	15.00	12.70	47,500	30,600	3.60	2.70	9.00	CBX32MV-048		5432532

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-048-230	49,500	14.70	12.50	48,000	30,600	3.54	2.64	8.70	CBX32MV-060		5432533
XP14-048-230	49,000	14.70	12.50	46,000	30,200	3.46	2.58	8.70	CBX32MV-068		5432534
XP14-048-230	49,000	15.00	12.70	47,500	30,600	3.62	2.70	9.00	CBX40UHV-048		5432535
XP14-048-230	50,000	14.70	12.50	48,000	30,600	3.54	2.64	9.00	CBX40UHV-060		5432536
XP14-048-230	50,500	15.20	13.20	46,500	31,000	3.66	2.74	9.20	CH23-68	EL180UH090E60C	5740261
XP14-048-230	50,000	15.20	13.00	46,500	31,000	3.64	2.74	9.20	CH23-68	EL180UH110E60C	5740718
XP14-048-230	50,500	15.20	13.00	47,000	31,000	3.72	2.76	9.20	CH23-68	EL180UH135E60D	5741091
XP14-048-230	50,000	15.00	12.70	47,000	31,200	3.64	2.72	9.20	CH23-68	EL195UH090XE48C	5432602
XP14-048-230	50,500	15.20	13.00	47,000	31,200	3.66	2.74	9.20	CH23-68	EL195UH110XE60C	5432608
XP14-048-230	50,500	14.70	12.70	47,000	31,400	3.64	2.72	9.20	CH23-68	EL195UH135XE60D	5432614
XP14-048-230	50,000	15.00	12.70	47,000	31,200	3.64	2.72	9.20	CH23-68	EL296UH090XE48C	5650819
XP14-048-230	50,500	15.20	13.00	47,000	31,200	3.66	2.74	9.20	CH23-68	EL296UH110XE60C	5650804
XP14-048-230	50,500	14.70	12.70	47,000	31,400	3.64	2.72	9.20	CH23-68	EL296UH135XE60D	5650808
XP14-048-230	51,000	15.20	13.20	47,000	30,800	3.68	2.68	9.20	CH23-68	EL296UH135XV60D	5562902
XP14-048-230	50,500	15.20	13.20	46,500	30,800	3.64	2.70	9.20	CH23-68	SL280UH135V60D	5432541
XP14-048-230	50,500	15.20	13.20	46,500	30,600	3.64	2.68	9.20	CH23-68	SLP98UH135XV60D	5432627
XP14-048-230	49,500	14.00	12.20	47,500	31,400	3.56	2.60	9.00	CH23-68		5432508
XP14-048-230	48,500	14.70	12.70	45,500	29,800	3.32	2.54	8.50	CH33-50/60C	EL180UH090E60C	5740260
XP14-048-230	49,000	14.20	12.20	46,500	30,200	3.38	2.52	8.50	CH33-50/60C	EL180UH110E60C	5740714
XP14-048-230	48,000	14.20	12.20	45,500	29,800	3.28	2.50	8.20	CH33-50/60C	EL195UH090XE48C	5432603
XP14-048-230	48,000	14.20	12.50	45,500	29,800	3.30	2.52	8.20	CH33-50/60C	EL195UH110XE60C	5432609
XP14-048-230	48,000	14.20	12.20	45,500	29,800	3.28	2.50	8.20	CH33-50/60C	EL296UH090XE48C	5650824
XP14-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	EL296UH090XV48C	5562878
XP14-048-230	48,500	14.20	12.20	46,000	29,800	3.32	2.50	8.20	CH33-50/60C	EL296UH090XV60C	5562884
XP14-048-230	48,000	14.20	12.50	45,500	29,800	3.30	2.52	8.20	CH33-50/60C	EL296UH110XE60C	5650820
XP14-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.50	CH33-50/60C	EL296UH110XV48C	5562892
XP14-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	EL296UH110XV60C	5562893
XP14-048-230	48,500	14.50	12.50	46,000	29,600	3.38	2.52	8.50	CH33-50/60C	SL280UH090V60C	5432559
XP14-048-230	48,500	14.50	12.50	46,000	29,600	3.38	2.52	8.50	CH33-50/60C	SL280UH090XV60C	8133244
XP14-048-230	48,500	14.20	12.50	46,000	29,600	3.36	2.50	8.50	CH33-50/60C	SL280UH110V60C	5432560
XP14-048-230	48,500	14.20	12.50	46,000	29,600	3.36	2.50	8.50	CH33-50/60C	SL280UH110XV60C	8133272
XP14-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	SLP98UH090XV48C	5432624
XP14-048-230	48,500	14.20	12.20	46,000	29,800	3.32	2.50	8.20	CH33-50/60C	SLP98UH090XV60C	5432625
XP14-048-230	48,500	14.20	12.50	46,000	29,800	3.34	2.50	8.20	CH33-50/60C	SLP98UH110XV60C	5432626
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.40	2.58	8.70	CH33-60D	EL180UH135E60D	5741093
XP14-048-230	48,000	14.20	12.20	46,500	30,600	3.38	2.54	8.50	CH33-60D	EL195UH135XE60D	5432615
XP14-048-230	48,000	14.20	12.20	46,500	30,600	3.38	2.54	8.50	CH33-60D	EL296UH135XE60D	5650813
XP14-048-230	48,500	14.20	12.50	46,500	30,200	3.44	2.52	8.70	CH33-60D	EL296UH135XV60D	5562898
XP14-048-230	48,500	14.50	12.70	46,000	30,000	3.40	2.52	8.70	CH33-60D	SL280UH135V60D	5432546
XP14-048-230	48,000	14.50	12.50	46,000	30,000	3.40	2.54	8.50	CH33-60D	SLP98UH135XV60D	5432628
XP14-048-230	48,500	15.00	12.70	46,000	30,200	3.44	2.58	8.70	CH33-62D	EL180UH135E60D	5741092
XP14-048-230	48,000	14.70	12.20	46,000	30,400	3.36	2.54	8.70	CH33-62D	EL195UH135XE60D	5432616

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-048-230	48,000	14.70	12.20	46,000	30,400	3.36	2.54	8.70	CH33-62D	EL296UH135XE60D	5650805
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.42	2.54	8.70	CH33-62D	EL296UH135XV60D	5562904
XP14-048-230	48,500	14.70	12.70	46,000	30,000	3.44	2.54	8.70	CH33-62D	SL280UH135V60D	5432549
XP14-048-230	48,000	14.70	12.70	45,500	30,000	3.40	2.54	8.70	CH33-62D	SLP98UH135XV60D	5432629
XP14-048-230	48,000	14.00	12.00	46,500	30,600	3.32	2.46	8.50	CH33-62D		5432511
XP14-048-230	49,500	15.00	12.70	48,500	31,200	3.50	2.66	9.00	CR33-50/60	EL180DF110E60C	5741637
XP14-048-230	49,500	14.20	12.50	49,000	31,400	3.44	2.60	8.70	CR33-50/60	EL195DF090XE48C	5432598
XP14-048-230	49,500	14.20	12.70	48,500	31,200	3.46	2.64	8.70	CR33-50/60	EL195DF110XE60C	5432599
XP14-048-230	49,500	14.20	12.50	49,000	31,400	3.44	2.60	8.70	CR33-50/60	EL296DF090XE48C	5650809
XP14-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.60	8.70	CR33-50/60	EL296DF090XV60C	5562876
XP14-048-230	49,500	14.20	12.70	48,500	31,200	3.46	2.64	8.70	CR33-50/60	EL296DF110XE60C	5650814
XP14-048-230	49,500	14.20	12.70	48,500	31,200	3.42	2.58	8.70	CR33-50/60	EL296DF110XV60C	5562877
XP14-048-230	49,500	14.70	12.70	48,500	31,000	3.48	2.62	8.70	CR33-50/60	SL280DF090V60C	5432553
XP14-048-230	49,500	14.70	13.00	48,500	31,000	3.52	2.64	8.70	CR33-50/60	SL280DF110V60C	5432554
XP14-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.58	8.70	CR33-50/60	SLP98DF090XV48C	5432630
XP14-048-230	49,500	14.20	12.50	49,000	31,400	3.46	2.60	8.70	CR33-50/60	SLP98DF090XV60C	5432631
XP14-048-230	49,500	14.20	12.70	48,500	31,200	3.42	2.58	8.70	CR33-50/60	SLP98DF110XV60C	5432633
XP14-048-230	49,000	15.00	12.70	45,500	30,000	3.38	2.54	8.70	CX34-49	EL180UH090E60C	5740263
XP14-048-230	48,500	14.70	12.70	45,500	30,000	3.36	2.52	8.50	CX34-49	EL180UH110E60C	5740719
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.38	2.52	8.50	CX34-49	EL195UH090XE48C	5432604
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.54	8.50	CX34-49	EL195UH110XE60C	5432610
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.38	2.52	8.50	CX34-49	EL296UH090XE48C	5650810
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	CX34-49	EL296UH090XV48C	5562881
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH090XV60C	5562887
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.54	8.50	CX34-49	EL296UH110XE60C	5650817
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH110XV48C	5562890
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	EL296UH110XV60C	5562897
XP14-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	CX34-49	SL280UH090V60C	5432596
XP14-048-230	49,000	14.70	12.70	46,000	30,000	3.44	2.52	8.50	CX34-49	SL280UH090XV60C	8133248
XP14-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	CX34-49	SL280UH110V60C	5432597
XP14-048-230	49,000	14.70	12.70	46,000	29,800	3.44	2.50	8.50	CX34-49	SL280UH110XV60C	8133276
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.48	8.50	CX34-49	SLP98UH090XV48C	5432642
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	SLP98UH090XV60C	5432643
XP14-048-230	49,000	14.50	12.70	46,000	30,000	3.40	2.50	8.50	CX34-49	SLP98UH110XV60C	5432644
XP14-048-230	49,000	14.00	12.20	46,500	30,400	3.32	2.44	8.20	CX34-49		5432519
XP14-048-230	47,500	14.70	12.50	47,500	31,000	3.14	2.44	8.20	CX34-60D	EL180UH135E60D	5741089
XP14-048-230	48,500	15.00	12.70	46,000	30,400	3.60	2.66	9.00	CX34-62C	EL180UH090E60C	5740258
XP14-048-230	48,500	15.00	12.70	46,000	30,400	3.58	2.66	9.00	CX34-62C	EL180UH110E60C	5740715
XP14-048-230	48,500	14.50	12.50	46,500	30,400	3.58	2.64	9.00	CX34-62C	EL195UH090XE48C	5432605
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	CX34-62C	EL195UH110XE60C	5432611
XP14-048-230	48,500	14.50	12.50	46,500	30,400	3.58	2.64	9.00	CX34-62C	EL296UH090XE48C	5650815
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	EL296UH090XV48C	5562880

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	EL296UH090XV60C	5562885
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.64	9.00	CX34-62C	EL296UH110XE60C	5650823
XP14-048-230	48,500	14.70	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	EL296UH110XV48C	5562888
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	EL296UH110XV60C	5562894
XP14-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	CX34-62C	SL280UH090V60C	5432576
XP14-048-230	49,000	14.70	12.70	46,500	30,200	3.66	2.64	9.00	CX34-62C	SL280UH090XV60C	8133246
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	CX34-62C	SL280UH110V60C	5432577
XP14-048-230	48,500	14.70	12.70	46,000	30,200	3.60	2.64	9.00	CX34-62C	SL280UH110XV60C	8133274
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	SLP98UH090XV48C	5432638
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.62	2.62	9.00	CX34-62C	SLP98UH090XV60C	5432640
XP14-048-230	48,500	14.50	12.70	46,500	30,400	3.60	2.62	9.00	CX34-62C	SLP98UH110XV60C	5432641
XP14-048-230	48,500	14.00	12.20	47,000	30,800	3.52	2.56	8.70	CX34-62C		5432517
XP14-048-230	48,000	14.70	12.50	46,000	30,400	3.52	2.60	8.70	CX34-62D	EL180UH135E60D	5741094
XP14-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	CX34-62D	EL195UH135XE60D	5432618
XP14-048-230	48,000	14.50	12.20	46,000	30,600	3.44	2.56	8.70	CX34-62D	EL296UH135XE60D	5650818
XP14-048-230	48,000	14.50	12.50	46,000	30,400	3.50	2.56	8.70	CX34-62D	EL296UH135XV60D	5562903
XP14-048-230	48,000	14.50	12.50	46,000	30,200	3.52	2.56	8.70	CX34-62D	SL280UH135V60D	5432587
XP14-048-230	48,000	14.50	12.70	46,000	30,000	3.52	2.56	8.70	CX34-62D	SLP98UH135XV60D	5432632
XP14-060-230	57,500	14.50	12.00	54,000	35,000	3.28	2.36	8.20	C33-60D	EL180UH135E60D	5741098
XP14-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	C33-60D	EL195UH135XE60D	5432707
XP14-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	C33-60D	EL296UH135XE60D	5650835
XP14-060-230	60,500	15.20	12.50	54,500	36,200	3.28	2.52	8.70	C33-62C	EL180UH090E60C	5740267
XP14-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.50	8.50	C33-62C	EL180UH110E60C	5740721
XP14-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	C33-62C	EL195UH110XE60C	5432703
XP14-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	C33-62C	EL296UH090XV60C	5562907
XP14-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.48	8.50	C33-62C	EL296UH110XE60C	5650830
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	EL296UH110XV60C	5562911
XP14-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	C33-62C	SL280UH090V60C	5432697
XP14-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	C33-62C	SL280UH090XV60C	8133250
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SL280UH110V60C	5432698
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SL280UH110XV60C	8133279
XP14-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	C33-62C	SLP98UH090XV60C	5432724
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C	SLP98UH110XV60C	5432715
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	C33-62C		5432645
XP14-060-230	57,500	14.50	12.20	55,000	36,400	3.20	2.38	8.20	C33-62D	EL180UH135E60D	5741096
XP14-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	C33-62D	EL195UH135XE60D	5432708
XP14-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	C33-62D	EL296UH135XE60D	5650836
XP14-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	C33-62D	EL296UH135XV60D	5562914
XP14-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	C33-62D	SL280UH135V60D	5432656
XP14-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	C33-62D	SLP98UH135XV60D	5432716
XP14-060-230	58,500	14.00	12.00	55,500	35,800	3.28	2.46	8.20	CBX25UH-060		5727008
XP14-060-230	58,000	14.50	12.50	54,500	35,000	3.28	2.50	8.50	CBX25UHV-060		6970221

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-060-230	59,000	15.00	12.50	55,500	36,000	3.52	2.62	8.50	CBX27UH-060		5432658
XP14-060-230	59,000	14.50	12.00	56,500	37,200	3.22	2.50	8.50	CBX32M-060		5432676
XP14-060-230	59,000	14.50	12.00	57,000	37,200	3.24	2.48	8.50	CBX32MV-060		5432678
XP14-060-230	59,000	14.50	12.20	53,500	36,000	3.28	2.48	8.70	CBX32MV-068		5432679
XP14-060-230	59,000	14.50	12.00	57,000	37,200	3.24	2.48	8.50	CBX40UHV-060		5432684
XP14-060-230	59,500	15.00	12.50	57,000	37,400	3.48	2.60	9.00	CH23-68	EL180UH090E60C	5740265
XP14-060-230	59,500	14.70	12.50	57,000	37,400	3.46	2.58	9.00	CH23-68	EL180UH110E60C	5740723
XP14-060-230	60,000	15.00	12.70	57,000	37,600	3.52	2.62	9.00	CH23-68	EL180UH135E60D	5741095
XP14-060-230	59,500	15.00	12.50	57,000	37,400	3.50	2.60	9.00	CH23-68	EL195UH110XE60C	5432704
XP14-060-230	60,000	14.70	12.20	57,500	37,800	3.48	2.58	9.00	CH23-68	EL195UH135XE60D	5432709
XP14-060-230	59,500	15.00	12.50	57,000	37,400	3.50	2.60	9.00	CH23-68	EL296UH110XE60C	5650825
XP14-060-230	60,000	14.70	12.20	57,500	37,800	3.48	2.58	9.00	CH23-68	EL296UH135XE60D	5650827
XP14-060-230	60,000	14.70	12.50	57,500	37,800	3.50	2.60	9.00	CH23-68	EL296UH135XV60D	5562913
XP14-060-230	60,000	14.70	12.50	57,500	37,800	3.50	2.60	9.00	CH23-68	SL280UH135V60D	5432689
XP14-060-230	59,500	15.00	12.50	57,000	37,400	3.46	2.60	9.00	CH23-68	SLP98UH135XV60D	5432722
XP14-060-230	59,500	14.20	12.20	57,500	38,000	3.42	2.56	8.70	CH23-68		5432650
XP14-060-230	57,000	14.20	11.70	54,000	35,000	3.24	2.36	8.20	CH33-60D	EL180UH135E60D	5741097
XP14-060-230	57,000	14.00	11.70	54,500	35,200	3.22	2.32	8.20	CH33-60D	EL195UH135XE60D	5432710
XP14-060-230	57,000	14.00	11.70	54,500	35,200	3.22	2.32	8.20	CH33-60D	EL296UH135XE60D	5650829
XP14-060-230	57,500	14.50	12.20	54,000	36,000	3.24	2.42	8.50	CH33-62D	EL180UH135E60D	5741100
XP14-060-230	57,500	14.20	12.00	54,000	36,400	3.20	2.40	8.50	CH33-62D	EL195UH135XE60D	5432711
XP14-060-230	57,500	14.20	12.00	54,000	36,400	3.20	2.40	8.50	CH33-62D	EL296UH135XE60D	5650831
XP14-060-230	57,500	14.20	12.20	54,000	36,200	3.24	2.42	8.50	CH33-62D	EL296UH135XV60D	5562915
XP14-060-230	57,500	14.20	12.20	54,000	36,200	3.22	2.42	8.50	CH33-62D	SL280UH135V60D	5432668
XP14-060-230	57,500	14.50	12.20	54,000	36,200	3.22	2.42	8.50	CH33-62D	SLP98UH135XV60D	5432719
XP14-060-230	57,000	14.00	11.70	54,000	36,400	3.16	2.38	8.20	CH33-62D		5432653
XP14-060-230	59,000	14.70	12.20	58,000	37,800	3.16	2.46	8.20	CR33-50/60	EL180DF110E60C	5741638
XP14-060-230	58,500	14.00	11.70	58,000	37,600	3.10	2.42	8.20	CR33-50/60	EL195DF110XE60C	5432702
XP14-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	EL296DF090XV60C	5562905
XP14-060-230	58,500	14.00	11.70	58,000	37,600	3.10	2.42	8.20	CR33-50/60	EL296DF110XE60C	5650828
XP14-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	EL296DF110XV60C	5562906
XP14-060-230	59,000	14.50	12.00	58,500	37,800	3.14	2.44	8.20	CR33-50/60	SL280DF090V60C	5432672
XP14-060-230	59,000	14.70	12.20	58,000	37,800	3.12	2.44	8.20	CR33-50/60	SL280DF110V60C	5432673
XP14-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	SLP98DF090XV60C	5432720
XP14-060-230	58,500	14.00	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60	SLP98DF110XV60C	5432721
XP14-060-230	58,500	14.20	11.70	58,500	38,000	3.08	2.38	8.20	CR33-50/60		5432648
XP14-060-230	58,500	14.20	11.70	58,500	38,000	3.08	2.38	8.20	CR33-60		5432649
XP14-060-230	57,500	14.50	12.00	54,000	35,000	3.28	2.36	8.20	CX34-60D	EL180UH135E60D	5741099
XP14-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	CX34-60D	EL195UH135XE60D	5432712
XP14-060-230	57,500	14.00	11.70	54,500	35,200	3.26	2.34	8.20	CX34-60D	EL296UH135XE60D	5650826
XP14-060-230	60,500	15.20	12.50	54,500	36,200	3.28	2.52	8.70	CX34-62C	EL180UH090E60C	5740268
XP14-060-230	60,500	15.00	12.50	54,500	36,200	3.26	2.50	8.50	CX34-62C	EL180UH110E60C	5740724

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP14-060-230	60,500	14.70	12.20	54,500	36,200	3.26	2.48	8.50	CX34-62C	EL195UH110XE60C	5432706
XP14-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	CX34-62C	EL296UH090XV60C	5562909
XP14-060-230	60,500	14.70	12.20	54,500	36,200	3.26	2.48	8.50	CX34-62C	EL296UH110XE60C	5650834
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	EL296UH110XV60C	5562910
XP14-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	CX34-62C	SL280UH090V60C	5432693
XP14-060-230	61,000	15.00	12.50	55,000	36,400	3.30	2.50	8.70	CX34-62C	SL280UH090XV60C	8133249
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SL280UH110V60C	5432694
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SL280UH110XV60C	8133277
XP14-060-230	61,000	14.50	12.20	55,000	36,800	3.24	2.48	8.50	CX34-62C	SLP98UH090XV60C	5432723
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C	SLP98UH110XV60C	5432725
XP14-060-230	61,000	14.70	12.20	55,000	36,600	3.26	2.48	8.50	CX34-62C		5432651
XP14-060-230	57,500	14.50	12.20	55,000	36,400	3.20	2.38	8.20	CX34-62D	EL180UH135E60D	5741101
XP14-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	CX34-62D	EL195UH135XE60D	5432713
XP14-060-230	57,500	14.20	12.00	55,000	36,800	3.14	2.36	8.20	CX34-62D	EL296UH135XE60D	5650833
XP14-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	CX34-62D	EL296UH135XV60D	5562916
XP14-060-230	57,500	14.20	12.00	55,000	36,600	3.18	2.38	8.20	CX34-62D	SL280UH135V60D	5432701
XP14-060-230	57,000	14.50	12.20	54,500	36,400	3.14	2.38	8.20	CX34-62D	SLP98UH135XV60D	5432726

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.



PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-024-230	24,200	16.00	12.50	21,600	13,300	3.64	2.48	8.50	C33-38A	SL280UH070V36A	7785776
XP16-024-230	24,200	15.10	12.50	21,600	13,300	3.64	2.48	8.50	C33-38A	SL280UH070XV36A	7785773
XP16-024-230	24,000	16.00	12.50	21,600	13,300	3.60	2.46	8.50	C33-38B	EL296UH070XV36B	7785768
XP16-024-230	24,200	16.00	12.50	21,600	13,300	3.66	2.50	8.50	C33-38B	SL280UH090V36B	7785762
XP16-024-230	24,000	16.00	12.50	21,600	13,300	3.60	2.46	8.50	C33-38B	SLP98UH070XV36B	7785767
XP16-024-230	24,000	14.50	12.00	23,400	14,400	3.40	2.42	8.20	CBX25UHV-030		7785764
XP16-024-230	24,200	15.50	11.20	22,400	13,700	3.70	2.54	8.50	CBX27UH-024		7785754
XP16-024-230	24,000	16.00	12.50	22,200	12,900	3.62	2.38	8.50	CBX27UH-030		7785755
XP16-024-230	24,400	16.50	12.50	22,400	14,000	3.72	2.60	8.50	CBX32MV-024/030		7785758
XP16-024-230	24,400	17.00	12.50	22,400	13,100	3.66	2.38	8.50	CBX32MV-036		7785757
XP16-024-230	24,200	16.00	12.00	22,200	13,000	3.60	2.38	8.50	CBX40UHV-024		7785759
XP16-024-230	24,000	16.00	12.00	22,200	12,900	3.60	2.36	8.50	CBX40UHV-030		7785756
XP16-024-230	24,400	16.00	12.50	22,400	13,100	3.68	2.40	8.50	CBX40UHV-036		7785765
XP16-024-230	24,800	16.00	12.00	21,000	13,900	3.30	2.50	8.50	CH33-31B	EL296UH070XV36B	7785771
XP16-024-230	24,800	15.10	12.20	21,000	13,900	3.34	2.52	8.20	CH33-31B	SL280UH090V36B	7785775
XP16-024-230	24,800	16.00	12.00	21,000	13,900	3.30	2.50	8.50	CH33-31B	SLP98UH070XV36B	7785774
XP16-024-230	23,600	16.00	12.50	23,200	13,900	3.36	2.34	8.20	CR33-30/36	SLP98DF070XV36B	7785772
XP16-024-230	23,600	16.00	12.50	23,200	13,900	3.36	2.36	8.20	CR33-30/36	SLP98DF090XV36C	7785766
XP16-024-230	24,200	16.00	12.50	21,600	13,300	3.64	2.48	8.50	CX34-38A	SL280UH070V36A	7785760
XP16-024-230	24,200	16.00	12.50	21,600	13,300	3.64	2.48	8.50	CX34-38A	SL280UH070XV36A	7785770
XP16-024-230	24,200	16.00	12.50	21,600	13,400	3.62	2.48	8.50	CX34-38B	EL296UH070XV36B	7785769
XP16-024-230	24,400	16.00	12.50	21,800	13,400	3.68	2.48	8.50	CX34-38B	SL280UH090V36B	7785761
XP16-024-230	24,000	16.00	12.50	21,600	13,300	3.60	2.46	8.50	CX34-38B	SLP98UH070XV36B	7785763
XP16-036-230	37,000	16.00	13.00	32,800	21,600	3.10	2.56	8.50	C33-43	EL180UH070E36B	7785832
XP16-036-230	37,000	15.50	12.50	33,600	22,200	3.02	2.46	8.50	C33-43	EL195UH045XE36B	7785808
XP16-036-230	37,000	16.00	12.50	33,200	21,800	3.08	2.52	8.50	C33-43	EL195UH070XE36B	7785837
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.10	2.56	8.50	C33-43	EL195UH090XE48C	7785849
XP16-036-230	37,000	15.50	12.50	33,600	22,200	3.02	2.46	8.50	C33-43	EL296UH045XE36B	7785848
XP16-036-230	37,000	16.00	12.50	33,200	21,800	3.08	2.52	8.50	C33-43	EL296UH070XE36B	7785822
XP16-036-230	37,200	16.00	12.50	33,200	22,000	3.06	2.52	8.50	C33-43	EL296UH070XV36B	7785843
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.10	2.56	8.50	C33-43	EL296UH090XE48C	7785811
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.56	8.50	C33-43	EL296UH090XV36C	7785844
XP16-036-230	37,000	16.00	13.00	33,000	21,600	3.10	2.54	8.50	C33-43	EL296UH090XV48C	7785833
XP16-036-230	37,800	16.00	13.00	33,400	22,000	3.18	2.58	8.50	C33-43	EL296UH090XV60C	7785828
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.18	2.58	8.50	C33-43	EL296UH110XV60C	7785803
XP16-036-230	37,200	16.00	13.00	32,800	21,600	3.12	2.56	8.50	C33-43	SL280UH090V36B	7785827
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.14	2.58	8.50	C33-43	SL280UH090V48B	7785802

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-036-230	37,800	16.00	13.00	33,200	21,800	3.18	2.58	8.50	C33-43	SL280UH090V60C	7785810
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.14	2.58	8.50	C33-43	SL280UH090XV48B	7785809
XP16-036-230	37,800	16.00	13.00	33,200	21,800	3.18	2.58	8.50	C33-43	SL280UH090XV60C	7785839
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.16	2.56	8.50	C33-43	SL280UH110V60C	7785850
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.16	2.56	8.50	C33-43	SL280UH110XV60C	7785812
XP16-036-230	37,200	16.00	12.50	33,200	22,000	3.06	2.52	8.50	C33-43	SLP98UH070XV36B	7785838
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.56	8.50	C33-43	SLP98UH090XV36C	7785845
XP16-036-230	37,000	16.00	13.00	33,000	21,600	3.10	2.54	8.50	C33-43	SLP98UH090XV48C	7785834
XP16-036-230	37,800	16.00	13.00	33,400	22,000	3.18	2.58	8.50	C33-43	SLP98UH090XV60C	7785817
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.18	2.58	8.50	C33-43	SLP98UH110XV60C	7785804
XP16-036-230	36,800	14.50	12.00	33,600	22,400	2.96	2.42	8.20	C33-43B		7785782
XP16-036-230	36,800	14.50	12.00	33,600	22,400	2.96	2.42	8.20	C33-43C		8444069
XP16-036-230	37,400	16.00	13.00	34,000	23,000	2.88	2.40	8.20	C33-50/60C	EL296UH090XV60C	7785794
XP16-036-230	37,200	16.00	13.00	33,600	22,800	2.86	2.40	8.20	C33-50/60C	EL296UH110XV60C	7785796
XP16-036-230	37,400	16.00	13.00	33,800	22,800	2.88	2.40	8.20	C33-50/60C	SL280UH090V60C	7785797
XP16-036-230	37,400	16.00	13.00	33,800	22,800	2.88	2.40	8.20	C33-50/60C	SL280UH090XV60C	7785798
XP16-036-230	37,400	16.00	13.00	34,000	23,000	2.88	2.40	8.20	C33-50/60C	SLP98UH090XV60C	7785795
XP16-036-230	37,200	16.00	13.00	33,600	22,800	2.86	2.40	8.20	C33-50/60C	SLP98UH110XV60C	7785789
XP16-036-230	36,200	14.50	12.00	36,800	24,400	2.80	2.68	8.20	CBX25UH-036		7785904
XP16-036-230	36,200	16.00	12.50	34,600	23,200	3.18	2.58	8.50	CBX25UHV-036		7785792
XP16-036-230	36,200	15.50	12.50	34,400	23,000	3.20	2.60	9.00	CBX27UH-036		7785786
XP16-036-230	37,600	16.00	13.00	34,200	23,400	3.36	2.84	9.50	CBX27UH-042		7785903
XP16-036-230	35,600	14.50	12.00	34,800	23,400	3.12	2.52	8.70	CBX32M-036		7785785
XP16-036-230	36,400	16.50	12.50	34,600	23,200	3.20	2.60	9.00	CBX32MV-036		7785784
XP16-036-230	37,600	16.00	13.00	34,200	23,400	3.36	2.84	9.50	CBX32MV-048		7785901
XP16-036-230	36,200	16.00	13.00	34,400	23,000	3.22	2.62	9.00	CBX40UHV-030		7785788
XP16-036-230	36,200	16.00	12.50	34,600	23,200	3.22	2.60	9.00	CBX40UHV-036		7785787
XP16-036-230	37,400	16.00	13.50	34,400	23,000	3.24	2.62	9.00	CBX40UHV-042		7785902
XP16-036-230	37,400	16.00	13.50	34,400	22,800	3.26	2.64	8.50	CBX40UHV-048		7785783
XP16-036-230	38,000	16.00	13.00	33,000	22,200	3.38	2.60	8.50	CH33-43B	EL180UH070E36B	7785898
XP16-036-230	38,000	16.00	13.00	33,000	22,200	3.44	2.64	9.00	CH33-43B	EL180UH090E48B	7785896
XP16-036-230	37,600	15.50	12.50	33,200	22,400	3.30	2.54	8.50	CH33-43B	EL195UH045XE36B	7785884
XP16-036-230	37,800	15.50	12.50	33,000	22,400	3.30	2.56	8.50	CH33-43B	EL195UH070XE36B	7785889
XP16-036-230	37,600	15.50	12.50	33,200	22,400	3.30	2.54	8.50	CH33-43B	EL296UH045XE36B	7785892
XP16-036-230	37,800	16.00	12.50	33,000	22,400	3.34	2.58	8.50	CH33-43B	EL296UH045XV36B	7785905
XP16-036-230	37,800	15.50	12.50	33,000	22,400	3.30	2.56	8.50	CH33-43B	EL296UH070XE36B	7785894
XP16-036-230	37,800	16.00	12.50	33,000	22,200	3.36	2.58	8.50	CH33-43B	EL296UH070XV36B	7785906
XP16-036-230	37,800	16.00	13.00	32,600	22,000	3.40	2.64	8.50	CH33-43B	SL280UH090V36B	7785897
XP16-036-230	38,000	16.00	13.00	32,800	22,000	3.40	2.62	8.50	CH33-43B	SL280UH090V48B	7785895
XP16-036-230	38,000	16.00	13.00	32,800	22,000	3.40	2.62	8.50	CH33-43B	SL280UH090XV48B	7785891
XP16-036-230	37,800	16.00	12.50	33,000	22,200	3.36	2.58	8.50	CH33-43B	SLP98UH070XV36B	7785899

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-036-230	37,400	14.50	12.00	33,200	22,600	3.22	2.50	8.50	CH33-43B		7785777
XP16-036-230	37,400	16.00	13.00	33,000	21,800	3.16	2.58	8.50	CH33-43C	EL195UH090XE48C	7785900
XP16-036-230	37,400	16.00	13.00	33,000	21,800	3.16	2.58	8.50	CH33-43C	EL296UH090XE48C	7785885
XP16-036-230	37,400	16.00	13.00	32,400	21,800	3.32	2.56	8.50	CH33-43C	EL296UH090XV36C	7785890
XP16-036-230	37,200	16.00	13.00	32,400	21,800	3.32	2.58	8.50	CH33-43C	EL296UH090XV48C	7785893
XP16-036-230	38,000	16.00	13.00	32,800	22,000	3.36	2.58	8.50	CH33-43C	EL296UH090XV60C	7785790
XP16-036-230	37,800	16.00	13.00	32,600	22,000	3.36	2.60	8.50	CH33-43C	EL296UH110XV60C	7785791
XP16-036-230	38,000	16.00	13.00	32,800	22,000	3.36	2.58	8.50	CH33-43C	SL280UH090V60C	7785883
XP16-036-230	38,000	16.00	13.00	32,600	22,000	3.38	2.62	8.50	CH33-43C	SL280UH090XV60C	7785888
XP16-036-230	37,800	16.00	13.00	32,600	22,000	3.36	2.60	8.50	CH33-43C	SL280UH110V60C	7785880
XP16-036-230	37,800	16.00	13.00	32,600	22,000	3.34	2.58	8.50	CH33-43C	SL280UH110XV60C	7785868
XP16-036-230	37,400	16.00	13.00	32,400	21,800	3.32	2.56	8.50	CH33-43C	SLP98UH090XV36C	7785872
XP16-036-230	37,200	16.00	13.00	32,400	21,800	3.32	2.58	8.50	CH33-43C	SLP98UH090XV48C	7785853
XP16-036-230	38,000	16.00	13.00	32,800	22,000	3.36	2.58	8.50	CH33-43C	SLP98UH090XV60C	7785876
XP16-036-230	37,800	16.00	13.00	32,600	22,000	3.36	2.60	8.50	CH33-43C	SLP98UH110XV60C	7785860
XP16-036-230	36,800	14.50	12.00	33,600	22,400	3.02	2.44	8.20	CH33-43C		7785779
XP16-036-230	37,000	16.00	13.00	33,000	21,800	3.16	2.54	8.50	CH33-48C	EL195UH090XE48C	7785855
XP16-036-230	37,000	16.00	13.00	33,000	21,800	3.16	2.54	8.50	CH33-48C	EL296UH090XE48C	7785866
XP16-036-230	37,000	16.00	13.00	33,000	21,800	3.16	2.54	8.50	CH33-48C	EL296UH090XV36C	7785881
XP16-036-230	36,800	16.00	13.00	32,800	21,800	3.14	2.56	8.50	CH33-48C	EL296UH090XV48C	7785877
XP16-036-230	37,600	16.00	13.00	33,200	22,000	3.20	2.56	8.50	CH33-48C	EL296UH090XV60C	7785869
XP16-036-230	37,400	16.00	13.00	33,000	21,800	3.20	2.56	8.50	CH33-48C	EL296UH110XV60C	7785873
XP16-036-230	37,600	16.00	13.00	33,200	22,000	3.24	2.60	8.50	CH33-48C	SL280UH090V60C	7785854
XP16-036-230	37,600	16.00	13.00	33,200	22,000	3.24	2.60	8.50	CH33-48C	SL280UH090XV60C	7785865
XP16-036-230	37,200	16.00	13.00	33,200	22,000	3.20	2.56	8.50	CH33-48C	SL280UH110V60C	7785861
XP16-036-230	37,200	16.00	13.00	33,200	22,000	3.20	2.56	8.50	CH33-48C	SL280UH110XV60C	7785863
XP16-036-230	37,000	16.00	13.00	33,000	21,800	3.16	2.54	8.50	CH33-48C	SLP98UH090XV36C	7785882
XP16-036-230	36,800	16.00	13.00	32,800	21,800	3.14	2.56	8.50	CH33-48C	SLP98UH090XV48C	7785878
XP16-036-230	37,600	16.00	13.00	33,200	22,000	3.20	2.56	8.50	CH33-48C	SLP98UH090XV60C	7785870
XP16-036-230	37,400	16.00	13.00	33,000	21,800	3.20	2.56	8.50	CH33-48C	SLP98UH110XV60C	7785874
XP16-036-230	36,400	14.50	12.00	33,600	22,400	3.00	2.42	8.20	CH33-48C		7785780
XP16-036-230	36,400	16.00	13.00	35,800	22,400	3.00	2.68	8.50	CR33-48B	EL180DF070E36B	7785859
XP16-036-230	36,600	15.50	12.00	36,400	23,000	2.96	2.60	8.50	CR33-48B	EL195DF045XE36B	7785862
XP16-036-230	36,400	15.50	12.50	36,000	22,600	3.00	2.64	8.70	CR33-48B	EL195DF070XE48B	7785864
XP16-036-230	36,600	15.50	12.00	36,400	23,000	2.96	2.60	8.50	CR33-48B	EL296DF045XE36B	7785871
XP16-036-230	36,400	15.50	12.50	36,000	22,600	3.00	2.64	8.70	CR33-48B	EL296DF070XE48B	7785879
XP16-036-230	36,000	15.00	12.50	36,000	22,800	2.96	2.62	8.50	CR33-48B	EL296DF070XV48B	8203819
XP16-036-230	36,600	16.00	12.50	36,000	22,600	3.02	2.66	8.50	CR33-48B	SL280DF090V48B	7785875
XP16-036-230	36,200	16.00	12.50	36,000	22,600	2.98	2.64	8.50	CR33-48B	SLP98DF070XV36B	7785887
XP16-036-230	36,000	14.00	11.50	36,600	23,200	2.88	2.54	8.20	CR33-48B		7785778
XP16-036-230	37,200	16.00	13.00	36,000	22,600	3.08	2.72	8.50	CR33-48C	SL280DF090V60C	7785856

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
XP16-036-230	36,800	16.00	13.00	36,000	22,600	3.06	2.72	8.50	CR33-48C	SL280DF110V60C	7785867
XP16-036-230	36,600	16.00	12.50	36,000	22,600	3.00	2.66	8.50	CR33-48C	SLP98DF090XV36C	7785886
XP16-036-230	36,600	16.00	12.50	36,000	22,600	3.02	2.68	8.50	CR33-48C	SLP98DF090XV48C	7785818
XP16-036-230	36,800	16.00	12.50	36,200	22,600	3.06	2.68	8.50	CR33-48C	SLP98DF090XV60C	7785851
XP16-036-230	36,800	16.00	12.50	36,200	22,800	3.06	2.70	8.50	CR33-48C	SLP98DF110XV60C	7785840
XP16-036-230	37,000	16.00	13.00	32,800	21,600	3.10	2.56	8.50	CX34-43	EL180UH070E36B	7785852
XP16-036-230	37,000	15.50	12.50	33,600	22,200	3.02	2.46	8.50	CX34-43	EL195UH045XE36B	7785813
XP16-036-230	37,000	16.00	12.50	33,200	21,800	3.08	2.52	8.50	CX34-43	EL195UH070XE36B	7785823
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.10	2.56	8.50	CX34-43	EL195UH090XE48C	7785835
XP16-036-230	37,000	15.50	12.50	33,600	22,200	3.02	2.46	8.50	CX34-43	EL296UH045XE36B	7785846
XP16-036-230	37,000	16.00	12.50	33,200	21,800	3.08	2.52	8.50	CX34-43	EL296UH070XE36B	7785857
XP16-036-230	37,200	16.00	12.50	33,200	22,000	3.06	2.52	8.50	CX34-43	EL296UH070XV36B	7785819
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.10	2.56	8.50	CX34-43	EL296UH090XE48C	7785858
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.56	8.50	CX34-43	EL296UH090XV36C	7785820
XP16-036-230	37,000	16.00	13.00	33,000	21,600	3.10	2.54	8.50	CX34-43	EL296UH090XV48C	7785841
XP16-036-230	37,800	16.00	13.00	33,400	22,000	3.18	2.58	8.50	CX34-43	EL296UH090XV60C	7785830
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.18	2.58	8.50	CX34-43	EL296UH110XV60C	7785825
XP16-036-230	37,200	16.00	13.00	32,800	21,600	3.12	2.56	8.50	CX34-43	SL280UH090V36B	7785829
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.58	8.50	CX34-43	SL280UH090V48B	7785824
XP16-036-230	37,800	16.00	13.00	33,200	21,800	3.18	2.58	8.50	CX34-43	SL280UH090V60C	7785801
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.58	8.50	CX34-43	SL280UH090XV48B	7785800
XP16-036-230	37,800	16.00	13.00	33,200	21,800	3.18	2.58	8.50	CX34-43	SL280UH090XV60C	7785807
XP16-036-230	37,400	16.00	13.00	33,200	21,800	3.14	2.56	8.50	CX34-43	SL280UH110V60C	7785836
XP16-036-230	37,400	16.00	13.00	33,200	21,800	3.14	2.56	8.50	CX34-43	SL280UH110XV60C	7785847
XP16-036-230	37,200	16.00	12.50	33,200	22,000	3.06	2.52	8.50	CX34-43	SLP98UH070XV36B	7785806
XP16-036-230	37,200	16.00	13.00	33,000	21,800	3.12	2.56	8.50	CX34-43	SLP98UH090XV36C	7785821
XP16-036-230	37,000	16.00	13.00	33,000	21,600	3.10	2.54	8.50	CX34-43	SLP98UH090XV48C	7785842
XP16-036-230	37,800	16.00	13.00	33,400	22,000	3.18	2.58	8.50	CX34-43	SLP98UH090XV60C	7785831
XP16-036-230	37,600	16.00	13.00	33,200	21,800	3.18	2.58	8.50	CX34-43	SLP98UH110XV60C	7785826
XP16-036-230	36,800	14.50	12.00	33,600	22,400	2.96	2.42	8.20	CX34-43		7785781
XP16-036-230	37,400	16.00	13.00	34,000	23,000	2.88	2.40	8.20	CX34-50/60C	EL296UH090XV60C	7785814
XP16-036-230	37,200	16.00	13.00	33,600	22,800	2.86	2.40	8.20	CX34-50/60C	EL296UH110XV60C	7785816
XP16-036-230	37,400	16.00	13.00	33,800	22,800	2.88	2.40	8.20	CX34-50/60C	SL280UH090V60C	7785793
XP16-036-230	37,400	16.50	13.00	33,800	22,800	2.88	2.40	8.20	CX34-50/60C	SL280UH090XV60C	7785799
XP16-036-230	37,400	16.00	13.00	34,000	23,000	2.88	2.40	8.20	CX34-50/60C	SLP98UH090XV60C	7785815
XP16-036-230	37,400	16.00	13.00	33,600	22,800	2.86	2.40	8.20	CX34-50/60C	SLP98UH110XV60C	7785805
XP16-048-230	47,000	15.50	12.00	41,500	28,000	3.46	2.58	9.00	C33-62C	EL180UH090E60C	7785931
XP16-048-230	47,500	15.00	11.50	42,000	28,600	3.44	2.56	9.00	C33-62C	EL180UH110E60C	7785924
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.40	2.54	8.70	C33-62C	EL195UH090XE48C	7785914
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.44	2.56	9.00	C33-62C	EL195UH110XE60C	7785917
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.40	2.54	8.70	C33-62C	EL296UH090XE48C	7785915

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.44	2.56	9.00	C33-62C	EL296UH110XE60C	7785918
XP16-048-230	47,500	15.00	12.00	44,000	29,400	3.48	2.56	8.50	CBX25UHV-048		7785919
XP16-048-230	48,500	16.00	12.50	45,000	29,800	3.40	2.64	9.00	CBX27UH-048		7785916
XP16-048-230	47,500	15.50	11.50	44,500	27,200	3.58	2.54	9.00	CBX27UH-060		7785972
XP16-048-230	48,000	15.50	12.00	45,500	30,200	3.32	2.58	8.70	CBX32M-048		7785973
XP16-048-230	48,000	16.00	12.50	45,500	30,000	3.38	2.62	8.50	CBX32MV-048		7785968
XP16-048-230	48,500	16.00	12.50	45,000	30,800	3.56	2.72	9.50	CBX32MV-060		7785913
XP16-048-230	48,000	16.00	12.50	41,000	26,600	3.36	2.46	8.50	CBX32MV-068		7785962
XP16-048-230	48,000	16.00	12.50	45,500	30,000	3.38	2.60	8.50	CBX40UHV-048		7785969
XP16-048-230	48,500	16.00	12.50	45,000	31,000	3.60	2.76	9.50	CBX40UHV-060		7785970
XP16-048-230	48,500	16.00	12.50	45,000	29,200	3.62	2.62	9.00	CH23-68	EL180UH090E60C	7785921
XP16-048-230	48,500	16.00	12.50	45,000	29,200	3.60	2.62	9.00	CH23-68	EL180UH110E60C	7785923
XP16-048-230	48,500	16.00	12.00	45,000	29,400	3.56	2.58	8.50	CH23-68	EL195UH090XE48C	7785971
XP16-048-230	48,500	16.00	12.00	45,000	29,400	3.58	2.60	9.00	CH23-68	EL195UH110XE60C	7785950
XP16-048-230	48,500	16.00	12.00	45,000	29,400	3.56	2.58	8.50	CH23-68	EL296UH090XE48C	7785951
XP16-048-230	48,500	16.00	12.00	45,000	29,400	3.58	2.60	9.00	CH23-68	EL296UH110XE60C	7785963
XP16-048-230	48,500	16.00	12.00	45,000	29,400	3.62	2.62	9.00	CH23-68	EL296UH135XV60D	7785959
XP16-048-230	48,500	16.00	12.00	45,000	29,200	3.60	2.60	9.00	CH23-68	SL280UH135V60D	7785965
XP16-048-230	48,500	16.00	12.00	45,500	29,400	3.62	2.60	9.00	CH23-68	SLP98UH135XV60D	7785956
XP16-048-230	48,000	14.50	11.50	45,500	30,000	3.44	2.52	8.50	CH23-68		7785907
XP16-048-230	48,000	15.00	12.00	45,500	31,600	3.26	2.64	8.70	CH33-60D	EL296UH135XV60D	7785966
XP16-048-230	48,000	15.00	12.00	45,000	31,400	3.22	2.64	8.70	CH33-60D	SL280UH135V60D	7785957
XP16-048-230	48,500	15.00	12.00	45,500	31,600	3.26	2.64	8.70	CH33-60D	SLP98UH135XV60D	7785960
XP16-048-230	47,000	15.00	12.00	43,500	28,600	3.38	2.48	8.70	CH33-62D	EL296UH135XV60D	7785952
XP16-048-230	46,500	15.00	12.00	43,500	28,600	3.40	2.50	8.70	CH33-62D	SL280UH135V60D	7785964
XP16-048-230	47,000	15.00	12.00	43,500	28,800	3.38	2.50	8.70	CH33-62D	SLP98UH135XV60D	7785953
XP16-048-230	47,500	16.00	12.50	44,000	30,200	3.54	2.70	9.50	CR33-50/60	EL180DF110E60C	7785925
XP16-048-230	47,000	15.50	12.00	44,500	30,400	3.48	2.64	9.20	CR33-50/60	EL195DF090XE48C	7785967
XP16-048-230	47,000	16.00	12.00	44,000	30,200	3.50	2.68	9.00	CR33-50/60	EL195DF110XE60C	7785958
XP16-048-230	47,000	15.50	12.00	44,500	30,400	3.48	2.64	9.20	CR33-50/60	EL296DF090XE48C	7785961
XP16-048-230	47,000	16.00	12.00	44,000	30,200	3.50	2.68	9.00	CR33-50/60	EL296DF110XE60C	7785933
XP16-048-230	47,000	16.00	12.00	44,500	30,600	3.48	2.64	9.00	CR33-50/60	EL296DF110XV60C	8688153
XP16-048-230	47,000	16.00	12.00	44,500	30,400	3.48	2.64	9.00	CR33-50/60	SLP98DF090XV60C	7785948
XP16-048-230	47,000	16.00	12.00	44,500	30,600	3.48	2.64	9.00	CR33-50/60	SLP98DF110XV60C	7785928
XP16-048-230	47,000	14.50	11.50	44,500	30,800	3.38	2.60	9.00	CR33-50/60		7785908
XP16-048-230	47,000	16.00	12.00	44,500	30,400	3.48	2.64	9.00	CR33-60	SLP98DF090XV60C	7785944
XP16-048-230	47,000	16.00	12.00	44,500	30,400	3.48	2.62	9.00	CR33-60	SLP98DF110XV60C	7785938
XP16-048-230	47,000	14.50	11.50	44,500	30,600	3.38	2.58	9.00	CR33-60		7785909
XP16-048-230	46,500	15.50	11.50	43,000	28,800	3.34	2.50	8.50	CX34-60D	SL280UH135V60D	7785934
XP16-048-230	46,500	16.00	11.50	43,500	29,000	3.36	2.50	8.50	CX34-60D	SLP98UH135XV60D	7785937
XP16-048-230	46,000	14.00	11.00	43,500	29,400	3.22	2.42	8.20	CX34-60D		7785912

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-048-230	47,000	15.50	12.00	41,500	28,000	3.46	2.58	9.00	CX34-62C	EL180UH090E60C	7785920
XP16-048-230	47,500	15.00	11.50	42,000	28,600	3.44	2.56	9.00	CX34-62C	EL180UH110E60C	7785922
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.40	2.54	8.70	CX34-62C	EL195UH090XE48C	7785929
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.44	2.56	9.00	CX34-62C	EL195UH110XE60C	7785954
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.40	2.54	8.70	CX34-62C	EL296UH090XE48C	7785945
XP16-048-230	47,000	15.50	11.50	42,000	28,400	3.42	2.54	8.70	CX34-62C	EL296UH090XV48C	7785942
XP16-048-230	47,000	15.50	11.50	42,000	28,400	3.42	2.54	8.70	CX34-62C	EL296UH090XV60C	7785935
XP16-048-230	47,000	15.00	12.00	41,500	28,200	3.44	2.56	9.00	CX34-62C	EL296UH110XE60C	7785939
XP16-048-230	47,000	15.50	12.00	41,500	28,200	3.42	2.56	8.70	CX34-62C	EL296UH110XV48C	7785926
XP16-048-230	47,000	15.50	11.50	42,000	28,400	3.44	2.54	8.70	CX34-62C	EL296UH110XV60C	7785949
XP16-048-230	47,000	15.50	12.00	41,500	28,200	3.46	2.58	9.00	CX34-62C	SL280UH090V60C	7785930
XP16-048-230	47,000	15.50	12.00	41,500	28,200	3.46	2.58	9.00	CX34-62C	SL280UH090XV60C	7785955
XP16-048-230	47,000	15.50	12.00	41,500	28,200	3.46	2.58	9.00	CX34-62C	SL280UH110V60C	7785946
XP16-048-230	47,000	15.50	12.00	41,500	28,200	3.46	2.58	9.00	CX34-62C	SL280UH110XV60C	7785940
XP16-048-230	47,000	15.50	11.50	42,000	28,200	3.44	2.54	8.70	CX34-62C	SLP98UH090XV48C	7785943
XP16-048-230	47,000	15.00	11.50	42,000	28,200	3.46	2.54	8.70	CX34-62C	SLP98UH090XV60C	7785936
XP16-048-230	47,000	15.50	11.50	42,000	28,400	3.44	2.54	8.70	CX34-62C	SLP98UH110XV60C	7785927
XP16-048-230	46,500	14.00	11.00	42,000	28,800	3.32	2.50	8.50	CX34-62C		7785911
XP16-048-230	48,500	16.00	12.00	43,000	27,600	3.42	2.44	8.50	CX34-62D	EL296UH135XV60D	7785947
XP16-048-230	48,000	16.00	12.00	42,500	27,600	3.40	2.46	8.50	CX34-62D	SL280UH135V60D	7785941
XP16-048-230	48,500	16.00	12.00	43,000	27,800	3.44	2.46	8.50	CX34-62D	SLP98UH135XV60D	7785932
XP16-048-230	48,000	15.00	11.50	43,000	28,200	3.28	2.40	8.20	CX34-62D		7785910
XP16-060-230	58,500	15.70	12.20	53,000	34,800	3.22	2.38	8.50	C33-62D	EL180UH135E60D	7785992
XP16-060-230	58,000	15.20	11.50	53,000	35,200	3.18	2.36	8.20	C33-62D	EL195UH135XE60D	7785987
XP16-060-230	58,000	15.20	11.50	53,000	35,200	3.18	2.36	8.20	C33-62D	EL296UH135XE60D	7785985
XP16-060-230	58,500	15.70	12.00	53,000	34,800	3.22	2.38	8.50	C33-62D	EL296UH135XV60D	7785990
XP16-060-230	58,000	15.70	12.00	53,000	35,000	3.20	2.38	8.50	C33-62D	SL280UH135V60D	7785994
XP16-060-230	58,500	15.70	12.00	53,000	34,800	3.22	2.38	8.50	C33-62D	SLP98UH135XV60D	7786000
XP16-060-230	57,000	14.50	11.50	53,000	35,000	3.16	2.36	8.20	C33-62D		7785977
XP16-060-230	57,000	15.00	11.50	53,500	35,400	3.24	2.44	8.20	CBX25UHV-060		7785988
XP16-060-230	58,000	15.50	12.00	56,500	34,400	3.62	2.52	8.50	CBX27UH-060		7785978
XP16-060-230	57,000	14.50	11.50	56,000	36,200	3.32	2.46	8.50	CBX32M-060		7785980
XP16-060-230	57,000	15.70	12.00	55,500	35,800	3.34	2.48	8.50	CBX32MV-060		7785979
XP16-060-230	58,000	15.70	12.20	55,500	34,000	3.38	2.42	8.20	CBX32MV-068		7785982
XP16-060-230	57,000	15.50	11.50	56,000	36,000	3.36	2.46	8.50	CBX40UHV-060		7785981
XP16-060-230	58,500	15.50	11.50	61,000	37,400	3.48	2.44	8.50	CH23-68	EL180UH135E60D	7785983
XP16-060-230	58,500	15.20	11.50	61,500	37,600	3.44	2.40	8.50	CH23-68	EL195UH135XE60D	7786017
XP16-060-230	58,500	15.20	11.50	61,500	37,600	3.44	2.40	8.50	CH23-68	EL296UH135XE60D	7786015
XP16-060-230	59,000	15.50	11.50	61,500	37,600	3.46	2.42	8.50	CH23-68	EL296UH135XV60D	7786013
XP16-060-230	58,500	15.70	11.50	61,000	37,400	3.46	2.42	8.50	CH23-68	SL280UH135V60D	7786012
XP16-060-230	59,000	15.50	11.50	61,500	37,600	3.46	2.42	8.50	CH23-68	SLP98UH135XV60D	7786014

## NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP16-060-230	58,500	14.50	11.50	61,500	37,800	3.42	2.40	8.20	CH23-68		7785974
XP16-060-230	54,500	15.70	11.50	52,500	34,600	3.14	2.34	8.20	CH33-62D	EL180UH135E60D	7786008
XP16-060-230	54,500	15.20	11.00	53,000	35,000	3.10	2.32	8.20	CH33-62D	EL195UH135XE60D	7786007
XP16-060-230	54,500	15.20	11.00	53,000	35,000	3.10	2.32	8.20	CH33-62D	EL296UH135XE60D	7786016
XP16-060-230	54,500	15.50	11.00	53,000	34,800	3.14	2.32	8.20	CH33-62D	EL296UH135XV60D	7786002
XP16-060-230	54,500	15.70	11.00	53,000	34,800	3.14	2.32	8.20	CH33-62D	SL280UH135V60D	7786010
XP16-060-230	54,500	15.50	11.00	53,000	34,800	3.14	2.32	8.20	CH33-62D	SLP98UH135XV60D	7786011
XP16-060-230	57,500	15.20	12.00	57,500	37,200	3.28	2.46	8.50	CR33-50/60	EL180DF110E60C	7786006
XP16-060-230	57,000	15.00	12.00	57,000	37,200	3.18	2.44	8.20	CR33-50/60	EL195DF110XE60C	7785997
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-50/60	EL296DF090XV60C	7785998
XP16-060-230	57,000	15.00	12.00	57,000	37,200	3.18	2.44	8.20	CR33-50/60	EL296DF110XE60C	7785995
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-50/60	EL296DF110XV60C	7785996
XP16-060-230	57,000	15.20	11.50	57,500	37,400	3.24	2.46	8.50	CR33-50/60	SL280DF090V60C	7786004
XP16-060-230	57,000	15.20	12.00	57,500	37,200	3.24	2.46	8.50	CR33-50/60	SL280DF110V60C	7786018
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-50/60	SLP98DF090XV60C	7786003
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-50/60	SLP98DF110XV60C	7786001
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-60	EL296DF110XV60C	7786005
XP16-060-230	56,500	15.00	11.50	57,000	37,400	3.14	2.42	8.20	CR33-60	SLP98DF110XV60C	7786009
XP16-060-230	57,000	14.20	11.50	57,500	37,600	3.16	2.40	8.20	CR33-60		7785975
XP16-060-230	58,500	15.70	12.20	53,000	34,800	3.22	2.38	8.50	CX34-62D	EL180UH135E60D	7785991
XP16-060-230	58,000	15.20	11.50	53,000	35,200	3.18	2.36	8.20	CX34-62D	EL195UH135XE60D	7785986
XP16-060-230	58,000	15.20	11.50	53,000	35,200	3.18	2.36	8.20	CX34-62D	EL296UH135XE60D	7785984
XP16-060-230	58,500	15.70	12.00	53,000	34,800	3.22	2.38	8.50	CX34-62D	EL296UH135XV60D	7785989
XP16-060-230	58,000	15.70	12.00	53,000	35,000	3.20	2.38	8.50	CX34-62D	SL280UH135V60D	7785993
XP16-060-230	58,500	15.70	12.00	53,000	34,800	3.22	2.38	8.50	CX34-62D	SLP98UH135XV60D	7785999
XP16-060-230	57,000	14.50	11.50	53,000	35,000	3.16	2.36	8.20	CX34-62D		7785976

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (ordered extra).

To convert HSPF from Region IV to Region V - Divide by 1.15.





PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.58	2.52	8.50	C33-31	EL180UH045E36A	5741669
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.58	2.52	8.50	C33-31	EL180UH045XE36A	5741821
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.64	2.56	8.50	C33-31	EL180UH070E36B	5741895
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.64	2.56	8.50	C33-31	EL180UH070XE36B	5742111
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.54	2.50	8.50	C33-31	EL195UH045XE36B	4693555
XP17-024-230	24,600	17.00	14.00	21,200	14,100	3.62	2.54	9.00	C33-31	EL195UH070XE36B	4693556
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.54	2.50	8.50	C33-31	EL296UH045XE36B	5651006
XP17-024-230	24,600	17.00	14.00	21,200	14,100	3.62	2.54	9.00	C33-31	EL296UH070XE36B	5651008
XP17-024-230	24,600	17.00	14.00	21,200	14,000	3.60	2.54	9.00	C33-31	EL296UH070XV36B	5054700
XP17-024-230	25,000	17.00	14.00	21,400	14,100	3.64	2.56	9.00	C33-31	SL280UH070V36A	3894581
XP17-024-230	25,000	17.00	14.00	21,400	14,100	3.64	2.56	9.00	C33-31	SL280UH070XV36A	4041563
XP17-024-230	24,800	17.00	14.50	21,200	14,000	3.60	2.54	8.70	C33-31	SL280UH090V36B	3894582
XP17-024-230	24,600	16.00	13.50	21,400	14,300	3.46	2.46	8.50	C33-31	SLO185UF79/105V42	7087745
XP17-024-230	24,600	17.00	14.00	21,200	14,000	3.60	2.54	9.00	C33-31	SLP98UH070XV36B	5137369
XP17-024-230	24,200	15.00	12.70	22,000	14,700	3.36	2.36	8.20	C33-31		3839730
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.60	2.54	9.00	C33-38	EL180UH045E36A	5741670
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.60	2.54	9.00	C33-38	EL180UH045XE36A	5741822
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.58	9.00	C33-38	EL180UH070E36B	5741896
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.58	9.00	C33-38	EL180UH070XE36B	5742112
XP17-024-230	24,200	17.00	14.00	21,200	14,100	3.56	2.52	8.50	C33-38	EL195UH045XE36B	4693557
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.66	2.56	9.00	C33-38	EL195UH070XE36B	4693558
XP17-024-230	24,200	17.00	14.00	21,200	14,100	3.56	2.52	8.50	C33-38	EL296UH045XE36B	5651011
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.66	2.56	9.00	C33-38	EL296UH070XE36B	5651013
XP17-024-230	24,600	16.00	14.00	21,400	14,100	3.70	2.58	9.00	C33-38	SL280UH070V36A	3894583
XP17-024-230	24,600	16.00	14.00	21,400	14,100	3.70	2.58	9.00	C33-38	SL280UH070XV36A	4041564
XP17-024-230	24,200	16.00	14.00	21,200	14,000	3.62	2.56	9.00	C33-38	SL280UH090V36B	3894584
XP17-024-230	24,200	16.00	13.50	21,400	14,300	3.48	2.46	8.50	C33-38	SLO185UF79/105V42	7087746
XP17-024-230	24,000	17.00	14.00	21,400	14,100	3.70	2.58	9.00	C33-38	SLP98UH070XV36B	5629091
XP17-024-230	24,000	15.00	12.50	22,000	14,700	3.40	2.38	8.50	C33-38		3839737
XP17-024-230	24,600	17.00	14.00	22,000	14,300	3.74	2.66	9.00	CBX27UH-024		3839712
XP17-024-230	24,800	17.70	14.50	22,000	14,200	3.84	2.70	9.50	CBX27UH-030		3839713
XP17-024-230	24,200	15.70	13.20	22,400	14,600	3.58	2.54	9.00	CBX32M-030		3839714
XP17-024-230	24,200	15.70	13.20	22,600	14,700	3.62	2.56	8.70	CBX32M-036		3839715
XP17-024-230	25,000	17.50	14.50	22,200	14,400	3.82	2.68	9.50	CBX32MV-024/030		3839707
XP17-024-230	25,000	17.00	14.00	22,400	14,500	3.86	2.70	9.50	CBX32MV-036		3839708
XP17-024-230	24,800	17.00	14.00	22,200	14,400	3.80	2.68	9.50	CBX40UHV-024		3839709
XP17-024-230	24,600	17.00	14.00	22,200	14,400	3.78	2.68	9.00	CBX40UHV-030		3839710
XP17-024-230	25,200	17.00	14.00	22,400	14,500	3.88	2.72	9.50	CBX40UHV-036		3839711

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-024-230	24,200	16.70	13.50	21,400	14,100	3.60	2.52	8.50	CH33-31	SL280UH090V48B	4249309
XP17-024-230	24,400	16.00	14.00	21,600	14,200	3.70	2.58	9.00	CH33-31A	EL180UH045E36A	5741664
XP17-024-230	24,400	16.00	14.00	21,600	14,200	3.70	2.58	9.00	CH33-31A	EL180UH045XE36A	5741816
XP17-024-230	24,400	17.00	13.50	21,600	14,200	3.76	2.60	9.00	CH33-31A	SL280UH070V36A	3894585
XP17-024-230	24,400	16.00	13.50	21,600	14,200	3.76	2.60	9.00	CH33-31A	SL280UH070XV36A	4041565
XP17-024-230	23,800	15.00	12.50	22,000	14,700	3.42	2.40	8.50	CH33-31A		3839744
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.70	2.58	9.00	CH33-31B	EL180UH070E36B	5741882
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.70	2.58	9.00	CH33-31B	EL180UH070XE36B	5742143
XP17-024-230	24,200	17.00	14.00	21,400	14,100	3.60	2.52	8.50	CH33-31B	EL195UH045XE36B	4693549
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.56	9.00	CH33-31B	EL195UH070XE36B	4693550
XP17-024-230	24,200	17.00	14.00	21,400	14,100	3.60	2.52	8.50	CH33-31B	EL296UH045XE36B	5649758
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.56	9.00	CH33-31B	EL296UH070XE36B	5649762
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.70	2.58	9.00	CH33-31B	EL296UH070XV36B	5054698
XP17-024-230	24,200	17.00	14.00	21,200	14,000	3.64	2.56	9.00	CH33-31B	SL280UH090V36B	3894586
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.70	2.58	9.00	CH33-31B	SLP98UH070XV36B	5137321
XP17-024-230	23,800	15.00	12.50	21,800	14,600	3.34	2.36	8.20	CH33-31B		3839746
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.64	2.56	9.00	CH33-42	EL180UH070E36B	5741894
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.64	2.56	9.00	CH33-42	EL180UH070XE36B	5742110
XP17-024-230	24,000	16.00	13.50	21,200	14,100	3.54	2.50	8.50	CH33-42	EL195UH045XE36B	4693551
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.62	2.54	9.00	CH33-42	EL195UH070XE36B	4693552
XP17-024-230	24,000	16.00	13.50	21,200	14,100	3.54	2.50	8.50	CH33-42	EL296UH045XE36B	5649763
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.62	2.54	9.00	CH33-42	EL296UH070XE36B	5649764
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.66	2.56	9.00	CH33-42	EL296UH070XV36B	5054699
XP17-024-230	24,200	17.00	14.00	21,200	14,000	3.60	2.54	8.70	CH33-42	SL280UH090V36B	3894587
XP17-024-230	24,000	16.70	13.50	21,400	14,100	3.56	2.50	8.50	CH33-42	SL280UH090V48B	4249310
XP17-024-230	24,400	17.00	14.00	21,400	14,100	3.66	2.56	9.00	CH33-42	SLP98UH070XV36B	5137322
XP17-024-230	23,600	14.70	12.50	21,800	14,600	3.30	2.34	8.20	CH33-42		3839752
XP17-024-230	22,400	15.00	12.50	21,600	14,300	3.78	2.64	9.00	CR33-48	EL180DF070E36B	5741539
XP17-024-230	22,400	15.50	13.00	21,600	14,300	3.66	2.58	9.00	CR33-48	EL195DF045XE36B	4693553
XP17-024-230	22,600	15.70	13.00	21,800	14,300	3.76	2.62	9.20	CR33-48	EL195DF070XE48B	4693554
XP17-024-230	22,400	15.50	13.00	21,600	14,300	3.66	2.58	9.00	CR33-48	EL296DF045XE36B	5649765
XP17-024-230	29,200	15.50	12.70	21,800	14,400	3.68	2.58	9.20	CR33-48	EL296DF045XV36B	7505738
XP17-024-230	22,600	15.70	13.00	21,800	14,300	3.76	2.62	9.20	CR33-48	EL296DF070XE48B	5649766
XP17-024-230	22,400	15.00	12.50	21,800	14,400	3.68	2.58	9.00	CR33-48	SL280DF070V36A	3894588
XP17-024-230	22,400	15.00	12.50	21,600	14,300	3.64	2.58	9.00	CR33-48	SL280DF090V48B	3894589
XP17-024-230	22,600	15.70	13.00	21,800	14,400	3.72	2.62	9.20	CR33-48	SLP98DF070XV36B	5136883
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.58	2.52	8.50	CX34-31	EL180UH045E36A	5741662
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.58	2.52	8.50	CX34-31	EL180UH045XE36A	5741814
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.64	2.56	8.50	CX34-31	EL180UH070E36B	5741880
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.64	2.56	8.50	CX34-31	EL180UH070XE36B	5742141
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.54	2.50	8.50	CX34-31	EL195UH045XE36B	4693545
XP17-024-230	24,600	17.00	14.00	21,200	14,100	3.62	2.54	9.00	CX34-31	EL195UH070XE36B	4693546

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.54	2.50	8.50	CX34-31	EL296UH045XE36B	5649754
XP17-024-230	24,600	17.00	14.00	21,200	14,100	3.62	2.54	9.00	CX34-31	EL296UH070XE36B	5649755
XP17-024-230	24,600	17.00	14.00	21,200	14,000	3.60	2.54	9.00	CX34-31	EL296UH070XV36B	5054697
XP17-024-230	25,000	17.00	14.00	21,400	14,100	3.64	2.56	9.00	CX34-31	SL280UH070V36A	3894577
XP17-024-230	25,000	17.00	14.00	21,400	14,100	3.64	2.56	9.00	CX34-31	SL280UH070XV36A	4041561
XP17-024-230	24,800	17.00	14.50	21,200	14,000	3.60	2.54	8.70	CX34-31	SL280UH090V36B	3894578
XP17-024-230	24,800	17.00	14.00	21,200	14,100	3.52	2.50	8.50	CX34-31	SL280UH090V48B	4249307
XP17-024-230	24,600	16.00	13.50	21,400	14,200	3.48	2.46	8.50	CX34-31	SLO185UF79/105V42	7087743
XP17-024-230	24,600	17.00	14.00	21,200	14,000	3.60	2.54	9.00	CX34-31	SLP98UH070XV36B	5136882
XP17-024-230	24,200	15.00	12.70	22,000	14,700	3.36	2.36	8.20	CX34-31		3839716
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.60	2.54	9.00	CX34-38	EL180UH045E36A	5741663
XP17-024-230	24,400	16.00	14.00	21,400	14,200	3.60	2.54	9.00	CX34-38	EL180UH045XE36A	5741815
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.58	9.00	CX34-38	EL180UH070E36B	5741881
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.68	2.58	9.00	CX34-38	EL180UH070XE36B	5742142
XP17-024-230	24,200	17.00	14.00	21,200	14,100	3.56	2.52	8.50	CX34-38	EL195UH045XE36B	4693547
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.66	2.56	9.00	CX34-38	EL195UH070XE36B	4693548
XP17-024-230	24,200	17.00	14.00	21,200	14,100	3.56	2.52	8.50	CX34-38	EL296UH045XE36B	5649756
XP17-024-230	24,600	17.00	14.00	21,400	14,100	3.66	2.56	9.00	CX34-38	EL296UH070XE36B	5649757
XP17-024-230	24,600	16.00	14.00	21,400	14,100	3.70	2.58	9.00	CX34-38	SL280UH070V36A	3894579
XP17-024-230	24,600	16.00	14.00	21,400	14,100	3.70	2.58	9.00	CX34-38	SL280UH070XV36A	4041562
XP17-024-230	24,200	16.00	14.00	21,200	14,000	3.62	2.56	9.00	CX34-38	SL280UH090V36B	3894580
XP17-024-230	24,200	15.10	13.50	21,400	14,100	3.58	2.52	8.50	CX34-38	SL280UH090V48B	4249308
XP17-024-230	24,200	16.00	13.50	21,400	14,300	3.48	2.46	8.50	CX34-38	SLO185UF79/105V42	7087744
XP17-024-230	24,000	17.00	14.00	21,400	14,100	3.70	2.58	9.00	CX34-38	SLP98UH070XV36B	5629092
XP17-024-230	24,000	15.00	12.50	22,000	14,700	3.40	2.38	8.50	CX34-38		3839723
XP17-030-230	28,000	16.00	13.00	25,600	16,800	3.50	2.50	8.50	C33-31	CBWMV-36B-070	4605502
XP17-030-230	28,800	15.70	13.20	25,600	16,900	3.46	2.48	8.50	C33-31	EL180UH045E36A	5741671
XP17-030-230	28,800	15.70	13.20	25,600	16,900	3.46	2.48	8.50	C33-31	EL180UH045XE36A	5741823
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	C33-31	EL180UH070E36B	5741897
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	C33-31	EL180UH070XE36B	5742113
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.52	8.50	C33-31	EL180UH090E48B	5742248
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.52	8.50	C33-31	EL180UH090XE48B	5740345
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	C33-31	EL195UH045XE36B	4693575
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.54	2.50	8.50	C33-31	EL195UH070XE36B	4693576
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	C33-31	EL296UH045XE36B	5649753
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.54	2.50	8.50	C33-31	EL296UH070XE36B	5649759
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.52	2.50	8.50	C33-31	EL296UH070XV36B	5054712
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.54	2.52	8.50	C33-31	SL280UH070V36A	3894612
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.54	2.52	8.50	C33-31	SL280UH070XV36A	4041573
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	C33-31	SL280UH090V36B	3894613
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	C33-31	SL280UH090V48B	3894614
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	C33-31	SL280UH090XV48B	4041758

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.52	2.50	8.50	C33-31	SLP98UH070XV36B	5137327
XP17-030-230	28,400	14.50	12.20	26,000	17,300	3.28	2.36	8.20	C33-31		3839790
XP17-030-230	29,000	16.00	13.00	25,600	16,900	3.50	2.50	8.50	C33-38	EL180UH045E36A	5741672
XP17-030-230	29,000	16.00	13.00	25,600	16,900	3.50	2.50	8.50	C33-38	EL180UH045XE36A	5741824
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	C33-38	EL180UH070E36B	5741898
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	C33-38	EL180UH070XE36B	5742114
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.58	8.50	C33-38	EL180UH090E48B	5742249
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.58	8.50	C33-38	EL180UH090XE48B	5740346
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	C33-38	EL195UH045XE36B	4693577
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.56	2.54	8.50	C33-38	EL195UH070XE36B	4693578
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	C33-38	EL296UH045XE36B	5649760
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.56	2.54	8.50	C33-38	EL296UH070XE36B	5649761
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.54	2.52	8.50	C33-38	EL296UH070XV36B	5054713
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.54	8.50	C33-38	SL280UH070V36A	3894615
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.54	8.50	C33-38	SL280UH070XV36A	4041574
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	C33-38	SL280UH090V36B	3894616
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	C33-38	SL280UH090V48B	3894617
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	C33-38	SL280UH090XV48B	4041759
XP17-030-230	29,000	15.00	12.50	25,800	17,100	3.42	2.44	8.50	C33-38	SLO185UF79/105V42	7087749
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.54	2.52	8.50	C33-38	SLP98UH070XV36B	5137328
XP17-030-230	28,800	14.70	12.20	26,200	17,400	3.34	2.40	8.20	C33-38		3839797
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	C33-43	EL180UH070E36B	5741899
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	C33-43	EL180UH070XE36B	5742115
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	C33-43	EL180UH090E48B	5742250
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	C33-43	EL180UH090XE48B	5740347
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.50	8.50	C33-43	EL195UH045XE36B	4693579
XP17-030-230	29,400	16.00	13.50	25,600	17,000	3.56	2.52	8.50	C33-43	EL195UH070XE36B	4693580
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	C33-43	EL195UH090XE48C	6350973
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.50	8.50	C33-43	EL296UH045XE36B	5649777
XP17-030-230	29,400	16.00	13.50	25,600	17,000	3.56	2.52	8.50	C33-43	EL296UH070XE36B	5649778
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.56	2.52	8.50	C33-43	EL296UH070XV36B	5054714
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	C33-43	EL296UH090XE48C	6350975
XP17-030-230	29,600	16.00	14.00	25,600	16,700	3.64	2.56	8.50	C33-43	EL296UH090XV36C	5054715
XP17-030-230	29,000	16.00	13.50	25,400	16,600	3.58	2.54	8.50	C33-43	EL296UH090XV48C	7786587
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	C33-43	SL280UH090V36B	3894618
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	C33-43	SL280UH090V48B	3894619
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	C33-43	SL280UH090XV48B	4041760
XP17-030-230	29,000	15.00	12.50	25,800	17,100	3.42	2.44	8.50	C33-43	SLO185UF79/105V42	7087750
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.56	2.52	8.50	C33-43	SLP98UH070XV36B	5137329
XP17-030-230	29,600	16.00	14.00	25,600	16,700	3.64	2.56	8.50	C33-43	SLP98UH090XV36C	5137330
XP17-030-230	28,800	14.70	12.20	26,200	17,300	3.34	2.36	8.20	C33-43		3839804
XP17-030-230	29,200	16.00	13.50	26,800	17,300	3.62	2.60	9.00	CBX27UH-030		3839841

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-030-230	29,200	16.00	13.50	26,800	17,200	3.64	2.60	9.00	CBX27UH-036		3839842
XP17-030-230	28,800	15.50	12.70	27,000	17,500	3.48	2.52	8.70	CBX32M-030		3839766
XP17-030-230	28,800	15.20	12.70	27,200	17,700	3.46	2.50	8.70	CBX32M-036		3839767
XP17-030-230	29,000	16.20	13.50	26,800	17,300	3.58	2.60	9.00	CBX32MV-024/030		3839761
XP17-030-230	29,200	16.00	13.50	26,800	17,300	3.60	2.58	9.00	CBX32MV-036		3839762
XP17-030-230	29,000	16.00	13.50	26,600	17,200	3.56	2.58	9.00	CBX40UHV-024		3839763
XP17-030-230	29,200	16.00	13.50	26,800	17,300	3.60	2.58	9.00	CBX40UHV-030		3839764
XP17-030-230	29,200	16.00	13.50	26,800	17,200	3.62	2.58	9.00	CBX40UHV-036		3839765
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.52	8.50	CH33-31	EL296UH070XV36B	5054701
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.52	8.50	CH33-31	SLP98UH070XV36B	5136857
XP17-030-230	28,600	15.50	13.00	25,800	17,000	3.54	2.52	8.70	CH33-31A	EL180UH045E36A	5741667
XP17-030-230	28,600	15.50	13.00	25,800	17,000	3.54	2.52	8.70	CH33-31A	EL180UH045XE36A	5741819
XP17-030-230	29,000	16.00	13.00	25,800	16,900	3.64	2.56	8.50	CH33-31A	SL280UH070V36A	3894620
XP17-030-230	29,000	16.00	13.00	25,800	16,900	3.64	2.56	8.50	CH33-31A	SL280UH070XV36A	4041575
XP17-030-230	28,600	14.50	12.20	26,200	17,400	3.42	2.44	8.50	CH33-31A		3839812
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.60	2.56	8.50	CH33-31B	EL180UH070E36B	5741886
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.60	2.56	8.50	CH33-31B	EL180UH070XE36B	5742147
XP17-030-230	29,200	16.00	13.50	25,600	16,700	3.62	2.56	8.50	CH33-31B	EL180UH090E48B	5742232
XP17-030-230	29,200	16.00	13.50	25,600	16,700	3.62	2.56	8.50	CH33-31B	EL180UH090XE48B	5740332
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	CH33-31B	EL195UH045XE36B	4693565
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.58	2.54	8.50	CH33-31B	EL195UH070XE36B	4693566
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	CH33-31B	EL296UH045XE36B	5649773
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.58	2.54	8.50	CH33-31B	EL296UH070XE36B	5649774
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.62	2.56	8.50	CH33-31B	SL280UH090V36B	3894621
XP17-030-230	29,400	16.00	13.50	25,800	16,800	3.66	2.56	8.50	CH33-31B	SL280UH090V48B	3894622
XP17-030-230	29,400	16.00	13.50	25,800	16,800	3.66	2.56	8.50	CH33-31B	SL280UH090XV48B	4041761
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CH33-42	EL180UH070E36B	5741887
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CH33-42	EL180UH070XE36B	5742148
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.54	8.50	CH33-42	EL180UH090E48B	5742233
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.54	8.50	CH33-42	EL180UH090XE48B	5740333
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	CH33-42	EL195UH045XE36B	4693567
XP17-030-230	29,200	15.70	13.20	25,800	17,000	3.54	2.52	8.70	CH33-42	EL195UH070XE36B	4693568
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	CH33-42	EL296UH045XE36B	5649775
XP17-030-230	29,200	15.70	13.20	25,800	17,000	3.54	2.52	8.70	CH33-42	EL296UH070XE36B	5649776
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CH33-42	SL280UH090V36B	3894627
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CH33-42	SL280UH090V48B	3894628
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CH33-42	SL280UH090XV48B	4041754
XP17-030-230	28,400	14.50	12.20	26,000	17,300	3.28	2.36	8.20	CH33-42		3839829
XP17-030-230	29,800	16.00	13.50	25,800	16,800	3.72	2.60	9.00	CH33-43	EL180UH070E36B	5741888
XP17-030-230	29,800	16.00	13.50	25,800	16,800	3.72	2.60	9.00	CH33-43	EL180UH070XE36B	5742149
XP17-030-230	29,800	16.00	14.00	25,800	16,800	3.72	2.62	9.00	CH33-43	EL180UH090E48B	5742234
XP17-030-230	29,800	16.00	14.00	25,800	16,800	3.72	2.62	9.00	CH33-43	EL180UH090XE48B	5740334

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-030-230	29,800	16.00	13.50	25,800	16,900	3.66	2.60	9.00	CH33-43	EL296UH070XV36B	5054711
XP17-030-230	29,400	16.00	14.00	25,400	16,600	3.60	2.56	8.50	CH33-43	EL296UH090XV36C	5054702
XP17-030-230	29,200	16.00	14.00	25,400	16,600	3.58	2.54	8.50	CH33-43	EL296UH090XV48C	5054703
XP17-030-230	30,000	16.00	14.00	25,800	16,900	3.72	2.62	9.00	CH33-43	SL280UH090V36B	3894623
XP17-030-230	30,000	16.00	14.00	25,800	16,900	3.74	2.64	9.00	CH33-43	SL280UH090V48B	3894624
XP17-030-230	30,000	16.00	14.00	25,800	16,900	3.74	2.64	9.00	CH33-43	SL280UH090XV48B	4041762
XP17-030-230	29,800	16.00	13.50	25,800	16,900	3.66	2.60	9.00	CH33-43	SLP98UH070XV36B	5136888
XP17-030-230	29,400	16.00	14.00	25,400	16,600	3.60	2.56	8.50	CH33-43	SLP98UH090XV36C	5136858
XP17-030-230	29,200	16.00	14.00	25,400	16,600	3.58	2.54	8.50	CH33-43	SLP98UH090XV48C	5136859
XP17-030-230	29,600	16.00	13.50	25,800	17,000	3.62	2.58	8.50	CH33-43B	EL195UH045XE36B	4693569
XP17-030-230	29,800	16.00	13.50	25,800	17,000	3.68	2.58	9.00	CH33-43B	EL195UH070XE36B	4693570
XP17-030-230	29,600	16.00	13.50	25,800	17,000	3.62	2.58	8.50	CH33-43B	EL296UH045XE36B	5649747
XP17-030-230	29,800	16.00	13.50	25,800	17,000	3.68	2.58	9.00	CH33-43B	EL296UH070XE36B	5649748
XP17-030-230	29,400	16.00	13.50	25,800	16,800	3.68	2.58	9.00	CH33-44/48	EL180UH070E36B	5741889
XP17-030-230	29,400	16.00	13.50	25,800	16,800	3.68	2.58	9.00	CH33-44/48	EL180UH070XE36B	5742150
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.66	2.60	9.00	CH33-44/48	EL180UH090E48B	5742235
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.66	2.60	9.00	CH33-44/48	EL180UH090XE48B	5740335
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.60	2.54	8.50	CH33-44/48	EL195UH045XE36B	4693571
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.64	2.56	8.50	CH33-44/48	EL195UH070XE36B	4693572
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.60	2.54	8.50	CH33-44/48	EL296UH045XE36B	5649749
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.64	2.56	8.50	CH33-44/48	EL296UH070XE36B	5649750
XP17-030-230	29,400	16.00	13.50	25,800	16,800	3.70	2.60	9.00	CH33-44/48	SL280UH090V36B	3894625
XP17-030-230	29,400	16.00	13.50	25,800	16,900	3.70	2.62	9.00	CH33-44/48	SL280UH090V48B	3894626
XP17-030-230	29,400	16.00	13.50	25,800	16,900	3.70	2.62	9.00	CH33-44/48	SL280UH090XV48B	4041763
XP17-030-230	28,800	14.70	12.20	26,200	17,400	3.38	2.42	8.20	CH33-44/48		3839823
XP17-030-230	28,800	16.00	13.50	25,400	16,700	3.48	2.50	8.50	CH33-48	EL296UH070XV36B	5054706
XP17-030-230	29,200	16.00	13.50	25,400	16,700	3.54	2.52	8.50	CH33-48	EL296UH090XV36C	5054704
XP17-030-230	29,000	16.00	13.50	25,400	16,600	3.52	2.50	8.50	CH33-48	EL296UH090XV48C	5054705
XP17-030-230	28,800	16.00	13.50	25,400	16,700	3.48	2.50	8.50	CH33-48	SLP98UH070XV36B	5136863
XP17-030-230	29,200	16.00	13.50	25,400	16,700	3.54	2.52	8.50	CH33-48	SLP98UH090XV36C	5136861
XP17-030-230	29,000	16.00	13.50	25,400	16,600	3.52	2.50	8.50	CH33-48	SLP98UH090XV48C	5136862
XP17-030-230	28,200	15.70	13.20	26,600	17,200	3.52	2.56	8.70	CR33-48	EL180DF070E36B	5741538
XP17-030-230	27,800	16.00	13.00	28,400	18,400	3.64	2.62	9.00	CR33-48	EL180DF090E48B	5741587
XP17-030-230	28,200	15.20	12.70	26,800	17,400	3.46	2.52	8.70	CR33-48	EL195DF045XE36B	4693573
XP17-030-230	28,000	15.20	12.70	26,600	17,400	3.46	2.52	8.70	CR33-48	EL195DF070XE48B	4693574
XP17-030-230	28,200	15.20	12.70	26,800	17,400	3.46	2.52	8.70	CR33-48	EL296DF045XE36B	5649751
XP17-030-230	27,400	15.50	12.70	26,600	17,200	3.56	2.58	8.70	CR33-48	EL296DF045XV36B	5549507
XP17-030-230	28,000	15.20	12.70	26,600	17,400	3.46	2.52	8.70	CR33-48	EL296DF070XE48B	5649752
XP17-030-230	27,400	15.20	12.70	26,800	17,300	3.56	2.56	8.50	CR33-48	EL296DF070XV48B	5549508
XP17-030-230	28,200	15.00	12.50	26,800	17,300	3.52	2.56	8.50	CR33-48	SL280DF070V36A	3894629
XP17-030-230	27,800	15.00	12.50	26,400	17,200	3.42	2.54	8.50	CR33-48	SL280DF090V48B	3894630
XP17-030-230	28,000	15.50	13.00	26,600	17,200	3.44	2.52	8.70	CR33-48	SLP98DF070XV36B	5137323

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-030-230	27,800	15.70	13.20	26,400	17,100	3.44	2.54	8.70	CR33-48	SLP98DF090XV36C	5137324
XP17-030-230	27,800	15.70	13.20	26,400	17,100	3.44	2.54	8.70	CR33-48	SLP98DF090XV48C	5137325
XP17-030-230	27,600	14.00	11.00	27,200	17,800	3.28	2.40	8.20	CR33-48		3839835
XP17-030-230	28,000	16.00	13.00	25,600	16,800	3.50	2.50	8.50	CX34-31	CBWMV-36B-070	4605503
XP17-030-230	28,800	15.70	13.20	25,600	16,900	3.46	2.48	8.50	CX34-31	EL180UH045E36A	5741665
XP17-030-230	28,800	15.70	13.20	25,600	16,900	3.46	2.48	8.50	CX34-31	EL180UH045XE36A	5741817
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CX34-31	EL180UH070E36B	5741883
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CX34-31	EL180UH070XE36B	5742144
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.52	8.50	CX34-31	EL180UH090E48B	5742229
XP17-030-230	29,000	16.00	13.50	25,400	16,700	3.54	2.52	8.50	CX34-31	EL180UH090XE48B	5740329
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	CX34-31	EL195UH045XE36B	4693559
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.54	2.50	8.50	CX34-31	EL195UH070XE36B	4693560
XP17-030-230	29,000	15.70	13.20	25,600	16,900	3.48	2.48	8.50	CX34-31	EL296UH045XE36B	5649767
XP17-030-230	29,000	16.00	13.00	25,600	17,000	3.54	2.50	8.50	CX34-31	EL296UH070XE36B	5649768
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.52	2.50	8.50	CX34-31	EL296UH070XV36B	5054707
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.54	2.52	8.50	CX34-31	SL280UH070V36A	3894604
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.54	2.52	8.50	CX34-31	SL280UH070XV36A	4041571
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CX34-31	SL280UH090V36B	3894605
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CX34-31	SL280UH090V48B	3894606
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.58	2.54	8.50	CX34-31	SL280UH090XV48B	4041755
XP17-030-230	29,000	16.00	13.50	25,600	16,800	3.52	2.50	8.50	CX34-31	SLP98UH070XV36B	5136884
XP17-030-230	28,400	14.50	12.20	26,000	17,300	3.28	2.36	8.20	CX34-31		3839768
XP17-030-230	29,000	16.00	13.00	25,600	16,900	3.50	2.50	8.50	CX34-38	EL180UH045E36A	5741666
XP17-030-230	29,000	16.00	13.00	25,600	16,900	3.50	2.50	8.50	CX34-38	EL180UH045XE36A	5741818
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	CX34-38	EL180UH070E36B	5741884
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	CX34-38	EL180UH070XE36B	5742145
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.58	8.50	CX34-38	EL180UH090E48B	5742230
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.58	8.50	CX34-38	EL180UH090XE48B	5740330
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	CX34-38	EL195UH045XE36B	4693561
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.56	2.54	8.50	CX34-38	EL195UH070XE36B	4693562
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.52	8.50	CX34-38	EL296UH045XE36B	5649769
XP17-030-230	29,200	16.00	13.00	25,600	17,000	3.56	2.54	8.50	CX34-38	EL296UH070XE36B	5649770
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.54	2.52	8.50	CX34-38	EL296UH070XV36B	5054708
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CX34-38	SL280UH070V36A	3894607
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.56	2.54	8.50	CX34-38	SL280UH070XV36A	4041572
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.56	8.50	CX34-38	SL280UH090V36B	3894608
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	CX34-38	SL280UH090V48B	3894609
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	CX34-38	SL280UH090XV48B	4041756
XP17-030-230	29,000	15.00	12.50	25,800	17,100	3.42	2.44	8.50	CX34-38	SLO185UF79/105V42	7087747
XP17-030-230	29,200	16.00	13.50	25,600	16,800	3.54	2.52	8.50	CX34-38	SLP98UH070XV36B	5136885
XP17-030-230	28,800	14.70	12.20	26,200	17,400	3.34	2.40	8.20	CX34-38		3839775
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	CX34-43	EL180UH070E36B	5741885

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	CX34-43	EL180UH070XE36B	5742146
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	CX34-43	EL180UH090E48B	5742231
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	CX34-43	EL180UH090XE48B	5740331
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.50	8.50	CX34-43	EL195UH045XE36B	4693563
XP17-030-230	29,400	16.00	13.50	25,600	17,000	3.56	2.52	8.50	CX34-43	EL195UH070XE36B	4693564
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	CX34-43	EL195UH090XE48C	6350974
XP17-030-230	29,200	16.00	13.00	25,800	16,900	3.54	2.50	8.50	CX34-43	EL296UH045XE36B	5649771
XP17-030-230	29,400	16.00	13.50	25,600	17,000	3.56	2.52	8.50	CX34-43	EL296UH070XE36B	5649772
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.56	2.52	8.50	CX34-43	EL296UH070XV36B	5054709
XP17-030-230	29,400	16.00	13.50	25,600	16,700	3.60	2.54	8.50	CX34-43	EL296UH090XE48C	6350976
XP17-030-230	29,600	16.00	14.00	25,600	16,700	3.64	2.56	8.50	CX34-43	EL296UH090XV36C	5054710
XP17-030-230	29,000	16.00	13.50	25,400	16,600	3.58	2.54	8.50	CX34-43	EL296UH090XV48C	7786586
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.60	2.54	8.50	CX34-43	SL280UH090V36B	3894610
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	CX34-43	SL280UH090V48B	3894611
XP17-030-230	29,600	16.00	13.50	25,600	16,800	3.62	2.56	8.50	CX34-43	SL280UH090XV48B	4041757
XP17-030-230	29,000	15.00	12.50	25,800	17,100	3.42	2.44	8.50	CX34-43	SLO185UF79/105V42	7087748
XP17-030-230	29,400	16.00	13.50	25,600	16,800	3.56	2.52	8.50	CX34-43	SLP98UH070XV36B	5136886
XP17-030-230	29,600	16.00	14.00	25,600	16,700	3.64	2.56	8.50	CX34-43	SLP98UH090XV36C	5136887
XP17-030-230	28,800	14.70	12.20	26,200	17,300	3.34	2.36	8.20	CX34-43		3839782
XP17-036-230	35,400	15.00	12.50	31,800	20,000	3.10	2.40	8.20	C33-38	EL180UH045E36A	5741673
XP17-036-230	35,400	15.00	12.50	31,800	20,000	3.10	2.40	8.20	C33-38	EL180UH045XE36A	5741825
XP17-036-230	35,200	15.70	13.00	31,200	19,600	3.12	2.44	8.50	C33-38	EL180UH070E36B	5741900
XP17-036-230	35,200	15.70	13.00	31,200	19,600	3.12	2.44	8.50	C33-38	EL180UH070XE36B	5742116
XP17-036-230	36,000	15.50	12.70	31,800	20,000	3.22	2.46	8.50	C33-38	EL180UH090E48B	5742251
XP17-036-230	36,000	15.50	12.70	31,800	20,000	3.22	2.46	8.50	C33-38	EL180UH090XE48B	5740348
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.06	2.40	8.20	C33-38	EL195UH045XE36B	4693614
XP17-036-230	35,400	14.70	12.20	31,400	20,200	3.10	2.38	8.20	C33-38	EL195UH070XE36B	4693615
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.06	2.40	8.20	C33-38	EL296UH045XE36B	5649812
XP17-036-230	35,400	14.70	12.20	31,400	20,200	3.10	2.38	8.20	C33-38	EL296UH070XE36B	5649813
XP17-036-230	35,400	15.50	12.70	31,400	19,800	3.12	2.44	8.20	C33-38	EL296UH070XV36B	5054746
XP17-036-230	35,600	15.00	12.50	31,800	20,000	3.14	2.42	8.50	C33-38	SL280UH070V36A	3894674
XP17-036-230	35,600	15.00	12.50	31,800	20,000	3.14	2.42	8.50	C33-38	SL280UH070XV36A	4041582
XP17-036-230	35,400	16.00	13.00	31,200	19,600	3.14	2.46	8.50	C33-38	SL280UH090V36B	3894675
XP17-036-230	35,800	16.00	13.00	31,600	19,800	3.20	2.48	8.50	C33-38	SL280UH090V48B	3894676
XP17-036-230	35,800	16.00	13.00	31,600	19,800	3.20	2.48	8.50	C33-38	SL280UH090XV48B	4041777
XP17-036-230	35,400	15.50	12.70	31,400	19,800	3.12	2.44	8.20	C33-38	SLP98UH070XV36B	5137331
XP17-036-230	35,200	14.50	12.00	32,200	20,400	3.04	2.34	8.20	C33-38		3839906
XP17-036-230	35,600	16.00	13.00	31,200	19,600	3.12	2.44	8.20	C33-43	EL180UH070E36B	5742028
XP17-036-230	36,200	15.70	13.00	31,800	20,000	3.20	2.46	8.50	C33-43	EL180UH090E48B	5740310
XP17-036-230	36,200	16.00	13.00	31,600	19,800	3.22	2.50	8.50	C33-43	EL180UH090E60C	5742489
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	C33-43	EL180UH110E60C	5740474
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	C33-43	EL180UH110XE60C	5740826

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,800	14.70	12.20	32,000	20,400	3.06	2.38	8.20	C33-43	EL195UH045XE36B	4693616
XP17-036-230	35,600	15.00	12.20	31,400	20,200	3.08	2.38	8.20	C33-43	EL195UH070XE36B	4693617
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.16	2.46	8.50	C33-43	EL195UH090XE48C	4693618
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	C33-43	EL195UH110XE60C	4693619
XP17-036-230	35,800	14.70	12.20	32,000	20,400	3.06	2.38	8.20	C33-43	EL296UH045XE36B	5649814
XP17-036-230	35,600	15.00	12.20	31,400	20,200	3.08	2.38	8.20	C33-43	EL296UH070XE36B	5649815
XP17-036-230	35,600	15.70	12.70	31,400	19,800	3.10	2.44	8.20	C33-43	EL296UH070XV36B	5054747
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.16	2.46	8.50	C33-43	EL296UH090XE48C	5649816
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-43	EL296UH090XV36C	5054748
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	C33-43	EL296UH090XV48C	5054749
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	C33-43	EL296UH110XE60C	5649817
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	C33-43	EL296UH110XV48C	5685206
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	C33-43	EL296UH110XV60C	5054750
XP17-036-230	35,800	16.00	13.00	31,200	19,600	3.14	2.46	8.50	C33-43	SL280UH090V36B	3894677
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.48	8.50	C33-43	SL280UH090V48B	3894678
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.26	2.50	8.50	C33-43	SL280UH090V60C	3894679
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.48	8.50	C33-43	SL280UH090XV48B	4041778
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.26	2.50	8.50	C33-43	SL280UH090XV60C	4235833
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.48	8.50	C33-43	SL280UH110V60C	3894680
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.48	8.50	C33-43	SL280UH110XV60C	4041984
XP17-036-230	35,600	15.70	12.70	31,400	19,800	3.10	2.44	8.20	C33-43	SLP98UH070XV36B	5137332
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-43	SLP98UH090XV36C	5137333
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	C33-43	SLP98UH090XV48C	5137334
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	C33-43	SLP98UH110XV60C	5137335
XP17-036-230	35,400	14.50	12.00	32,000	20,400	3.00	2.34	8.20	C33-43		3839913
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.02	2.42	8.20	C33-48	EL180UH070E36B	5742026
XP17-036-230	35,800	15.50	12.70	31,600	19,900	3.10	2.44	8.20	C33-48	EL180UH090E48B	5740309
XP17-036-230	35,400	15.70	12.70	31,200	19,700	3.08	2.44	8.20	C33-48	EL180UH090E60C	5742482
XP17-036-230	35,200	15.50	12.70	31,000	19,500	3.04	2.40	8.20	C33-48	EL180UH110E60C	5740469
XP17-036-230	35,200	15.50	12.70	31,000	19,500	3.04	2.40	8.20	C33-48	EL180UH110XE60C	5740821
XP17-036-230	35,000	14.70	12.20	31,000	20,200	3.00	2.36	8.20	C33-48	EL195UH070XE36B	4693682
XP17-036-230	35,200	15.50	12.70	31,000	19,700	3.02	2.40	8.20	C33-48	EL195UH090XE48C	4693683
XP17-036-230	35,600	15.50	12.70	31,400	19,800	3.10	2.44	8.20	C33-48	EL195UH110XE60C	4693684
XP17-036-230	35,000	14.70	12.20	31,000	20,200	3.00	2.36	8.20	C33-48	EL296UH070XE36B	5649880
XP17-036-230	35,000	15.20	12.70	31,000	19,700	3.00	2.40	8.20	C33-48	EL296UH070XV36B	5054751
XP17-036-230	35,200	15.50	12.70	31,000	19,700	3.02	2.40	8.20	C33-48	EL296UH090XE48C	5649881
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.00	2.40	8.20	C33-48	EL296UH090XV36C	5054752
XP17-036-230	35,400	15.70	13.00	31,000	19,600	3.06	2.44	8.20	C33-48	EL296UH090XV48C	5054753
XP17-036-230	35,600	15.50	12.70	31,400	19,800	3.10	2.44	8.20	C33-48	EL296UH110XE60C	5649882
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.12	2.46	8.50	C33-48	EL296UH110XV48C	5685201
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.14	2.46	8.50	C33-48	EL296UH110XV60C	5054754
XP17-036-230	35,200	15.70	13.00	31,000	19,500	3.04	2.42	8.20	C33-48	SL280UH090V36B	3894681

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,600	15.70	13.00	31,200	19,700	3.10	2.44	8.20	C33-48	SL280UH090V48B	3894682
XP17-036-230	36,000	15.10	13.00	31,400	19,800	3.16	2.48	8.20	C33-48	SL280UH090V60C	3894683
XP17-036-230	35,600	15.70	13.00	31,200	19,700	3.10	2.44	8.20	C33-48	SL280UH090XV48B	4041779
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.16	2.48	8.20	C33-48	SL280UH090XV60C	4235834
XP17-036-230	35,800	15.70	12.50	31,400	19,900	3.12	2.46	8.20	C33-48	SL280UH110V60C	3894684
XP17-036-230	35,800	15.10	12.50	31,400	19,900	3.12	2.46	8.20	C33-48	SL280UH110XV60C	4041985
XP17-036-230	35,000	15.20	12.70	31,000	19,700	3.00	2.40	8.20	C33-48	SLP98UH070XV36B	5137336
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.00	2.40	8.20	C33-48	SLP98UH090XV36C	5137337
XP17-036-230	35,400	15.70	13.00	31,000	19,600	3.06	2.44	8.20	C33-48	SLP98UH090XV48C	5137338
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.14	2.46	8.50	C33-48	SLP98UH110XV60C	5137339
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-49	EL180UH090E60C	5742484
XP17-036-230	35,800	15.70	13.00	31,400	19,700	3.14	2.48	8.50	C33-49	EL180UH110E60C	5740470
XP17-036-230	35,800	15.70	13.00	31,400	19,700	3.14	2.48	8.50	C33-49	EL180UH110XE60C	5740822
XP17-036-230	36,000	16.00	13.00	31,400	19,900	3.20	2.50	8.50	C33-49	EL195UH090XE48C	4693620
XP17-036-230	36,600	16.00	13.00	31,600	19,900	3.22	2.52	8.50	C33-49	EL195UH110XE60C	4693621
XP17-036-230	36,000	16.00	13.00	31,400	19,900	3.20	2.50	8.50	C33-49	EL296UH090XE48C	5649818
XP17-036-230	35,800	15.70	13.20	31,200	19,700	3.12	2.48	8.50	C33-49	EL296UH090XV36C	5054755
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.50	8.50	C33-49	EL296UH090XV48C	5054756
XP17-036-230	36,600	16.00	13.00	31,600	19,900	3.22	2.52	8.50	C33-49	EL296UH110XE60C	5649819
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.52	8.50	C33-49	EL296UH110XV60C	5054757
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.28	2.54	8.50	C33-49	SL280UH090V60C	3894685
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.28	2.54	8.50	C33-49	SL280UH090XV60C	4235835
XP17-036-230	36,600	15.10	13.00	31,800	20,000	3.24	2.50	8.50	C33-49	SL280UH110V60C	3894686
XP17-036-230	36,600	15.10	13.00	31,800	20,000	3.24	2.50	8.50	C33-49	SL280UH110XV60C	4041986
XP17-036-230	35,800	15.70	13.20	31,200	19,700	3.12	2.48	8.50	C33-49	SLP98UH090XV36C	5137343
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.50	8.50	C33-49	SLP98UH090XV48C	5137344
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.52	8.50	C33-49	SLP98UH110XV60C	5137345
XP17-036-230	35,800	14.50	12.20	32,200	20,600	3.04	2.38	8.20	C33-49		3839941
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.14	2.46	8.50	C33-50/60C	EL180UH090E60C	5742485
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-50/60C	EL180UH110E60C	5740471
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-50/60C	EL180UH110XE60C	5740823
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.14	2.46	8.50	C33-50/60C	EL195UH090XE48C	4693622
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-50/60C	EL195UH110XE60C	4693623
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.14	2.46	8.50	C33-50/60C	EL296UH090XE48C	5649820
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-50/60C	EL296UH090XV36C	5054758
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.12	2.46	8.50	C33-50/60C	EL296UH090XV48C	5054759
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-50/60C	EL296UH110XE60C	5649821
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-50/60C	EL296UH110XV48C	5685222
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-50/60C	EL296UH110XV60C	5054760
XP17-036-230	36,400	15.10	13.00	31,600	19,900	3.24	2.50	8.50	C33-50/60C	SL280UH090V60C	3894687
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	C33-50/60C	SL280UH090XV60C	4235839
XP17-036-230	36,200	15.70	12.50	31,600	19,900	3.18	2.48	8.50	C33-50/60C	SL280UH110V60C	3894688

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	36,200	15.10	12.50	31,600	19,900	3.18	2.48	8.50	C33-50/60C	SL280UH110XV60C	4041989
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	C33-50/60C	SLP98UH090XV36C	5137346
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.12	2.46	8.50	C33-50/60C	SLP98UH090XV48C	5137347
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	C33-50/60C	SLP98UH110XV60C	5137348
XP17-036-230	35,400	14.50	12.00	32,000	20,400	3.00	2.34	8.20	C33-50/60C		3839950
XP17-036-230	35,400	15.70	12.70	32,400	20,400	3.52	2.70	9.20	CBX27UH-036		3839848
XP17-036-230	36,800	16.00	13.50	32,400	20,400	3.56	2.74	9.00	CBX27UH-042		3839849
XP17-036-230	35,000	14.50	12.00	33,000	21,000	3.40	2.60	8.70	CBX32M-036		3839850
XP17-036-230	35,000	14.50	12.00	33,000	21,000	3.40	2.60	8.70	CBX32M-042		3839851
XP17-036-230	36,200	15.00	12.50	33,000	21,000	3.40	2.60	8.70	CBX32M-048		3839852
XP17-036-230	35,400	15.20	12.70	32,600	20,600	3.50	2.68	9.00	CBX32MV-036		3839844
XP17-036-230	37,000	16.50	13.50	32,600	20,400	3.58	2.72	9.20	CBX32MV-048		3839843
XP17-036-230	35,600	15.50	12.70	32,600	20,600	3.54	2.70	9.20	CBX40UHV-036		3839845
XP17-036-230	36,800	16.00	13.00	32,400	20,400	3.54	2.70	9.00	CBX40UHV-042		3839846
XP17-036-230	36,800	16.00	13.50	32,400	20,400	3.54	2.70	9.00	CBX40UHV-048		3839847
XP17-036-230	34,800	15.50	12.70	31,000	19,600	3.08	2.44	8.20	CH33-42	EL180UH070E36B	5742029
XP17-036-230	35,600	15.50	12.70	31,800	20,000	3.18	2.46	8.50	CH33-42	EL180UH090E48B	5740306
XP17-036-230	35,000	14.50	12.00	32,000	20,400	3.04	2.38	8.20	CH33-42	EL195UH045XE36B	4693595
XP17-036-230	34,800	14.70	12.20	31,400	20,200	3.06	2.38	8.20	CH33-42	EL195UH070XE36B	4693596
XP17-036-230	35,000	14.50	12.00	32,000	20,400	3.04	2.38	8.20	CH33-42	EL296UH045XE36B	5649793
XP17-036-230	34,800	14.70	12.20	31,400	20,200	3.06	2.38	8.20	CH33-42	EL296UH070XE36B	5649794
XP17-036-230	34,800	15.20	12.50	31,400	19,800	3.06	2.42	8.20	CH33-42	EL296UH070XV36B	5054743
XP17-036-230	35,000	15.70	12.70	31,200	19,600	3.12	2.46	8.50	CH33-42	SL280UH090V36B	3894693
XP17-036-230	35,400	15.70	12.70	31,400	19,800	3.16	2.48	8.50	CH33-42	SL280UH090V48B	3894694
XP17-036-230	35,400	15.70	12.70	31,400	19,800	3.16	2.48	8.50	CH33-42	SL280UH090XV48B	4041781
XP17-036-230	34,800	15.20	12.50	31,400	19,800	3.06	2.42	8.20	CH33-42	SL98UH070V36B	3894695
XP17-036-230	34,800	15.20	12.50	31,400	19,800	3.06	2.42	8.20	CH33-42	SLP98UH070XV36B	5136890
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.20	2.48	8.50	CH33-43	EL180UH070E36B	5742027
XP17-036-230	36,800	16.00	13.00	32,000	20,200	3.28	2.50	8.50	CH33-43	EL180UH090E48B	5740307
XP17-036-230	36,200	16.00	13.00	31,600	19,800	3.22	2.50	8.50	CH33-43	EL180UH090E60C	5742459
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	CH33-43	EL180UH110E60C	5740444
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	CH33-43	EL180UH110XE60C	5740796
XP17-036-230	36,000	15.70	12.70	31,600	19,900	3.16	2.44	8.50	CH33-43	EL296UH070XV36B	5054739
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-43	EL296UH090XV36C	5054740
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CH33-43	EL296UH090XV48C	5054741
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	CH33-43	EL296UH110XV60C	5054742
XP17-036-230	36,000	15.70	12.70	31,600	19,900	3.16	2.44	8.50	CH33-43	SLP98UH070XV36B	5136879
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-43	SLP98UH090XV36C	5136880
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CH33-43	SLP98UH090XV48C	5136881
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	CH33-43	SLP98UH110XV60C	5136889
XP17-036-230	36,200	15.00	12.50	32,200	20,400	3.14	2.40	8.20	CH33-43B	EL195UH045XE36B	4693597
XP17-036-230	36,000	15.20	12.50	31,600	20,400	3.16	2.42	8.50	CH33-43B	EL195UH070XE36B	4693598

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,800	16.00	13.00	31,400	19,800	3.18	2.46	8.50	CH33-43B	EL195UH090XE48C	4693599
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CH33-43B	EL195UH110XE60C	4693600
XP17-036-230	36,200	15.00	12.50	32,200	20,400	3.14	2.40	8.20	CH33-43B	EL296UH045XE36B	5649795
XP17-036-230	36,000	15.20	12.50	31,600	20,400	3.16	2.42	8.50	CH33-43B	EL296UH070XE36B	5649796
XP17-036-230	35,800	16.00	13.00	31,400	19,800	3.18	2.46	8.50	CH33-43B	EL296UH090XE48C	5649797
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CH33-43B	EL296UH110XE60C	5649798
XP17-036-230	36,200	16.00	13.00	31,400	19,700	3.22	2.50	8.50	CH33-43B	SL280UH090V36B	3894689
XP17-036-230	36,600	16.00	13.00	31,800	19,900	3.28	2.52	8.50	CH33-43B	SL280UH090V48B	3894690
XP17-036-230	36,600	16.00	13.00	31,800	19,900	3.28	2.52	8.50	CH33-43B	SL280UH090XV48B	4041780
XP17-036-230	36,000	14.70	12.20	32,400	20,600	3.10	2.38	8.20	CH33-43B		3839959
XP17-036-230	36,200	16.00	13.00	31,400	19,800	3.18	2.48	8.50	CH33-43C	EL296UH110XV48C	5685212
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.28	2.50	8.50	CH33-43C	SL280UH090V60C	3894691
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.28	2.50	8.50	CH33-43C	SL280UH090XV60C	4235836
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.50	8.50	CH33-43C	SL280UH110V60C	3894692
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.50	8.50	CH33-43C	SL280UH110XV60C	4041987
XP17-036-230	35,600	14.50	12.00	32,000	20,400	3.00	2.34	8.20	CH33-43C		3839962
XP17-036-230	35,200	15.70	13.00	31,200	19,600	3.14	2.46	8.50	CH33-44/48	EL180UH070E36B	5742025
XP17-036-230	36,000	15.50	12.70	31,800	20,000	3.24	2.48	8.70	CH33-44/48	EL180UH090E48B	5740308
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.10	2.40	8.20	CH33-44/48	EL195UH045XE36B	4693601
XP17-036-230	35,200	14.70	12.20	31,600	20,200	3.12	2.40	8.20	CH33-44/48	EL195UH070XE36B	4693602
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.10	2.40	8.20	CH33-44/48	EL296UH045XE36B	5649799
XP17-036-230	35,200	14.70	12.20	31,600	20,200	3.12	2.40	8.20	CH33-44/48	EL296UH070XE36B	5649800
XP17-036-230	35,200	15.20	12.70	31,600	19,900	3.14	2.44	8.20	CH33-44/48	EL296UH070XV36B	5054744
XP17-036-230	35,400	15.70	13.00	31,400	19,600	3.20	2.46	8.50	CH33-44/48	SL280UH090V36B	3894696
XP17-036-230	35,800	15.70	13.00	31,600	19,800	3.22	2.48	8.70	CH33-44/48	SL280UH090V48B	3894697
XP17-036-230	35,800	15.70	13.00	31,600	19,800	3.22	2.48	8.70	CH33-44/48	SL280UH090XV48B	4041782
XP17-036-230	35,200	15.20	12.70	31,600	19,900	3.14	2.44	8.20	CH33-44/48	SLP98UH070XV36B	5136891
XP17-036-230	35,200	14.20	12.00	32,200	20,400	3.06	2.34	8.20	CH33-44/48		3839975
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.16	2.46	8.50	CH33-48	EL180UH090E60C	5742460
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-48	EL180UH110E60C	5740445
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-48	EL180UH110XE60C	5740797
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-48	EL296UH090XV36C	5054745
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.14	2.46	8.50	CH33-48	EL296UH090XV48C	5054716
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CH33-48	EL296UH110XV60C	5054717
XP17-036-230	36,400	15.10	13.00	31,600	19,900	3.24	2.50	8.50	CH33-48	SL280UH090V60C	3894698
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	CH33-48	SL280UH090XV60C	4235837
XP17-036-230	36,200	15.70	12.50	31,600	19,900	3.18	2.48	8.50	CH33-48	SL280UH110V60C	3894699
XP17-036-230	36,200	15.10	12.50	31,600	19,900	3.18	2.48	8.50	CH33-48	SL280UH110XV60C	4041988
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CH33-48	SLP98UH090XV36C	5136892
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.14	2.46	8.50	CH33-48	SLP98UH090XV48C	5136844
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CH33-48	SLP98UH110XV60C	5136845
XP17-036-230	35,400	14.50	12.00	32,000	20,400	3.00	2.34	8.20	CH33-48		3839981

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.16	2.46	8.50	CH33-48C	EL195UH090XE48C	4693603
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CH33-48C	EL195UH110XE60C	4693604
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.16	2.46	8.50	CH33-48C	EL296UH090XE48C	5649801
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CH33-48C	EL296UH110XE60C	5649802
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.48	8.50	CH33-48C	EL296UH110XV48C	5685197
XP17-036-230	36,600	16.00	13.00	31,600	19,900	3.26	2.52	8.50	CH33-49	EL180UH090E60C	5742461
XP17-036-230	36,400	16.00	13.00	31,400	19,700	3.22	2.50	8.50	CH33-49	EL180UH110E60C	5740446
XP17-036-230	36,400	16.00	13.00	31,400	19,700	3.22	2.50	8.50	CH33-49	EL180UH110XE60C	5740798
XP17-036-230	36,200	16.00	13.00	31,400	19,900	3.22	2.50	8.50	CH33-49	EL195UH090XE48C	4693605
XP17-036-230	36,800	16.00	13.00	31,800	19,900	3.28	2.50	8.50	CH33-49	EL195UH110XE60C	4693606
XP17-036-230	36,200	16.00	13.00	31,400	19,900	3.22	2.50	8.50	CH33-49	EL296UH090XE48C	5649803
XP17-036-230	35,800	16.00	13.00	31,200	19,700	3.14	2.46	8.50	CH33-49	EL296UH090XV36C	5054718
XP17-036-230	36,200	16.00	13.00	31,400	19,700	3.20	2.48	8.50	CH33-49	EL296UH090XV48C	5054719
XP17-036-230	36,800	16.00	13.00	31,800	19,900	3.28	2.50	8.50	CH33-49	EL296UH110XE60C	5649804
XP17-036-230	36,800	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-49	EL296UH110XV48C	5685187
XP17-036-230	36,800	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-49	EL296UH110XV60C	5054720
XP17-036-230	37,000	15.10	13.00	31,800	20,000	3.30	2.52	8.50	CH33-49	SL280UH090V60C	3894700
XP17-036-230	37,000	16.00	13.00	31,800	20,000	3.30	2.52	8.50	CH33-49	SL280UH090XV60C	4235838
XP17-036-230	36,800	16.00	13.00	31,800	20,000	3.26	2.50	8.50	CH33-49	SL280UH110V60C	3894701
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.26	2.50	8.50	CH33-49	SL280UH110XV60C	4041978
XP17-036-230	35,800	16.00	13.00	31,200	19,700	3.14	2.46	8.50	CH33-49	SLP98UH090XV36C	5136846
XP17-036-230	36,200	16.00	13.00	31,400	19,700	3.20	2.48	8.50	CH33-49	SLP98UH090XV48C	5136847
XP17-036-230	36,800	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-49	SLP98UH110XV60C	5136848
XP17-036-230	35,800	14.70	12.20	32,200	20,600	3.06	2.38	8.20	CH33-49		3839988
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CH33-50/60C	EL180UH090E60C	5742462
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CH33-50/60C	EL180UH110E60C	5740447
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CH33-50/60C	EL180UH110XE60C	5740799
XP17-036-230	35,800	15.70	12.70	31,400	19,800	3.16	2.44	8.50	CH33-50/60C	EL195UH090XE48C	4693607
XP17-036-230	36,200	15.70	13.00	31,600	19,900	3.20	2.48	8.50	CH33-50/60C	EL195UH110XE60C	4693608
XP17-036-230	35,800	15.70	12.70	31,400	19,800	3.16	2.44	8.50	CH33-50/60C	EL296UH090XE48C	5649805
XP17-036-230	35,600	16.00	13.00	31,200	19,600	3.14	2.46	8.50	CH33-50/60C	EL296UH090XV36C	5054721
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.20	2.48	8.50	CH33-50/60C	EL296UH090XV48C	5054722
XP17-036-230	36,200	15.70	13.00	31,600	19,900	3.20	2.48	8.50	CH33-50/60C	EL296UH110XE60C	5649806
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-50/60C	EL296UH110XV48C	5685218
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-50/60C	EL296UH110XV60C	5054723
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.30	2.54	8.50	CH33-50/60C	SL280UH090V60C	3894702
XP17-036-230	36,800	16.00	13.00	31,800	20,000	3.30	2.54	8.50	CH33-50/60C	SL280UH090XV60C	4235827
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.50	8.50	CH33-50/60C	SL280UH110V60C	3894703
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.50	8.50	CH33-50/60C	SL280UH110XV60C	4041979
XP17-036-230	35,600	16.00	13.00	31,200	19,600	3.14	2.46	8.50	CH33-50/60C	SLP98UH090XV36C	5136849
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.20	2.48	8.50	CH33-50/60C	SLP98UH090XV48C	5136850
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.28	2.52	8.50	CH33-50/60C	SLP98UH110XV60C	5136851

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,600	14.50	12.00	32,200	20,400	3.06	2.34	8.20	CH33-50/60C		3839997
XP17-036-230	35,400	15.70	13.00	31,600	20,000	3.26	2.58	8.70	CR33-48	EL180DF070E36B	5741557
XP17-036-230	35,600	15.00	12.50	31,800	20,200	3.30	2.58	8.50	CR33-48	EL180DF090E48B	5741582
XP17-036-230	36,000	15.00	12.50	31,800	20,200	3.32	2.62	8.50	CR33-48	EL180DF110E60C	5741595
XP17-036-230	35,800	14.70	12.20	32,400	20,800	3.22	2.52	8.70	CR33-48	EL195DF045XE36B	4693609
XP17-036-230	35,600	15.50	12.70	31,800	20,200	3.24	2.56	8.70	CR33-48	EL195DF070XE48B	4693610
XP17-036-230	35,600	15.70	12.70	31,600	20,200	3.26	2.58	8.70	CR33-48	EL195DF090XE48C	4693680
XP17-036-230	35,800	15.70	13.00	31,800	20,200	3.28	2.60	8.70	CR33-48	EL195DF110XE60C	4693611
XP17-036-230	35,800	14.70	12.20	32,400	20,800	3.22	2.52	8.70	CR33-48	EL296DF045XE36B	5649807
XP17-036-230	35,800	15.20	12.70	32,000	20,400	3.26	2.56	8.70	CR33-48	EL296DF045XV36B	7505736
XP17-036-230	35,600	15.50	12.70	31,800	20,200	3.24	2.56	8.70	CR33-48	EL296DF070XE48B	5649808
XP17-036-230	35,800	15.20	12.50	32,200	20,600	3.26	2.58	8.70	CR33-48	EL296DF070XV48B	7487524
XP17-036-230	35,600	15.70	12.70	31,600	20,200	3.26	2.58	8.70	CR33-48	EL296DF090XE48C	5649878
XP17-036-230	35,800	15.70	13.00	31,800	20,200	3.28	2.60	8.70	CR33-48	EL296DF110XE60C	5649809
XP17-036-230	35,600	15.00	12.50	31,800	20,200	3.26	2.60	8.50	CR33-48	SL280DF090V48B	3894749
XP17-036-230	36,600	15.00	12.50	32,200	20,400	3.42	2.68	8.50	CR33-48	SL280DF090V60C	3894750
XP17-036-230	36,200	15.00	12.50	31,800	20,200	3.36	2.66	8.50	CR33-48	SL280DF110V60C	3894751
XP17-036-230	35,600	15.70	12.70	31,800	20,200	3.26	2.58	8.70	CR33-48	SLP98DF070XV36B	5136852
XP17-036-230	35,600	15.70	13.00	31,800	20,200	3.26	2.60	8.70	CR33-48	SLP98DF090XV36C	5136853
XP17-036-230	35,600	16.00	13.00	31,600	20,000	3.26	2.60	8.50	CR33-48	SLP98DF090XV48C	5136854
XP17-036-230	36,400	15.70	13.20	32,200	20,400	3.36	2.64	9.00	CR33-48	SLP98DF110XV60C	5136855
XP17-036-230	35,400	14.50	12.00	32,400	20,800	3.14	2.46	8.20	CR33-48		3840006
XP17-036-230	36,800	16.00	13.00	32,600	20,400	3.60	2.74	9.00	CR33-50/60	EL180DF110E60C	5741596
XP17-036-230	36,400	15.70	13.00	32,400	20,600	3.54	2.72	9.20	CR33-50/60	EL195DF090XE48C	4693612
XP17-036-230	36,600	15.70	13.00	32,600	20,600	3.56	2.74	9.20	CR33-50/60	EL195DF110XE60C	4693613
XP17-036-230	36,400	15.70	13.00	32,400	20,600	3.54	2.72	9.20	CR33-50/60	EL296DF090XE48C	5649810
XP17-036-230	36,600	15.70	13.00	32,600	20,600	3.54	2.72	9.20	CR33-50/60	EL296DF090XV60C	5537042
XP17-036-230	36,600	15.70	13.00	32,600	20,600	3.56	2.74	9.20	CR33-50/60	EL296DF110XE60C	5649811
XP17-036-230	36,400	15.10	13.00	32,400	20,400	3.56	2.74	9.00	CR33-50/60	SL280DF110V60C	4042160
XP17-036-230	35,800	15.70	12.70	32,200	20,400	3.44	2.68	9.20	CR33-50/60	SLP98DF090XV36C	5136984
XP17-036-230	36,400	15.70	13.00	32,400	20,400	3.52	2.70	9.20	CR33-50/60	SLP98DF090XV48C	5136985
XP17-036-230	36,600	15.70	13.00	32,600	20,600	3.54	2.72	9.20	CR33-50/60	SLP98DF090XV60C	5136986
XP17-036-230	36,600	15.70	13.00	32,600	20,600	3.54	2.72	9.20	CR33-50/60	SLP98DF110XV60C	5136987
XP17-036-230	35,800	14.50	12.00	33,000	21,000	3.30	2.54	8.70	CR33-50/60		4042156
XP17-036-230	35,400	15.00	12.50	31,800	20,000	3.10	2.40	8.20	CX34-38	EL180UH045E36A	5741668
XP17-036-230	35,400	15.00	12.50	31,800	20,000	3.10	2.40	8.20	CX34-38	EL180UH045XE36A	5741820
XP17-036-230	35,200	15.70	13.00	31,200	19,600	3.12	2.44	8.50	CX34-38	EL180UH070E36B	5741890
XP17-036-230	35,200	15.70	13.00	31,200	19,600	3.12	2.44	8.50	CX34-38	EL180UH070XE36B	5742151
XP17-036-230	36,000	15.50	12.70	31,800	20,000	3.22	2.46	8.50	CX34-38	EL180UH090E48B	5742236
XP17-036-230	36,000	15.50	12.70	31,800	20,000	3.22	2.46	8.50	CX34-38	EL180UH090XE48B	5740336
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.06	2.40	8.20	CX34-38	EL195UH045XE36B	4693581
XP17-036-230	35,400	14.70	12.20	31,400	20,200	3.10	2.38	8.20	CX34-38	EL195UH070XE36B	4693582

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,400	14.70	12.20	32,000	20,400	3.06	2.40	8.20	CX34-38	EL296UH045XE36B	5649779
XP17-036-230	35,400	14.70	12.20	31,400	20,200	3.10	2.38	8.20	CX34-38	EL296UH070XE36B	5649780
XP17-036-230	35,400	15.50	12.70	31,400	19,800	3.12	2.44	8.20	CX34-38	EL296UH070XV36B	5054724
XP17-036-230	35,600	15.00	12.50	31,800	20,000	3.14	2.42	8.50	CX34-38	SL280UH070V36A	3894659
XP17-036-230	35,600	15.00	12.50	31,800	20,000	3.14	2.42	8.50	CX34-38	SL280UH070XV36A	4041581
XP17-036-230	35,400	16.00	13.00	31,200	19,600	3.14	2.46	8.50	CX34-38	SL280UH090V36B	3894660
XP17-036-230	35,800	16.00	13.00	31,600	19,800	3.20	2.48	8.50	CX34-38	SL280UH090V48B	3894661
XP17-036-230	35,800	16.00	13.00	31,600	19,800	3.20	2.48	8.50	CX34-38	SL280UH090XV48B	4041774
XP17-036-230	35,400	15.50	12.70	31,400	19,800	3.12	2.44	8.20	CX34-38	SLP98UH070XV36B	5136864
XP17-036-230	35,200	14.50	12.00	32,200	20,400	3.04	2.34	8.20	CX34-38		3839853
XP17-036-230	35,600	16.00	13.00	31,200	19,600	3.12	2.44	8.20	CX34-43	EL180UH070E36B	5742024
XP17-036-230	36,200	15.70	13.00	31,800	20,000	3.20	2.46	8.50	CX34-43	EL180UH090E48B	5740305
XP17-036-230	36,200	16.00	13.00	31,600	19,800	3.22	2.50	8.50	CX34-43	EL180UH090E60C	5742455
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	CX34-43	EL180UH110E60C	5740440
XP17-036-230	36,000	16.00	13.00	31,400	19,700	3.18	2.48	8.50	CX34-43	EL180UH110XE60C	5740792
XP17-036-230	35,800	14.70	12.20	32,000	20,400	3.06	2.38	8.20	CX34-43	EL195UH045XE36B	4693583
XP17-036-230	35,600	15.00	12.20	31,400	20,200	3.08	2.38	8.20	CX34-43	EL195UH070XE36B	4693584
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.16	2.46	8.50	CX34-43	EL195UH090XE48C	4693585
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CX34-43	EL195UH110XE60C	4693586
XP17-036-230	35,800	14.70	12.20	32,000	20,400	3.06	2.38	8.20	CX34-43	EL296UH045XE36B	5649781
XP17-036-230	35,600	15.00	12.20	31,400	20,200	3.08	2.38	8.20	CX34-43	EL296UH070XE36B	5649782
XP17-036-230	35,600	15.70	12.70	31,400	19,800	3.10	2.44	8.20	CX34-43	EL296UH070XV36B	5054725
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.16	2.46	8.50	CX34-43	EL296UH090XE48C	5649783
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-43	EL296UH090XV36C	5054726
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CX34-43	EL296UH090XV48C	5054727
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CX34-43	EL296UH110XE60C	5649784
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.22	2.50	8.50	CX34-43	EL296UH110XV48C	5685192
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	CX34-43	EL296UH110XV60C	5054728
XP17-036-230	35,800	16.00	13.00	31,200	19,600	3.14	2.46	8.50	CX34-43	SL280UH090V36B	3894662
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.48	8.50	CX34-43	SL280UH090V48B	3894663
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.26	2.50	8.50	CX34-43	SL280UH090V60C	3894664
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.48	8.50	CX34-43	SL280UH090XV48B	4041775
XP17-036-230	36,600	15.10	13.00	31,800	19,900	3.26	2.50	8.50	CX34-43	SL280UH090XV60C	4235829
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.48	8.50	CX34-43	SL280UH110V60C	3894665
XP17-036-230	36,400	15.10	13.00	31,600	20,000	3.20	2.48	8.50	CX34-43	SL280UH110XV60C	4041980
XP17-036-230	35,600	15.70	12.70	31,400	19,800	3.10	2.44	8.20	CX34-43	SLP98UH070XV36B	5136865
XP17-036-230	35,600	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-43	SLP98UH090XV36C	5136866
XP17-036-230	35,800	16.00	13.00	31,400	19,700	3.16	2.46	8.50	CX34-43	SLP98UH090XV48C	5136867
XP17-036-230	36,400	16.00	13.00	31,600	19,900	3.24	2.50	8.50	CX34-43	SLP98UH110XV60C	5136868
XP17-036-230	35,400	14.50	12.00	32,000	20,400	3.00	2.34	8.20	CX34-43		3839860
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.02	2.42	8.20	CX34-44/48	EL180UH070E36B	5741891
XP17-036-230	35,800	15.50	12.70	31,600	19,900	3.10	2.44	8.20	CX34-44/48	EL180UH090E48B	5742237

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,400	15.70	12.70	31,200	19,700	3.08	2.44	8.20	CX34-44/48	EL180UH090E60C	5742456
XP17-036-230	35,200	15.50	12.70	31,000	19,500	3.04	2.40	8.20	CX34-44/48	EL180UH110E60C	5740441
XP17-036-230	35,200	15.50	12.70	31,000	19,500	3.04	2.40	8.20	CX34-44/48	EL180UH110XE60C	5740793
XP17-036-230	35,000	14.70	12.20	31,000	20,200	3.00	2.36	8.20	CX34-44/48	EL195UH070XE36B	4693588
XP17-036-230	35,200	15.50	12.70	31,000	19,700	3.02	2.40	8.20	CX34-44/48	EL195UH090XE48C	4693589
XP17-036-230	35,600	15.50	12.70	31,400	19,800	3.10	2.44	8.20	CX34-44/48	EL195UH110XE60C	4693590
XP17-036-230	35,000	14.70	12.20	31,000	20,200	3.00	2.36	8.20	CX34-44/48	EL296UH070XE36B	5649786
XP17-036-230	35,000	15.20	12.70	31,000	19,700	3.00	2.40	8.20	CX34-44/48	EL296UH070XV36B	5054729
XP17-036-230	35,200	15.50	12.70	31,000	19,700	3.02	2.40	8.20	CX34-44/48	EL296UH090XE48C	5649787
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.00	2.40	8.20	CX34-44/48	EL296UH090XV36C	5054730
XP17-036-230	35,400	15.70	13.00	31,000	19,600	3.06	2.44	8.20	CX34-44/48	EL296UH090XV48C	5054731
XP17-036-230	35,600	15.50	12.70	31,400	19,800	3.10	2.44	8.20	CX34-44/48	EL296UH110XE60C	5649788
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.12	2.46	8.50	CX34-44/48	EL296UH110XV48C	5685181
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.14	2.46	8.50	CX34-44/48	EL296UH110XV60C	5054732
XP17-036-230	35,200	15.70	13.00	31,000	19,500	3.04	2.42	8.20	CX34-44/48	SL280UH090V36B	3894666
XP17-036-230	35,600	15.70	13.00	31,200	19,700	3.10	2.44	8.20	CX34-44/48	SL280UH090V48B	3894667
XP17-036-230	36,000	15.10	13.00	31,400	19,800	3.16	2.48	8.20	CX34-44/48	SL280UH090V60C	3894668
XP17-036-230	35,600	15.70	13.00	31,200	19,700	3.10	2.44	8.20	CX34-44/48	SL280UH090XV48B	4041776
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.16	2.48	8.20	CX34-44/48	SL280UH090XV60C	4235830
XP17-036-230	35,800	15.70	12.50	31,400	19,900	3.12	2.46	8.20	CX34-44/48	SL280UH110V60C	3894669
XP17-036-230	35,800	15.10	12.50	31,400	19,900	3.12	2.46	8.20	CX34-44/48	SL280UH110XV60C	4041981
XP17-036-230	35,000	15.20	12.70	31,000	19,700	3.00	2.40	8.20	CX34-44/48	SLP98UH070XV36B	5136869
XP17-036-230	35,000	15.70	12.70	30,800	19,500	3.00	2.40	8.20	CX34-44/48	SLP98UH090XV36C	5136870
XP17-036-230	35,400	15.70	13.00	31,000	19,600	3.06	2.44	8.20	CX34-44/48	SLP98UH090XV48C	5136871
XP17-036-230	36,000	15.70	13.00	31,400	19,800	3.14	2.46	8.50	CX34-44/48	SLP98UH110XV60C	5136872
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-49	EL180UH090E60C	5742457
XP17-036-230	35,800	15.70	13.00	31,400	19,700	3.14	2.48	8.50	CX34-49	EL180UH110E60C	5740442
XP17-036-230	35,800	15.70	13.00	31,400	19,700	3.14	2.48	8.50	CX34-49	EL180UH110XE60C	5740794
XP17-036-230	36,000	16.00	13.00	31,400	19,900	3.20	2.50	8.50	CX34-49	EL195UH090XE48C	4693591
XP17-036-230	36,600	16.00	13.00	31,600	19,900	3.22	2.52	8.50	CX34-49	EL195UH110XE60C	4693592
XP17-036-230	36,000	16.00	13.00	31,400	19,900	3.20	2.50	8.50	CX34-49	EL296UH090XE48C	5649789
XP17-036-230	35,800	15.70	13.20	31,200	19,700	3.12	2.48	8.50	CX34-49	EL296UH090XV36C	5054733
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.50	8.50	CX34-49	EL296UH090XV48C	5054734
XP17-036-230	36,600	16.00	13.00	31,600	19,900	3.22	2.52	8.50	CX34-49	EL296UH110XE60C	5649790
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.52	8.50	CX34-49	EL296UH110XV60C	5054735
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.28	2.54	8.50	CX34-49	SL280UH090V60C	3894670
XP17-036-230	36,800	15.10	13.00	31,800	20,000	3.28	2.54	8.50	CX34-49	SL280UH090XV60C	4235831
XP17-036-230	36,600	15.10	13.00	31,800	20,000	3.24	2.50	8.50	CX34-49	SL280UH110V60C	3894671
XP17-036-230	36,600	15.10	13.00	31,800	20,000	3.24	2.50	8.50	CX34-49	SL280UH110XV60C	4041982
XP17-036-230	35,800	15.70	13.20	31,200	19,700	3.12	2.48	8.50	CX34-49	SLP98UH090XV36C	5136873
XP17-036-230	36,000	16.00	13.00	31,400	19,800	3.18	2.50	8.50	CX34-49	SLP98UH090XV48C	5136874
XP17-036-230	36,600	16.00	13.00	31,800	20,000	3.26	2.52	8.50	CX34-49	SLP98UH110XV60C	5136875

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-036-230	35,800	14.50	12.20	32,200	20,600	3.04	2.38	8.20	CX34-49		3839888
XP17-036-230	35,800	15.70	13.00	31,400	19,800	3.14	2.46	8.50	CX34-50/60C	EL180UH090E60C	5742458
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-50/60C	EL180UH110E60C	5740443
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-50/60C	EL180UH110XE60C	5740795
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.14	2.46	8.50	CX34-50/60C	EL195UH090XE48C	4693593
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-50/60C	EL195UH110XE60C	4693594
XP17-036-230	35,600	15.70	13.00	31,200	19,800	3.14	2.46	8.50	CX34-50/60C	EL296UH090XE48C	5649791
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-50/60C	EL296UH090XV36C	5054736
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.12	2.46	8.50	CX34-50/60C	EL296UH090XV48C	5054737
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-50/60C	EL296UH110XE60C	5649792
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-50/60C	EL296UH110XV48C	5685223
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-50/60C	EL296UH110XV60C	5054738
XP17-036-230	36,400	15.10	13.00	31,600	19,900	3.24	2.50	8.50	CX34-50/60C	SL280UH090V60C	3894672
XP17-036-230	36,400	15.10	13.00	31,600	19,900	3.24	2.50	8.50	CX34-50/60C	SL280UH090XV60C	4235832
XP17-036-230	36,200	15.10	12.50	31,600	19,900	3.18	2.48	8.50	CX34-50/60C	SL280UH110V60C	3894673
XP17-036-230	36,200	14.50	12.50	31,600	19,900	3.18	2.48	8.50	CX34-50/60C	SL280UH110XV60C	4041983
XP17-036-230	35,400	15.70	13.00	31,200	19,600	3.10	2.44	8.20	CX34-50/60C	SLP98UH090XV36C	5136876
XP17-036-230	35,600	16.00	13.00	31,200	19,700	3.12	2.46	8.50	CX34-50/60C	SLP98UH090XV48C	5136877
XP17-036-230	36,200	16.00	13.00	31,600	19,900	3.20	2.50	8.50	CX34-50/60C	SLP98UH110XV60C	5136878
XP17-036-230	35,400	14.50	12.00	32,000	20,400	3.00	2.34	8.20	CX34-50/60C		3839897
XP17-042-230	39,000	14.70	12.00	35,400	22,200	3.08	2.38	8.20	C33-38	EL180UH090E48B	5742252
XP17-042-230	39,000	14.70	12.00	35,400	22,200	3.08	2.38	8.20	C33-38	EL180UH090XE48B	5740349
XP17-042-230	39,000	14.50	12.00	35,600	22,400	3.08	2.38	8.20	C33-38	EL296UH070XV36B	5054816
XP17-042-230	39,500	14.70	12.20	35,400	22,400	3.10	2.40	8.20	C33-38	SL280UH090V36B	3894770
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.08	2.40	8.20	C33-38	SL280UH090V48B	3894771
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.08	2.40	8.20	C33-38	SL280UH090XV48B	4041792
XP17-042-230	39,000	14.50	12.00	35,600	22,400	3.08	2.38	8.20	C33-38	SLP98UH070XV36B	5137367
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.32	2.46	8.70	C33-43	EL180UH090E48B	5742253
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.36	2.48	8.70	C33-43	EL180UH090E60C	5742486
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.32	2.46	8.70	C33-43	EL180UH090XE48B	5740350
XP17-042-230	39,000	15.00	12.50	35,000	22,000	3.34	2.48	8.70	C33-43	EL180UH110E60C	5740463
XP17-042-230	39,000	15.00	12.50	35,000	22,000	3.34	2.48	8.70	C33-43	EL180UH110XE60C	5740815
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.44	8.50	C33-43	EL195UH090XE48C	4693644
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.46	8.70	C33-43	EL195UH110XE60C	4693686
XP17-042-230	38,500	14.20	11.70	35,400	22,600	3.20	2.38	8.20	C33-43	EL296UH070XV36B	5054798
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.44	8.50	C33-43	EL296UH090XE48C	5649842
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	C33-43	EL296UH090XV36C	5054799
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	C33-43	EL296UH090XV48C	5054800
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	C33-43	EL296UH090XV60C	5054801
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.46	8.70	C33-43	EL296UH110XE60C	5649884
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	C33-43	EL296UH110XV48C	5685207
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	C33-43	EL296UH110XV60C	5054802

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-43	SL280UH090V36B	3894772
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	C33-43	SL280UH090V48B	3894773
XP17-042-230	38,500	14.50	12.20	34,600	21,800	3.30	2.46	8.50	C33-43	SL280UH090V60C	3894774
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	C33-43	SL280UH090XV48B	4041793
XP17-042-230	38,500	15.10	12.20	34,600	21,800	3.30	2.46	8.50	C33-43	SL280UH090XV60C	4235849
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.34	2.48	8.70	C33-43	SL280UH110V60C	3894775
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.34	2.48	8.70	C33-43	SL280UH110XV60C	4042005
XP17-042-230	38,500	14.20	11.70	35,400	22,600	3.20	2.38	8.20	C33-43	SLP98UH070XV36B	5137349
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	C33-43	SLP98UH090XV36C	5137350
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	C33-43	SLP98UH090XV48C	5137351
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	C33-43	SLP98UH090XV60C	5137352
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	C33-43	SLP98UH110XV60C	5137353
XP17-042-230	39,000	14.50	12.00	35,000	22,000	2.98	2.32	8.20	C33-48	EL180UH090E48B	5742247
XP17-042-230	39,000	15.00	12.20	35,000	22,000	3.04	2.36	8.20	C33-48	EL180UH090E60C	5742478
XP17-042-230	39,000	14.50	12.00	35,000	22,000	2.98	2.32	8.20	C33-48	EL180UH090XE48B	5740344
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.02	2.36	8.20	C33-48	EL180UH110E60C	5740464
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.02	2.36	8.20	C33-48	EL180UH110XE60C	5740816
XP17-042-230	38,500	14.70	12.00	34,800	22,000	2.98	2.34	8.20	C33-48	EL195UH090XE48C	4693687
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	C33-48	EL195UH110XE60C	4693688
XP17-042-230	38,500	14.70	12.00	34,800	22,000	2.98	2.34	8.20	C33-48	EL296UH090XE48C	5649885
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.00	2.34	8.20	C33-48	EL296UH090XV36C	5054804
XP17-042-230	39,000	14.70	12.00	35,200	22,000	3.02	2.34	8.20	C33-48	EL296UH090XV48C	5054805
XP17-042-230	39,000	14.70	12.20	34,800	22,000	2.98	2.36	8.20	C33-48	EL296UH090XV60C	5054806
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	C33-48	EL296UH110XE60C	5649886
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	C33-48	EL296UH110XV48C	5685190
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	C33-48	EL296UH110XV60C	5054807
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.02	2.34	8.20	C33-48	SL280UH090V36B	3894776
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.00	2.34	8.20	C33-48	SL280UH090V48B	3894777
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.00	2.34	8.20	C33-48	SL280UH090XV48B	4041794
XP17-042-230	39,000	14.70	12.20	35,200	22,000	3.04	2.36	8.20	C33-48	SL280UH110V60C	3894780
XP17-042-230	39,000	14.70	12.20	35,200	22,000	3.04	2.36	8.20	C33-48	SL280UH110XV60C	4042007
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.00	2.34	8.20	C33-48	SLP98UH090XV36C	5137355
XP17-042-230	39,000	14.70	12.00	35,200	22,000	3.02	2.34	8.20	C33-48	SLP98UH090XV48C	5137356
XP17-042-230	39,000	14.70	12.20	34,800	22,000	2.98	2.36	8.20	C33-48	SLP98UH090XV60C	5137357
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	C33-48	SLP98UH110XV60C	5137358
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	C33-49	EL180UH090E60C	5742483
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.22	2.52	8.70	C33-49	EL180UH110E60C	5740468
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.22	2.52	8.70	C33-49	EL180UH110XE60C	5740820
XP17-042-230	39,500	15.00	12.20	35,200	22,000	3.18	2.48	8.70	C33-49	EL195UH090XE48C	4693645
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.24	2.50	8.70	C33-49	EL195UH110XE60C	4693646
XP17-042-230	39,500	15.00	12.20	35,200	22,000	3.18	2.48	8.70	C33-49	EL296UH090XE48C	5649843
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.22	2.52	8.70	C33-49	EL296UH090XV36C	5054808

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	40,000	15.20	12.20	35,400	22,000	3.24	2.50	8.70	C33-49	EL296UH090XV48C	5054809
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	C33-49	EL296UH090XV60C	5054810
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.24	2.50	8.70	C33-49	EL296UH110XE60C	5649844
XP17-042-230	40,000	15.20	12.20	35,400	22,200	3.26	2.54	8.70	C33-49	EL296UH110XV48C	5685220
XP17-042-230	40,000	15.20	12.50	35,400	22,000	3.26	2.52	8.70	C33-49	EL296UH110XV60C	5054811
XP17-042-230	39,500	14.50	12.50	35,000	21,800	3.24	2.54	8.50	C33-49	SL280UH090V60C	3894781
XP17-042-230	39,500	15.10	12.50	35,000	21,800	3.24	2.54	8.50	C33-49	SL280UH090XV60C	4235860
XP17-042-230	40,500	15.20	12.70	35,400	22,000	3.28	2.54	8.70	C33-49	SL280UH110V60C	3894782
XP17-042-230	40,500	15.20	12.70	35,400	22,000	3.28	2.54	8.70	C33-49	SL280UH110XV60C	4042008
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.22	2.52	8.70	C33-49	SLP98UH090XV36C	5137359
XP17-042-230	40,000	15.20	12.20	35,400	22,000	3.24	2.50	8.70	C33-49	SLP98UH090XV48C	5137360
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	C33-49	SLP98UH090XV60C	5137361
XP17-042-230	40,000	15.20	12.50	35,400	22,000	3.26	2.52	8.70	C33-49	SLP98UH110XV60C	5137362
XP17-042-230	39,500	14.00	11.50	36,000	22,800	3.10	2.40	8.50	C33-49		3840107
XP17-042-230	38,500	15.00	12.20	35,000	22,000	3.30	2.44	8.50	C33-50/60C	EL180UH090E60C	5742487
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.28	2.44	8.50	C33-50/60C	EL180UH110E60C	5740472
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.28	2.44	8.50	C33-50/60C	EL180UH110XE60C	5740824
XP17-042-230	38,000	14.70	12.00	34,800	22,000	3.24	2.40	8.50	C33-50/60C	EL195UH090XE48C	4693647
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-50/60C	EL195UH110XE60C	4693648
XP17-042-230	38,000	14.70	12.00	34,800	22,000	3.24	2.40	8.50	C33-50/60C	EL296UH090XE48C	5649845
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	C33-50/60C	EL296UH090XV36C	5054812
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	C33-50/60C	EL296UH090XV48C	5054813
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.24	2.42	8.50	C33-50/60C	EL296UH090XV60C	5054814
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-50/60C	EL296UH110XE60C	5649846
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-50/60C	EL296UH110XV48C	5685208
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-50/60C	EL296UH110XV60C	5054815
XP17-042-230	38,000	15.00	12.20	34,600	21,800	3.26	2.44	8.50	C33-50/60C	SL280UH090V60C	3894783
XP17-042-230	38,000	14.50	12.20	34,600	21,800	3.26	2.44	8.50	C33-50/60C	SL280UH090XV60C	4235861
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	C33-50/60C	SLP98UH090XV36C	5137363
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	C33-50/60C	SLP98UH090XV48C	5137364
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.24	2.42	8.50	C33-50/60C	SLP98UH090XV60C	5137365
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	C33-50/60C	SLP98UH110XV60C	5137366
XP17-042-230	40,000	15.50	12.70	36,200	22,600	3.60	2.58	9.20	CBX27UH-042		3840018
XP17-042-230	40,000	15.20	12.70	36,400	22,600	3.60	2.58	9.20	CBX27UH-048		3840019
XP17-042-230	39,500	14.70	12.20	36,600	23,000	3.50	2.52	9.00	CBX32M-048		3840020
XP17-042-230	40,000	15.70	12.70	36,200	22,600	3.62	2.60	9.20	CBX32MV-048		3840015
XP17-042-230	39,500	15.20	12.70	36,000	22,600	3.54	2.56	9.00	CBX40UHV-042		3840016
XP17-042-230	40,000	15.50	12.70	36,200	22,600	3.60	2.60	9.20	CBX40UHV-048		3840017
XP17-042-230	39,000	15.00	12.20	35,400	22,400	3.36	2.48	8.70	CH33-43	EL180UH090E48B	5742241
XP17-042-230	39,000	15.00	12.20	35,200	22,000	3.34	2.44	8.70	CH33-43	EL180UH090E60C	5742467
XP17-042-230	39,000	15.00	12.20	35,400	22,400	3.36	2.48	8.70	CH33-43	EL180UH090XE48B	5740340
XP17-042-230	38,500	15.00	12.20	35,000	22,000	3.32	2.44	8.50	CH33-43	EL180UH110E60C	5740452

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	38,500	15.00	12.20	35,000	22,000	3.32	2.44	8.50	CH33-43	EL180UH110XE60C	5740804
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.28	2.42	8.50	CH33-43	EL195UH090XE48C	4693631
XP17-042-230	39,000	14.70	12.20	35,200	22,400	3.34	2.46	8.70	CH33-43	EL195UH110XE60C	4693632
XP17-042-230	39,000	14.20	11.70	35,800	22,600	3.32	2.40	8.50	CH33-43	EL296UH070XV36B	5054779
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.28	2.42	8.50	CH33-43	EL296UH090XE48C	5649829
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.44	8.50	CH33-43	EL296UH090XV36C	5054780
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.46	8.70	CH33-43	EL296UH090XV48C	5054781
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CH33-43	EL296UH090XV60C	5054782
XP17-042-230	39,000	14.70	12.20	35,200	22,400	3.34	2.46	8.70	CH33-43	EL296UH110XE60C	5649830
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.48	8.70	CH33-43	EL296UH110XV60C	5054783
XP17-042-230	39,000	14.20	11.70	35,800	22,600	3.32	2.40	8.50	CH33-43	SLP98UH070XV36B	5136910
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.44	8.50	CH33-43	SLP98UH090XV36C	5136911
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.46	8.70	CH33-43	SLP98UH090XV48C	5136912
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CH33-43	SLP98UH090XV60C	5136913
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.48	8.70	CH33-43	SLP98UH110XV60C	5136914
XP17-042-230	39,500	14.70	12.20	35,600	22,400	3.40	2.48	8.70	CH33-43B	SL280UH090V36B	3894784
XP17-042-230	39,000	15.00	12.20	35,400	22,200	3.38	2.46	8.70	CH33-43B	SL280UH090V48B	3894785
XP17-042-230	39,000	15.00	12.20	35,400	22,200	3.38	2.46	8.70	CH33-43B	SL280UH090XV48B	4041798
XP17-042-230	39,000	14.00	11.70	36,000	22,800	3.26	2.38	8.50	CH33-43B		3840129
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.46	8.70	CH33-43C	EL296UH110XV48C	5685211
XP17-042-230	38,500	14.50	12.20	34,600	21,800	3.32	2.46	8.50	CH33-43C	SL280UH090V60C	3894786
XP17-042-230	38,500	15.10	12.20	34,600	21,800	3.32	2.46	8.50	CH33-43C	SL280UH090XV60C	4235864
XP17-042-230	39,000	15.20	12.50	35,200	22,000	3.38	2.46	8.70	CH33-43C	SL280UH110V60C	3894787
XP17-042-230	39,000	15.20	12.50	35,200	22,000	3.38	2.46	8.70	CH33-43C	SL280UH110XV60C	4042011
XP17-042-230	38,000	14.50	12.00	35,400	22,200	3.34	2.44	8.70	CH33-44/48	EL180UH090E48B	5742242
XP17-042-230	38,000	14.50	12.00	35,400	22,200	3.34	2.44	8.70	CH33-44/48	EL180UH090XE48B	5740341
XP17-042-230	38,000	14.00	11.50	35,600	22,600	3.26	2.40	8.50	CH33-44/48	EL296UH070XV36B	5054784
XP17-042-230	38,500	14.50	12.00	35,400	22,400	3.36	2.46	8.70	CH33-44/48	SL280UH090V36B	3894788
XP17-042-230	38,000	14.70	12.00	35,200	22,200	3.34	2.46	8.70	CH33-44/48	SL280UH090V48B	3894789
XP17-042-230	38,000	14.70	12.00	35,200	22,200	3.34	2.46	8.70	CH33-44/48	SL280UH090XV48B	4041799
XP17-042-230	38,000	14.00	11.50	35,600	22,600	3.26	2.40	8.50	CH33-44/48	SLP98UH070XV36B	5136915
XP17-042-230	38,500	15.00	12.20	35,000	22,000	3.32	2.44	8.70	CH33-48	EL180UH090E60C	5742468
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.30	2.44	8.50	CH33-48	EL180UH110E60C	5740453
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.30	2.44	8.50	CH33-48	EL180UH110XE60C	5740805
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	CH33-48	EL296UH090XV36C	5054785
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	CH33-48	EL296UH090XV48C	5054786
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.28	2.42	8.50	CH33-48	EL296UH090XV60C	5054787
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CH33-48	EL296UH110XV60C	5054788
XP17-042-230	38,000	15.00	12.20	34,800	21,800	3.28	2.44	8.50	CH33-48	SL280UH090V60C	3894790
XP17-042-230	38,000	15.00	12.20	34,800	21,800	3.28	2.44	8.50	CH33-48	SL280UH090XV60C	4235865
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.46	8.50	CH33-48	SL280UH110V60C	3894791
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.46	8.50	CH33-48	SL280UH110XV60C	4042012

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	CH33-48	SLP98UH090XV36C	5136916
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	CH33-48	SLP98UH090XV48C	5136917
XP17-042-230	38,500	14.70	12.20	35,000	22,000	3.28	2.42	8.50	CH33-48	SLP98UH090XV60C	5136918
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CH33-48	SLP98UH110XV60C	5136919
XP17-042-230	38,000	14.70	12.00	35,000	22,000	3.26	2.42	8.50	CH33-48C	EL195UH090XE48C	4693633
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.32	2.44	8.50	CH33-48C	EL195UH110XE60C	4693634
XP17-042-230	38,000	14.70	12.00	35,000	22,000	3.26	2.42	8.50	CH33-48C	EL296UH090XE48C	5649831
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.32	2.44	8.50	CH33-48C	EL296UH110XE60C	5649832
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CH33-48C	EL296UH110XV48C	5685191
XP17-042-230	40,000	15.50	12.70	35,400	22,200	3.28	2.44	8.50	CH33-49	EL180UH090E60C	5742469
XP17-042-230	40,000	15.20	12.70	35,400	22,000	3.26	2.40	8.50	CH33-49	EL180UH110E60C	5740454
XP17-042-230	40,000	15.20	12.70	35,400	22,000	3.26	2.40	8.50	CH33-49	EL180UH110XE60C	5740806
XP17-042-230	39,500	15.20	12.50	35,200	22,200	3.22	2.40	8.50	CH33-49	EL195UH090XE48C	4693635
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.26	2.42	8.50	CH33-49	EL195UH110XE60C	4693636
XP17-042-230	39,500	15.20	12.50	35,200	22,200	3.22	2.40	8.50	CH33-49	EL296UH090XE48C	5649833
XP17-042-230	40,000	15.00	12.50	35,600	22,400	3.24	2.40	8.50	CH33-49	EL296UH090XV36C	5054789
XP17-042-230	40,000	15.20	12.50	35,400	22,200	3.24	2.40	8.50	CH33-49	EL296UH090XV48C	5054790
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.22	2.40	8.50	CH33-49	EL296UH090XV60C	5054791
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.26	2.42	8.50	CH33-49	EL296UH110XE60C	5649834
XP17-042-230	40,000	15.20	12.50	35,600	22,200	3.28	2.40	8.50	CH33-49	EL296UH110XV48C	5685221
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.28	2.42	8.50	CH33-49	EL296UH110XV60C	5054792
XP17-042-230	39,500	15.10	12.50	35,000	22,000	3.24	2.42	8.20	CH33-49	SL280UH090V60C	3894792
XP17-042-230	39,500	15.00	12.50	35,000	22,000	3.24	2.42	8.20	CH33-49	SL280UH090XV60C	4235862
XP17-042-230	40,000	15.20	12.70	35,600	22,200	3.28	2.42	8.50	CH33-49	SL280UH110V60C	3894793
XP17-042-230	40,000	15.20	12.70	35,600	22,200	3.28	2.42	8.50	CH33-49	SL280UH110XV60C	4042009
XP17-042-230	40,000	15.00	12.50	35,600	22,400	3.24	2.40	8.50	CH33-49	SLP98UH090XV36C	5136920
XP17-042-230	40,000	15.20	12.50	35,400	22,200	3.24	2.40	8.50	CH33-49	SLP98UH090XV48C	5136921
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.22	2.40	8.50	CH33-49	SLP98UH090XV60C	5136922
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.28	2.42	8.50	CH33-49	SLP98UH110XV60C	5136923
XP17-042-230	40,000	15.20	12.70	35,400	22,200	3.26	2.44	8.50	CH33-50/60C	EL180UH090E60C	5742470
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.24	2.40	8.50	CH33-50/60C	EL180UH110E60C	5740455
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.24	2.40	8.50	CH33-50/60C	EL180UH110XE60C	5740807
XP17-042-230	39,500	15.00	12.50	35,200	22,200	3.20	2.40	8.50	CH33-50/60C	EL195UH090XE48C	4693637
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.26	2.42	8.50	CH33-50/60C	EL195UH110XE60C	4693638
XP17-042-230	39,500	15.00	12.50	35,200	22,200	3.20	2.40	8.50	CH33-50/60C	EL296UH090XE48C	5649835
XP17-042-230	39,500	15.00	12.20	35,600	22,200	3.22	2.38	8.50	CH33-50/60C	EL296UH090XV36C	5054793
XP17-042-230	40,000	15.20	12.50	35,400	22,200	3.24	2.40	8.50	CH33-50/60C	EL296UH090XV48C	5054794
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.22	2.40	8.50	CH33-50/60C	EL296UH090XV60C	5054795
XP17-042-230	40,000	15.20	12.50	35,600	22,400	3.26	2.42	8.50	CH33-50/60C	EL296UH110XE60C	5649836
XP17-042-230	40,000	15.20	12.50	35,600	22,200	3.26	2.40	8.50	CH33-50/60C	EL296UH110XV48C	5685210
XP17-042-230	40,000	15.20	12.50	35,600	22,200	3.26	2.40	8.50	CH33-50/60C	EL296UH110XV60C	5054796
XP17-042-230	39,500	15.10	12.50	35,000	22,000	3.22	2.42	8.20	CH33-50/60C	SL280UH090V60C	3894794

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	39,500	15.10	12.50	35,000	22,000	3.22	2.42	8.20	CH33-50/60C	SL280UH090XV60C	4235863
XP17-042-230	40,000	15.20	12.70	35,600	22,200	3.28	2.42	8.50	CH33-50/60C	SL280UH110V60C	3894795
XP17-042-230	40,000	15.20	12.70	35,600	22,200	3.28	2.42	8.50	CH33-50/60C	SL280UH110XV60C	4042010
XP17-042-230	39,500	15.00	12.20	35,600	22,200	3.22	2.38	8.50	CH33-50/60C	SLP98UH090XV36C	5136924
XP17-042-230	40,000	15.20	12.50	35,400	22,200	3.24	2.40	8.50	CH33-50/60C	SLP98UH090XV48C	5136925
XP17-042-230	39,500	15.20	12.50	35,200	22,000	3.22	2.40	8.50	CH33-50/60C	SLP98UH090XV60C	5136926
XP17-042-230	40,000	15.20	12.50	35,600	22,200	3.26	2.40	8.50	CH33-50/60C	SLP98UH110XV60C	5136927
XP17-042-230	39,500	14.20	11.70	36,200	22,800	3.14	2.32	8.20	CH33-50/60C		3840169
XP17-042-230	38,500	14.50	12.00	35,600	22,600	3.32	2.48	8.50	CR33-48	EL180DF090E48B	5741571
XP17-042-230	39,000	14.50	12.00	35,400	22,400	3.28	2.48	8.50	CR33-48	EL180DF110E60C	5741597
XP17-042-230	38,500	14.20	11.70	35,800	22,800	3.24	2.44	8.50	CR33-48	EL195DF070XE48B	4693639
XP17-042-230	38,500	14.70	12.00	35,400	22,400	3.28	2.48	8.50	CR33-48	EL195DF090XE48C	4693640
XP17-042-230	38,500	14.70	12.00	35,800	22,600	3.30	2.46	8.70	CR33-48	EL195DF110XE60C	4693641
XP17-042-230	38,000	14.20	11.70	35,800	22,600	3.22	2.40	8.50	CR33-48	EL296DF045XV36B	7505737
XP17-042-230	38,500	14.20	11.70	35,800	22,800	3.24	2.44	8.50	CR33-48	EL296DF070XE48B	5649837
XP17-042-230	38,500	14.20	11.70	35,800	22,800	3.24	2.44	8.50	CR33-48	EL296DF070XV48B	7487525
XP17-042-230	38,500	14.70	12.00	35,400	22,400	3.28	2.48	8.50	CR33-48	EL296DF090XE48C	5649838
XP17-042-230	38,500	14.70	12.00	35,800	22,600	3.30	2.46	8.70	CR33-48	EL296DF110XE60C	5649839
XP17-042-230	39,000	14.50	12.00	36,000	22,800	3.30	2.46	8.50	CR33-48	SL280DF090V48B	3894796
XP17-042-230	38,500	14.50	12.20	35,200	22,200	3.30	2.50	8.50	CR33-48	SL280DF090V60C	3894797
XP17-042-230	39,000	14.50	12.00	35,600	22,400	3.34	2.48	8.50	CR33-48	SL280DF110V60C	3894798
XP17-042-230	38,500	14.20	11.70	36,000	22,800	3.24	2.42	8.50	CR33-48	SLP98DF070XV36B	5136928
XP17-042-230	38,500	14.50	12.00	35,800	22,800	3.28	2.46	8.50	CR33-48	SLP98DF090XV36C	5136929
XP17-042-230	38,500	14.70	12.20	35,600	22,600	3.28	2.46	8.50	CR33-48	SLP98DF090XV48C	5136930
XP17-042-230	39,000	14.50	12.00	36,000	22,800	3.32	2.46	8.70	CR33-48	SLP98DF090XV60C	5136931
XP17-042-230	39,000	14.70	12.00	36,000	22,800	3.34	2.48	8.70	CR33-48	SLP98DF110XV60C	5136932
XP17-042-230	39,500	15.00	12.50	36,000	22,600	3.56	2.62	9.20	CR33-50/60	EL180DF110E60C	5741598
XP17-042-230	39,000	14.70	12.00	36,000	22,600	3.50	2.58	9.00	CR33-50/60	EL195DF090XE48C	4693642
XP17-042-230	39,500	15.00	12.20	36,200	22,800	3.56	2.60	9.20	CR33-50/60	EL195DF110XE60C	4693643
XP17-042-230	39,000	14.70	12.00	36,000	22,600	3.50	2.58	9.00	CR33-50/60	EL296DF090XE48C	5649840
XP17-042-230	39,500	15.00	12.20	36,200	22,800	3.56	2.60	9.20	CR33-50/60	EL296DF110XE60C	5649841
XP17-042-230	39,500	15.20	12.50	36,000	22,600	3.58	2.62	9.20	CR33-50/60	SL280DF090V60C	4042170
XP17-042-230	39,500	15.20	12.50	35,800	22,400	3.58	2.62	9.20	CR33-50/60	SL280DF110V60C	4042171
XP17-042-230	39,000	14.70	12.00	36,200	22,800	3.52	2.58	9.00	CR33-50/60	SLP98DF090XV36C	5136988
XP17-042-230	39,000	15.00	12.20	36,000	22,600	3.52	2.58	9.00	CR33-50/60	SLP98DF090XV48C	5136989
XP17-042-230	39,500	14.70	12.20	36,400	22,800	3.56	2.58	9.20	CR33-50/60	SLP98DF090XV60C	5136990
XP17-042-230	39,500	15.00	12.20	36,200	22,800	3.58	2.62	9.20	CR33-50/60	SLP98DF110XV60C	5136991
XP17-042-230	39,000	14.70	12.00	35,400	22,200	3.08	2.38	8.20	CX34-38	EL180UH090E48B	5742238
XP17-042-230	39,000	14.70	12.00	35,400	22,200	3.08	2.38	8.20	CX34-38	EL180UH090XE48B	5740337
XP17-042-230	39,000	14.50	12.00	35,600	22,400	3.08	2.38	8.20	CX34-38	EL296UH070XV36B	5054797
XP17-042-230	39,500	14.70	12.20	35,400	22,400	3.10	2.40	8.20	CX34-38	SL280UH090V36B	3894755
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.08	2.40	8.20	CX34-38	SL280UH090V48B	3894756

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.08	2.40	8.20	CX34-38	SL280UH090XV48B	4041795
XP17-042-230	39,000	14.50	12.00	35,600	22,400	3.08	2.38	8.20	CX34-38	SLP98UH070XV36B	5137326
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.32	2.46	8.70	CX34-43	EL180UH090E48B	5742239
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.36	2.48	8.70	CX34-43	EL180UH090E60C	5742463
XP17-042-230	39,000	14.70	12.20	35,200	22,200	3.32	2.46	8.70	CX34-43	EL180UH090XE48B	5740338
XP17-042-230	39,000	15.00	12.50	35,000	22,000	3.34	2.48	8.70	CX34-43	EL180UH110E60C	5740448
XP17-042-230	39,000	15.00	12.50	35,000	22,000	3.34	2.48	8.70	CX34-43	EL180UH110XE60C	5740800
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.44	8.50	CX34-43	EL195UH090XE48C	4693624
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.46	8.70	CX34-43	EL195UH110XE60C	4693685
XP17-042-230	38,500	14.20	11.70	35,400	22,600	3.20	2.38	8.20	CX34-43	EL296UH070XV36B	5054761
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.44	8.50	CX34-43	EL296UH090XE48C	5649822
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	CX34-43	EL296UH090XV36C	5054762
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CX34-43	EL296UH090XV48C	5054763
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CX34-43	EL296UH090XV60C	5054764
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.36	2.46	8.70	CX34-43	EL296UH110XE60C	5649883
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	CX34-43	EL296UH110XV48C	5685202
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	CX34-43	EL296UH110XV60C	5054765
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-43	SL280UH090V36B	3894757
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	CX34-43	SL280UH090V48B	3894758
XP17-042-230	38,500	14.50	12.20	34,600	21,800	3.30	2.46	8.50	CX34-43	SL280UH090V60C	3894759
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	CX34-43	SL280UH090XV48B	4041796
XP17-042-230	38,500	15.10	12.20	34,600	21,800	3.30	2.46	8.50	CX34-43	SL280UH090XV60C	4235855
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.34	2.48	8.70	CX34-43	SL280UH110V60C	3894760
XP17-042-230	39,000	15.20	12.50	35,000	22,000	3.34	2.48	8.70	CX34-43	SL280UH110XV60C	4042006
XP17-042-230	38,500	14.20	11.70	35,400	22,600	3.20	2.38	8.20	CX34-43	SLP98UH070XV36B	5136856
XP17-042-230	38,500	14.70	12.20	35,000	22,200	3.28	2.44	8.50	CX34-43	SLP98UH090XV36C	5136893
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CX34-43	SLP98UH090XV48C	5136894
XP17-042-230	38,500	15.00	12.20	34,800	22,000	3.30	2.46	8.50	CX34-43	SLP98UH090XV60C	5136895
XP17-042-230	39,000	15.00	12.20	35,200	22,200	3.34	2.48	8.70	CX34-43	SLP98UH110XV60C	5136896
XP17-042-230	39,000	14.50	12.00	35,000	22,000	2.98	2.32	8.20	CX34-44/48	EL180UH090E48B	5742240
XP17-042-230	39,000	15.00	12.20	35,000	22,000	3.04	2.36	8.20	CX34-44/48	EL180UH090E60C	5742464
XP17-042-230	39,000	14.50	12.00	35,000	22,000	2.98	2.32	8.20	CX34-44/48	EL180UH090XE48B	5740339
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.02	2.36	8.20	CX34-44/48	EL180UH110E60C	5740449
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.02	2.36	8.20	CX34-44/48	EL180UH110XE60C	5740801
XP17-042-230	38,500	14.70	12.00	34,800	22,000	2.98	2.34	8.20	CX34-44/48	EL195UH090XE48C	4693625
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	CX34-44/48	EL195UH110XE60C	4693626
XP17-042-230	38,500	14.70	12.00	34,800	22,000	2.98	2.34	8.20	CX34-44/48	EL296UH090XE48C	5649823
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.00	2.34	8.20	CX34-44/48	EL296UH090XV36C	5054767
XP17-042-230	39,000	14.70	12.00	35,200	22,000	3.02	2.34	8.20	CX34-44/48	EL296UH090XV48C	5054768
XP17-042-230	39,000	14.70	12.20	34,800	22,000	2.98	2.36	8.20	CX34-44/48	EL296UH090XV60C	5054769
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	CX34-44/48	EL296UH110XE60C	5649824
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	CX34-44/48	EL296UH110XV48C	5685196

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	CX34-44/48	EL296UH110XV60C	5054770
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.02	2.34	8.20	CX34-44/48	SL280UH090V36B	3894761
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.00	2.34	8.20	CX34-44/48	SL280UH090V48B	3894762
XP17-042-230	39,000	14.70	12.20	35,000	22,000	3.00	2.34	8.20	CX34-44/48	SL280UH090XV48B	4041797
XP17-042-230	39,000	14.70	12.20	35,200	22,000	3.04	2.36	8.20	CX34-44/48	SL280UH110V60C	3894765
XP17-042-230	39,000	14.70	12.20	35,200	22,000	3.04	2.36	8.20	CX34-44/48	SL280UH110XV60C	4042002
XP17-042-230	39,000	14.50	12.00	35,200	22,200	3.00	2.34	8.20	CX34-44/48	SLP98UH090XV36C	5136898
XP17-042-230	39,000	14.70	12.00	35,200	22,000	3.02	2.34	8.20	CX34-44/48	SLP98UH090XV48C	5136899
XP17-042-230	39,000	14.70	12.20	34,800	22,000	2.98	2.36	8.20	CX34-44/48	SLP98UH090XV60C	5136900
XP17-042-230	39,000	14.70	12.00	35,200	22,200	3.04	2.36	8.20	CX34-44/48	SLP98UH110XV60C	5136901
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	CX34-49	EL180UH090E60C	5742465
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.22	2.52	8.70	CX34-49	EL180UH110E60C	5740450
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.22	2.52	8.70	CX34-49	EL180UH110XE60C	5740802
XP17-042-230	39,500	15.00	12.20	35,200	22,000	3.18	2.48	8.70	CX34-49	EL195UH090XE48C	4693627
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.24	2.50	8.70	CX34-49	EL195UH110XE60C	4693628
XP17-042-230	39,500	15.00	12.20	35,200	22,000	3.18	2.48	8.70	CX34-49	EL296UH090XE48C	5649825
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.22	2.52	8.70	CX34-49	EL296UH090XV36C	5054771
XP17-042-230	40,000	15.20	12.20	35,400	22,000	3.24	2.50	8.70	CX34-49	EL296UH090XV48C	5054772
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	CX34-49	EL296UH090XV60C	5054773
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.24	2.50	8.70	CX34-49	EL296UH110XE60C	5649826
XP17-042-230	40,000	15.20	12.20	35,400	22,200	3.26	2.54	8.70	CX34-49	EL296UH110XV48C	5685185
XP17-042-230	40,000	15.20	12.50	35,400	22,000	3.26	2.52	8.70	CX34-49	EL296UH110XV60C	5054774
XP17-042-230	39,500	14.50	12.50	35,000	21,800	3.24	2.54	8.50	CX34-49	SL280UH090V60C	3894766
XP17-042-230	39,500	15.50	12.50	35,000	21,800	3.24	2.54	8.50	CX34-49	SL280UH090XV60C	4235847
XP17-042-230	40,500	15.20	12.70	35,400	22,000	3.28	2.54	8.70	CX34-49	SL280UH110V60C	3894767
XP17-042-230	40,500	15.20	12.70	35,400	22,000	3.28	2.54	8.70	CX34-49	SL280UH110XV60C	4042003
XP17-042-230	40,000	15.00	12.20	35,400	22,200	3.22	2.52	8.70	CX34-49	SLP98UH090XV36C	5136902
XP17-042-230	40,000	15.20	12.20	35,400	22,000	3.24	2.50	8.70	CX34-49	SLP98UH090XV48C	5136903
XP17-042-230	40,000	15.20	12.50	35,200	22,000	3.24	2.52	8.70	CX34-49	SLP98UH090XV60C	5136904
XP17-042-230	40,000	15.20	12.50	35,400	22,000	3.26	2.52	8.70	CX34-49	SLP98UH110XV60C	5136905
XP17-042-230	39,500	14.00	11.50	36,000	22,800	3.10	2.40	8.50	CX34-49		3840053
XP17-042-230	38,500	15.00	12.20	35,000	22,000	3.30	2.44	8.50	CX34-50/60C	EL180UH090E60C	5742466
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.28	2.44	8.50	CX34-50/60C	EL180UH110E60C	5740451
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.28	2.44	8.50	CX34-50/60C	EL180UH110XE60C	5740803
XP17-042-230	38,000	14.70	12.00	34,800	22,000	3.24	2.40	8.50	CX34-50/60C	EL195UH090XE48C	4693629
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	EL195UH110XE60C	4693630
XP17-042-230	38,000	14.70	12.00	34,800	22,000	3.24	2.40	8.50	CX34-50/60C	EL296UH090XE48C	5649827
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	CX34-50/60C	EL296UH090XV36C	5054775
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	EL296UH090XV48C	5054776
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.24	2.42	8.50	CX34-50/60C	EL296UH090XV60C	5054777
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	EL296UH110XE60C	5649828
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	EL296UH110XV48C	5685216

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	EL296UH110XV60C	5054778
XP17-042-230	38,000	15.00	12.20	34,600	21,800	3.26	2.44	8.50	CX34-50/60C	SL280UH090V60C	3894768
XP17-042-230	38,000	15.00	12.20	34,600	21,800	3.26	2.44	8.50	CX34-50/60C	SL280UH090XV60C	4235848
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.44	8.50	CX34-50/60C	SL280UH110V60C	3894769
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.32	2.44	8.50	CX34-50/60C	SL280UH110XV60C	4042004
XP17-042-230	38,500	14.50	12.00	35,200	22,200	3.26	2.40	8.50	CX34-50/60C	SLP98UH090XV36C	5136906
XP17-042-230	38,500	14.70	12.20	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	SLP98UH090XV48C	5136907
XP17-042-230	38,500	14.70	12.20	34,800	22,000	3.24	2.42	8.50	CX34-50/60C	SLP98UH090XV60C	5136908
XP17-042-230	38,500	14.70	12.00	35,200	22,200	3.30	2.44	8.50	CX34-50/60C	SLP98UH110XV60C	5136909
XP17-048-230	48,000	14.70	12.20	45,000	31,200	3.34	2.42	8.50	C33-49	CBWMV-60C-100	4150373
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	C33-49	EL180UH090E60C	5742488
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.32	2.42	8.70	C33-49	EL180UH110E60C	5740473
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.32	2.42	8.70	C33-49	EL180UH110XE60C	5740825
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.42	8.50	C33-49	EL195UH090XE48C	4693663
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	C33-49	EL195UH110XE60C	4693664
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.42	8.50	C33-49	EL296UH090XE48C	5649861
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	C33-49	EL296UH090XV48C	5054833
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.32	2.40	8.50	C33-49	EL296UH090XV60C	5054834
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	C33-49	EL296UH110XE60C	5649862
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	C33-49	EL296UH110XV48C	5685203
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	C33-49	EL296UH110XV60C	5054835
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.36	2.42	8.70	C33-49	SL280UH090V60C	3894849
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.36	2.42	8.70	C33-49	SL280UH090XV60C	4235871
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	C33-49	SL280UH110V60C	3894850
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	C33-49	SL280UH110XV60C	4042026
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	C33-49	SLP98UH090XV48C	5137368
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.32	2.40	8.50	C33-49	SLP98UH090XV60C	5137370
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	C33-49	SLP98UH110XV60C	5137371
XP17-048-230	47,500	14.00	11.70	46,000	31,800	3.30	2.40	8.50	C33-49		3840223
XP17-048-230	47,500	14.50	12.20	45,000	31,200	3.40	2.48	8.70	C33-60D	EL180UH135E60D	5740966
XP17-048-230	47,000	14.20	12.00	45,000	31,400	3.38	2.44	8.70	C33-60D	EL195UH135XE60D	4693665
XP17-048-230	47,000	14.20	12.00	45,000	31,400	3.38	2.44	8.70	C33-60D	EL296UH135XE60D	5649863
XP17-048-230	47,000	14.50	12.20	45,000	31,200	3.38	2.46	8.70	C33-60D	EL296UH135XV60D	5054840
XP17-048-230	47,000	14.50	12.20	45,000	31,000	3.40	2.46	8.70	C33-60D	SL280UH135V60D	3894853
XP17-048-230	47,000	14.50	12.20	45,000	31,200	3.38	2.46	8.70	C33-60D	SLP98UH135XV60D	5137376
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	C33-62C	EL180UH090E60C	5742479
XP17-048-230	49,000	15.20	12.70	45,000	31,000	3.42	2.46	8.70	C33-62C	EL180UH110E60C	5740465
XP17-048-230	49,000	15.20	12.70	45,000	31,000	3.42	2.46	8.70	C33-62C	EL180UH110XE60C	5740817
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	C33-62C	EL195UH090XE48C	4693666
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.46	2.46	8.70	C33-62C	EL195UH110XE60C	4693667
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	C33-62C	EL296UH090XE48C	5649864
XP17-048-230	49,500	15.20	12.70	45,500	31,400	3.44	2.46	8.70	C33-62C	EL296UH090XV48C	5054836

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.44	2.44	8.70	C33-62C	EL296UH090XV60C	5054837
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.46	2.46	8.70	C33-62C	EL296UH110XE60C	5649865
XP17-048-230	49,000	15.00	12.50	45,500	31,400	3.42	2.46	8.70	C33-62C	EL296UH110XV48C	5685193
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	C33-62C	EL296UH110XV60C	5054838
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	C33-62C	SL280UH090V60C	3894851
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	C33-62C	SL280UH090XV60C	4235872
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.48	2.48	8.70	C33-62C	SL280UH110V60C	3894852
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.48	2.48	8.70	C33-62C	SL280UH110XV60C	4042027
XP17-048-230	49,500	15.20	12.70	45,500	31,400	3.44	2.46	8.70	C33-62C	SLP98UH090XV48C	5137372
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.44	2.44	8.70	C33-62C	SLP98UH090XV60C	5137373
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	C33-62C	SLP98UH110XV60C	5137374
XP17-048-230	49,000	14.70	12.00	46,000	31,800	3.36	2.40	8.50	C33-62C		3840230
XP17-048-230	49,000	15.20	12.70	45,500	31,200	3.46	2.48	8.70	C33-62D	EL180UH135E60D	5740967
XP17-048-230	48,500	14.70	12.20	45,000	31,400	3.38	2.44	8.70	C33-62D	EL195UH135XE60D	4693668
XP17-048-230	48,500	14.70	12.20	45,000	31,400	3.38	2.44	8.70	C33-62D	EL296UH135XE60D	5649866
XP17-048-230	48,500	15.20	12.50	45,000	31,200	3.40	2.48	8.70	C33-62D	EL296UH135XV60D	5054839
XP17-048-230	48,500	15.20	12.70	45,000	31,000	3.40	2.48	9.00	C33-62D	SL280UH135V60D	3894854
XP17-048-230	48,500	15.20	12.50	45,000	31,200	3.40	2.48	8.70	C33-62D	SLP98UH135XV60D	5137375
XP17-048-230	48,500	14.20	12.00	46,000	31,800	3.32	2.40	8.50	C33-62D		3840245
XP17-048-230	48,000	15.00	12.50	47,000	31,800	3.48	2.58	9.20	CBX27UH-048		3840193
XP17-048-230	48,000	15.00	12.50	47,000	31,800	3.50	2.58	9.20	CBX27UH-060		3840194
XP17-048-230	48,000	14.70	12.20	47,000	32,000	3.44	2.56	8.50	CBX32M-048		3840195
XP17-048-230	48,000	14.50	12.20	47,000	32,000	3.40	2.52	9.00	CBX32M-060		3840196
XP17-048-230	47,000	15.00	12.50	46,000	31,000	3.40	2.54	8.50	CBX32MV-048		3840288
XP17-048-230	48,000	15.20	12.70	46,000	31,000	3.44	2.54	9.00	CBX32MV-060		3840286
XP17-048-230	48,000	15.20	12.70	45,500	30,800	3.18	2.38	8.50	CBX32MV-068		3840290
XP17-048-230	47,500	15.00	12.50	46,500	31,200	3.46	2.54	9.00	CBX40UHV-048		3840191
XP17-048-230	47,500	15.00	12.50	46,500	31,200	3.46	2.54	9.00	CBX40UHV-060		3840192
XP17-048-230	48,500	15.00	12.50	45,000	31,200	3.36	2.44	8.70	CH33-49	EL180UH090E60C	5742473
XP17-048-230	48,000	14.70	12.20	45,000	31,000	3.34	2.42	8.70	CH33-49	EL180UH110E60C	5740458
XP17-048-230	48,000	14.70	12.20	45,000	31,000	3.34	2.42	8.70	CH33-49	EL180UH110XE60C	5740810
XP17-048-230	48,500	14.70	12.20	45,500	31,200	3.36	2.42	8.70	CH33-49	EL195UH090XE48C	4693655
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.36	2.44	8.70	CH33-49	EL195UH110XE60C	4693656
XP17-048-230	48,500	14.70	12.20	45,500	31,200	3.36	2.42	8.70	CH33-49	EL296UH090XE48C	5649853
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	EL296UH090XV48C	5054825
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	EL296UH090XV60C	5054826
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.36	2.44	8.70	CH33-49	EL296UH110XE60C	5649854
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	EL296UH110XV48C	5685198
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	EL296UH110XV60C	5054827
XP17-048-230	48,500	15.00	12.50	45,500	31,200	3.40	2.44	8.70	CH33-49	SL280UH090V60C	3894855
XP17-048-230	48,500	15.00	12.50	45,500	31,200	3.40	2.44	8.70	CH33-49	SL280UH090XV60C	4235873
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.38	2.44	8.70	CH33-49	SL280UH110V60C	3894856

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.38	2.44	8.70	CH33-49	SL280UH110XV60C	4042028
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	SLP98UH090XV48C	5136941
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	SLP98UH090XV60C	5136942
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.36	2.42	8.70	CH33-49	SLP98UH110XV60C	5136943
XP17-048-230	48,500	14.20	12.00	46,000	31,800	3.32	2.40	8.50	CH33-49		3840249
XP17-048-230	48,000	15.00	12.20	45,000	31,000	3.34	2.44	8.70	CH33-50/60C	EL180UH090E60C	5742474
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.34	2.42	8.70	CH33-50/60C	EL180UH110E60C	5740459
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.34	2.42	8.70	CH33-50/60C	EL180UH110XE60C	5740811
XP17-048-230	48,000	14.70	12.20	45,500	31,200	3.34	2.42	8.70	CH33-50/60C	EL195UH090XE48C	4693657
XP17-048-230	48,000	14.50	12.20	45,000	31,000	3.34	2.44	8.70	CH33-50/60C	EL195UH110XE60C	4693658
XP17-048-230	48,000	14.70	12.20	45,500	31,200	3.34	2.42	8.70	CH33-50/60C	EL296UH090XE48C	5649855
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	EL296UH090XV48C	5054828
XP17-048-230	48,500	14.50	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	EL296UH090XV60C	5054829
XP17-048-230	48,000	14.50	12.20	45,000	31,000	3.34	2.44	8.70	CH33-50/60C	EL296UH110XE60C	5649856
XP17-048-230	48,000	14.50	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	EL296UH110XV48C	5685188
XP17-048-230	48,000	14.50	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	EL296UH110XV60C	5054830
XP17-048-230	48,500	15.00	12.50	45,000	31,200	3.40	2.48	8.70	CH33-50/60C	SL280UH090V60C	3894857
XP17-048-230	48,500	15.00	12.50	45,000	31,200	3.40	2.48	8.70	CH33-50/60C	SL280UH090XV60C	4235874
XP17-048-230	48,500	15.00	12.50	45,000	31,200	3.40	2.48	8.70	CH33-50/60C	SL280UH110V60C	3894858
XP17-048-230	48,500	15.00	12.50	45,000	31,200	3.40	2.48	8.70	CH33-50/60C	SL280UH110XV60C	4042029
XP17-048-230	48,500	14.70	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	SLP98UH090XV48C	5136944
XP17-048-230	48,500	14.50	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	SLP98UH090XV60C	5136945
XP17-048-230	48,000	14.50	12.20	45,500	31,400	3.34	2.42	8.70	CH33-50/60C	SLP98UH110XV60C	5136946
XP17-048-230	48,000	14.20	11.70	46,000	31,800	3.32	2.40	8.50	CH33-50/60C		3840260
XP17-048-230	47,000	14.50	12.00	46,000	31,400	3.10	2.34	8.20	CH33-60D	EL180UH135E60D	5740963
XP17-048-230	47,000	14.20	12.00	46,000	31,800	3.04	2.32	8.20	CH33-60D	EL195UH135XE60D	4693659
XP17-048-230	47,000	14.20	12.00	46,000	31,800	3.04	2.32	8.20	CH33-60D	EL296UH135XE60D	5649857
XP17-048-230	47,000	14.50	12.20	46,000	31,400	3.08	2.32	8.20	CH33-60D	EL296UH135XV60D	5054831
XP17-048-230	46,500	14.50	12.20	45,500	31,200	3.04	2.32	8.20	CH33-60D	SL280UH135V60D	3894859
XP17-048-230	47,000	14.50	12.20	46,000	31,400	3.08	2.32	8.20	CH33-60D	SLP98UH135XV60D	5136947
XP17-048-230	48,500	15.00	12.50	46,000	31,600	3.16	2.38	8.50	CH33-62D	EL180UH135E60D	5740964
XP17-048-230	48,000	14.50	12.20	46,000	31,800	3.14	2.34	8.20	CH33-62D	EL195UH135XE60D	4693660
XP17-048-230	48,000	14.50	12.20	46,000	31,800	3.14	2.34	8.20	CH33-62D	EL296UH135XE60D	5649858
XP17-048-230	48,000	14.70	12.50	46,000	31,600	3.14	2.38	8.20	CH33-62D	EL296UH135XV60D	5054832
XP17-048-230	48,000	15.00	12.50	46,000	31,400	3.14	2.38	8.20	CH33-62D	SL280UH135V60D	3894860
XP17-048-230	48,000	14.70	12.50	46,000	31,600	3.14	2.38	8.20	CH33-62D	SLP98UH135XV60D	5136948
XP17-048-230	48,000	14.00	11.70	46,500	32,000	3.04	2.30	8.20	CH33-62D		3840275
XP17-048-230	48,000	15.00	12.50	47,500	32,200	3.40	2.54	9.00	CR33-50/60	EL180DF110E60C	5741599
XP17-048-230	47,500	14.50	12.00	48,000	32,400	3.36	2.50	8.70	CR33-50/60	EL195DF090XE48C	4693661
XP17-048-230	47,500	14.50	12.20	47,500	32,200	3.36	2.50	8.70	CR33-50/60	EL195DF110XE60C	4693662
XP17-048-230	47,500	14.50	12.00	48,000	32,400	3.36	2.50	8.70	CR33-50/60	EL296DF090XE48C	5649859
XP17-048-230	47,500	14.50	12.20	47,500	32,200	3.36	2.50	8.70	CR33-50/60	EL296DF110XE60C	5649860

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

## AHRI SYSTEM MATCHES

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-048-230	48,000	15.00	12.50	48,000	32,200	3.46	2.54	9.00	CR33-50/60	SL280DF090V60C	4016201
XP17-048-230	48,000	15.00	12.50	47,500	32,200	3.44	2.56	9.00	CR33-50/60	SL280DF110V60C	4016202
XP17-048-230	48,000	14.50	12.20	48,000	32,400	3.40	2.50	8.70	CR33-50/60	SLP98DF090XV60C	5136949
XP17-048-230	48,000	14.50	12.20	48,000	32,400	3.40	2.50	8.70	CR33-50/60	SLP98DF110XV60C	5136950
XP17-048-230	47,500	14.00	11.70	48,500	32,800	3.34	2.46	8.70	CR33-50/60		4016194
XP17-048-230	48,000	14.70	12.20	45,000	31,200	3.34	2.42	8.50	CX34-49	CBWMV-60C-100	4150374
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	CX34-49	EL180UH090E60C	5742471
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.32	2.42	8.70	CX34-49	EL180UH110E60C	5740456
XP17-048-230	48,000	15.00	12.50	45,000	31,000	3.32	2.42	8.70	CX34-49	EL180UH110XE60C	5740808
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.42	8.50	CX34-49	EL195UH090XE48C	4693649
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	CX34-49	EL195UH110XE60C	4693650
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.42	8.50	CX34-49	EL296UH090XE48C	5649847
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	CX34-49	EL296UH090XV48C	5054817
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.32	2.40	8.50	CX34-49	EL296UH090XV60C	5054818
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	CX34-49	EL296UH110XE60C	5649848
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	CX34-49	EL296UH110XV48C	5685182
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	CX34-49	EL296UH110XV60C	5054819
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.36	2.42	8.70	CX34-49	SL280UH090V60C	3894843
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.36	2.42	8.70	CX34-49	SL280UH090XV60C	4235869
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	CX34-49	SL280UH110V60C	3894844
XP17-048-230	48,500	15.00	12.50	45,000	31,000	3.34	2.42	8.70	CX34-49	SL280UH110XV60C	4042024
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.30	2.40	8.50	CX34-49	SLP98UH090XV48C	5136933
XP17-048-230	48,500	14.70	12.20	45,000	31,200	3.32	2.40	8.50	CX34-49	SLP98UH090XV60C	5136934
XP17-048-230	48,500	14.70	12.50	45,000	31,200	3.32	2.42	8.50	CX34-49	SLP98UH110XV60C	5136935
XP17-048-230	47,500	14.00	11.70	46,000	31,800	3.30	2.40	8.50	CX34-49		3840197
XP17-048-230	47,500	14.50	12.20	45,000	31,200	3.40	2.48	8.70	CX34-60D	EL180UH135E60D	5740961
XP17-048-230	47,000	14.20	12.00	45,000	31,400	3.38	2.44	8.70	CX34-60D	EL195UH135XE60D	4693651
XP17-048-230	47,000	14.20	12.00	45,000	31,400	3.38	2.44	8.70	CX34-60D	EL296UH135XE60D	5649849
XP17-048-230	47,000	14.50	12.20	45,000	31,200	3.38	2.46	8.70	CX34-60D	EL296UH135XV60D	5054823
XP17-048-230	47,000	14.50	12.20	45,000	31,000	3.40	2.46	8.70	CX34-60D	SL280UH135V60D	3894847
XP17-048-230	47,000	14.50	12.20	45,000	31,200	3.38	2.46	8.70	CX34-60D	SLP98UH135XV60D	5136939
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	CX34-62C	EL180UH090E60C	5742472
XP17-048-230	49,000	15.20	12.70	45,000	31,000	3.42	2.46	8.70	CX34-62C	EL180UH110E60C	5740457
XP17-048-230	49,000	15.20	12.70	45,000	31,000	3.42	2.46	8.70	CX34-62C	EL180UH110XE60C	5740809
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	CX34-62C	EL195UH090XE48C	4693652
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.46	2.46	8.70	CX34-62C	EL195UH110XE60C	4693653
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	CX34-62C	EL296UH090XE48C	5649850
XP17-048-230	49,500	15.20	12.70	45,500	31,400	3.44	2.46	8.70	CX34-62C	EL296UH090XV48C	5054820
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.44	2.44	8.70	CX34-62C	EL296UH090XV60C	5054821
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.46	2.46	8.70	CX34-62C	EL296UH110XE60C	5649851
XP17-048-230	49,000	15.00	12.50	45,500	31,400	3.42	2.46	8.70	CX34-62C	EL296UH110XV48C	5685213
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	CX34-62C	EL296UH110XV60C	5054822

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	CX34-62C	SL280UH090V60C	3894845
XP17-048-230	49,500	15.50	12.70	45,500	31,000	3.48	2.46	8.70	CX34-62C	SL280UH090XV60C	4235870
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.48	2.48	8.70	CX34-62C	SL280UH110V60C	3894846
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.48	2.48	8.70	CX34-62C	SL280UH110XV60C	4042025
XP17-048-230	49,500	15.20	12.70	45,500	31,400	3.44	2.46	8.70	CX34-62C	SLP98UH090XV48C	5136936
XP17-048-230	49,500	15.20	12.70	45,500	31,200	3.44	2.44	8.70	CX34-62C	SLP98UH090XV60C	5136937
XP17-048-230	49,000	15.20	12.50	45,500	31,200	3.44	2.44	8.70	CX34-62C	SLP98UH110XV60C	5136938
XP17-048-230	49,000	14.70	12.00	46,000	31,800	3.36	2.40	8.50	CX34-62C		3840204
XP17-048-230	49,000	15.20	12.70	45,500	31,200	3.46	2.48	8.70	CX34-62D	EL180UH135E60D	5740962
XP17-048-230	48,500	14.70	12.20	45,000	31,400	3.38	2.44	8.70	CX34-62D	EL195UH135XE60D	4693654
XP17-048-230	48,500	14.70	12.20	45,000	31,400	3.38	2.44	8.70	CX34-62D	EL296UH135XE60D	5649852
XP17-048-230	48,500	15.20	12.50	45,000	31,200	3.40	2.48	8.70	CX34-62D	EL296UH135XV60D	5054824
XP17-048-230	48,500	15.20	12.70	45,000	31,000	3.40	2.48	9.00	CX34-62D	SL280UH135V60D	3894848
XP17-048-230	48,500	15.20	12.50	45,000	31,200	3.40	2.48	8.70	CX34-62D	SLP98UH135XV60D	5136940
XP17-048-230	48,500	14.20	12.00	46,000	31,800	3.32	2.40	8.50	CX34-62D		3840219
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.16	2.34	8.50	C33-49	EL180UH090E60C	5742480
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.14	2.34	8.20	C33-49	EL180UH110E60C	5740466
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.14	2.34	8.20	C33-49	EL180UH110XE60C	5740818
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.14	2.34	8.20	C33-49	EL195UH110XE60C	4693677
XP17-060-230	54,000	14.20	11.70	51,000	35,800	3.10	2.32	8.20	C33-49	EL296UH090XV60C	5054851
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.14	2.34	8.20	C33-49	EL296UH110XE60C	5649875
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.12	2.32	8.20	C33-49	EL296UH110XV60C	5054852
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.16	2.36	8.50	C33-49	SL280UH090V60C	3894887
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.16	2.36	8.50	C33-49	SL280UH090XV60C	4235882
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.14	2.36	8.20	C33-49	SL280UH110V60C	3894888
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.14	2.36	8.20	C33-49	SL280UH110XV60C	4042036
XP17-060-230	54,000	14.20	11.70	51,000	35,800	3.10	2.32	8.20	C33-49	SLP98UH090XV60C	5137341
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.12	2.32	8.20	C33-49	SLP98UH110XV60C	5137342
XP17-060-230	55,000	14.00	11.70	51,500	36,200	3.14	2.34	8.20	C33-49		3840371
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.42	8.70	C33-62C	EL180UH090E60C	5742481
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.40	8.70	C33-62C	EL180UH110E60C	5740467
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.40	8.70	C33-62C	EL180UH110XE60C	5740819
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.28	2.40	8.50	C33-62C	EL195UH110XE60C	4693678
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.28	2.40	8.50	C33-62C	EL296UH110XE60C	5649876
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.40	8.70	C33-62C	SL280UH090V60C	3894884
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.40	8.70	C33-62C	SL280UH090XV60C	4235892
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.28	2.40	8.70	C33-62C	SL280UH110V60C	3894885
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.28	2.40	8.70	C33-62C	SL280UH110XV60C	4042041
XP17-060-230	56,500	14.20	12.00	52,000	36,200	3.28	2.38	8.50	C33-62C		3840358
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.42	8.70	C33-62D	EL180UH135E60D	5740968
XP17-060-230	56,000	14.20	12.00	51,000	36,200	3.26	2.40	8.50	C33-62D	EL195UH135XE60D	4693679
XP17-060-230	56,000	14.20	12.00	51,000	36,200	3.26	2.40	8.50	C33-62D	EL296UH135XE60D	5649877

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines):

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-060-230	56,000	14.70	12.20	51,000	35,800	3.24	2.40	8.50	C33-62D	EL296UH135XV60D	5054850
XP17-060-230	56,000	15.00	12.50	51,000	35,400	3.30	2.44	8.70	C33-62D	SL280UH135V60D	3894886
XP17-060-230	56,000	14.70	12.20	51,000	35,800	3.24	2.40	8.50	C33-62D	SLP98UH135XV60D	5137340
XP17-060-230	56,000	14.20	11.70	52,000	36,200	3.22	2.36	8.50	C33-62D		3840367
XP17-060-230	55,500	14.50	12.00	53,000	36,400	3.36	2.50	9.00	CBX27UH-060		3840334
XP17-060-230	55,500	14.50	12.00	53,500	36,600	3.34	2.48	8.70	CBX32M-060		3840335
XP17-060-230	56,000	15.00	12.50	52,500	36,000	3.34	2.52	9.00	CBX32MV-060		3840331
XP17-060-230	56,000	15.00	12.50	51,000	35,400	3.32	2.46	8.70	CBX32MV-068		3840332
XP17-060-230	55,500	14.70	12.20	53,000	36,200	3.34	2.50	9.00	CBX40UHV-060		3840333
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CH33-49	EL195UH110XE60C	4693672
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CH33-49	EL296UH090XV60C	5054846
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CH33-49	EL296UH110XE60C	5649870
XP17-060-230	55,000	14.20	11.70	51,500	36,000	3.22	2.38	8.50	CH33-49	EL296UH110XV60C	5054847
XP17-060-230	55,000	14.50	12.00	51,500	35,800	3.26	2.40	8.50	CH33-49	SL280UH090V60C	3894890
XP17-060-230	55,000	14.50	12.00	51,500	35,800	3.26	2.40	8.50	CH33-49	SL280UH090XV60C	4235883
XP17-060-230	55,000	14.20	12.00	51,500	35,800	3.24	2.40	8.50	CH33-49	SL280UH110V60C	3894891
XP17-060-230	55,000	14.20	12.00	51,500	35,800	3.24	2.40	8.50	CH33-49	SL280UH110XV60C	4042037
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CH33-49	SLP98UH090XV60C	5136956
XP17-060-230	55,000	14.20	11.70	51,500	36,000	3.22	2.38	8.50	CH33-49	SLP98UH110XV60C	5136957
XP17-060-230	54,500	14.00	11.70	51,500	36,000	3.18	2.36	8.50	CH33-49		3840384
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.18	2.38	8.50	CH33-50/60C	EL180UH090E60C	5742477
XP17-060-230	54,000	14.00	11.70	51,000	35,800	3.16	2.38	8.50	CH33-50/60C	EL180UH110E60C	5740462
XP17-060-230	54,000	14.00	11.70	51,000	35,800	3.16	2.38	8.50	CH33-50/60C	EL180UH110XE60C	5740814
XP17-060-230	54,000	14.00	11.70	51,000	35,800	3.14	2.36	8.20	CH33-50/60C	EL195UH110XE60C	4693673
XP17-060-230	54,000	14.00	11.70	51,500	35,800	3.14	2.34	8.20	CH33-50/60C	EL296UH090XV60C	5054848
XP17-060-230	54,000	14.00	11.70	51,000	35,800	3.14	2.36	8.20	CH33-50/60C	EL296UH110XE60C	5649871
XP17-060-230	54,000	14.00	11.70	51,000	35,600	3.12	2.34	8.20	CH33-50/60C	EL296UH110XV60C	5054849
XP17-060-230	54,500	14.20	11.70	51,500	35,800	3.24	2.40	8.50	CH33-50/60C	SL280UH090V60C	3894892
XP17-060-230	54,500	14.20	11.70	51,500	35,800	3.24	2.40	8.50	CH33-50/60C	SL280UH090XV60C	4235884
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.18	2.40	8.50	CH33-50/60C	SL280UH110V60C	3894893
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.18	2.40	8.50	CH33-50/60C	SL280UH110XV60C	4042038
XP17-060-230	54,000	14.00	11.70	51,500	35,800	3.14	2.34	8.20	CH33-50/60C	SLP98UH090XV60C	5136958
XP17-060-230	54,000	14.00	11.70	51,000	35,600	3.12	2.34	8.20	CH33-50/60C	SLP98UH110XV60C	5136959
XP17-060-230	54,500	14.00	11.70	51,500	36,000	3.16	2.36	8.50	CH33-50/60C		3840393
XP17-060-230	54,500	14.00	11.50	51,000	36,200	3.16	2.36	8.50	CH33-60D	EL195UH135XE60D	4693674
XP17-060-230	54,500	14.00	11.50	51,000	36,200	3.16	2.36	8.50	CH33-60D	EL296UH135XE60D	5649872
XP17-060-230	54,500	14.20	11.70	51,000	35,600	3.18	2.38	8.50	CH33-60D	EL296UH135XV60D	5054845
XP17-060-230	54,500	14.20	11.70	51,000	35,600	3.18	2.38	8.50	CH33-60D	SLP98UH135XV60D	5136955
XP17-060-230	54,500	14.00	11.70	51,000	36,200	3.18	2.36	8.50	CH33-62D	EL195UH135XE60D	4693675
XP17-060-230	54,500	14.00	11.70	51,000	36,200	3.18	2.36	8.50	CH33-62D	EL296UH135XE60D	5649873
XP17-060-230	54,500	14.50	12.00	51,000	35,600	3.20	2.38	8.50	CH33-62D	EL296UH135XV60D	5054844
XP17-060-230	55,000	14.70	12.20	50,500	35,400	3.24	2.42	8.70	CH33-62D	SL280UH135V60D	3894889

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-060-230	54,500	14.50	12.00	51,000	35,600	3.20	2.38	8.50	CH33-62D	SLP98UH135XV60D	5136954
XP17-060-230	55,000	14.00	11.70	51,500	36,200	3.16	2.36	8.50	CH33-62D		3840380
XP17-060-230	54,000	14.20	11.70	54,500	37,000	3.22	2.46	8.70	CR33-50/60	EL195DF110XE60C	4693676
XP17-060-230	54,000	14.20	11.70	54,500	37,000	3.22	2.46	8.70	CR33-50/60	EL296DF110XE60C	5649874
XP17-060-230	54,500	14.20	11.70	54,500	37,000	3.24	2.46	8.70	CR33-50/60	SL280DF090V60C	4042181
XP17-060-230	54,500	14.50	12.00	54,000	37,000	3.24	2.48	8.70	CR33-50/60	SL280DF110V60C	4042182
XP17-060-230	53,500	14.00	11.50	54,500	37,000	3.16	2.42	8.70	CR33-50/60	SLP98DF110XV60C	6507220
XP17-060-230	54,500	14.00	11.50	55,000	37,400	3.22	2.42	8.70	CR33-50/60		4042214
XP17-060-230	54,500	14.00	11.50	55,000	37,400	3.22	2.42	8.70	CR33-60		4042183
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.16	2.34	8.50	CX34-49	EL180UH090E60C	5742475
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.14	2.34	8.20	CX34-49	EL180UH110E60C	5740460
XP17-060-230	55,000	14.20	12.00	51,000	35,600	3.14	2.34	8.20	CX34-49	EL180UH110XE60C	5740812
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.14	2.34	8.20	CX34-49	EL195UH110XE60C	4693669
XP17-060-230	54,000	14.20	11.70	51,000	35,800	3.10	2.32	8.20	CX34-49	EL296UH090XV60C	5054842
XP17-060-230	54,500	14.20	11.70	51,000	35,800	3.14	2.34	8.20	CX34-49	EL296UH110XE60C	5649867
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.12	2.32	8.20	CX34-49	EL296UH110XV60C	5054843
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CX34-49	SL280UH090V60C	3894882
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.16	2.36	8.50	CX34-49	SL280UH090XV60C	4235891
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.14	2.36	8.20	CX34-49	SL280UH110V60C	3894883
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.14	2.36	8.20	CX34-49	SL280UH110XV60C	4042040
XP17-060-230	54,000	14.20	11.70	51,000	35,800	3.10	2.32	8.20	CX34-49	SLP98UH090XV60C	5136952
XP17-060-230	55,000	14.20	11.70	51,000	35,800	3.12	2.32	8.20	CX34-49	SLP98UH110XV60C	5136953
XP17-060-230	55,000	14.00	11.70	51,500	36,200	3.14	2.34	8.20	CX34-49		3840349
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.42	8.70	CX34-62C	EL180UH090E60C	5742476
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.40	8.70	CX34-62C	EL180UH110E60C	5740461
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.40	8.70	CX34-62C	EL180UH110XE60C	5740813
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.28	2.40	8.50	CX34-62C	EL195UH110XE60C	4693670
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.24	2.38	8.50	CX34-62C	EL296UH090XV60C	5054853
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.28	2.40	8.50	CX34-62C	EL296UH110XE60C	5649868
XP17-060-230	55,500	14.70	12.20	51,000	35,600	3.22	2.38	8.50	CX34-62C	EL296UH110XV60C	5054854
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.40	8.70	CX34-62C	SL280UH090V60C	3894879
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.30	2.40	8.70	CX34-62C	SL280UH090XV60C	4235881
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.28	2.40	8.70	CX34-62C	SL280UH110V60C	3894880
XP17-060-230	56,000	14.70	12.20	51,500	35,800	3.28	2.40	8.70	CX34-62C	SL280UH110XV60C	4042039
XP17-060-230	55,500	14.50	12.00	51,500	35,800	3.24	2.38	8.50	CX34-62C	SLP98UH090XV60C	5137377
XP17-060-230	55,500	14.70	12.20	51,000	35,600	3.22	2.38	8.50	CX34-62C	SLP98UH110XV60C	5137378
XP17-060-230	56,500	14.20	12.00	52,000	36,200	3.28	2.38	8.50	CX34-62C		3840336
XP17-060-230	56,000	14.70	12.00	51,500	35,800	3.28	2.42	8.70	CX34-62D	EL180UH135E60D	5740965
XP17-060-230	56,000	14.20	12.00	51,000	36,200	3.26	2.40	8.50	CX34-62D	EL195UH135XE60D	4693671
XP17-060-230	56,000	14.20	12.00	51,000	36,200	3.26	2.40	8.50	CX34-62D	EL296UH135XE60D	5649869
XP17-060-230	56,000	14.70	12.20	51,000	35,800	3.24	2.40	8.50	CX34-62D	EL296UH135XV60D	5054841
XP17-060-230	56,000	15.00	12.50	51,000	35,400	3.30	2.44	8.70	CX34-62D	SL280UH135V60D	3894881

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP17-060-230	56,000	14.70	12.20	51,000	35,800	3.24	2.40	8.50	CX34-62D	SLP98UH135XV60D	5136951
XP17-060-230	56,000	14.20	11.70	52,000	36,200	3.22	2.36	8.50	CX34-62D		3840345

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80 °F db/67° F wb entering indoor coil air.
- High Temperature Heating Ratings - 47° F db/43° F wb outdoor air temperature and 70 °F db entering indoor coil air.
- Low Temperature Heating Ratings - 17 °F db/15° F wb outdoor air temperature and 70 °F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP20-024-230A	22,600	18.50	13.50	21,600	13,500	3.62	2.34	9.00	C33-31A	SL280UH070V36A	8635948
XP20-024-230A	22,600	18.50	13.50	21,600	13,500	3.62	2.34	9.00	C33-31A	SL280UH070XV36A	8635949
XP20-024-230A	22,600	18.50	13.50	21,600	13,600	3.60	2.34	9.00	C33-31B	EL296UH045XV36B	8635950
XP20-024-230A	22,600	19.00	13.50	21,600	13,500	3.62	2.34	9.00	C33-31B	EL296UH070XV36B	8635951
XP20-024-230A	22,600	19.00	13.50	21,400	13,500	3.62	2.36	9.00	C33-31B	SL280UH090V36B	8635952
XP20-024-230A	22,600	19.00	13.50	21,600	13,500	3.62	2.34	9.00	C33-31B	SLP98UH070XV36B	8635953
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.50	C33-38A	SL280UH070V36A	8550435
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.50	C33-38A	SL280UH070XV36A	8550436
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.66	2.32	9.60	C33-38B	EL296UH045XV36B	8550437
XP20-024-230A	23,000	19.00	13.50	21,800	13,300	3.68	2.34	9.60	C33-38B	EL296UH070XV36B	8550438
XP20-024-230A	23,000	19.00	13.50	21,800	13,300	3.72	2.36	9.60	C33-38B	SL280UH090V36B	8550439
XP20-024-230A	23,000	19.00	13.50	21,800	13,300	3.68	2.34	9.60	C33-38B	SLP98UH070XV36B	8550440
XP20-024-230A	22,400	19.00	13.50	21,800	14,700	3.56	2.40	9.60	CBX32MV-018/024		8593940
XP20-024-230A	23,200	20.00	14.00	22,000	13,700	3.82	2.44	10.00	CBX32MV-024/030		8550431
XP20-024-230A	23,000	19.50	14.00	22,200	14,400	3.62	2.44	9.60	CH35-30B	EL296UH045XV36B	8550447
XP20-024-230A	23,000	19.50	13.50	22,200	14,400	3.64	2.46	9.60	CH35-30B	EL296UH070XV36B	8550448
XP20-024-230A	23,200	20.00	13.50	22,200	14,300	3.68	2.46	9.60	CH35-30B	SL280UH090V36B	8550449
XP20-024-230A	23,000	19.50	13.50	22,200	14,400	3.64	2.46	9.60	CH35-30B	SLP98UH070XV36B	8550450
XP20-024-230A	22,600	19.00	13.50	22,000	14,700	3.70	2.52	9.60	CR33-48B	EL296DF045XV36B	8550432
XP20-024-230A	22,600	19.00	13.50	22,000	14,700	3.70	2.50	9.60	CR33-48B	SL280DF070V36A	8688155
XP20-024-230A	22,600	19.00	13.50	22,000	14,700	3.72	2.52	9.60	CR33-48B	SL280DF090V48B	8688154
XP20-024-230A	22,600	19.00	13.50	22,000	14,700	3.74	2.54	9.60	CR33-48B	SLP98DF070XV36B	8550433
XP20-024-230A	22,600	19.50	14.00	22,000	14,700	3.74	2.54	9.60	CR33-48B	SLP98DF090XV36C	8550434
XP20-024-230A	22,600	18.50	13.50	21,600	13,500	3.62	2.34	9.00	CX34-31A	SL280UH070V36A	8550441
XP20-024-230A	22,600	18.50	13.50	21,600	13,500	3.62	2.34	9.00	CX34-31A	SL280UH070XV36A	8550442
XP20-024-230A	22,600	18.50	13.50	21,600	13,600	3.60	2.34	9.00	CX34-31B	EL296UH045XV36B	8550443
XP20-024-230A	22,600	19.00	13.50	21,600	13,500	3.62	2.34	9.00	CX34-31B	EL296UH070XV36B	8550444
XP20-024-230A	22,600	19.00	13.50	21,400	13,500	3.62	2.36	9.00	CX34-31B	SL280UH090V36B	8550445
XP20-024-230A	22,600	19.00	13.50	21,600	13,500	3.62	2.34	9.00	CX34-31B	SLP98UH070XV36B	8550446
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.50	CX34-38A	SL280UH070V36A	8635936
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.50	CX34-38A	SL280UH070XV36A	8635937
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.66	2.32	9.60	CX34-38B	EL296UH045XV36B	8635938
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.60	CX34-38B	EL296UH070XV36B	8635939
XP20-024-230A	23,000	19.00	13.50	21,800	13,300	3.72	2.36	9.60	CX34-38B	SL280UH090V36B	8635940
XP20-024-230A	23,000	18.50	13.50	21,800	13,300	3.68	2.34	9.60	CX34-38B	SLP98UH070XV36B	8635941
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.00	C33-38A	SL280UH070V36A	8550451
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.00	C33-38A	SL280UH070XV36A	8550452
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.00	C33-38B	EL296UH045XV36B	8550454
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.18	2.36	9.60	C33-38B	EL296UH070XV36B	8550455
XP20-036-230A	34,200	20.00	13.00	32,600	21,800	3.22	2.42	9.60	C33-38B	SL280UH090V36B	8550453
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.18	2.36	9.60	C33-38B	SLP98UH070XV36B	8550456
XP20-036-230A	34,200	20.00	12.50	32,600	21,400	3.14	2.18	9.00	C33-43B	EL296UH045XV36B	8550458
XP20-036-230A	34,400	20.00	12.50	32,600	21,400	3.14	2.18	9.00	C33-43B	EL296UH070XV36B	8550459
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.22	2.22	9.00	C33-43B	SL280UH090V36B	8550457
XP20-036-230A	34,400	20.00	12.50	32,600	21,400	3.14	2.18	9.00	C33-43B	SLP98UH070XV36B	8550460
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.20	2.22	9.00	C33-43C	EL296UH090XV36C	8550461

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.20	2.22	9.00	C33-43C	SLP98UH090XV36C	8550462
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	C33-48B	EL296UH045XV36B	8550464
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	C33-48B	EL296UH070XV36B	8550465
XP20-036-230A	33,800	19.00	13.00	32,800	21,400	3.02	2.38	9.60	C33-48B	SL280UH090V36B	8550463
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	C33-48B	SLP98UH070XV36B	8550466
XP20-036-230A	33,800	19.00	12.50	32,800	21,400	3.00	2.36	9.60	C33-48C	EL296UH090XV36C	8550467
XP20-036-230A	33,800	19.00	12.50	32,800	21,400	3.00	2.36	9.60	C33-48C	SLP98UH090XV36C	8550468
XP20-036-230A	34,400	20.00	13.50	33,200	21,800	3.24	2.36	10.00	CBX32MV-036		8550469
XP20-036-230A	34,400	20.00	13.50	33,000	21,800	3.24	2.38	10.00	CBX40UHV-036		8550470
XP20-036-230A	34,800	19.50	13.00	32,600	21,200	3.34	2.32	9.00	CH33-43C	EL296UH090XV36C	8550471
XP20-036-230A	34,800	19.50	13.00	32,600	21,200	3.34	2.32	9.00	CH33-43C	SLP98UH090XV36C	8550472
XP20-036-230A	33,800	19.00	12.50	33,000	22,000	3.26	2.38	9.00	CH33-44/48B	EL296UH045XV36B	8550474
XP20-036-230A	33,800	19.00	12.50	32,800	22,000	3.26	2.38	9.00	CH33-44/48B	EL296UH070XV36B	8550475
XP20-036-230A	34,000	19.00	13.00	32,600	21,600	3.32	2.40	9.60	CH33-44/48B	SL280UH090V36B	8550473
XP20-036-230A	33,800	19.00	12.50	32,800	22,000	3.26	2.38	9.00	CH33-44/48B	SLP98UH070XV36B	8550476
XP20-036-230A	34,400	19.00	12.50	33,600	22,400	2.82	2.14	8.50	CH35-48B	EL296UH045XV36B	8550478
XP20-036-230A	34,400	19.00	12.50	33,600	22,400	2.82	2.14	8.50	CH35-48B	EL296UH070XV36B	8550479
XP20-036-230A	34,600	19.00	13.00	33,400	22,200	2.88	2.18	9.00	CH35-48B	SL280UH090V36B	8550477
XP20-036-230A	34,400	19.00	12.50	33,600	22,400	2.82	2.16	8.50	CH35-48B	SLP98UH070XV36B	8550480
XP20-036-230A	34,000	19.00	13.00	32,400	21,600	3.38	2.36	9.00	CH35-48C	EL296UH090XV36C	8550481
XP20-036-230A	35,000	20.00	13.00	33,200	21,200	3.54	2.46	10.00	CR33-50/60	SLP98DF090XV36C	8550482
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.60	CX34-38A	SL280UH070V36A	8550483
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.60	CX34-38A	SL280UH070XV36A	8550484
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.16	2.36	9.00	CX34-38B	EL296UH045XV36B	8550486
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.18	2.36	9.60	CX34-38B	EL296UH070XV36B	8550487
XP20-036-230A	34,200	20.00	13.00	32,600	21,800	3.22	2.42	9.60	CX34-38B	SL280UH090V36B	8550485
XP20-036-230A	34,000	20.00	12.50	33,000	22,000	3.18	2.36	9.60	CX34-38B	SLP98UH070XV36B	8550488
XP20-036-230A	34,200	20.00	12.50	32,600	21,400	3.14	2.18	9.00	CX34-43B	EL296UH045XV36B	8550490
XP20-036-230A	34,400	20.00	12.50	32,600	21,400	3.14	2.18	9.00	CX34-43B	EL296UH070XV36B	8550491
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.22	2.22	9.00	CX34-43B	SL280UH090V36B	8550489
XP20-036-230A	34,400	20.00	12.50	32,600	21,400	3.14	2.18	9.00	CX34-43B	SLP98UH070XV36B	8550492
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.20	2.22	9.00	CX34-43C	EL296UH090XV36C	8550493
XP20-036-230A	34,400	20.00	13.00	32,400	21,200	3.20	2.22	9.00	CX34-43C	SLP98UH090XV36C	8550494
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	CX34-44/48B	EL296UH045XV36B	8550496
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	CX34-44/48B	EL296UH070XV36B	8550497
XP20-036-230A	33,600	19.00	12.50	33,000	21,600	2.96	2.32	9.60	CX34-44/48B	SLP98UH070XV36B	8550498
XP20-036-230A	33,800	19.00	13.00	32,800	21,400	3.02	2.38	9.60	CX34-44/48B	SLP98UH090XV36B	8550495
XP20-036-230A	33,800	19.00	12.50	32,800	21,400	3.00	2.36	9.60	CX34-44/48C	EL296UH090XV36C	8550499
XP20-036-230A	33,800	19.00	12.50	32,800	21,400	3.00	2.36	9.60	CX34-44/48C	SLP98UH090XV36C	8550500
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	C33-49	EL296UH090XV48C	8601378
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	C33-49	EL296UH090XV60C	8601379
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	C33-49	EL296UH110XV48C	8601380
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	C33-49	EL296UH110XV60C	8601381
XP20-048-230A	47,000	18.50	12.50	43,500	27,800	3.40	2.42	9.00	C33-49	SL280UH090V60C	8601382
XP20-048-230A	47,000	18.50	12.50	43,500	27,800	3.40	2.42	9.00	C33-49	SL280UH090XV60C	8601383
XP20-048-230A	47,000	18.00	12.00	43,500	27,800	3.36	2.40	9.00	C33-49	SL280UH110V60C	8601384
XP20-048-230A	47,000	18.00	12.00	43,500	27,800	3.36	2.40	9.00	C33-49	SL280UH110XV60C	8601385
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	C33-49	SLP98UH090XV48C	8601386
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	C33-49	SLP98UH090XV60C	8601387
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	C33-49	SLP98UH110XV60C	8601388
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.42	9.00	C33-62C	EL296UH090XV48C	8547500

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.52	2.44	9.00	C33-62C	EL296UH090XV60C	8547501
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.44	9.00	C33-62C	EL296UH110XV48C	8547502
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	C33-62C	EL296UH110XV60C	8547503
XP20-048-230A	48,000	18.50	12.50	43,500	27,000	3.54	2.46	9.00	C33-62C	SL280UH090V60C	8547504
XP20-048-230A	48,000	18.50	12.50	43,500	27,000	3.54	2.46	9.00	C33-62C	SL280UH090XV60C	8547505
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	C33-62C	SL280UH110V60C	8547506
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	C33-62C	SL280UH110XV60C	8547507
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.42	9.00	C33-62C	SLP98UH090XV48C	8547508
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.52	2.44	9.00	C33-62C	SLP98UH090XV60C	8547509
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	C33-62C	SLP98UH110XV60C	8547510
XP20-048-230A	47,500	18.00	12.00	44,000	28,200	3.56	2.58	9.50	C33-62D	EL296UH1135XV60D	8601354
XP20-048-230A	47,500	18.50	12.00	44,000	28,200	3.58	2.58	9.60	C33-62D	SL280UH135V60D	8601355
XP20-048-230A	47,500	18.00	12.00	44,000	28,200	3.56	2.58	9.50	C33-62D	SLP98UH135XV60D	8601356
XP20-048-230A	48,000	19.50	12.50	45,000	29,000	3.42	2.48	9.60	CBX32MV-048		8547522
XP20-048-230A	48,000	19.00	12.50	44,500	27,200	3.22	2.28	9.60	CBX32MV-060		8601357
XP20-048-230A	48,000	19.00	12.50	45,000	28,800	3.46	2.50	9.60	CBX40UHV-048		8547477
XP20-048-230A	48,000	19.00	12.50	44,500	27,200	3.22	2.28	9.60	CBX40UHV-060		8601358
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.30	2.32	9.00	CH33-49	EL296UH090XV48C	8547478
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	EL296UH090XV60C	8547479
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	EL296UH110XV48C	8547480
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	EL296UH110XV60C	8547481
XP20-048-230A	48,000	19.00	12.00	44,000	28,200	3.32	2.34	9.00	CH33-49	SL280UH090V60C	8547482
XP20-048-230A	48,000	19.00	12.00	44,000	28,200	3.32	2.34	9.00	CH33-49	SL280UH090XV60C	8547483
XP20-048-230A	48,000	18.50	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	SL280UH110V60C	8547484
XP20-048-230A	48,000	18.50	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	SL280UH110XV60C	8547485
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.30	2.32	9.00	CH33-49	SLP98UH090XV48C	8547486
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	SLP98UH090XV60C	8547487
XP20-048-230A	48,000	19.00	12.00	44,500	28,400	3.32	2.32	9.00	CH33-49	SLP98UH110XV60C	8547488
XP20-048-230A	47,500	19.00	12.00	44,500	28,400	3.30	2.30	9.00	CH33-50/60C	EL296UH090XV48C	8547489
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	EL296UH090XV60C	8547490
XP20-048-230A	47,500	19.00	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	EL296UH110XV48C	8547491
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	EL296UH110XV60C	8547492
XP20-048-230A	48,000	18.50	12.00	44,000	28,400	3.30	2.34	9.00	CH33-50/60C	SL280UH090V60C	8547493
XP20-048-230A	48,000	18.50	12.00	44,000	28,400	3.30	2.34	9.00	CH33-50/60C	SL280UH090XV60C	8547494
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.32	2.32	9.00	CH33-50/60C	SL280UH110V60C	8547495
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.32	2.32	9.00	CH33-50/60C	SL280UH110XV60C	8547496
XP20-048-230A	47,500	19.00	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	SLP98UH090XV48C	8547497
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	SLP98UH090XV60C	8547498
XP20-048-230A	47,500	18.50	12.00	44,500	28,400	3.30	2.32	9.00	CH33-50/60C	SLP98UH110XV60C	8547499
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.46	2.36	9.60	CH33-62D	EL296UH1135XV60D	8601359
XP20-048-230A	48,000	18.00	12.00	43,500	26,800	3.48	2.36	9.60	CH33-62D	SL280UH135V60D	8601360
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.46	2.36	9.60	CH33-62D	SLP98UH135XV60D	8601361
XP20-048-230A	48,000	18.00	12.00	44,000	29,200	3.18	2.34	9.00	CH35-60D	EL296UH1135XV60D	8601362
XP20-048-230A	48,000	18.50	12.00	44,000	29,200	3.20	2.36	9.00	CH35-60D	SL280UH135V60D	8601363
XP20-048-230A	48,000	18.00	12.00	44,000	29,200	3.18	2.34	9.00	CH35-60D	SLP98UH135XV60D	8601364
XP20-048-230A	47,000	17.50	12.00	45,500	29,600	3.12	2.28	8.50	CR33-50/60	EL296DF090XV60C	8601365
XP20-048-230A	47,000	18.00	12.00	45,500	29,600	3.12	2.28	8.50	CR33-50/60	EL296DF110XV60C	8601366
XP20-048-230A	47,000	18.00	12.00	45,500	29,200	3.18	2.32	8.50	CR33-50/60	SL280DF090V60C	8601367
XP20-048-230A	47,000	18.00	12.00	45,500	29,200	3.18	2.32	8.50	CR33-50/60	SL280DF110V60C	8601368
XP20-048-230A	47,000	18.00	12.00	45,500	29,600	3.10	2.28	8.50	CR33-50/60	SLP98DF090XV48C	8601369
XP20-048-230A	47,000	17.50	12.00	45,500	29,600	3.12	2.28	8.50	CR33-50/60	SLP98DF090XV60C	8601370

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP20-048-230A	47,000	18.00	12.00	45,500	29,600	3.12	2.28	8.50	CR33-50/60	SLP98DF110XV60C	8601371
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	CX34-49	EL296UH090XV48C	8601389
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	CX34-49	EL296UH090XV60C	8601390
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	CX34-49	EL296UH110XV48C	8601391
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	CX34-49	EL296UH110XV60C	8601392
XP20-048-230A	47,000	18.50	12.50	43,500	27,800	3.40	2.42	9.00	CX34-49	SL280UH090V60C	8601393
XP20-048-230A	47,000	18.50	12.50	43,500	27,800	3.40	2.42	9.00	CX34-49	SL280UH090XV60C	8601394
XP20-048-230A	47,000	18.00	12.00	43,500	27,800	3.36	2.40	9.00	CX34-49	SL280UH110V60C	8601395
XP20-048-230A	47,000	18.00	12.00	43,500	27,800	3.36	2.40	9.00	CX34-49	SL280UH110XV60C	8601396
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	CX34-49	SLP98UH090XV48C	8601397
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.36	2.40	9.00	CX34-49	SLP98UH090XV60C	8601398
XP20-048-230A	47,000	18.50	12.00	43,500	27,800	3.34	2.38	9.00	CX34-49	SLP98UH110XV60C	8601399
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.42	9.00	CX34-62C	EL296UH090XV48C	8547511
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.52	2.44	9.00	CX34-62C	EL296UH090XV60C	8547512
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.44	9.00	CX34-62C	EL296UH110XV48C	8547513
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	CX34-62C	EL296UH110XV60C	8547514
XP20-048-230A	48,000	18.50	12.50	43,500	27,000	3.54	2.46	9.00	CX34-62C	SL280UH090V60C	8547515
XP20-048-230A	48,000	18.50	12.50	43,500	27,000	3.54	2.46	9.00	CX34-62C	SL280UH090XV60C	8547516
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	CX34-62C	SL280UH110V60C	8547517
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	CX34-62C	SL280UH110XV60C	8547518
XP20-048-230A	48,000	18.50	12.00	43,500	27,000	3.50	2.42	9.00	CX34-62C	SLP98UH090XV48C	8547519
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.52	2.44	9.00	CX34-62C	SLP98UH090XV60C	8547520
XP20-048-230A	48,000	18.00	12.00	43,500	27,000	3.50	2.44	9.00	CX34-62C	SLP98UH110XV60C	8547521
XP20-048-230A	47,500	18.00	12.00	44,000	28,200	3.56	2.58	9.50	CX34-62D	EL296UH135XV60D	8601372
XP20-048-230A	47,500	18.50	12.00	44,000	28,200	3.58	2.58	9.60	CX34-62D	SL280UH135V60D	8601373
XP20-048-230A	47,500	18.00	12.00	44,000	28,200	3.56	2.58	9.50	CX34-62D	SLP98UH135XV60D	8601374
XP20-060-230A	56,500	18.00	11.50	54,000	35,400	3.16	2.36	9.00	C33-49C	EL296UH090XV60C	8561539
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.18	2.36	9.00	C33-49C	EL296UH110XV60C	8561540
XP20-060-230A	57,000	18.50	12.00	54,000	35,000	3.22	2.40	9.00	C33-49C	SL280UH090V60C	8561541
XP20-060-230A	57,000	18.50	12.00	54,000	35,000	3.22	2.40	9.00	C33-49C	SL280UH090XV60C	8561543
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.20	2.38	9.00	C33-49C	SL280UH110V60C	8561542
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.20	2.38	9.00	C33-49C	SL280UH110XV60C	8561544
XP20-060-230A	56,500	18.00	11.50	54,000	35,400	3.16	2.36	9.00	C33-49C	SLP98UH090XV60C	8561545
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.18	2.36	9.00	C33-49C	SLP98UH110XV60C	8561546
XP20-060-230A	57,000	18.50	12.00	54,500	35,200	3.04	2.24	9.60	C33-62C	EL296UH090XV60C	8561547
XP20-060-230A	57,500	18.50	12.00	54,500	35,000	3.04	2.24	9.60	C33-62C	EL296UH110XV60C	8561548
XP20-060-230A	57,500	18.50	12.00	54,000	34,800	3.06	2.28	9.60	C33-62C	SL280UH090V60C	8561549
XP20-060-230A	57,500	18.50	12.00	54,000	34,800	3.06	2.28	9.60	C33-62C	SL280UH090XV60C	8561551
XP20-060-230A	57,500	18.50	12.00	54,000	35,000	3.04	2.26	9.60	C33-62C	SL280UH110V60C	8561550
XP20-060-230A	57,500	18.50	12.00	54,000	35,000	3.04	2.26	9.60	C33-62C	SL280UH110XV60C	8561552
XP20-060-230A	57,000	18.50	12.00	54,500	35,200	3.04	2.24	9.60	C33-62C	SLP98UH090XV60C	8561553
XP20-060-230A	57,500	18.50	12.00	54,500	35,000	3.04	2.24	9.60	C33-62C	SLP98UH110XV60C	8561554
XP20-060-230A	58,000	18.50	12.50	53,000	36,000	3.18	2.46	9.60	C33-62D	EL296UH135XV60D	8561555
XP20-060-230A	58,000	19.00	12.50	53,000	35,800	3.18	2.46	9.60	C33-62D	SL280UH135V60D	8561556
XP20-060-230A	58,000	18.50	12.50	53,000	36,000	3.18	2.46	9.60	C33-62D	SLP98UH135XV60D	8561557
XP20-060-230A	56,500	19.00	12.50	54,500	36,400	3.28	2.40	9.60	CBX32MV-060		8561558
XP20-060-230A	57,000	18.50	12.50	54,500	36,200	3.32	2.40	9.60	CBX40UHV-060		8561559
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.94	2.20	9.00	CH33-49	EL296UH090XV60C	8561560
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.96	2.22	9.00	CH33-49	EL296UH110XV60C	8561561
XP20-060-230A	57,000	19.00	12.00	54,500	36,000	2.98	2.24	9.00	CH33-49	SL280UH090V60C	8561562
XP20-060-230A	57,000	19.00	12.00	54,500	36,000	2.98	2.24	9.00	CH33-49	SL280UH090XV60C	8561564

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP20-060-230A	57,000	18.50	12.00	54,500	36,200	2.94	2.22	9.00	CH33-49	SL280UH110V60C	8561563
XP20-060-230A	57,000	18.50	12.00	54,500	36,200	2.94	2.22	9.00	CH33-49	SL280UH110XV60C	8561565
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.94	2.20	9.00	CH33-49	SLP98UH090XV60C	8561566
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.96	2.22	9.00	CH33-49	SLP98UH110XV60C	8561567
XP20-060-230A	56,000	18.50	11.50	55,000	36,400	2.94	2.20	9.00	CH33-50/60C	EL296UH090XV60C	8561568
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.94	2.22	9.00	CH33-50/60C	EL296UH110XV60C	8561569
XP20-060-230A	56,500	18.50	12.00	54,500	36,000	2.96	2.24	9.00	CH33-50/60C	SL280UH090V60C	8561570
XP20-060-230A	56,500	18.50	12.00	54,500	36,000	2.96	2.24	9.00	CH33-50/60C	SL280UH090XV60C	8561572
XP20-060-230A	56,500	18.50	12.00	54,500	36,200	2.94	2.22	9.00	CH33-50/60C	SL280UH110V60C	8561571
XP20-060-230A	56,500	18.50	12.00	54,500	36,200	2.94	2.22	9.00	CH33-50/60C	SL280UH110XV60C	8561573
XP20-060-230A	56,000	18.50	11.50	55,000	36,400	2.94	2.20	9.00	CH33-50/60C	SLP98UH090XV60C	8561574
XP20-060-230A	56,500	18.50	11.50	55,000	36,400	2.94	2.22	9.00	CH33-50/60C	SLP98UH110XV60C	8561575
XP20-060-230A	56,500	18.00	12.00	55,000	36,200	3.12	2.38	9.60	CH33-62D	EL296UH135XV60D	8561576
XP20-060-230A	56,500	18.00	12.00	55,000	36,200	3.14	2.40	9.00	CH33-62D	SL280UH135V60D	8561577
XP20-060-230A	56,500	18.00	12.00	55,000	36,200	3.12	2.38	9.00	CH33-62D	SLP98UH135XV60D	8561578
XP20-060-230A	56,500	18.50	12.00	55,000	36,600	2.88	2.10	9.00	CH35-60D	EL296UH135XV60D	8593312
XP20-060-230A	57,000	18.50	12.00	55,000	36,400	2.90	2.10	9.00	CH35-60D	SL280UH135V60D	8593313
XP20-060-230A	56,500	18.50	12.00	55,000	36,600	2.88	2.10	9.00	CH35-60D	SLP98UH135XV60D	8593311
XP20-060-230A	56,000	18.50	12.00	54,000	36,400	3.16	2.36	9.60	CR33-60	EL296DF090XV60C	8561579
XP20-060-230A	56,000	18.50	12.00	54,000	36,400	3.16	2.36	9.60	CR33-60	EL296DF110XV60C	8561580
XP20-060-230A	56,500	19.00	12.00	53,500	36,000	3.20	2.40	9.60	CR33-60	SL280DF090V60C	8561581
XP20-060-230A	56,500	19.00	12.50	53,500	36,000	3.22	2.40	9.60	CR33-60	SL280DF110V60C	8561582
XP20-060-230A	56,000	18.50	12.00	54,000	36,400	3.16	2.36	9.60	CR33-60	SLP98DF090XV60C	8561583
XP20-060-230A	56,000	18.50	12.00	54,000	36,400	3.16	2.36	9.60	CR33-60	SLP98DF110XV60C	8561584
XP20-060-230A	56,500	18.00	11.50	54,000	35,400	3.16	2.36	9.00	CX34-49C	EL296UH090XV60C	8561585
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.18	2.36	9.00	CX34-49C	EL296UH110XV60C	8561586
XP20-060-230A	57,000	18.50	12.00	54,000	35,000	3.22	2.40	9.00	CX34-49C	SL280UH090V60C	8561587
XP20-060-230A	57,000	18.50	12.00	54,000	35,000	3.22	2.40	9.00	CX34-49C	SL280UH090XV60C	8561589
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.20	2.38	9.00	CX34-49C	SL280UH110V60C	8561588
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.20	2.38	9.00	CX34-49C	SL280UH110XV60C	8561590
XP20-060-230A	56,500	18.00	11.50	54,000	35,400	3.16	2.36	9.00	CX34-49C	SLP98UH090XV60C	8561591
XP20-060-230A	56,500	18.00	11.50	54,000	35,200	3.18	2.36	9.00	CX34-49C	SLP98UH110XV60C	8561592
XP20-060-230A	57,000	18.50	12.00	54,500	35,200	3.04	2.24	9.60	CX34-62C	EL296UH090XV60C	8561593
XP20-060-230A	57,500	18.50	12.00	54,500	35,000	3.04	2.24	9.60	CX34-62C	EL296UH110XV60C	8561594
XP20-060-230A	57,500	18.50	12.00	54,000	34,800	3.06	2.28	9.60	CX34-62C	SL280UH090V60C	8561595
XP20-060-230A	57,500	18.50	12.00	54,000	34,800	3.06	2.28	9.60	CX34-62C	SL280UH090XV60C	8561597
XP20-060-230A	57,500	18.50	12.00	54,000	35,000	3.04	2.26	9.60	CX34-62C	SL280UH110V60C	8561596
XP20-060-230A	57,500	18.50	12.00	54,000	35,000	3.04	2.26	9.60	CX34-62C	SL280UH110XV60C	8561598
XP20-060-230A	57,000	18.50	12.00	54,500	35,200	3.04	2.24	9.60	CX34-62C	SLP98UH090XV60C	8561599
XP20-060-230A	57,500	18.50	12.00	54,500	35,000	3.04	2.24	9.60	CX34-62C	SLP98UH110XV60C	8561600
XP20-060-230A	58,000	18.50	12.50	53,000	36,000	3.18	2.46	9.60	CX34-62D	EL296UH135XV60D	8561601
XP20-060-230A	58,000	19.00	12.50	53,000	35,800	3.18	2.46	9.60	CX34-62D	SL280UH135V60D	8561602
XP20-060-230A	58,000	18.50	12.50	53,000	36,000	3.18	2.46	9.60	CX34-62D	SLP98UH135XV60D	8561603

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-024-230	25,200	18.00	13.00	22,200	14,000	2.92	2.34	8.20	C33-31	SLO185B79/105V42	7087742
XP21-024-230	25,000	17.00	12.50	22,400	14,100	2.90	2.30	8.20	C33-31	SLO185UF79/105V42	7087715
XP21-024-230	25,600	18.00	13.00	22,400	14,100	3.04	2.40	8.50	C33-31A	EL180UH045E36A	5741789
XP21-024-230	25,600	19.00	13.00	22,200	13,900	3.04	2.40	8.50	C33-31A	SL280UH070V36A	5269248
XP21-024-230	25,600	19.00	13.00	22,200	13,900	3.04	2.40	8.50	C33-31A	SL280UH070XV36A	5269249
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	C33-31B	CBWMV-24B-040	5269262
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.04	2.38	8.50	C33-31B	CBWMV-36B-070	5269263
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.36	8.20	C33-31B	EL296UH045XV36B	5760886
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	C33-31B	EL296UH070XV36B	5760987
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.02	2.40	8.20	C33-31B	SL280UH090V36B	5269254
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	C33-31B	SL280UH090V48B	5269255
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	C33-31B	SL280UH090XV48B	5269265
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	C33-31B	SLP98UH070XV36B	5269256
XP21-024-230	25,800	18.00	13.00	22,400	14,000	3.04	2.38	8.50	C33-38A	EL180UH070E36B	5741855
XP21-024-230	25,600	18.00	13.00	22,200	13,900	3.02	2.40	8.50	C33-38A	SL280UH070V36A	5269276
XP21-024-230	25,600	18.00	13.00	22,200	13,900	3.02	2.40	8.50	C33-38A	SL280UH070XV36A	5269278
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.36	8.20	C33-38B	CBWMV-24B-040	5269290
XP21-024-230	25,600	18.00	13.00	22,400	14,000	3.04	2.38	8.50	C33-38B	CBWMV-36B-070	5269291
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.36	8.20	C33-38B	EL296UH045XV36B	5760885
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.38	8.20	C33-38B	EL296UH070XV36B	5760985
XP21-024-230	25,600	17.00	13.00	22,200	13,900	3.04	2.40	8.20	C33-38B	SL280UH090V36B	5269281
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	C33-38B	SL280UH090V48B	5269283
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	C33-38B	SL280UH090XV48B	5269293
XP21-024-230	25,200	18.00	13.00	22,200	14,000	2.92	2.34	8.20	C33-38B	SLO185B79/105V42	7087740
XP21-024-230	25,200	17.00	12.50	22,400	14,100	2.92	2.32	8.20	C33-38B	SLO185UF79/105V42	7087713
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.94	2.36	8.20	C33-48B	CBWMV-24B-040	5269313
XP21-024-230	25,400	18.00	13.00	22,200	14,000	2.96	2.38	8.20	C33-48B	CBWMV-36B-070	5269314
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.94	2.36	8.20	C33-48B	EL296UH045XV36B	5760884
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.96	2.38	8.20	C33-48B	EL296UH070XV36B	5760982
XP21-024-230	25,400	18.00	13.00	22,200	13,800	3.00	2.38	8.20	C33-48B	SL280UH090V36B	5269303
XP21-024-230	25,400	18.00	13.00	22,200	14,000	2.96	2.36	8.20	C33-48B	SL280UH090V48B	5269305
XP21-024-230	25,400	18.00	13.00	22,200	14,000	2.96	2.36	8.20	C33-48B	SL280UH090XV48B	5269316
XP21-024-230	25,000	18.00	13.00	22,200	14,000	2.90	2.34	8.20	C33-48B	SLO185B79/105V42	7087741
XP21-024-230	25,000	17.00	12.50	22,400	14,100	2.86	2.30	8.20	C33-48B	SLO185UF79/105V42	7087712
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.96	2.38	8.20	C33-48B	SLP98UH070XV36B	5269306
XP21-024-230	24,800	17.00	13.00	22,800	14,200	3.36	2.58	9.00	CBX27UH-024		5269236
XP21-024-230	25,000	19.00	13.00	22,800	14,200	3.42	2.60	9.00	CBX27UH-030		5269237

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-024-230	24,600	16.00	12.00	23,200	14,600	3.24	2.48	8.50	CBX32M-030		5269234
XP21-024-230	24,600	16.00	12.00	23,200	14,700	3.22	2.46	8.50	CBX32M-036		5269235
XP21-024-230	24,800	18.00	13.00	22,800	14,300	3.34	2.58	9.00	CBX32MV-024/030		5269230
XP21-024-230	25,600	19.20	13.50	23,000	14,300	3.50	2.62	9.20	CBX32MV-036		5268652
XP21-024-230	25,200	18.00	13.00	22,800	14,200	3.42	2.58	9.00	CBX40UHV-024		5269231
XP21-024-230	25,000	18.00	13.00	22,800	14,200	3.40	2.58	9.00	CBX40UHV-030		5269232
XP21-024-230	25,600	18.00	13.00	23,000	14,300	3.48	2.62	9.00	CBX40UHV-036		5269233
XP21-024-230	25,400	18.00	13.00	22,400	14,000	2.98	2.34	8.50	CH33-31A	EL180UH045E36A	5741785
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.00	2.36	8.50	CH33-31A	SL280UH070V36A	5268786
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.00	2.36	8.50	CH33-31A	SL280UH070XV36A	5268827
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.00	2.38	8.20	CH33-31B	EL296UH045XV36B	5760874
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.00	2.38	8.20	CH33-31B	EL296UH070XV36B	5760979
XP21-024-230	25,600	17.00	13.00	22,200	13,900	3.04	2.40	8.20	CH33-31B	SL280UH090V36B	5268788
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	CH33-31B	SL280UH090V48B	5268790
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	CH33-31B	SL280UH090XV48B	5268794
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	CH33-42B	EL296UH045XV36B	5760875
XP21-024-230	26,000	19.00	13.00	22,600	14,200	3.12	2.42	8.50	CH33-42B	EL296UH070XV36B	5760972
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.04	2.40	8.20	CH33-42B	SL280UH090V36B	5268793
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	CH33-42B	SL280UH090V48B	5268795
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	CH33-42B	SL280UH090XV48B	5268831
XP21-024-230	25,200	18.00	13.00	22,200	13,900	3.00	2.38	8.20	CH33-42B	SLP98UH070XV36B	5268796
XP21-024-230	25,600	18.00	13.00	22,000	13,800	3.32	2.50	8.50	CH35-42B	EL296UH045XV36B	9114968
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.28	2.46	8.50	CH35-42B	EL296UH070XV36B	9114969
XP21-024-230	25,800	18.00	13.00	22,000	13,800	3.36	2.54	8.50	CH35-42B	SL280UH090V36B	9114970
XP21-024-230	25,800	18.00	13.00	22,200	13,900	3.34	2.52	8.50	CH35-42B	SL280UH090V48B	9114971
XP21-024-230	25,800	18.00	13.00	22,200	13,900	3.34	2.52	8.50	CH35-42B	SL280UH090XV48B	9114972
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.28	2.46	8.50	CH35-42B	SLP98UH070XV36B	9114973
XP21-024-230	25,000	15.50	12.20	22,600	14,400	3.08	2.38	8.50	CH35-42B		9114967
XP21-024-230	25,200	18.00	13.00	22,400	13,200	2.86	2.36	8.50	CH35-42C	EL296UH090XV36C	9114974
XP21-024-230	25,800	18.00	13.00	22,600	13,400	2.96	2.40	8.50	CH35-42C	EL296UH090XV48C	9114975
XP21-024-230	25,200	18.00	13.00	22,400	13,200	2.86	2.36	8.50	CH35-42C	SLP98UH090XV36C	9114976
XP21-024-230	25,800	18.00	13.00	22,600	13,400	2.96	2.40	8.50	CH35-42C	SLP98UH090XV48C	9114977
XP21-024-230	24,200	15.70	11.50	23,000	14,700	3.18	2.44	8.50	CR33-48		5269246
XP21-024-230	24,600	18.00	12.50	22,600	14,100	3.38	2.60	9.00	CR33-48B	EL296DF045XV36B	7505739
XP21-024-230	25,000	17.00	12.50	22,800	14,300	3.40	2.58	9.00	CR33-48B	EL296DF070XV48B	7487526
XP21-024-230	25,200	17.00	12.70	22,800	14,200	3.48	2.62	9.20	CR33-48B	SL280DF090V48B	5268799
XP21-024-230	25,000	18.00	12.50	22,600	14,100	3.42	2.62	9.00	CR33-48B	SLP98DF070XV36B	5268800
XP21-024-230	25,400	18.00	13.00	22,600	14,100	3.48	2.62	9.00	CR33-50/60	SLP98DF090XV36C	5268803
XP21-024-230	25,800	18.00	13.00	22,800	14,200	3.54	2.64	9.00	CR33-50/60	SLP98DF090XV48C	5268804
XP21-024-230	24,800	16.00	11.70	23,000	14,700	3.20	2.44	8.50	CR33-50/60		5269247
XP21-024-230	25,600	18.00	13.00	22,400	14,100	3.04	2.40	8.50	CX34-31A	EL180UH045E36A	5741790

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-024-230	25,600	19.00	13.00	22,200	13,900	3.04	2.40	8.50	CX34-31A	SL280UH070V36A	5269251
XP21-024-230	25,600	19.00	13.00	22,200	13,900	3.04	2.40	8.50	CX34-31A	SL280UH070XV36A	5269252
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	CX34-31B	CBWMV-24B-040	5269274
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.04	2.38	8.50	CX34-31B	CBWMV-36B-070	5269275
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.36	8.20	CX34-31B	EL296UH045XV36B	5760887
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	CX34-31B	EL296UH070XV36B	5760986
XP21-024-230	25,400	18.00	13.00	22,200	13,900	3.02	2.40	8.20	CX34-31B	SL280UH090V36B	5269264
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	CX34-31B	SL280UH090V48B	5269266
XP21-024-230	25,400	18.00	13.00	22,400	14,000	3.02	2.38	8.20	CX34-31B	SL280UH090XV48B	5269282
XP21-024-230	25,200	18.00	13.00	22,200	14,000	2.92	2.34	8.20	CX34-31B	SLO185B79/105V42	7087739
XP21-024-230	25,000	17.00	12.50	22,400	14,100	2.90	2.30	8.20	CX34-31B	SLO185UF79/105V42	7087714
XP21-024-230	25,200	18.00	13.00	22,200	13,900	2.98	2.38	8.20	CX34-31B	SLP98UH070XV36B	5269267
XP21-024-230	25,800	18.00	13.00	22,400	14,000	3.04	2.38	8.50	CX34-38A	EL180UH045E36A	5741788
XP21-024-230	25,600	18.00	13.00	22,200	13,900	3.02	2.40	8.50	CX34-38A	SL280UH070V36A	5269279
XP21-024-230	25,600	18.00	13.00	22,200	13,900	3.02	2.40	8.50	CX34-38A	SL280UH070XV36A	5269327
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.36	8.20	CX34-38B	CBWMV-24B-040	5269301
XP21-024-230	25,600	18.00	13.00	22,400	14,000	3.04	2.38	8.50	CX34-38B	CBWMV-36B-070	5269302
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.36	8.20	CX34-38B	EL296UH045XV36B	5760882
XP21-024-230	25,400	18.00	13.00	22,200	13,900	2.98	2.38	8.20	CX34-38B	EL296UH070XV36B	5760983
XP21-024-230	25,600	17.00	13.00	22,200	13,900	3.04	2.40	8.20	CX34-38B	SL280UH090V36B	5269292
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	CX34-38B	SL280UH090V48B	5269294
XP21-024-230	25,600	17.00	13.00	22,400	14,000	3.02	2.38	8.20	CX34-38B	SL280UH090XV48B	5269304
XP21-024-230	25,200	18.00	13.00	22,200	14,000	2.92	2.34	8.20	CX34-38B	SLO185B79/105V42	7087738
XP21-024-230	25,200	17.00	12.50	22,400	14,100	2.90	2.30	8.20	CX34-38B	SLO185UF79/105V42	7087710
XP21-024-230	24,600	16.00	13.00	22,600	15,900	2.98	2.44	8.50	CX35-48B	EL195UH045XE36B	9114979
XP21-024-230	25,200	16.00	13.00	22,000	15,200	2.98	2.44	8.50	CX35-48B	EL296UH045XE36B	9114980
XP21-024-230	25,200	17.00	13.00	22,000	15,200	3.00	2.46	8.50	CX35-48B	EL296UH045XV36B	9114981
XP21-024-230	25,400	17.00	13.00	22,000	15,200	2.98	2.44	8.50	CX35-48B	EL296UH070XV36B	9114982
XP21-024-230	25,400	17.00	13.00	22,200	15,400	3.06	2.50	8.50	CX35-48B	SL280UH090V36B	9114983
XP21-024-230	25,600	17.00	13.00	22,000	15,200	3.06	2.48	8.50	CX35-48B	SL280UH090V48B	9114984
XP21-024-230	25,600	17.00	13.00	22,200	15,300	3.06	2.48	8.50	CX35-48B	SL280UH090XV48B	9114985
XP21-024-230	25,600	17.00	13.00	22,200	15,300	2.98	2.44	8.50	CX35-48B	SLP98UH070XV36B	9114986
XP21-024-230	24,600	14.50	12.00	22,600	15,900	2.86	2.36	8.20	CX35-48B		9114978
XP21-024-230	25,400	18.00	13.00	22,200	15,400	3.14	2.22	8.20	CX35-49C	EL296UH090XV36C	9114987
XP21-024-230	25,600	18.00	13.00	22,200	13,200	3.24	2.28	8.50	CX35-49C	EL296UH090XV48C	9114988
XP21-024-230	26,200	18.00	13.00	22,400	13,500	3.24	2.26	8.50	CX35-49C	EL296UH110XV48C	9114989
XP21-024-230	26,000	18.00	13.00	22,400	13,400	3.14	2.22	8.20	CX35-49C	SLP98UH090XV36C	9114990
XP21-024-230	25,600	18.00	13.00	22,200	13,200	3.24	2.28	8.50	CX35-49C	SLP98UH090XV48C	9114991
XP21-036-230	35,400	15.50	11.70	33,000	21,200	3.22	2.38	8.50	C33-38		5268811
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.34	2.48	8.50	C33-38A	EL180UH045E36A	5741786
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	C33-38A	SL280UH070V36A	5268828

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	C33-38A	SL280UH070XV36A	5268844
XP21-036-230	35,800	17.00	13.00	32,200	20,400	3.40	2.52	9.00	C33-38B	EL180UH070E36B	5742096
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.42	2.54	9.00	C33-38B	EL180UH090E48B	5742411
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-38B	EL195UH045XE36B	5269189
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.34	2.48	9.00	C33-38B	EL195UH070XE36B	5269190
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-38B	EL296UH045XE36B	5650489
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	C33-38B	EL296UH045XV36B	5760878
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.34	2.48	9.00	C33-38B	EL296UH070XE36B	5650491
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	C33-38B	EL296UH070XV36B	5760975
XP21-036-230	36,000	17.00	13.00	32,400	20,600	3.42	2.54	9.00	C33-38B	SL280UH090V36B	5268830
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.42	2.54	9.00	C33-38B	SL280UH090V48B	5268832
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.42	2.54	9.00	C33-38B	SL280UH090XV48B	5268848
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.28	2.44	8.50	C33-38B	SLO185B79/105V42	7087735
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-38B	SLO185UF79/105V42	7087699
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	C33-38B	SLP98UH070XV36B	5268833
XP21-036-230	35,800	17.00	12.50	32,400	20,800	3.34	2.50	8.50	C33-43	CBWMV-36B-070	5268843
XP21-036-230	35,600	15.50	11.70	33,000	21,200	3.20	2.38	8.50	C33-43		5268813
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.32	2.48	8.50	C33-43B	CBWMV-36B-070	5268876
XP21-036-230	35,800	17.00	13.00	32,000	20,400	3.36	2.52	9.00	C33-43B	EL180UH070E36B	5742097
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.40	2.54	9.00	C33-43B	EL180UH090E48B	5742412
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-43B	EL195UH045XE36B	5269193
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.32	2.46	8.50	C33-43B	EL195UH070XE36B	5269194
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-43B	EL296UH045XE36B	5650495
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.32	2.48	8.50	C33-43B	EL296UH045XV36B	5760879
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.32	2.46	8.50	C33-43B	EL296UH070XE36B	5650490
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	C33-43B	EL296UH070XV36B	5760976
XP21-036-230	36,200	17.00	13.00	32,200	20,600	3.38	2.54	8.50	C33-43B	SL280UH090V36B	5268862
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.40	2.54	9.00	C33-43B	SL280UH090V48B	5268864
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.40	2.54	9.00	C33-43B	SL280UH090XV48B	5268878
XP21-036-230	35,800	17.00	12.00	32,600	21,000	3.26	2.44	8.50	C33-43B	SLO185B79/105V42	7087724
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-43B	SLO185UF79/105V42	7087704
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	C33-43B	SLP98UH070XV36B	5268865
XP21-036-230	35,800	17.00	12.50	32,200	20,600	3.34	2.50	8.50	C33-43C	CBWMV-36C-090	5268909
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	C33-43C	EL195UH090XE48C	5269197
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	C33-43C	EL296UH090XE48C	5650492
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	C33-43C	EL296UH090XV36C	5761059
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.36	2.50	8.50	C33-43C	EL296UH090XV48C	5761149
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.42	2.54	9.00	C33-43C	EL296UH090XV60C	5761238
XP21-036-230	36,200	18.00	13.00	32,200	20,600	3.38	2.54	9.00	C33-43C	EL296UH110XV48C	5685241
XP21-036-230	36,200	18.00	13.00	32,200	20,600	3.38	2.54	9.00	C33-43C	EL296UH110XV48C	5761279
XP21-036-230	36,400	18.00	13.00	32,600	20,600	3.44	2.54	9.00	C33-43C	EL296UH110XV60C	5761362

## NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.46	2.54	9.00	C33-43C	SL280UH090V60C	5268892
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.46	2.54	9.00	C33-43C	SL280UH090XV60C	5268910
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.42	2.54	8.50	C33-43C	SL280UH110V60C	5268893
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.42	2.54	8.50	C33-43C	SL280UH110XV60C	5268912
XP21-036-230	35,800	17.00	12.00	32,600	21,000	3.26	2.44	8.50	C33-43C	SLO185B79/105V42	7087753
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-43C	SLO185UF79/105V42	7087698
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	C33-43C	SLP98UH090XV36C	5268894
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.36	2.50	8.50	C33-43C	SLP98UH090XV48C	5268895
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.42	2.54	9.00	C33-43C	SLP98UH090XV60C	5268896
XP21-036-230	36,400	18.00	13.00	32,600	20,600	3.44	2.54	9.00	C33-43C	SLP98UH110XV60C	5268897
XP21-036-230	35,000	15.20	11.70	32,600	21,000	3.10	2.34	8.20	C33-48		5268815
XP21-036-230	35,400	17.00	12.50	32,200	20,600	3.24	2.44	8.50	C33-48B	CBWMV-36B-070	5268944
XP21-036-230	35,400	17.00	12.50	31,800	20,200	3.26	2.46	8.50	C33-48B	EL180UH070E36B	5742100
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.32	2.48	8.50	C33-48B	EL180UH090E48B	5742417
XP21-036-230	35,400	17.00	12.00	32,600	21,000	3.18	2.40	8.50	C33-48B	EL195UH045XE36B	5269199
XP21-036-230	35,400	17.00	12.50	32,200	20,600	3.22	2.44	8.50	C33-48B	EL195UH070XE36B	5269200
XP21-036-230	35,400	17.00	12.00	32,600	21,000	3.18	2.40	8.50	C33-48B	EL296UH045XE36B	5650502
XP21-036-230	35,400	17.00	12.00	32,200	20,600	3.22	2.42	8.50	C33-48B	EL296UH045XV36B	5760880
XP21-036-230	35,400	17.00	12.50	32,200	20,600	3.22	2.44	8.50	C33-48B	EL296UH070XE36B	5650512
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.24	2.42	8.50	C33-48B	EL296UH070XV36B	5760978
XP21-036-230	35,600	17.00	12.50	32,000	20,400	3.28	2.48	8.50	C33-48B	SL280UH090V36B	5268930
XP21-036-230	35,800	17.00	12.50	32,000	20,400	3.28	2.48	8.50	C33-48B	SL280UH090V48B	5268932
XP21-036-230	35,800	17.00	12.50	32,000	20,400	3.28	2.48	8.50	C33-48B	SL280UH090XV48B	5268946
XP21-036-230	35,400	16.00	12.00	32,400	20,800	3.18	2.40	8.50	C33-48B	SLO185B79/105V42	7087730
XP21-036-230	35,200	16.00	12.00	32,400	20,800	3.16	2.38	8.50	C33-48B	SLO185UF79/105V42	7087706
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.24	2.42	8.50	C33-48B	SLP98UH070XV36B	5268933
XP21-036-230	35,400	17.00	12.50	32,000	20,400	3.26	2.44	8.50	C33-48C	CBWMV-36C-090	5268979
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	C33-48C	EL195UH090XE48C	5269203
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	C33-48C	EL296UH090XE48C	5650516
XP21-036-230	35,600	17.00	12.50	32,200	20,400	3.30	2.46	8.50	C33-48C	EL296UH090XV36C	5761061
XP21-036-230	35,400	17.00	12.50	32,000	20,400	3.28	2.48	8.50	C33-48C	EL296UH090XV48C	5761155
XP21-036-230	36,200	17.00	12.50	32,400	20,800	3.34	2.50	8.50	C33-48C	EL296UH090XV60C	5761239
XP21-036-230	35,600	17.00	12.50	32,000	20,400	3.30	2.48	8.50	C33-48C	EL296UH110XV48C	5685245
XP21-036-230	35,600	17.00	12.50	32,000	20,400	3.30	2.48	8.50	C33-48C	EL296UH110XV48C	5761283
XP21-036-230	36,000	17.00	12.50	32,200	20,600	3.32	2.50	8.50	C33-48C	EL296UH110XV60C	5761359
XP21-036-230	36,200	17.00	12.50	32,200	20,600	3.36	2.50	8.50	C33-48C	SL280UH090V60C	5268961
XP21-036-230	36,200	17.00	12.50	32,200	20,600	3.36	2.50	8.50	C33-48C	SL280UH090XV60C	5268980
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.32	2.48	8.50	C33-48C	SL280UH110V60C	5268963
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.32	2.48	8.50	C33-48C	SL280UH110XV60C	5268982
XP21-036-230	35,400	16.00	12.00	32,400	20,800	3.18	2.40	8.50	C33-48C	SLO185B79/105V42	7087725
XP21-036-230	35,200	16.00	12.00	32,400	20,800	3.16	2.38	8.50	C33-48C	SLO185UF79/105V42	7087700

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	35,600	17.00	12.50	32,200	20,400	3.30	2.46	8.50	C33-48C	SLP98UH090XV36C	5268964
XP21-036-230	35,400	17.00	12.50	32,000	20,400	3.28	2.48	8.50	C33-48C	SLP98UH090XV48C	5268965
XP21-036-230	36,200	17.00	12.50	32,400	20,800	3.34	2.50	8.50	C33-48C	SLP98UH090XV60C	5268966
XP21-036-230	36,000	17.00	12.50	32,200	20,600	3.32	2.50	8.50	C33-48C	SLP98UH110XV60C	5268967
XP21-036-230	35,600	15.50	11.70	33,000	21,200	3.22	2.40	8.50	C33-49		5268817
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.38	2.52	9.00	C33-49C	CBWMV-36C-090	5269019
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	C33-49C	EL195UH090XE48C	5269205
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	C33-49C	EL296UH090XE48C	5650493
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	C33-49C	EL296UH090XV36C	5761062
XP21-036-230	36,000	17.00	13.00	32,200	20,400	3.38	2.52	9.00	C33-49C	EL296UH090XV48C	5761156
XP21-036-230	36,800	17.00	13.00	32,400	20,800	3.46	2.54	9.00	C33-49C	EL296UH090XV60C	5761241
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	C33-49C	EL296UH110XV48C	5685247
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	C33-49C	EL296UH110XV48C	5761285
XP21-036-230	36,600	17.00	13.00	32,600	20,600	3.46	2.56	9.00	C33-49C	EL296UH110XV60C	5761360
XP21-036-230	36,800	17.00	13.00	32,600	20,600	3.48	2.56	9.00	C33-49C	SL280UH090V60C	5269001
XP21-036-230	36,800	17.00	13.00	32,600	20,600	3.48	2.56	9.00	C33-49C	SL280UH090XV60C	5269020
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.44	2.56	8.50	C33-49C	SL280UH110V60C	5269003
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.44	2.56	8.50	C33-49C	SL280UH110XV60C	5269022
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.30	2.44	8.50	C33-49C	SLO185B79/105V42	7087732
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	C33-49C	SLO185UF79/105V42	7087701
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	C33-49C	SLP98UH090XV36C	5269004
XP21-036-230	36,000	17.00	13.00	32,200	20,400	3.38	2.52	9.00	C33-49C	SLP98UH090XV48C	5269005
XP21-036-230	36,800	17.00	13.00	32,800	20,800	3.46	2.54	9.00	C33-49C	SLP98UH090XV60C	5269006
XP21-036-230	36,600	17.00	13.00	32,600	20,600	3.46	2.56	9.00	C33-49C	SLP98UH110XV60C	5269007
XP21-036-230	35,800	17.00	12.50	32,200	20,600	3.32	2.50	8.50	C33-50/60C	CBWMV-36C-090	5269057
XP21-036-230	36,000	17.00	12.50	32,200	20,600	3.34	2.50	9.00	C33-50/60C	EL195UH090XE48C	5269207
XP21-036-230	36,000	17.00	12.50	32,200	20,600	3.34	2.50	9.00	C33-50/60C	EL296UH090XE48C	5650503
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.38	2.52	8.50	C33-50/60C	EL296UH090XV36C	5761066
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.34	2.50	8.50	C33-50/60C	EL296UH090XV48C	5761154
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.40	2.52	8.50	C33-50/60C	EL296UH090XV60C	5761242
XP21-036-230	36,000	17.00	13.00	32,200	20,600	3.38	2.54	9.00	C33-50/60C	EL296UH110XV48C	5685251
XP21-036-230	36,000	17.00	13.00	32,200	20,600	3.38	2.54	9.00	C33-50/60C	EL296UH110XV48C	5761289
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.52	9.00	C33-50/60C	EL296UH110XV60C	5761363
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.44	2.54	8.50	C33-50/60C	SL280UH090V60C	5269039
XP21-036-230	36,400	18.00	12.50	32,600	20,600	3.44	2.54	8.50	C33-50/60C	SL280UH090XV60C	5269058
XP21-036-230	36,400	17.70	12.50	32,600	20,600	3.42	2.52	8.50	C33-50/60C	SL280UH110V60C	5269041
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.42	2.52	8.50	C33-50/60C	SL280UH110XV60C	5269060
XP21-036-230	35,600	17.00	12.00	32,600	21,000	3.26	2.44	8.50	C33-50/60C	SLO185B79/105V42	7087737
XP21-036-230	35,600	17.00	12.00	32,600	21,000	3.22	2.42	8.50	C33-50/60C	SLO185UF79/105V42	7087702
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.38	2.52	8.50	C33-50/60C	SLP98UH090XV36C	5269042
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.34	2.50	8.50	C33-50/60C	SLP98UH090XV48C	5269043

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.40	2.52	8.50	C33-50/60C	SLP98UH090XV60C	5269044
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.52	9.00	C33-50/60C	SLP98UH110XV60C	5269045
XP21-036-230	35,400	15.50	11.70	32,800	21,200	3.18	2.38	8.20	C33-50/60C		5268819
XP21-036-230	35,200	17.00	12.50	33,200	21,000	3.72	2.72	9.50	CBX27UH-036		5268809
XP21-036-230	36,400	18.00	13.00	33,000	21,000	3.76	2.76	9.60	CBX27UH-042		5268810
XP21-036-230	35,200	17.00	12.00	33,400	21,200	3.68	2.70	9.50	CBX32MV-036		5268805
XP21-036-230	36,600	18.50	13.20	33,200	21,000	3.80	2.76	9.70	CBX32MV-048		5268653
XP21-036-230	35,200	17.00	12.50	33,200	21,000	3.70	2.70	9.50	CBX40UHV-036		5268806
XP21-036-230	36,400	18.00	13.00	33,200	21,000	3.74	2.74	9.50	CBX40UHV-042		5268807
XP21-036-230	36,400	17.00	13.00	33,000	21,000	3.76	2.76	9.50	CBX40UHV-048		5268808
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.40	2.52	8.50	CH33-43B	CBWMV-36B-070	5269092
XP21-036-230	37,000	18.00	12.50	33,000	21,000	3.44	2.54	9.00	CH33-43B	EL180UH070E36B	5742099
XP21-036-230	36,600	17.00	13.00	32,600	20,800	3.44	2.56	9.00	CH33-43B	EL180UH090E48B	5742410
XP21-036-230	36,600	17.00	12.50	33,000	21,200	3.34	2.48	8.50	CH33-43B	EL195UH045XE36B	5269209
XP21-036-230	36,600	16.00	12.50	33,000	21,200	3.36	2.50	8.50	CH33-43B	EL195UH070XE36B	5269210
XP21-036-230	36,600	17.00	12.50	33,000	21,200	3.34	2.48	8.50	CH33-43B	EL296UH045XE36B	5650497
XP21-036-230	36,600	17.00	12.50	32,800	21,000	3.38	2.50	8.50	CH33-43B	EL296UH045XV36B	5760872
XP21-036-230	36,600	16.00	12.50	33,000	21,200	3.36	2.50	8.50	CH33-43B	EL296UH070XE36B	5650500
XP21-036-230	36,800	17.00	12.50	32,800	21,000	3.40	2.52	8.50	CH33-43B	EL296UH070XV36B	5760973
XP21-036-230	36,800	17.00	13.00	32,600	20,800	3.46	2.58	9.00	CH33-43B	SL280UH090V36B	5269078
XP21-036-230	36,800	17.00	13.00	32,600	20,800	3.44	2.56	9.00	CH33-43B	SL280UH090V48B	5269080
XP21-036-230	36,800	17.00	13.00	32,600	20,800	3.44	2.56	9.00	CH33-43B	SL280UH090XV48B	5269114
XP21-036-230	36,400	17.00	12.00	33,000	21,200	3.34	2.48	8.50	CH33-43B	SLO185B79/105V42	7087721
XP21-036-230	36,400	17.00	12.00	33,000	21,200	3.30	2.44	8.50	CH33-43B	SLO185UF79/105V42	7087692
XP21-036-230	36,800	17.00	12.50	32,800	21,000	3.40	2.52	8.50	CH33-43B	SLP98UH070XV36B	5269081
XP21-036-230	36,400	16.00	12.00	33,200	21,400	3.28	2.44	8.50	CH33-43B		5268821
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.36	2.50	8.50	CH33-43C	CBWMV-36C-090	5269112
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	CH33-43C	EL195UH090XE48B	5269211
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	CH33-43C	EL296UH090XE48C	5650517
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CH33-43C	EL296UH090XV36C	5761056
XP21-036-230	36,000	18.00	13.00	32,200	20,400	3.36	2.50	9.00	CH33-43C	EL296UH090XV48C	5761146
XP21-036-230	36,800	18.00	13.00	32,800	20,800	3.44	2.54	9.00	CH33-43C	EL296UH090XV60C	5761234
XP21-036-230	36,400	18.00	13.00	32,200	20,600	3.40	2.54	9.00	CH33-43C	EL296UH110XV48C	5685242
XP21-036-230	36,400	18.00	13.00	32,200	20,600	3.40	2.54	9.00	CH33-43C	EL296UH110XV48C	5761280
XP21-036-230	36,600	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CH33-43C	EL296UH110XV60C	5761356
XP21-036-230	36,800	17.00	13.00	32,600	20,600	3.46	2.54	9.00	CH33-43C	SL280UH090V60C	5269094
XP21-036-230	36,800	18.00	13.00	32,600	20,600	3.46	2.54	9.00	CH33-43C	SL280UH090XV60C	5269128
XP21-036-230	36,600	18.00	12.50	32,600	20,800	3.42	2.54	8.50	CH33-43C	SL280UH110V60C	5269096
XP21-036-230	36,600	18.00	12.50	32,600	20,800	3.42	2.54	8.50	CH33-43C	SL280UH110XV60C	5269130
XP21-036-230	36,000	17.00	12.00	32,800	21,000	3.28	2.44	8.50	CH33-43C	SLO185B79/105V42	7087720
XP21-036-230	36,000	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CH33-43C	SLO185UF79/105V42	7087691

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CH33-43C	SLP98UH090XV36C	5269097
XP21-036-230	36,000	18.00	13.00	32,200	20,400	3.36	2.50	9.00	CH33-43C	SLP98UH090XV48C	5269098
XP21-036-230	36,800	18.00	13.00	32,800	20,800	3.44	2.54	9.00	CH33-43C	SLP98UH090XV60C	5269099
XP21-036-230	36,600	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CH33-43C	SLP98UH110XV60C	5269100
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.36	2.50	8.50	CH33-44/48B	CBWMV-36B-070	5269127
XP21-036-230	36,000	17.00	12.50	32,800	21,000	3.38	2.52	9.00	CH33-44/48B	EL180UH070E36B	5742093
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.40	2.52	9.00	CH33-44/48B	EL180UH090E48B	5742413
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.34	2.48	8.50	CH33-44/48B	EL296UH045XV36B	5760873
XP21-036-230	35,800	17.00	12.50	32,800	21,000	3.36	2.50	8.50	CH33-44/48B	EL296UH070XV36B	5760974
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.40	2.54	9.00	CH33-44/48B	SL280UH090V36B	5269113
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.40	2.54	8.50	CH33-44/48B	SL280UH090V48B	5269115
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.40	2.54	8.50	CH33-44/48B	SL280UH090XV48B	5269219
XP21-036-230	35,600	17.00	12.00	33,000	21,200	3.30	2.46	8.50	CH33-44/48B	SLO185B79/105V42	7087722
XP21-036-230	35,600	16.00	12.00	33,000	21,200	3.26	2.44	8.50	CH33-44/48B	SLO185UF79/105V42	7087693
XP21-036-230	35,800	17.00	12.50	32,800	21,000	3.36	2.50	8.50	CH33-44/48B	SLP98UH070XV36B	5269116
XP21-036-230	35,400	15.50	11.70	33,000	21,200	3.24	2.40	8.50	CH33-44/48B		5268822
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.40	2.54	9.00	CH33-49	CBWMV-36C-090	5269147
XP21-036-230	36,600	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CH33-49	EL195UH090XE48B	5269212
XP21-036-230	36,600	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CH33-49	EL296UH090XE48C	5650511
XP21-036-230	36,600	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CH33-49	EL296UH090XV36C	5761057
XP21-036-230	36,400	18.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-49	EL296UH090XV48C	5761147
XP21-036-230	37,200	18.00	13.00	32,800	20,800	3.48	2.56	9.00	CH33-49	EL296UH090XV60C	5761235
XP21-036-230	36,600	18.00	13.00	32,400	20,600	3.46	2.56	9.00	CH33-49	EL296UH110XV48C	5685249
XP21-036-230	36,600	18.00	13.00	32,400	20,600	3.46	2.56	9.00	CH33-49	EL296UH110XV48C	5761287
XP21-036-230	37,000	18.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-49	EL296UH110XV60C	5761357
XP21-036-230	37,200	18.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-49	SL280UH090V60C	5269129
XP21-036-230	37,200	18.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-49	SL280UH090XV60C	5269148
XP21-036-230	37,000	18.00	13.00	32,600	20,800	3.46	2.58	9.00	CH33-49	SL280UH110V60C	5269131
XP21-036-230	37,000	17.00	13.00	32,600	20,800	3.46	2.58	9.00	CH33-49	SL280UH110XV60C	5269150
XP21-036-230	36,400	17.00	12.50	32,800	21,000	3.32	2.46	8.50	CH33-49	SLO185B79/105V42	7087729
XP21-036-230	36,200	17.00	12.00	32,800	21,000	3.30	2.44	8.50	CH33-49	SLO185UF79/105V42	7087694
XP21-036-230	36,600	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CH33-49	SLP98UH090XV36C	5269132
XP21-036-230	36,400	18.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-49	SLP98UH090XV48C	5269133
XP21-036-230	37,200	18.00	13.00	32,800	20,800	3.48	2.56	9.00	CH33-49	SLP98UH090XV60C	5269134
XP21-036-230	37,000	18.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-49	SLP98UH110XV60C	5269135
XP21-036-230	36,000	15.70	12.00	33,000	21,200	3.24	2.40	8.50	CH33-49		5268823
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.40	2.54	9.00	CH33-50/60C	CBWMV-36C-090	5269166
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-50/60C	EL195UH090XE48B	5269213
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-50/60C	EL296UH090XE48C	5650494
XP21-036-230	36,600	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-50/60C	EL296UH090XV36C	5761058
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.42	2.56	9.00	CH33-50/60C	EL296UH090XV48C	5761148

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	37,000	18.00	13.00	32,800	21,000	3.48	2.58	9.00	CH33-50/60C	EL296UH090XV60C	5761236
XP21-036-230	36,600	18.00	13.00	32,400	20,600	3.44	2.56	9.00	CH33-50/60C	EL296UH110XV48C	5685243
XP21-036-230	36,600	18.00	13.00	32,400	20,600	3.44	2.56	9.00	CH33-50/60C	EL296UH110XV48C	5761281
XP21-036-230	37,000	17.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-50/60C	SL280UH090V60C	5269149
XP21-036-230	37,000	17.00	13.00	32,600	20,800	3.50	2.60	9.00	CH33-50/60C	SL280UH090XV60C	5269557
XP21-036-230	36,800	17.00	13.00	32,600	20,800	3.46	2.56	9.00	CH33-50/60C	SL280UH110V60C	5269151
XP21-036-230	36,800	17.00	13.00	32,600	20,800	3.46	2.56	9.00	CH33-50/60C	SL280UH110XV60C	5269558
XP21-036-230	36,200	17.00	12.00	32,800	21,000	3.32	2.46	8.50	CH33-50/60C	SLO185B79/105V42	7087736
XP21-036-230	36,200	17.00	12.00	32,800	21,000	3.30	2.44	8.50	CH33-50/60C	SLO185UF79/105V42	7087705
XP21-036-230	36,600	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CH33-50/60C	SLP98UH090XV36C	5269152
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.42	2.56	9.00	CH33-50/60C	SLP98UH090XV48C	5269153
XP21-036-230	37,000	18.00	13.00	32,800	21,000	3.48	2.58	9.00	CH33-50/60C	SLP98UH090XV60C	5269154
XP21-036-230	36,800	18.00	13.00	32,600	20,800	3.48	2.60	9.00	CH33-50/60C	SLP98UH110XV60C	5269155
XP21-036-230	36,000	15.70	12.00	33,000	21,200	3.24	2.40	8.50	CH33-50/60C		5268824
XP21-036-230	35,200	16.00	12.50	33,600	22,200	3.26	2.52	8.50	CH35-42C	EL195UH090XE48C	9114993
XP21-036-230	35,200	16.00	12.50	33,600	22,200	3.26	2.52	8.50	CH35-42C	EL296UH090XE48C	9114994
XP21-036-230	35,400	16.50	12.50	33,600	22,200	3.26	2.52	8.50	CH35-42C	EL296UH090XV36C	9114995
XP21-036-230	35,600	16.50	12.50	33,800	22,200	3.30	2.52	9.00	CH35-42C	EL296UH090XV48C	9114996
XP21-036-230	35,800	16.50	12.50	34,000	22,400	3.34	2.54	9.00	CH35-42C	EL296UH090XV60C	9114997
XP21-036-230	35,400	16.50	12.50	33,400	22,000	3.26	2.52	9.00	CH35-42C	EL296UH110XV48C	9114998
XP21-036-230	35,600	16.50	12.50	33,600	22,200	3.32	2.56	9.00	CH35-42C	EL296UH110XV60C	9114999
XP21-036-230	35,800	16.50	12.50	33,800	22,200	3.34	2.56	9.00	CH35-42C	SL280UH090V60C	9115000
XP21-036-230	35,800	16.50	12.50	33,800	22,200	3.34	2.56	9.00	CH35-42C	SL280UH090XV60C	9115001
XP21-036-230	35,600	16.50	12.50	33,800	22,200	3.32	2.54	9.00	CH35-42C	SL280UH110V60C	9115002
XP21-036-230	35,600	16.50	12.50	33,800	22,200	3.32	2.54	9.00	CH35-42C	SL280UH110XV60C	9115003
XP21-036-230	35,400	16.50	12.50	33,600	22,200	3.26	2.52	8.50	CH35-42C	SLP98UH090XV36C	9115004
XP21-036-230	35,600	16.50	12.50	33,800	22,200	3.30	2.52	9.00	CH35-42C	SLP98UH090XV48C	9115005
XP21-036-230	35,800	16.50	12.50	34,000	22,400	3.34	2.54	9.00	CH35-42C	SLP98UH090XV60C	9115006
XP21-036-230	35,600	16.50	12.50	33,600	22,200	3.32	2.56	9.00	CH35-42C	SLP98UH110XV60C	9115007
XP21-036-230	34,800	14.50	11.50	34,200	22,800	3.12	2.40	8.50	CH35-42C		9114992
XP21-036-230	35,400	16.50	12.50	34,200	23,200	3.52	2.66	9.00	CH35-48B	EL180UH070E36B	9115170
XP21-036-230	35,200	16.50	12.50	34,000	23,000	3.54	2.70	9.00	CH35-48B	EL180UH090E48B	9115171
XP21-036-230	35,000	16.00	12.20	34,400	23,400	3.44	2.60	9.00	CH35-48B	EL195UH045XE36B	9115172
XP21-036-230	35,000	16.00	12.20	34,400	23,400	3.46	2.62	9.00	CH35-48B	EL195UH070XE36B	9115173
XP21-036-230	35,000	16.00	12.20	34,400	23,400	3.44	2.60	9.00	CH35-48B	EL296UH045XE36B	9115011
XP21-036-230	35,200	16.50	12.50	34,200	23,200	3.50	2.64	9.00	CH35-48B	EL296UH045XV36B	9115012
XP21-036-230	35,000	16.00	12.20	34,400	23,400	3.46	2.62	9.00	CH35-48B	EL296UH070XE36B	9115013
XP21-036-230	35,200	16.50	12.50	34,200	23,200	3.50	2.66	9.00	CH35-48B	EL296UH070XV36B	9115014
XP21-036-230	35,400	16.50	12.50	33,800	23,000	3.56	2.72	9.00	CH35-48B	SL280UH090V36B	9115015
XP21-036-230	35,400	16.50	12.50	34,000	23,000	3.56	2.70	9.00	CH35-48B	SL280UH090V48B	9115016
XP21-036-230	35,400	16.50	12.50	34,000	23,000	3.56	2.70	9.00	CH35-48B	SL280UH090XV48B	9115017

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	35,200	16.50	12.50	34,200	23,200	3.50	2.66	9.00	CH35-48B	SLP98UH070XV36B	9115018
XP21-036-230	34,800	15.00	12.00	34,600	23,600	3.38	2.56	9.00	CH35-48B		9115008
XP21-036-230	35,200	16.00	12.50	32,400	21,400	3.22	2.48	8.50	CH35-48C	EL195UH090XE48B	9115032
XP21-036-230	35,200	16.00	12.50	32,400	21,400	3.22	2.48	8.50	CH35-48C	EL296UH090XE48C	9115033
XP21-036-230	35,200	16.00	12.50	32,600	21,400	3.26	2.48	8.50	CH35-48C	EL296UH090XV36C	9115174
XP21-036-230	35,600	16.50	12.50	32,800	21,600	3.28	2.50	8.50	CH35-48C	EL296UH090XV48C	9115020
XP21-036-230	35,600	16.50	12.50	33,000	21,600	3.32	2.50	8.50	CH35-48C	EL296UH090XV60C	9115021
XP21-036-230	35,200	16.50	12.50	32,400	21,400	3.24	2.50	8.50	CH35-48C	EL296UH110XV48C	9115022
XP21-036-230	35,600	16.50	12.50	32,800	21,400	3.30	2.50	8.50	CH35-48C	EL296UH110XV60C	9115023
XP21-036-230	35,600	16.50	12.50	32,800	21,400	3.32	2.52	8.50	CH35-48C	SL280UH090V60C	9115024
XP21-036-230	35,600	16.50	12.50	32,800	21,400	3.32	2.52	8.50	CH35-48C	SL280UH090XV60C	9115025
XP21-036-230	35,600	16.50	12.50	32,800	21,600	3.28	2.52	8.50	CH35-48C	SL280UH110V60C	9115027
XP21-036-230	35,600	16.50	12.50	32,800	21,600	3.28	2.52	8.50	CH35-48C	SL280UH110XV60C	9115026
XP21-036-230	35,200	16.00	12.50	32,600	21,400	3.26	2.48	8.50	CH35-48C	SLP98UH090XV36C	9115028
XP21-036-230	35,600	16.50	12.50	32,800	21,600	3.28	2.50	8.50	CH35-48C	SLP98UH090XV48C	9115029
XP21-036-230	35,600	16.50	12.50	33,000	21,600	3.32	2.50	8.50	CH35-48C	SLP98UH090XV60C	9115030
XP21-036-230	35,600	16.50	12.50	32,800	21,400	3.30	2.50	8.50	CH35-48C	SLP98UH110XV60C	9115031
XP21-036-230	34,800	14.50	11.50	33,000	22,000	3.06	2.36	8.20	CH35-48C		9115019
XP21-036-230	36,400	16.50	12.50	33,400	20,800	3.38	2.46	8.50	CH35-51C	EL195UH090XE48B	9115035
XP21-036-230	36,400	16.50	12.50	33,400	20,800	3.38	2.46	8.50	CH35-51C	EL296UH090XE48C	9115036
XP21-036-230	36,400	16.50	12.50	33,600	20,800	3.40	2.46	8.50	CH35-51C	EL296UH090XV36C	9115037
XP21-036-230	36,600	17.00	12.50	33,600	21,000	3.42	2.48	9.00	CH35-51C	EL296UH090XV48C	9115038
XP21-036-230	36,800	17.00	12.50	33,800	21,000	3.44	2.48	9.00	CH35-51C	EL296UH090XV60C	9115039
XP21-036-230	36,400	17.00	12.50	33,400	20,800	3.42	2.48	8.50	CH35-51C	EL296UH110XV48C	9115040
XP21-036-230	36,800	17.00	12.50	33,600	20,800	3.46	2.48	9.00	CH35-51C	EL296UH110XV60C	9115041
XP21-036-230	37,000	17.00	12.50	33,600	20,800	3.48	2.50	9.00	CH35-51C	SL280UH090V60C	9115042
XP21-036-230	37,000	17.00	12.50	33,600	20,800	3.48	2.50	9.00	CH35-51C	SL280UH090XV60C	9115043
XP21-036-230	36,800	16.50	12.50	33,600	20,800	3.44	2.46	8.50	CH35-51C	SL280UH110V60C	9115044
XP21-036-230	36,800	16.50	12.50	33,600	20,800	3.44	2.46	8.50	CH35-51C	SL280UH110XV60C	9115045
XP21-036-230	36,400	16.50	12.50	33,600	20,800	3.40	2.46	8.50	CH35-51C	SLP98UH090XV36C	9115046
XP21-036-230	36,200	16.50	12.50	33,400	20,600	3.38	2.44	8.50	CH35-51C	SLP98UH090XV48C	9115047
XP21-036-230	36,800	17.00	12.50	33,800	21,000	3.44	2.48	9.00	CH35-51C	SLP98UH090XV60C	9115048
XP21-036-230	36,800	17.00	12.50	33,600	20,800	3.46	2.48	9.00	CH35-51C	SLP98UH110XV60C	9115049
XP21-036-230	36,000	14.50	11.50	34,000	21,400	3.22	2.34	8.50	CH35-51C		9115034
XP21-036-230	34,600	15.00	11.50	33,000	21,200	3.40	2.52	8.50	CR33-48		5268825
XP21-036-230	35,000	17.00	12.50	32,200	20,600	3.58	2.66	9.00	CR33-48B	EL180DF070E36B	5741565
XP21-036-230	35,000	17.00	12.50	32,400	20,600	3.60	2.66	9.00	CR33-48B	EL180DF090E48B	5741589
XP21-036-230	35,000	17.00	12.00	32,600	20,800	3.58	2.64	9.00	CR33-48B	EL195DF070XE48B	5269215
XP21-036-230	34,600	16.00	12.00	32,600	20,800	3.52	2.60	9.00	CR33-48B	EL296DF045XE36B	5650507
XP21-036-230	35,000	17.00	12.00	32,600	21,000	3.54	2.62	9.00	CR33-48B	EL296DF045XV36B	7505740
XP21-036-230	35,000	17.00	12.00	32,600	20,800	3.58	2.64	9.00	CR33-48B	EL296DF070XE48B	5650504

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	35,000	16.00	12.00	32,800	21,000	3.54	2.60	9.00	CR33-48B	EL296DF070XV48B	7487527
XP21-036-230	35,200	17.00	12.50	32,400	20,800	3.60	2.66	9.00	CR33-48B	SL280DF090V48B	5269167
XP21-036-230	35,200	17.00	12.50	32,800	20,800	3.58	2.62	9.00	CR33-48B	SLP98DF070XV36B	5269168
XP21-036-230	35,000	17.00	12.50	32,400	20,600	3.58	2.62	9.00	CR33-48C	CBWMV-36C-090	5269180
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	EL195DF090XE48C	5269216
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	EL296DF090V60C	5269178
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	EL296DF090XE48C	5650514
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	EL296DF110V60C	5269179
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.70	2.70	9.20	CR33-48C	SL280DF090V60C	5269173
XP21-036-230	35,200	17.00	12.50	32,600	20,800	3.60	2.64	9.00	CR33-48C	SLP98DF090XV36C	5269174
XP21-036-230	35,200	17.00	12.50	32,600	20,800	3.62	2.68	9.00	CR33-48C	SLP98DF090XV48C	5269175
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	SLP98DF090XV60C	5269176
XP21-036-230	35,400	17.00	12.50	32,600	20,800	3.64	2.66	9.00	CR33-48C	SLP98DF110XV60C	5269177
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.66	2.68	9.00	CR33-50/60	CBWMV-36C-090	5269188
XP21-036-230	35,400	17.00	12.50	32,800	20,800	3.72	2.70	9.00	CR33-50/60	EL195DF090XE48C	5269217
XP21-036-230	36,400	17.00	12.50	32,800	20,800	3.74	2.70	9.00	CR33-50/60	EL296DF090V60C	5269186
XP21-036-230	35,400	17.00	12.50	32,800	20,800	3.72	2.70	9.00	CR33-50/60	EL296DF090XE48C	5650498
XP21-036-230	36,400	17.00	12.50	33,000	21,000	3.76	2.72	9.00	CR33-50/60	EL296DF110V60C	5269187
XP21-036-230	36,600	18.00	13.00	33,000	20,800	3.82	2.74	9.50	CR33-50/60	SL280DF090V60C	5269181
XP21-036-230	36,000	17.00	12.50	32,800	20,800	3.70	2.68	9.00	CR33-50/60	SLP98DF090XV36C	5269182
XP21-036-230	36,200	17.00	12.50	32,800	20,800	3.72	2.70	9.00	CR33-50/60	SLP98DF090XV48C	5269183
XP21-036-230	36,400	17.00	12.50	32,800	20,800	3.74	2.70	9.00	CR33-50/60	SLP98DF090XV60C	5269184
XP21-036-230	36,400	17.00	12.50	33,000	21,000	3.76	2.72	9.00	CR33-50/60	SLP98DF110XV60C	5269185
XP21-036-230	35,600	15.70	11.70	33,400	21,200	3.50	2.54	8.70	CR33-50/60		5268826
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.34	2.48	8.50	CX34-38A	EL180UH045E36A	5741787
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	CX34-38A	SL280UH070V36A	5268845
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	CX34-38A	SL280UH070XV36A	5269218
XP21-036-230	35,800	17.00	12.50	32,400	20,800	3.34	2.50	8.50	CX34-38B	CBWMV-36B-070	5268861
XP21-036-230	35,800	17.00	13.00	32,200	20,400	3.40	2.52	9.00	CX34-38B	EL180UH070E36B	5742094
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.42	2.54	9.00	CX34-38B	EL180UH090E48B	5742415
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-38B	EL195UH045XE36B	5269191
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.34	2.48	9.00	CX34-38B	EL195UH070XE36B	5269192
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-38B	EL296UH045XE36B	5650501
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	CX34-38B	EL296UH045XV36B	5760876
XP21-036-230	35,600	17.00	12.50	32,400	20,600	3.34	2.48	9.00	CX34-38B	EL296UH070XE36B	5650508
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	CX34-38B	EL296UH070XV36B	5760977
XP21-036-230	36,000	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CX34-38B	SL280UH090V36B	5268847
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.42	2.54	9.00	CX34-38B	SL280UH090V48B	5268849
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.42	2.54	9.00	CX34-38B	SL280UH090XV48B	5268863
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.28	2.44	8.50	CX34-38B	SLO185B79/105V42	7087727
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-38B	SLO185UF79/105V42	7087695

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.34	2.48	8.50	CX34-38B	SLP98UH070XV36B	5268850
XP21-036-230	35,600	15.50	11.70	33,000	21,200	3.20	2.38	8.50	CX34-43		8145904
XP21-036-230	35,800	17.00	12.50	32,400	20,800	3.34	2.50	8.50	CX34-43B	CBWMV-36B-070	8145923
XP21-036-230	35,800	17.00	13.00	32,000	20,400	3.36	2.52	9.00	CX34-43B	EL180UH070E36B	8145934
XP21-036-230	36,200	18.00	13.00	32,400	20,600	3.40	2.54	9.00	CX34-43B	EL180UH090E48B	8145933
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-43B	EL195UH045XE36B	8145936
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.32	2.46	8.50	CX34-43B	EL195UH070XE36B	8145935
XP21-036-230	35,600	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-43B	EL296UH045XE36B	8145932
XP21-036-230	36,000	17.00	12.50	32,600	20,800	3.32	2.48	8.50	CX34-43B	EL296UH045XV36B	8145929
XP21-036-230	35,800	17.00	12.50	32,400	20,600	3.32	2.46	8.50	CX34-43B	EL296UH070XE36B	8145931
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	CX34-43B	EL296UH070XV36B	8145930
XP21-036-230	36,200	17.00	13.00	32,200	20,600	3.38	2.54	8.50	CX34-43B	SL280UH090V36B	8145925
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.40	2.54	9.00	CX34-43B	SL280UH090V48B	8145924
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.40	2.54	9.00	CX34-43B	SL280UH090XV48B	8145937
XP21-036-230	35,800	17.00	12.00	32,600	21,000	3.26	2.44	8.50	CX34-43B	SLO185B79/105V42	8145928
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-43B	SLO185UF79/105V42	8145927
XP21-036-230	35,800	17.00	12.50	32,600	20,800	3.32	2.48	8.50	CX34-43B	SLP98UH070XV36B	8145926
XP21-036-230	35,800	17.00	12.50	32,200	20,600	3.34	2.50	8.50	CX34-43C	CBWMV-36C-090	8145918
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CX34-43C	EL195UH090XE48C	8145915
XP21-036-230	36,200	17.00	13.00	32,400	20,600	3.38	2.52	9.00	CX34-43C	EL296UH090XE48C	8145913
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	CX34-43C	EL296UH090XV36C	8145909
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.36	2.50	8.50	CX34-43C	EL296UH090XV48C	8145910
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.42	2.54	9.00	CX34-43C	EL296UH090XV60C	8145911
XP21-036-230	36,200	18.00	13.00	32,200	20,600	3.38	2.54	9.00	CX34-43C	EL296UH110XV48C	8145912
XP21-036-230	36,400	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CX34-43C	EL296UH110XV60C	8145906
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.46	2.54	9.00	CX34-43C	SL280UH090V60C	8145919
XP21-036-230	36,400	17.00	12.50	32,600	20,600	3.46	2.54	9.00	CX34-43C	SL280UH090XV60C	8145917
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.42	2.54	8.50	CX34-43C	SL280UH110V60C	8145905
XP21-036-230	36,400	17.00	12.50	32,600	20,800	3.42	2.54	8.50	CX34-43C	SL280UH110XV60C	8145916
XP21-036-230	35,800	17.00	12.00	32,600	21,000	3.26	2.44	8.50	CX34-43C	SLO185B79/105V42	8145908
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-43C	SLO185UF79/105V42	8145907
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.38	2.52	9.00	CX34-43C	SLP98UH090XV36C	8145922
XP21-036-230	35,800	17.00	12.50	32,200	20,400	3.36	2.50	8.50	CX34-43C	SLP98UH090XV48C	8145920
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.42	2.54	9.00	CX34-43C	SLP98UH090XV60C	8145921
XP21-036-230	36,400	18.00	13.00	32,600	20,600	3.44	2.54	9.00	CX34-43C	SLP98UH110XV60C	8145914
XP21-036-230	35,000	15.20	11.70	32,600	21,000	3.10	2.34	8.20	CX34-44/48		5268816
XP21-036-230	35,600	17.00	12.50	32,200	20,400	3.30	2.46	8.50	CX34-44/48C	SLP98UH090XV36C	8935138
XP21-036-230	36,000	17.00	12.50	32,400	20,600	3.38	2.52	9.00	CX34-49C	CBWMV-36C-090	5269037
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	CX34-49C	EL195UH090XE48C	5269206
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	CX34-49C	EL296UH090XE48C	5650506
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	CX34-49C	EL296UH090XV36C	5761063

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	36,000	17.00	13.00	32,200	20,400	3.38	2.52	9.00	CX34-49C	EL296UH090XV48C	5761152
XP21-036-230	36,800	17.00	13.00	32,800	20,800	3.46	2.54	9.00	CX34-49C	EL296UH090XV60C	5761244
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CX34-49C	EL296UH110XV48C	5685248
XP21-036-230	36,400	17.00	13.00	32,400	20,600	3.42	2.54	9.00	CX34-49C	EL296UH110XV48C	5761286
XP21-036-230	36,600	17.00	13.00	32,600	20,600	3.46	2.56	9.00	CX34-49C	EL296UH110XV60C	5761364
XP21-036-230	36,800	17.00	13.00	32,600	20,600	3.48	2.56	9.00	CX34-49C	SL280UH090V60C	5269021
XP21-036-230	36,800	17.00	13.00	32,600	20,600	3.48	2.56	9.00	CX34-49C	SL280UH090XV60C	5269038
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.44	2.56	8.50	CX34-49C	SL280UH110V60C	5269023
XP21-036-230	36,600	17.00	12.50	32,600	20,800	3.44	2.56	8.50	CX34-49C	SL280UH110XV60C	5269040
XP21-036-230	35,800	17.00	12.00	32,800	21,000	3.26	2.42	8.50	CX34-49C	SLO185UF79/105V42	7087709
XP21-036-230	36,200	17.00	12.50	32,400	20,600	3.40	2.52	9.00	CX34-49C	SLP98UH090XV36C	5269024
XP21-036-230	36,000	17.00	13.00	32,200	20,400	3.38	2.52	9.00	CX34-49C	SLP98UH090XV48C	5269025
XP21-036-230	36,800	17.00	13.00	32,800	20,800	3.46	2.54	9.00	CX34-49C	SLP98UH090XV60C	5269026
XP21-036-230	36,600	17.00	13.00	32,600	20,600	3.46	2.56	9.00	CX34-49C	SLP98UH110XV60C	5269027
XP21-036-230	35,600	15.50	11.70	33,000	21,200	3.22	2.40	8.50	CX34-49C		5268818
XP21-036-230	34,200	16.00	12.20	34,400	21,800	3.30	2.56	9.00	CX35-48B	EL180UH070E36B	9115051
XP21-036-230	34,400	16.00	12.20	34,600	22,000	3.34	2.58	9.00	CX35-48B	EL180UH090E48B	9115052
XP21-036-230	34,000	15.50	11.50	35,000	22,400	3.20	2.46	8.50	CX35-48B	EL195UH045XE36B	9115053
XP21-036-230	34,000	16.00	12.00	34,600	22,000	3.24	2.50	8.50	CX35-48B	EL195UH070XE36B	9115054
XP21-036-230	34,000	15.50	11.50	35,000	22,400	3.20	2.46	8.50	CX35-48B	EL296UH045XE36B	9115055
XP21-036-230	34,200	16.00	12.00	34,800	22,200	3.26	2.52	8.50	CX35-48B	EL296UH045XV36B	9115056
XP21-036-230	34,000	16.00	12.00	34,600	22,000	3.24	2.50	8.50	CX35-48B	EL296UH070XE36B	9115057
XP21-036-230	34,200	16.00	12.00	34,800	22,200	3.26	2.50	8.50	CX35-48B	EL296UH070XV36B	9115058
XP21-036-230	34,200	16.00	12.20	34,600	21,800	3.32	2.54	9.00	CX35-48B	SL280UH090V36B	9115059
XP21-036-230	34,400	16.00	12.20	34,600	22,000	3.32	2.56	9.00	CX35-48B	SL280UH090V48B	9115060
XP21-036-230	34,400	16.00	12.20	34,600	22,000	3.32	2.56	9.00	CX35-48B	SL280UH090XV48B	9115061
XP21-036-230	34,200	16.00	12.00	34,800	22,200	3.26	2.50	8.50	CX35-48B	SLP98UH070XV36B	9115062
XP21-036-230	33,800	14.30	11.00	35,200	22,600	3.14	2.42	8.50	CX35-48B		9115050
XP21-036-230	34,600	16.00	12.20	30,000	19,400	3.36	2.46	8.50	CX35-49C	EL195UH090XE48C	9115064
XP21-036-230	34,600	16.00	12.20	30,000	19,400	3.36	2.46	8.50	CX35-49C	EL296UH090XE48C	9115065
XP21-036-230	34,600	16.00	12.20	30,000	19,400	3.38	2.48	8.50	CX35-49C	EL296UH090XV36C	9115066
XP21-036-230	34,800	16.00	12.20	30,200	19,500	3.40	2.48	9.00	CX35-49C	EL296UH090XV48C	9115067
XP21-036-230	34,600	16.00	12.50	30,000	19,300	3.40	2.50	9.00	CX35-49C	EL296UH110XV48C	9115068
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.44	2.52	9.00	CX35-49C	EL296UH110XV60C	9115069
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.44	2.52	9.00	CX35-49C	SL280UH090V60C	9115070
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.44	2.52	9.00	CX35-49C	SL280UH090XV60C	9115071
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.42	2.50	9.00	CX35-49C	SL280UH110V60C	9115072
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.42	2.50	9.00	CX35-49C	SL280UH110XV60C	9115073
XP21-036-230	34,600	16.00	12.50	30,000	19,400	3.38	2.48	8.50	CX35-49C	SLP98UH090XV36C	9115074
XP21-036-230	34,800	16.00	12.20	30,200	19,500	3.40	2.48	9.00	CX35-49C	SLP98UH090XV48C	9115075
XP21-036-230	35,000	16.00	12.50	30,200	19,500	3.44	2.52	9.00	CX35-49C	SLP98UH110XV60C	9115076

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-036-230	34,000	14.30	11.50	30,600	20,000	3.16	2.34	8.50	CX35-49C		9115063
XP21-048-230	47,000	15.20	11.70	46,000	29,000	3.00	2.34	8.20	C33-49		5272174
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	C33-49C	CBWMV-60C-100	5272198
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.08	2.40	8.20	C33-49C	CBWMV-60C-120	5272199
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.50	C33-49C	EL180UH090E60C	5740290
XP21-048-230	47,000	16.00	12.00	45,000	28,200	3.04	2.40	8.50	C33-49C	EL180UH110E60C	5740746
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	C33-49C	EL195UH090XE48C	5272299
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.40	8.20	C33-49C	EL195UH110XE60C	5272300
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.40	8.20	C33-49C	EL296DF110XE60C	5650530
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	C33-49C	EL296UH090XE48C	5650526
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.06	2.38	8.20	C33-49C	EL296UH090XV48C	5761162
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.40	8.20	C33-49C	EL296UH090XV60C	5761249
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	C33-49C	EL296UH110XV48C	5685256
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	C33-49C	EL296UH110XV48C	5761294
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	C33-49C	EL296UH110XV60C	5761370
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.06	2.40	8.20	C33-49C	SL280UH090V60C	5272185
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.06	2.40	8.20	C33-49C	SL280UH090XV60C	5272200
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.20	C33-49C	SL280UH110V60C	5272186
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.20	C33-49C	SL280UH110XV60C	5272202
XP21-048-230	47,000	15.50	11.50	46,000	29,000	3.02	2.34	8.20	C33-49C	SLO185UF79/105V42	7087718
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.06	2.38	8.20	C33-49C	SLP98UH090XV48C	5272187
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.40	8.20	C33-49C	SLP98UH090XV60C	5272188
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	C33-49C	SLP98UH110XV60C	5272189
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.10	2.38	8.20	C33-62C	CBWMV-60C-100	5272232
XP21-048-230	49,000	17.00	12.50	45,500	28,600	3.10	2.38	8.20	C33-62C	CBWMV-60C-120	5272233
XP21-048-230	49,000	17.00	12.50	45,000	28,200	3.08	2.40	8.20	C33-62C	EL180UH090E60C	5740291
XP21-048-230	48,500	17.00	12.50	45,000	28,200	3.06	2.40	8.50	C33-62C	EL180UH110E60C	5740747
XP21-048-230	48,500	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	EL195UH090XE48C	5272303
XP21-048-230	49,000	17.00	12.50	45,000	28,400	3.06	2.40	8.20	C33-62C	EL195UH110XE60C	5272304
XP21-048-230	49,000	17.00	12.50	45,000	28,400	3.06	2.40	8.20	C33-62C	EL296DF110XE60C	5650518
XP21-048-230	48,500	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	EL296UH090XE48C	5650520
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	EL296UH090XV48C	5761159
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	EL296UH090XV60C	5761247
XP21-048-230	48,500	17.00	12.50	45,500	28,400	3.10	2.38	8.20	C33-62C	EL296UH110XV48C	5685255
XP21-048-230	48,500	17.00	12.50	45,500	28,400	3.10	2.38	8.20	C33-62C	EL296UH110XV48C	5761293
XP21-048-230	49,000	17.00	12.50	45,500	28,600	3.10	2.38	8.20	C33-62C	EL296UH110XV60C	5761374
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.14	2.40	8.20	C33-62C	SL280UH090V60C	5272218
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.14	2.40	8.20	C33-62C	SL280UH090XV60C	5272234
XP21-048-230	49,000	17.00	12.50	45,000	28,200	3.08	2.40	8.20	C33-62C	SL280UH110V60C	5272220
XP21-048-230	49,000	17.00	12.50	45,000	28,200	3.08	2.40	8.20	C33-62C	SL280UH110XV60C	5272236
XP21-048-230	48,500	16.00	12.00	46,000	29,000	3.04	2.34	8.20	C33-62C	SLO185UF79/105V42	7087719

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	SLP98UH090XV48C	5272221
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.08	2.38	8.20	C33-62C	SLP98UH090XV60C	5272222
XP21-048-230	49,000	17.00	12.50	45,500	28,600	3.10	2.38	8.20	C33-62C	SLP98UH110XV60C	5272223
XP21-048-230	48,500	15.70	12.00	46,000	29,000	3.02	2.34	8.20	C33-62C		5272176
XP21-048-230	48,000	17.00	12.50	45,500	28,400	3.14	2.42	8.50	C33-62D	EL180UH135E60D	5741103
XP21-048-230	48,000	16.00	12.00	45,500	28,200	3.08	2.38	8.50	C33-62D	EL195UH135XE60D	5272307
XP21-048-230	48,000	16.00	12.00	45,500	28,200	3.08	2.38	8.50	C33-62D	EL296UH135XE60D	5650527
XP21-048-230	48,000	17.00	12.00	45,500	28,600	3.12	2.42	8.50	C33-62D	EL296UH135XV60D	5761430
XP21-048-230	48,000	16.00	12.50	45,500	28,400	3.12	2.40	8.50	C33-62D	SL280UH135V60D	5272251
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.08	2.38	8.20	C33-62D	SLO185UF124/141V60	7087751
XP21-048-230	48,000	17.00	12.00	45,500	28,600	3.12	2.42	8.50	C33-62D	SLP98UH135XV60D	5272252
XP21-048-230	47,500	15.20	11.70	46,000	29,000	3.04	2.34	8.20	C33-62D		5272178
XP21-048-230	47,500	17.00	12.00	46,500	29,000	3.48	2.64	9.00	CBX27UH-048		5272172
XP21-048-230	46,500	16.00	12.00	46,000	28,800	3.36	2.60	9.00	CBX27UH-060		5272173
XP21-048-230	47,500	17.00	12.00	46,500	29,000	3.48	2.64	9.00	CBX32MV-048		5272168
XP21-048-230	47,500	17.20	12.50	46,000	28,800	3.46	2.60	9.20	CBX32MV-060		5272167
XP21-048-230	47,500	17.00	12.50	45,500	28,400	3.20	2.48	8.50	CBX32MV-068		5272169
XP21-048-230	47,500	16.00	12.00	46,500	29,000	3.48	2.62	9.00	CBX40UHV-048		5272170
XP21-048-230	47,500	16.00	12.00	46,500	29,000	3.42	2.60	9.00	CBX40UHV-060		5272171
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.08	2.38	8.20	CH33-49	CBWMV-60C-100	5272274
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.38	8.20	CH33-49	EL180UH090E60C	5740287
XP21-048-230	47,000	16.00	12.00	45,000	28,200	3.04	2.38	8.50	CH33-49	EL180UH110E60C	5740754
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.02	2.36	8.20	CH33-49	EL180UH110E60C	5272309
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	CH33-49	EL195UH110XE60C	5272310
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	CH33-49	EL296DF110XE60C	5650523
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.02	2.36	8.20	CH33-49	EL296UH090XE48C	5650525
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.36	8.20	CH33-49	EL296UH090XV48C	5761157
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.06	2.36	8.20	CH33-49	EL296UH090XV60C	5761246
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-49	EL296UH110XV48C	5685253
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-49	EL296UH110XV48C	5761291
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-49	EL296UH110XV60C	5761367
XP21-048-230	48,000	16.00	12.50	45,500	28,400	3.10	2.38	8.20	CH33-49	SL280UH090V60C	5272262
XP21-048-230	48,000	16.00	12.50	45,500	28,400	3.10	2.38	8.20	CH33-49	SL280UH090XV60C	5272330
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	CH33-49	SL280UH110V60C	5272264
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	CH33-49	SL280UH110XV60C	5272275
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.36	8.20	CH33-49	SLP98UH090XV48C	5272265
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.06	2.36	8.20	CH33-49	SLP98UH090XV60C	5272266
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-49	SLP98UH110XV60C	5272267
XP21-048-230	47,500	15.20	11.70	46,000	29,000	3.04	2.34	8.20	CH33-49		5272180
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.08	2.38	8.20	CH33-50/60C	CBWMV-60C-100	5272286
XP21-048-230	47,500	16.00	12.00	45,500	28,800	3.04	2.38	8.20	CH33-50/60C	CBWMV-60C-120	5272287

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-048-230	47,000	16.00	12.00	45,000	28,200	3.04	2.38	8.20	CH33-50/60C	EL180UH090E60C	5740286
XP21-048-230	47,000	16.00	12.00	45,000	28,200	3.04	2.38	8.50	CH33-50/60C	EL180UH110E60C	5740744
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.36	8.20	CH33-50/60C	EL195UH090XE48C	5272311
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	CH33-50/60C	EL195UH110XE60C	5272312
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	CH33-50/60C	EL296DF110XE60C	5650519
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.36	8.20	CH33-50/60C	EL296UH090XE48C	5650521
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.04	2.36	8.20	CH33-50/60C	EL296UH090XV48C	5761158
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.04	2.36	8.20	CH33-50/60C	EL296UH090XV60C	5761256
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-50/60C	EL296UH110XV48C	5685252
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-50/60C	EL296UH110XV48C	5761290
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-50/60C	EL296UH110XV60C	5761368
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	CH33-50/60C	SL280UH110V60C	5272276
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	CH33-50/60C	SL280UH110XV60C	5272332
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.04	2.36	8.20	CH33-50/60C	SLP98UH090XV48C	5272277
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.04	2.36	8.20	CH33-50/60C	SLP98UH090XV60C	5272278
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CH33-50/60C	SLP98UH110XV60C	5272279
XP21-048-230	47,000	15.20	11.70	46,000	29,000	3.02	2.34	8.20	CH33-50/60C		5272181
XP21-048-230	47,500	16.00	12.50	45,500	28,400	3.18	2.44	8.50	CH33-62D	EL180UH135E60D	5741102
XP21-048-230	47,500	16.00	12.00	45,500	28,200	3.12	2.40	8.50	CH33-62D	EL195UH135XE60D	5272313
XP21-048-230	47,500	16.00	12.00	45,500	28,200	3.12	2.40	8.50	CH33-62D	EL296UH135XE60D	5650541
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.16	2.44	8.50	CH33-62D	SL280UH135V60D	5272288
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.14	2.44	8.50	CH33-62D	SLP98UH135XV60D	5272289
XP21-048-230	47,000	15.00	11.70	46,000	29,000	3.06	2.36	8.20	CH33-62D		5272182
XP21-048-230	46,500	16.00	12.20	48,500	32,000	3.08	2.38	8.20	CH35-60D	EL180UH135E60D	9115078
XP21-048-230	46,000	15.50	11.50	49,000	32,400	3.06	2.36	8.20	CH35-60D	EL195UH135XE60D	9115079
XP21-048-230	46,000	15.50	11.50	49,000	32,400	3.06	2.36	8.20	CH35-60D	EL296UH135XE60D	9115080
XP21-048-230	46,500	16.00	12.00	49,000	32,200	3.10	2.38	8.20	CH35-60D	EL296UH135XVE60D	9115081
XP21-048-230	46,500	16.00	12.00	48,500	32,200	3.06	2.38	8.20	CH35-60D	SL280UH135V60D	9115082
XP21-048-230	46,500	16.00	12.00	49,000	32,200	3.10	2.38	8.20	CH35-60D	SLP98UH135XV60D	9115083
XP21-048-230	46,000	14.50	11.50	49,000	32,800	2.98	2.32	8.20	CH35-60D		9115077
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.50	2.62	9.00	CR33-50/60	CBWMV-60C-100	5272297
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.50	2.60	9.00	CR33-50/60	CBWMV-60C-120	5272298
XP21-048-230	47,000	16.00	11.70	46,000	28,800	3.54	2.62	9.00	CR33-50/60	EL195UH090XE48C	5272314
XP21-048-230	47,000	16.00	11.70	46,000	28,600	3.60	2.66	9.00	CR33-50/60	EL195UH110XE60C	5272315
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.46	2.60	9.00	CR33-50/60	EL296DF090V60C	5272295
XP21-048-230	47,000	16.00	11.70	46,000	28,800	3.54	2.62	9.00	CR33-50/60	EL296DF090XE48C	5650535
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.46	2.58	9.00	CR33-50/60	EL296DF110V60C	5272296
XP21-048-230	47,000	16.00	11.70	46,000	28,600	3.60	2.66	9.00	CR33-50/60	EL296DF110XE60C	5650528
XP21-048-230	47,000	16.00	12.50	46,000	28,600	3.54	2.62	9.00	CR33-50/60	SL280DF090V60C	5272291
XP21-048-230	47,000	16.00	12.50	46,000	28,600	3.54	2.64	9.00	CR33-50/60	SL280DF110V60C	5277847
XP21-048-230	47,000	16.00	12.00	46,000	29,000	3.44	2.56	9.00	CR33-50/60	SLP98DF090XV48C	5272292

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.46	2.60	9.00	CR33-50/60	SLP98DF090XV60C	5272293
XP21-048-230	47,000	16.00	11.70	46,000	29,000	3.46	2.58	9.00	CR33-50/60	SLP98DF110XV60C	5272294
XP21-048-230	46,500	15.00	11.50	47,000	29,200	3.44	2.52	8.50	CR33-50/60		5272183
XP21-048-230	46,500	15.00	11.50	47,000	29,200	3.44	2.52	8.50	CR33-60		5272184
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.08	2.38	8.20	CX34-49C	CBWMV-60C-100	5272215
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.08	2.40	8.20	CX34-49C	CBWMV-60C-120	5272216
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.50	CX34-49C	EL180UH090E60C	5740289
XP21-048-230	47,000	16.00	12.00	45,000	28,200	3.04	2.40	8.50	CX34-49C	EL180UH110E60C	5740745
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	CX34-49C	EL195UH090XE48C	5272301
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.40	8.20	CX34-49C	EL195UH110XE60C	5272302
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.40	8.20	CX34-49C	EL296DF110XE60C	5650522
XP21-048-230	47,000	16.00	12.00	45,000	28,400	3.02	2.38	8.20	CX34-49C	EL296UH090XE48C	5650524
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.06	2.38	8.20	CX34-49C	EL296UH090XV48C	5761160
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.40	8.20	CX34-49C	EL296UH090XV60C	5761248
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	CX34-49C	EL296UH110XV48C	5685257
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.04	2.38	8.20	CX34-49C	EL296UH110XV48C	5761295
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CX34-49C	EL296UH110XV60C	5761369
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.06	2.40	8.20	CX34-49C	SL280UH090V60C	5272201
XP21-048-230	47,500	16.00	12.00	45,000	28,400	3.06	2.40	8.20	CX34-49C	SL280UH090XV60C	5272217
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.20	CX34-49C	SL280UH110V60C	5272203
XP21-048-230	47,500	16.00	12.50	45,000	28,200	3.06	2.40	8.20	CX34-49C	SL280UH110XV60C	5272219
XP21-048-230	47,000	15.50	11.50	46,000	29,000	3.02	2.34	8.20	CX34-49C	SLO185UF79/105V42	7087717
XP21-048-230	47,500	16.00	12.00	45,500	28,400	3.06	2.38	8.20	CX34-49C	SLP98UH090XV48C	5272204
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.40	8.20	CX34-49C	SLP98UH090XV60C	5272205
XP21-048-230	47,500	16.00	12.00	45,500	28,600	3.06	2.38	8.20	CX34-49C	SLP98UH110XV60C	5272206
XP21-048-230	47,000	15.20	11.70	46,000	29,000	3.00	2.34	8.20	CX34-49C		5272175
XP21-048-230	49,000	17.00	12.50	45,500	28,400	3.08	2.38	8.20	CX34-62C	EL296UH090XV48C	8066785
XP21-048-230	48,000	17.00	12.50	45,500	28,400	3.14	2.42	8.50	CX34-62D	EL180UH135E60D	5741104
XP21-048-230	48,000	16.00	12.00	45,500	28,200	3.08	2.38	8.50	CX34-62D	EL195UH135XE60D	5272308
XP21-048-230	48,000	16.00	12.00	45,500	28,200	3.08	2.38	8.50	CX34-62D	EL296UH135XE60D	5650531
XP21-048-230	48,000	17.00	12.00	45,500	28,600	3.12	2.42	8.50	CX34-62D	EL296UH135XV60D	5761429
XP21-048-230	48,000	16.00	12.50	45,500	28,400	3.12	2.40	8.50	CX34-62D	SL280UH135V60D	5272256
XP21-048-230	48,000	16.00	12.00	45,500	28,600	3.08	2.38	8.20	CX34-62D	SLO185UF124/141V60	7087752
XP21-048-230	48,000	17.00	12.00	45,500	28,600	3.12	2.42	8.50	CX34-62D	SLP98UH135XV60D	5272257
XP21-048-230	47,500	15.20	11.70	46,000	29,000	3.04	2.34	8.20	CX34-62D		5272179
XP21-048-230	45,000	15.50	11.50	46,000	31,600	3.30	2.48	8.50	CX35-49C	EL180UH090E60C	9115085
XP21-048-230	44,500	15.50	11.50	46,000	31,600	3.28	2.46	8.50	CX35-49C	EL180UH110E60C	9115086
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	EL195UH090XE48C	9115087
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.28	2.48	8.50	CX35-49C	EL195UH110XE60C	9115088
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.28	2.48	8.50	CX35-49C	EL296DF110XE60C	9115092
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	EL296UH090XE48C	9115089

## NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	EL296UH090XV48C	9115090
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	EL296UH090XV60C	9115091
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.28	2.46	8.50	CX35-49C	EL296UH110XV48C	9115093
XP21-048-230	45,000	15.50	11.50	46,500	32,000	3.30	2.46	8.50	CX35-49C	EL296UH110XV60C	9115094
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.30	2.48	8.50	CX35-49C	SL280UH090V60C	9115095
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.30	2.48	8.50	CX35-49C	SL280UH090XV60C	9115096
XP21-048-230	45,000	15.50	11.50	46,000	31,600	3.30	2.46	8.50	CX35-49C	SL280UH110V60C	9115097
XP21-048-230	45,000	15.50	11.50	46,000	31,600	3.30	2.46	8.50	CX35-49C	SL280UH110XV60C	9115098
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	SLP98UH090XV48C	9115169
XP21-048-230	45,000	15.50	11.50	46,000	31,800	3.26	2.46	8.50	CX35-49C	SLP98UH090XV60C	9115099
XP21-048-230	45,000	15.50	11.50	46,500	32,000	3.30	2.46	8.50	CX35-49C	SLP98UH110XV60C	9115100
XP21-048-230	44,500	14.30	11.00	46,500	32,400	3.20	2.42	8.50	CX35-49C		9115084
XP21-048-230	45,500	14.50	11.50	47,000	30,400	3.24	2.40	8.50	CX35-60D	EL180UH135E60D	9115101
XP21-048-230	45,500	14.30	11.50	47,500	30,600	3.20	2.36	8.50	CX35-60D	EL195UH135XE60D	9115102
XP21-048-230	45,500	14.30	11.50	47,500	30,600	3.20	2.36	8.50	CX35-60D	EL296UH135XE60D	9115103
XP21-048-230	45,500	14.50	11.50	47,500	30,600	3.26	2.40	8.50	CX35-60D	EL296UH135XV60D	9115104
XP21-048-230	45,500	14.50	11.50	47,000	30,400	3.22	2.40	8.50	CX35-60D	SL280UH135V60D	9115105
XP21-048-230	45,500	14.50	11.50	47,500	30,600	3.26	2.40	8.50	CX35-60D	SLP98UH135XV60D	9115106
XP21-060-230	56,000	14.70	12.00	53,000	33,600	3.04	2.28	8.20	C33-49		5272321
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.08	2.30	8.50	C33-49C	CBWMV-60C-100	5272340
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	C33-49C	CBWMV-60C-120	5272341
XP21-060-230	56,000	15.70	12.20	52,500	33,200	3.06	2.30	8.50	C33-49C	EL180UH090E60C	5740294
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.06	2.30	8.50	C33-49C	EL180UH110E60C	5740752
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.04	2.28	8.50	C33-49C	EL195UH110XE60C	5272412
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.04	2.28	8.50	C33-49C	EL296DF110XE60C	5650539
XP21-060-230	55,500	15.50	12.00	52,000	33,200	2.98	2.28	8.20	C33-49C	EL296UH090XV60C	5761250
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.04	2.28	8.20	C33-49C	EL296UH110XV60C	5761375
XP21-060-230	56,500	15.70	12.20	52,500	33,400	3.06	2.30	8.50	C33-49C	SL280UH090V60C	5272331
XP21-060-230	56,500	15.70	12.20	52,500	33,400	3.06	2.30	8.50	C33-49C	SL280UH090XV60C	5272342
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	C33-49C	SL280UH110V60C	5272333
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	C33-49C	SL280UH110XV60C	5272344
XP21-060-230	55,500	15.50	12.00	52,000	33,200	2.98	2.28	8.20	C33-49C	SLP98UH090XV60C	5272334
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.04	2.28	8.20	C33-49C	SLP98UH110XV60C	5272335
XP21-060-230	56,500	16.00	12.00	53,000	33,600	3.12	2.32	8.50	C33-60D	EL296UH135XV60D	5611119
XP21-060-230	56,500	16.00	12.00	53,000	33,400	3.14	2.32	8.50	C33-60D	SL280UH135V60D	5611118
XP21-060-230	56,500	16.00	12.00	53,000	33,600	3.12	2.32	8.50	C33-60D	SLP98UH135XV60D	5611124
XP21-060-230	56,000	14.50	11.70	53,000	33,600	3.06	2.28	8.50	C33-60D		5646340
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.10	2.30	8.50	C33-62C	CBWMV-60C-100	5272364
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	C33-62C	CBWMV-60C-120	5272365
XP21-060-230	57,000	16.00	12.50	52,500	33,200	3.10	2.30	8.50	C33-62C	EL180UH090E60C	5740296
XP21-060-230	57,000	16.00	12.50	52,500	33,200	3.08	2.30	8.50	C33-62C	EL180UH110E60C	5740753

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (85W66) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (58M81) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-060-230	57,000	15.70	12.20	52,500	33,200	3.06	2.30	8.50	C33-62C	EL195UH110XE60C	5272414
XP21-060-230	56,500	16.00	12.00	52,500	33,200	3.04	2.28	8.20	C33-62C	EL296UH090XV60C	5761251
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.06	2.28	8.50	C33-62C	EL296UH110XV60C	5761376
XP21-060-230	57,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	C33-62C	SL280UH090V60C	5272355
XP21-060-230	57,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	C33-62C	SL280UH090XV60C	5272366
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	C33-62C	SL280UH110V60C	5272357
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	C33-62C	SL280UH110XV60C	5272368
XP21-060-230	56,500	16.00	12.00	52,500	33,200	3.04	2.28	8.20	C33-62C	SLP98UH090XV60C	5272358
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.06	2.28	8.50	C33-62C	SLP98UH110XV60C	5272359
XP21-060-230	57,000	15.00	12.00	53,000	33,600	3.06	2.28	8.50	C33-62C		5272323
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	C33-62D	EL296UH135XV60D	5611117
XP21-060-230	57,000	16.00	12.00	53,000	33,400	3.14	2.32	8.50	C33-62D	SL280UH135V60D	5611116
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	C33-62D	SLP98UH135XV60D	5611123
XP21-060-230	56,000	16.00	12.00	53,500	33,400	3.46	2.48	9.00	CBX27UH-060		5272320
XP21-060-230	55,500	15.00	12.00	54,000	34,000	3.42	2.48	9.00	CBX32M-060		5272318
XP21-060-230	56,500	16.50	12.50	53,500	33,400	3.48	2.52	9.20	CBX32MV-060		5272316
XP21-060-230	56,500	16.00	12.50	52,500	33,200	3.20	2.38	8.50	CBX32MV-068		5272317
XP21-060-230	55,500	15.70	12.00	54,000	34,000	3.40	2.46	9.00	CBX40UHV-060		5272319
XP21-060-230	56,500	15.70	12.00	53,000	33,600	3.10	2.30	8.50	CH33-49	CBWMV-60C-100	5272387
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CH33-49	CBWMV-60C-120	5272388
XP21-060-230	56,000	15.70	12.20	52,500	33,200	3.10	2.32	8.50	CH33-49	EL180UH090E60C	5740297
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.06	2.30	8.50	CH33-49	EL195UH110XE60C	5272416
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.06	2.30	8.50	CH33-49	EL296DF110XE60C	5650533
XP21-060-230	55,500	15.70	12.00	52,500	33,200	3.04	2.28	8.20	CH33-49	EL296UH090XV60C	5761252
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.06	2.28	8.50	CH33-49	EL296UH110XV60C	5761377
XP21-060-230	56,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	CH33-49	SL280UH090V60C	5272379
XP21-060-230	56,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	CH33-49	SL280UH090XV60C	5272389
XP21-060-230	56,500	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CH33-49	SL280UH110V60C	5272381
XP21-060-230	56,500	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CH33-49	SL280UH110XV60C	5272391
XP21-060-230	56,500	15.70	12.00	52,500	33,200	3.04	2.28	8.20	CH33-49	SLP98UH090XV60C	5272382
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.06	2.28	8.50	CH33-49	SLP98UH110XV60C	5272383
XP21-060-230	55,000	14.70	11.70	52,500	33,200	2.98	2.26	8.20	CH33-49		5272325
XP21-060-230	56,000	15.50	11.70	53,000	33,600	3.06	2.28	8.50	CH33-50/60C	CBWMV-60C-100	5272399
XP21-060-230	55,000	15.20	12.00	52,000	33,200	2.98	2.28	8.20	CH33-50/60C	CBWMV-60C-120	5272400
XP21-060-230	55,500	15.50	12.00	52,500	33,200	3.04	2.30	8.50	CH33-50/60C	EL180UH090E60C	5740298
XP21-060-230	55,500	15.50	12.00	52,500	33,200	3.04	2.28	8.50	CH33-50/60C	EL180UH110E60C	5740751
XP21-060-230	55,500	15.50	12.00	52,500	33,200	3.06	2.30	8.50	CH33-50/60C	EL195UH110XE60C	5272417
XP21-060-230	55,500	15.50	12.00	52,500	33,200	3.06	2.30	8.50	CH33-50/60C	EL296DF110XE60C	5650542
XP21-060-230	55,000	15.20	11.70	52,500	33,200	3.00	2.26	8.20	CH33-50/60C	EL296UH090XV60C	5761253
XP21-060-230	55,000	15.50	12.00	52,000	33,000	2.98	2.26	8.20	CH33-50/60C	EL296UH110XV60C	5761373
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CH33-50/60C	SL280UH090V60C	5272390

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE – Due to Lennox’ ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CH33-50/60C	SL280UH090XV60C	5272420
XP21-060-230	55,500	15.50	12.00	52,500	33,400	3.02	2.28	8.20	CH33-50/60C	SL280UH110V60C	5272392
XP21-060-230	55,500	15.50	12.00	52,500	33,400	3.02	2.28	8.20	CH33-50/60C	SL280UH110XV60C	5272421
XP21-060-230	55,000	15.20	11.70	52,500	33,200	3.00	2.26	8.20	CH33-50/60C	SLP98UH090XV60C	5272393
XP21-060-230	55,000	15.50	12.00	52,000	33,000	2.98	2.26	8.20	CH33-50/60C	SLP98UH110XV60C	5272394
XP21-060-230	54,500	14.50	11.70	52,500	33,200	2.98	2.26	8.20	CH33-50/60C		5272326
XP21-060-230	56,000	16.00	12.00	53,000	33,400	3.16	2.36	8.50	CH33-62D	EL180UH135E60D	5741105
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.12	2.32	8.50	CH33-62D	EL195UH135XE60D	5272418
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.12	2.32	8.50	CH33-62D	EL296UH135XE60D	5650538
XP21-060-230	56,000	15.70	12.00	53,000	33,400	3.16	2.34	8.50	CH33-62D	EL296UH135XV60D	5761431
XP21-060-230	56,000	16.00	12.00	53,000	33,400	3.14	2.34	8.50	CH33-62D	SL280UH135V60D	5272401
XP21-060-230	56,000	15.70	12.00	53,000	33,400	3.16	2.34	8.50	CH33-62D	SLP98UH135XV60D	5272402
XP21-060-230	55,500	14.50	11.70	53,000	33,800	3.08	2.30	8.50	CH33-62D		5272327
XP21-060-230	54,500	15.50	11.50	55,000	35,600	3.18	2.28	8.50	CH35-51C	EL180UH090E60C	9115107
XP21-060-230	54,000	15.10	11.50	55,000	35,800	3.14	2.26	8.20	CH35-51C	EL195UH110XE60C	9115108
XP21-060-230	53,500	15.10	11.50	55,000	35,800	3.10	2.24	8.20	CH35-51C	EL296UH090XV60C	9115109
XP21-060-230	54,000	15.10	11.50	55,000	35,800	3.14	2.26	8.20	CH35-51C	EL296UH110XE60C	9115110
XP21-060-230	54,500	15.10	11.50	55,500	36,000	3.16	2.26	8.20	CH35-51C	EL296UH110XV48C	9115111
XP21-060-230	54,000	15.50	11.50	55,000	36,000	3.12	2.26	8.20	CH35-51C	EL296UH110XV60C	9115112
XP21-060-230	54,500	15.50	11.50	55,000	35,800	3.16	2.28	8.20	CH35-51C	SL280UH090V60C	9115113
XP21-060-230	54,500	15.50	11.50	55,000	35,800	3.16	2.28	8.20	CH35-51C	SL280UH090XV60C	9115114
XP21-060-230	54,000	15.10	11.50	55,000	35,800	3.14	2.26	8.20	CH35-51C	SL280UH110V60C	9115115
XP21-060-230	54,000	15.10	11.50	55,000	35,800	3.14	2.26	8.20	CH35-51C	SL280UH110XV60C	9115116
XP21-060-230	53,500	15.10	11.50	55,000	35,800	3.10	2.24	8.20	CH35-51C	SLP98UH090XV60C	9115117
XP21-060-230	54,000	15.50	11.50	55,000	36,000	3.12	2.26	8.20	CH35-51C	SLP98UH110XV60C	9115118
XP21-060-230	54,500	14.50	11.50	55,500	36,200	3.16	2.26	8.20	CH35-51C		9115119
XP21-060-230	55,000	15.50	11.50	53,000	34,400	3.22	2.36	8.50	CH35-60D	EL296UH135XV60D	9115120
XP21-060-230	55,000	15.50	11.50	53,000	34,400	3.24	2.36	8.50	CH35-60D	SL280UH135V60D	9115121
XP21-060-230	55,000	15.50	11.50	53,000	34,400	3.22	2.36	8.50	CH35-60D	SLP98UH135XV60D	9115122
XP21-060-230	54,500	14.00	11.50	53,500	34,600	3.18	2.32	8.50	CH35-60D		9115123
XP21-060-230	55,000	15.20	11.70	53,500	33,800	3.40	2.46	8.70	CR33-50/60	CBWMV-60C-100	5272410
XP21-060-230	55,000	15.20	11.50	53,500	34,000	3.38	2.46	8.70	CR33-50/60	CBWMV-60C-120	5272411
XP21-060-230	54,500	15.20	11.70	53,000	33,400	3.38	2.46	8.70	CR33-50/60	EL195DF110XE60C	5272419
XP21-060-230	54,000	15.20	11.50	53,000	33,600	3.32	2.44	8.70	CR33-50/60	EL296DF090V60C	5272408
XP21-060-230	54,000	15.20	11.50	53,000	33,600	3.32	2.44	8.70	CR33-50/60	EL296DF110V60C	5272409
XP21-060-230	54,500	15.20	11.70	53,000	33,400	3.38	2.46	8.70	CR33-50/60	EL296DF110XE60C	5650537
XP21-060-230	55,500	15.50	11.70	53,500	33,800	3.44	2.50	8.70	CR33-50/60	SL280DF090V60C	5272405
XP21-060-230	54,000	15.20	11.50	53,000	33,600	3.32	2.44	8.70	CR33-50/60	SLP98DF090XV60C	5272406
XP21-060-230	54,000	15.20	11.50	53,000	33,600	3.32	2.44	8.70	CR33-50/60	SLP98DF110XV60C	5272407
XP21-060-230	54,500	14.20	11.50	53,000	33,600	3.34	2.44	8.50	CR33-50/60		5272328
XP21-060-230	54,500	14.20	11.50	53,000	33,600	3.34	2.44	8.50	CR33-60		5272329

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.08	2.30	8.50	CX34-49C	CBWMV-60C-100	5272352
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	CX34-49C	CBWMV-60C-120	5272353
XP21-060-230	56,000	15.70	12.20	52,500	33,200	3.06	2.30	8.50	CX34-49C	EL180UH090E60C	5740292
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.06	2.30	8.50	CX34-49C	EL180UH110E60C	5740748
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.04	2.28	8.50	CX34-49C	EL195UH110XE60C	5272413
XP21-060-230	56,000	15.50	12.20	52,500	33,200	3.04	2.28	8.50	CX34-49C	EL296DF110XE60C	5650536
XP21-060-230	55,500	15.50	12.00	52,000	33,200	2.98	2.28	8.20	CX34-49C	EL296UH090XV60C	5761254
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.04	2.28	8.20	CX34-49C	EL296UH110XV60C	5761371
XP21-060-230	56,500	15.70	12.20	52,500	33,400	3.06	2.30	8.50	CX34-49C	SL280UH090V60C	5272343
XP21-060-230	56,500	15.70	12.20	52,500	33,400	3.06	2.30	8.50	CX34-49C	SL280UH090XV60C	5272354
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	CX34-49C	SL280UH110V60C	5272345
XP21-060-230	56,000	15.50	12.00	53,000	33,600	3.06	2.28	8.50	CX34-49C	SL280UH110XV60C	5272356
XP21-060-230	55,500	15.50	12.00	52,000	33,200	2.98	2.28	8.20	CX34-49C	SLP98UH090XV60C	5272346
XP21-060-230	56,000	15.70	12.00	53,000	33,600	3.04	2.28	8.20	CX34-49C	SLP98UH110XV60C	5272347
XP21-060-230	56,000	14.70	12.00	53,000	33,600	3.04	2.28	8.20	CX34-49C		5272322
XP21-060-230	56,500	16.00	12.00	53,000	33,600	3.12	2.32	8.50	CX34-60D	EL296UH135XV60D	5611121
XP21-060-230	56,500	16.00	12.00	53,000	33,400	3.14	2.32	8.50	CX34-60D	SL280UH135V60D	5611120
XP21-060-230	56,500	16.00	12.00	53,000	33,600	3.12	2.32	8.50	CX34-60D	SLP98UH135XV60D	5611125
XP21-060-230	56,000	14.50	11.70	53,000	33,600	3.06	2.28	8.50	CX34-60D		5646341
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.10	2.30	8.50	CX34-62C	CBWMV-60C-100	8196168
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	CX34-62C	CBWMV-60C-120	8196176
XP21-060-230	57,000	16.00	12.50	52,500	33,200	3.10	2.30	8.50	CX34-62C	EL180UH090E60C	8196172
XP21-060-230	57,000	16.00	12.50	52,500	33,200	3.08	2.30	8.50	CX34-62C	EL180UH110E60C	8196171
XP21-060-230	57,000	15.70	12.20	52,500	33,200	3.06	2.30	8.50	CX34-62C	EL195UH110XE60C	8196177
XP21-060-230	56,500	16.00	12.00	52,500	33,200	3.04	2.28	8.20	CX34-62C	EL296UH090XV60C	8196173
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.06	2.28	8.50	CX34-62C	EL296UH110XV60C	8196174
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	CX34-62C	EL296UH135XV60D	8196178
XP21-060-230	57,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	CX34-62C	SL280UH090V60C	8196164
XP21-060-230	57,500	16.00	12.00	53,000	33,400	3.12	2.30	8.50	CX34-62C	SL280UH090XV60C	8196175
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	CX34-62C	SL280UH110V60C	8196167
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.08	2.28	8.50	CX34-62C	SL280UH110XV60C	8196169
XP21-060-230	57,000	16.00	12.00	53,000	33,400	3.14	2.32	8.50	CX34-62C	SL280UH135V60D	8196179
XP21-060-230	56,500	16.00	12.00	52,500	33,200	3.04	2.28	8.20	CX34-62C	SLP98UH090XV60C	8196166
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.06	2.28	8.50	CX34-62C	SLP98UH110XV60C	8196165
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	CX34-62C	SLP98UH135XV60D	8196180
XP21-060-230	57,000	15.00	12.00	53,000	33,600	3.06	2.28	8.50	CX34-62C		8196163
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	CX34-62D	EL296UH135XV60D	5611115
XP21-060-230	57,000	16.00	12.00	53,000	33,400	3.14	2.32	8.50	CX34-62D	SL280UH135V60D	5611114
XP21-060-230	57,000	16.00	12.00	53,000	33,600	3.14	2.32	8.50	CX34-62D	SLP98UH135XV60D	5611122
XP21-060-230	54,500	14.50	11.50	53,500	37,600	3.06	2.42	8.50	CX35-49C	EL180UH090E60C	9115124
XP21-060-230	54,000	14.50	11.50	53,500	37,800	3.04	2.42	8.50	CX35-49C	EL195UH110XE60C	9115125

**NOTES:**

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP21-060-230	54,000	14.50	11.50	53,500	37,800	3.04	2.42	8.50	CX35-49C	EL296DF110XE60C	9115128
XP21-060-230	54,000	14.50	11.00	53,500	38,000	3.02	2.40	8.50	CX35-49C	EL296UH090XV48C	9115126
XP21-060-230	53,500	14.50	11.50	53,000	37,600	2.98	2.40	8.20	CX35-49C	EL296UH090XV60C	9115127
XP21-060-230	54,500	14.50	11.50	53,500	37,800	3.06	2.42	8.50	CX35-49C	EL296UH110XV48C	9115129
XP21-060-230	54,000	14.50	11.00	53,500	38,000	3.02	2.40	8.50	CX35-49C	EL296UH110XV60C	9115130
XP21-060-230	54,500	14.50	11.50	53,500	37,600	3.08	2.42	8.50	CX35-49C	SL280UH090V60C	9115131
XP21-060-230	54,500	14.50	11.50	53,500	37,600	3.08	2.42	8.50	CX35-49C	SL280UH090XV60C	9115132
XP21-060-230	54,000	14.50	11.50	53,000	37,600	3.04	2.42	8.50	CX35-49C	SL280UH110V60C	9115133
XP21-060-230	54,000	14.50	11.50	53,000	37,600	3.04	2.42	8.50	CX35-49C	SL280UH110XV60C	9115134
XP21-060-230	54,000	14.50	11.00	53,500	38,000	3.02	2.40	8.50	CX35-49C	SLP98UH090XV48C	9115135
XP21-060-230	53,500	14.50	11.50	53,000	37,600	2.98	2.40	8.20	CX35-49C	SLP98UH090XV60C	9115136
XP21-060-230	54,000	14.50	11.00	53,500	38,000	3.02	2.40	8.50	CX35-49C	SLP98UH110XV60C	9115137
XP21-060-230	54,500	14.00	11.00	54,000	38,000	3.06	2.40	8.50	CX35-49C		9115138

NOTES:

All matches with EL195E and ML180E gas furnaces require the use of a Blower Motor Relay Kit (**85W66**) for proper unit operation.

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.



PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP25-024-230	22,600	22.00	15.00	20,800	13,400	3.38	2.32	9.70	C33-31A	SL280UH070V36A	5947727
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.60	C33-31B	EL296UH045XV36B	5947245
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.70	C33-31B	EL296UH070XV36B	5947246
XP25-024-230	22,600	22.50	15.00	20,800	13,200	3.38	2.30	9.70	C33-31B	SL280UH090V36B	5947247
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.70	C33-31B	SLP98UH070XV36B	5947248
XP25-024-230	23,000	22.00	15.50	21,400	13,800	3.12	2.12	9.20	C33-38A	SL280UH070V36A	5947249
XP25-024-230	23,000	22.50	15.50	21,400	13,800	3.10	2.12	9.20	C33-38B	EL296UH045XV36B	5947250
XP25-024-230	23,000	23.00	15.50	21,400	13,800	3.10	2.12	9.20	C33-38B	EL296UH070XV36B	5947251
XP25-024-230	23,000	23.00	15.50	21,200	13,700	3.12	2.12	9.20	C33-38B	SL280UH090V48B	5947252
XP25-024-230	23,000	23.00	15.50	21,400	13,800	3.10	2.12	9.20	C33-38B	SLP98UH070XV36B	5947253
XP25-024-230	22,800	23.00	15.50	21,600	13,900	3.38	2.32	9.60	C33-48B	EL296UH045XV36B	5947254
XP25-024-230	22,800	23.50	15.50	21,600	13,900	3.38	2.32	9.60	C33-48B	EL296UH070XV36B	5947255
XP25-024-230	22,800	23.50	16.00	21,400	13,900	3.40	2.36	9.70	C33-48B	SL280UH090V36B	5947256
XP25-024-230	22,800	23.50	15.50	21,600	13,900	3.38	2.32	9.60	C33-48B	SLP98UH070XV36B	5947257
XP25-024-230	23,000	22.00	15.50	21,400	13,500	3.50	2.34	10.00	CBX32MV-036		5947726
XP25-024-230	22,800	22.00	15.50	21,600	13,600	3.52	2.34	10.00	CBX40UHV-024		5947243
XP25-024-230	22,800	22.00	15.50	21,600	13,600	3.50	2.34	10.00	CBX40UHV-030		5947244
XP25-024-230	22,400	23.50	15.50	22,200	14,600	3.64	2.58	10.20	CH33-31B	EL296UH045XV36B	5947275
XP25-024-230	22,400	23.50	16.00	22,200	14,600	3.66	2.60	10.20	CH33-31B	EL296UH070XV36B	5947276
XP25-024-230	22,400	23.00	16.00	22,200	14,600	3.66	2.60	10.20	CH33-31B	SL280UH070V36A	5947277
XP25-024-230	22,400	23.50	16.00	22,200	14,500	3.68	2.60	10.20	CH33-31B	SL280UH090V36B	5947278
XP25-024-230	22,400	23.50	16.00	22,200	14,600	3.66	2.60	10.20	CH33-31B	SLP98UH070XV36B	5947279
XP25-024-230	22,200	22.50	15.50	22,200	14,600	3.58	2.54	10.00	CH33-42B	EL296UH045XV36B	5947280
XP25-024-230	22,200	22.50	15.50	22,200	14,600	3.62	2.56	10.20	CH33-42B	EL296UH070XV36B	5947281
XP25-024-230	22,200	22.00	15.50	22,200	14,600	3.62	2.56	10.20	CH33-42B	SL280UH070V36A	5947282
XP25-024-230	22,200	23.00	15.50	22,000	14,600	3.62	2.58	10.20	CH33-42B	SL280UH090V36B	5947283
XP25-024-230	22,200	22.50	15.50	22,200	14,600	3.62	2.56	10.20	CH33-42B	SLP98UH070XV36B	5947284
XP25-024-230	23,000	22.50	15.50	23,600	15,000	3.50	2.40	8.50	CR33-48B	EL296DF045XV36B	7505748
XP25-024-230	23,000	22.50	16.00	23,600	15,000	3.54	2.42	8.50	CR33-48B	SL280DF070V36A	5947272
XP25-024-230	23,000	23.00	16.00	23,600	15,000	3.54	2.42	8.50	CR33-48B	SLP98DF070XV36B	5947273
XP25-024-230	23,000	23.50	16.00	23,600	14,900	3.58	2.44	8.70	CR33-48B	SLP98DF090XV36C	5947274
XP25-024-230	22,600	22.00	15.00	20,800	13,400	3.38	2.32	9.70	CX34-31A	SL280UH070V36A	5947728
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.60	CX34-31B	EL296UH045XV36B	5947258
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.70	CX34-31B	EL296UH070XV36B	5947259
XP25-024-230	22,600	22.50	15.00	20,800	13,200	3.38	2.30	9.70	CX34-31B	SL280UH090V36B	5947260
XP25-024-230	22,400	22.50	15.00	20,800	13,300	3.34	2.30	9.70	CX34-31B	SLP98UH070XV36B	5947261
XP25-024-230	23,000	22.00	15.50	21,400	13,800	3.12	2.12	9.20	CX34-38A	SL280UH090V36B	5947262
XP25-024-230	23,000	22.50	15.50	21,400	13,800	3.10	2.12	9.20	CX34-38B	EL296UH045XV36B	5947263

NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP25-024-230	23,000	23.00	15.50	21,400	13,800	3.10	2.12	9.20	CX34-38B	EL296UH070XV36B	5947264
XP25-024-230	23,000	23.00	15.50	21,200	13,700	3.12	2.12	9.20	CX34-38B	SL280UH090V36B	5947265
XP25-024-230	23,000	23.00	15.50	21,400	13,800	3.10	2.12	9.20	CX34-38B	SLP98UH070XV36B	5947266
XP25-036-230	35,000	21.00	13.00	31,600	20,000	2.96	1.78	8.70	C33-38A	SL280UH070V36A	5947681
XP25-036-230	35,000	21.00	13.00	31,600	20,000	2.94	1.78	8.70	C33-38B	EL296UH045XV36B	5947682
XP25-036-230	35,000	21.50	13.00	31,600	20,000	2.96	1.78	8.70	C33-38B	EL296UH070XV36B	5947683
XP25-036-230	35,200	21.50	13.50	31,400	19,800	3.02	1.80	8.70	C33-38B	SL280UH090V36B	5947684
XP25-036-230	35,000	21.50	13.00	31,600	20,000	2.96	1.80	8.70	C33-38B	SLP98UH070XV36B	5947685
XP25-036-230	35,200	20.00	13.00	31,200	20,800	2.96	2.08	9.20	C33-43B	EL296UH045XV36B	5947686
XP25-036-230	35,400	20.00	13.00	31,200	20,800	2.98	2.10	9.20	C33-43B	EL296UH070XV36B	5947687
XP25-036-230	35,600	20.50	13.50	31,000	20,400	3.04	2.10	9.20	C33-43B	SL280UH090V36B	5947688
XP25-036-230	35,400	20.00	13.00	31,200	20,800	2.98	2.10	9.20	C33-43B	SLP98UH070XV36B	5947689
XP25-036-230	35,400	20.50	13.50	31,000	20,600	3.02	2.12	9.20	C33-43C	EL296UH090XV36C	5947690
XP25-036-230	35,400	20.50	13.50	31,000	20,600	3.02	2.12	9.20	C33-43C	SLP98UH090XV36C	5947691
XP25-036-230	34,600	21.00	13.00	31,800	20,600	2.80	1.80	8.50	C33-48B	EL296UH045XV36B	5947692
XP25-036-230	34,600	21.00	13.00	31,600	20,400	2.80	1.80	8.50	C33-48B	EL296UH070XV36B	5947693
XP25-036-230	34,800	21.50	13.50	31,400	20,200	2.84	1.82	8.70	C33-48B	SL280UH090V36B	5947694
XP25-036-230	34,600	21.00	13.00	31,600	20,400	2.80	1.80	8.50	C33-48B	SLP98UH070XV36B	5947695
XP25-036-230	34,800	21.00	13.00	31,600	20,200	2.84	1.82	8.50	C33-48C	EL296UH090XV36C	5947696
XP25-036-230	34,800	21.00	13.00	31,600	20,200	2.84	1.82	8.50	C33-48C	SLP98UH090XV36C	5947697
XP25-036-230	35,200	20.00	13.00	31,000	20,400	3.00	2.08	9.20	C33-50/60C	EL296UH090XV36C	5947698
XP25-036-230	35,200	20.00	13.00	31,000	20,400	3.00	2.08	9.20	C33-50/60C	SLP98UH090XV36C	5947699
XP25-036-230	34,400	21.50	13.00	32,200	21,000	3.28	2.26	10.00	CBX32MV-036		5947680
XP25-036-230	34,400	21.50	13.50	32,000	21,000	3.28	2.28	10.00	CBX40UHV-036		5947679
XP25-036-230	35,200	21.00	13.50	31,000	20,600	3.00	2.10	9.20	CH33-43C	EL296UH090XV36C	5947720
XP25-036-230	35,200	20.00	13.00	31,000	20,600	2.98	2.08	9.20	CH33-43C	SLP98UH070XV36B	6810978
XP25-036-230	35,200	21.00	13.50	31,000	20,600	3.00	2.10	9.20	CH33-43C	SLP98UH090XV36C	5947721
XP25-036-230	34,600	20.00	12.50	31,200	20,800	2.96	2.06	9.20	CH33-44/48B	EL296UH045XV36B	5947722
XP25-036-230	34,600	20.00	12.50	31,200	20,800	2.98	2.08	9.20	CH33-44/48B	EL296UH070XV36B	5947723
XP25-036-230	34,800	20.50	13.00	31,000	20,600	3.04	2.12	9.20	CH33-44/48B	SL280UH090V36B	5947724
XP25-036-230	34,800	20.00	13.00	31,200	20,600	3.02	2.10	9.20	CH33-44/48B	SLP98UH070XV36B	5947725
XP25-036-230	35,200	20.50	13.50	30,200	19,900	3.50	2.38	9.50	CR33-50/60	SL280DF090V48B	7176690
XP25-036-230	35,000	20.50	13.00	30,200	20,000	3.44	2.36	9.50	CR33-50/60	SLP98DF070XV36B	7133800
XP25-036-230	35,200	21.00	13.50	30,200	20,000	3.48	2.38	10.00	CR33-50/60	SLP98DF090XV36C	5947719
XP25-036-230	35,000	21.00	13.00	31,600	20,000	2.96	1.78	8.70	CX34-38A	SL280UH070V36A	5947700
XP25-036-230	35,000	21.00	13.00	31,600	20,000	2.94	1.78	8.70	CX34-38B	EL296UH045XV36B	5947701
XP25-036-230	35,000	21.50	13.00	31,600	20,000	2.96	1.78	8.70	CX34-38B	EL296UH070XV36B	5947702
XP25-036-230	35,200	21.50	13.50	31,400	19,800	3.02	1.80	8.70	CX34-38B	SL280UH090V36B	5947703
XP25-036-230	35,000	21.50	13.00	31,600	20,000	2.96	1.80	8.70	CX34-38B	SLP98UH070XV36B	5947704
XP25-036-230	35,600	20.50	13.50	31,000	20,400	3.04	2.10	9.20	CX34-43B	SL280UH090V36B	5947707
XP25-036-230	34,800	21.00	13.00	31,600	20,200	2.84	1.82	8.50	CX34-43C	SLP98UH090XV36C	8935136
XP25-036-230	34,800	21.50	13.50	31,400	20,200	2.84	1.82	8.70	CX34-44/48B	SL280UH090V36B	9104552

NOTES:

- Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);
- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP25-036-230	34,800	21.00	13.00	31,600	20,200	2.84	1.82	8.50	CX34-44/48C	SLP98UH090XV36C	8103443
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.18	2.30	9.20	C33-49C	EL296UH090XV48C	5947733
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	EL296UH090XV60C	5947734
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	EL296UH110XV48C	5947735
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	EL296UH110XV60C	5947736
XP25-048-230	47,500	20.00	13.00	45,000	29,400	3.22	2.32	9.20	C33-49C	SL280UH090V60C	5947737
XP25-048-230	47,500	19.50	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	SL280UH110V60C	5947738
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.30	9.20	C33-49C	SLP98UH090XV48C	5947739
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	SLP98UH090XV60C	5947740
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	C33-49C	SLP98UH110XV60C	5947741
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.94	2.24	9.50	C33-62C	EL296UH090XV48C	5947742
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	EL296UH090XV60C	5947743
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	EL296UH110XV48C	5947744
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	EL296UH110XV60C	5947745
XP25-048-230	49,000	20.00	13.00	46,000	29,800	2.98	2.24	9.60	C33-62C	SL280UH090V60C	5947746
XP25-048-230	49,000	19.50	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	SL280UH110V60C	5947747
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.94	2.24	9.50	C33-62C	SLP98UH090XV48C	5947748
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	SLP98UH090XV60C	5947749
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	C33-62C	SLP98UH110XV60C	5947750
XP25-048-230	47,500	19.50	13.00	45,000	28,600	3.38	2.32	9.70	C33-62D	EL296UH135XV60D	5947751
XP25-048-230	47,500	19.50	13.00	45,000	28,400	3.40	2.32	9.70	C33-62D	SL280UH135V60D	5947752
XP25-048-230	47,500	19.50	13.00	45,000	28,600	3.38	2.32	9.70	C33-62D	SLP98UH135XV60D	5947753
XP25-048-230	48,000	20.50	13.00	47,500	30,600	3.18	2.30	9.70	CBX32MV-048		5947732
XP25-048-230	47,000	20.00	13.00	47,000	30,000	3.24	2.40	10.00	CBX32MV-060		5947730
XP25-048-230	48,000	20.00	13.00	47,500	30,600	3.18	2.30	9.70	CBX40UHV-048		5947731
XP25-048-230	47,000	20.50	13.00	47,000	30,000	3.24	2.42	10.20	CBX40UHV-060		5947729
XP25-048-230	48,000	20.50	12.50	46,500	30,400	3.00	2.12	9.50	CH33-49	EL296UH090XV48C	5947782
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	EL296UH090XV60C	5947783
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	EL296UH110XV48C	5947784
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	EL296UH110XV60C	5947785
XP25-048-230	48,000	20.00	13.00	46,000	30,200	3.00	2.14	9.50	CH33-49	SL280UH090V60C	5947786
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	SL280UH110V60C	5947787
XP25-048-230	48,000	20.50	12.50	46,500	30,400	3.00	2.12	9.50	CH33-49	SLP98UH090XV48C	5947788
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	SLP98UH090XV60C	5947789
XP25-048-230	48,000	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-49	SLP98UH110XV60C	5947790
XP25-048-230	47,500	20.00	12.50	46,500	30,400	2.98	2.12	9.20	CH33-50/60C	EL296UH090XV48C	5947791
XP25-048-230	47,500	19.50	12.50	46,500	30,400	2.98	2.12	9.20	CH33-50/60C	EL296UH090XV60C	5947792
XP25-048-230	47,500	20.00	12.50	46,500	30,400	3.00	2.14	9.20	CH33-50/60C	EL296UH110XV48C	5947793
XP25-048-230	47,500	19.50	12.50	46,500	30,400	3.00	2.14	9.20	CH33-50/60C	EL296UH110XV60C	5947794
XP25-048-230	47,500	19.50	12.50	46,000	30,200	3.00	2.14	9.20	CH33-50/60C	SL280UH090V60C	5947795
XP25-048-230	47,500	19.50	12.50	46,500	30,400	3.00	2.14	9.20	CH33-50/60C	SL280UH110V60C	5947796
XP25-048-230	47,500	20.00	12.50	46,500	30,400	2.98	2.12	9.20	CH33-50/60C	SLP98UH090XV48C	5947797

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP25-048-230	47,500	19.50	12.50	46,500	30,400	2.98	2.12	9.20	CH33-50/60C	SLP98UH090XV60C	5947798
XP25-048-230	47,500	19.50	12.50	46,500	30,400	3.00	2.14	9.20	CH33-50/60C	SLP98UH110XV60C	5947799
XP25-048-230	47,500	19.50	12.50	46,000	30,200	3.04	2.18	9.50	CH33-62D	EL296UH135XE60D	5947800
XP25-048-230	47,500	19.50	13.00	46,000	30,200	3.04	2.18	9.50	CH33-62D	SL280UH135V60D	5947801
XP25-048-230	47,500	19.50	12.50	46,000	30,200	3.04	2.18	9.50	CH33-62D	SLP98UH135XV60D	5947802
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-50/60	EL296DF090XV60C	5947775
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-50/60	EL296DF110XV60C	5947776
XP25-048-230	46,500	19.50	12.50	45,500	30,000	2.98	2.18	9.00	CR33-50/60	SL280DF090V60C	5947777
XP25-048-230	47,000	20.00	12.50	45,500	30,000	3.00	2.20	9.00	CR33-50/60	SL280DF110V60C	5947778
XP25-048-230	46,500	20.00	12.00	46,000	30,400	2.94	2.16	9.00	CR33-50/60	SLP98DF090XV48C	5947779
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-50/60	SLP98DF090XV60C	5947780
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-50/60	SLP98DF110XV60C	5947781
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-60	EL296DF090XV60C	5947849
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-60	EL296DF110XV60C	5947850
XP25-048-230	46,500	19.50	12.50	45,500	30,000	2.98	2.18	9.00	CR33-60	SL280DF090V60C	5947851
XP25-048-230	47,000	20.00	12.50	45,500	30,000	3.00	2.20	9.00	CR33-60	SL280DF110V60C	5947852
XP25-048-230	46,500	20.00	12.00	46,000	30,400	2.94	2.16	9.00	CR33-60	SLP98DF090XV48C	5947853
XP25-048-230	46,500	19.50	12.50	46,000	30,400	2.96	2.18	9.00	CR33-60	SLP98DF110XV60C	5947854
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.18	2.30	9.20	CX34-49C	EL296UH090XV48C	5947754
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	EL296UH090XV60C	5947755
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	EL296UH110XV48C	5947756
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	EL296UH110XV60C	5947757
XP25-048-230	47,500	20.00	13.00	45,000	29,400	3.22	2.32	9.20	CX34-49C	SL280UH090XV60C	5947758
XP25-048-230	47,500	19.50	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	SL280UH110V60C	5947759
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.30	9.20	CX34-49C	SLP98UH090XV48C	5947760
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	SLP98UH090XV60C	5947761
XP25-048-230	47,500	20.00	12.50	45,000	29,600	3.20	2.32	9.20	CX34-49C	SLP98UH110XV60C	5947762
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.94	2.24	9.50	CX34-62C	EL296UH090XV48C	8203147
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	EL296UH090XV60C	8203148
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	EL296UH110XV48C	8203152
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	EL296UH110XV60C	8203151
XP25-048-230	49,000	20.00	13.00	46,000	29,800	2.98	2.24	9.60	CX34-62C	SL280UH090V60C	8203149
XP25-048-230	49,000	19.50	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	SL280UH110V60C	8203150
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.94	2.24	9.50	CX34-62C	SLP98UH090XV48C	8203154
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	SLP98UH090XV60C	8203155
XP25-048-230	49,000	20.00	13.00	46,000	30,000	2.96	2.24	9.50	CX34-62C	SLP98UH110XV60C	8203153
XP25-048-230	47,500	19.50	13.00	45,000	28,600	3.38	2.32	9.70	CX34-62D	EL296UH135XV60D	5947772
XP25-048-230	47,500	19.50	13.00	45,000	28,400	3.40	2.32	9.70	CX34-62D	SL280UH135V60D	5947773
XP25-048-230	47,500	19.50	13.00	45,000	28,600	3.38	2.32	9.70	CX34-62D	SLP98UH135XV60D	5947774
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.32	9.70	C33-49C	EL296UH090XV60C	5947804
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.34	9.70	C33-49C	EL296UH110XV60C	5947805
XP25-060-230	58,000	19.00	12.00	51,500	32,800	3.30	2.36	9.70	C33-49C	SL280UH090V60C	5947806

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
				High	Low	High	Low				
XP25-060-230	58,000	18.50	12.00	51,500	33,000	3.26	2.34	9.70	C33-49C	SL280UH110V60C	5947807
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.32	9.70	C33-49C	SLP98UH090XV60C	5947808
XP25-060-230	58,000	18.50	12.00	52,000	33,200	3.26	2.34	9.70	C33-49C	SLP98UH110XV60C	5947809
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	9.70	C33-62C	EL296UH090XV60C	5947810
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	10.00	C33-62C	EL296UH110XV60C	5947811
XP25-060-230	60,500	19.50	12.50	54,000	33,200	3.28	2.32	10.00	C33-62C	SL280UH090V60C	5947812
XP25-060-230	60,000	19.00	12.50	54,000	33,200	3.24	2.30	10.00	C33-62C	SL280UH110V60C	5947813
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	9.70	C33-62C	SLP98UH090XV60C	5947814
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	10.00	C33-62C	SLP98UH110XV60C	5947815
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.30	2.36	9.70	C33-62D	EL296UH135XV60D	5947816
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.32	2.36	9.70	C33-62D	SL280UH135V60D	5947817
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.30	2.36	9.70	C33-62D	SLP98UH135XV60D	5947818
XP25-060-230	57,500	19.00	12.00	54,500	35,800	3.28	2.46	10.20	CBX32MV-060		5947803
XP25-060-230	58,000	19.50	12.50	54,500	35,600	3.28	2.46	10.20	CBX40UHV-060		5947855
XP25-060-230	58,000	19.00	12.00	54,000	33,800	2.94	2.08	9.20	CH33-49	EL296UH090XV60C	5947834
XP25-060-230	58,000	19.00	12.00	54,000	33,600	2.96	2.06	9.20	CH33-49	EL296UH110XV60C	5947835
XP25-060-230	58,000	19.00	12.00	54,000	33,400	3.00	2.10	9.20	CH33-49	SL280UH090V60C	5947836
XP25-060-230	58,000	19.00	12.00	54,000	33,400	3.00	2.10	9.20	CH33-49	SL280UH090XV60C	8177629
XP25-060-230	58,000	19.00	12.00	54,000	33,600	2.98	2.08	9.20	CH33-49	SL280UH110V60C	5947837
XP25-060-230	58,000	19.00	12.00	54,000	33,600	2.98	2.08	9.20	CH33-49	SL280UH110XV60C	8177630
XP25-060-230	58,000	19.00	12.00	54,000	33,800	2.94	2.08	9.20	CH33-49	SLP98UH090XV60C	5947838
XP25-060-230	58,000	19.00	12.00	54,000	33,600	2.96	2.08	9.20	CH33-49	SLP98UH110XV60C	5947839
XP25-060-230	57,500	18.50	11.50	54,000	33,800	2.94	2.06	9.20	CH33-50/60C	EL296UH090XV60C	5947840
XP25-060-230	57,500	18.50	11.50	54,000	33,600	2.96	2.06	9.20	CH33-50/60C	EL296UH110XV60C	5947841
XP25-060-230	58,000	19.00	12.00	54,000	33,400	3.00	2.08	9.20	CH33-50/60C	SL280UH090V60C	5947842
XP25-060-230	58,000	19.00	12.00	54,000	33,400	3.00	2.08	9.20	CH33-50/60C	SL280UH090XV60C	8177631
XP25-060-230	57,500	18.50	12.00	54,000	33,600	2.96	2.08	9.20	CH33-50/60C	SL280UH110V60C	5947843
XP25-060-230	57,500	18.50	12.00	54,000	33,600	2.96	2.08	9.20	CH33-50/60C	SL280UH110XV60C	8177632
XP25-060-230	57,500	18.50	11.50	54,000	33,800	2.94	2.06	9.20	CH33-50/60C	SLP98UH090XV60C	5947844
XP25-060-230	57,500	18.50	11.50	54,000	33,600	2.96	2.06	9.20	CH33-50/60C	SLP98UH110XV60C	5947845
XP25-060-230	59,000	19.00	12.00	55,500	35,600	3.00	2.22	8.70	CH33-62D	EL296UH135XV60D	5947846
XP25-060-230	59,000	19.00	12.00	55,000	35,400	3.00	2.22	8.70	CH33-62D	SL280UH135V60D	5947847
XP25-060-230	59,000	19.00	12.00	55,500	35,600	3.00	2.22	8.70	CH33-62D	SLP98UH135XV60D	5947848
XP25-060-230	57,500	18.50	11.50	53,500	35,600	3.08	2.32	9.70	CR33-60	EL296DF090XV60C	5947856
XP25-060-230	58,000	18.50	12.00	53,500	35,600	3.08	2.32	9.70	CR33-60	EL296DF110XV60C	5947857
XP25-060-230	58,000	19.00	12.00	53,000	35,200	3.14	2.36	10.00	CR33-60	SL280DF090V60C	5947858
XP25-060-230	58,000	19.00	12.00	53,000	35,200	3.14	2.36	10.00	CR33-60	SL280DF110V60C	5947859
XP25-060-230	57,500	18.50	11.50	53,500	35,600	3.08	2.32	9.70	CR33-60	SLP98DF090XV60C	7979864
XP25-060-230	58,000	18.50	12.00	53,500	35,600	3.08	2.32	9.70	CR33-60	SLP98DF110XV60C	5947861
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.32	9.70	CX34-49C	EL296UH090XV60C	5947819
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.34	9.70	CX34-49C	EL296UH110XV60C	5947820
XP25-060-230	58,000	19.00	12.00	51,500	32,800	3.30	2.36	9.70	CX34-49C	SL280UH090V60C	5947821

**NOTES:**

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Capacity	SEER	EER	Heat Capacity High	Heat Capacity Low	Heat COP High	Heat COP Low	HSPF (IV)	Coil or Air Handler	Furnace	AHRI Reference
XP25-060-230	58,000	18.50	12.00	51,500	33,000	3.26	2.34	9.70	CX34-49C	SL280UH110V60C	5947822
XP25-060-230	57,500	18.50	12.00	52,000	33,200	3.26	2.32	9.70	CX34-49C	SLP98UH090XV60C	5947823
XP25-060-230	58,000	18.50	12.00	52,000	33,200	3.26	2.34	9.70	CX34-49C	SLP98UH110XV60C	5947824
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	9.70	CX34-62C	EL296UH090XV60C	8203141
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	10.00	CX34-62C	EL296UH110XV60C	8203142
XP25-060-230	60,500	19.50	12.50	54,000	33,200	3.28	2.32	10.00	CX34-62C	SL280UH090V60C	8203145
XP25-060-230	60,000	19.00	12.50	54,000	33,200	3.24	2.30	10.00	CX34-62C	SL280UH110V60C	8203146
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	9.70	CX34-62C	SLP98UH090XV60C	8203143
XP25-060-230	60,000	19.00	12.00	54,000	33,400	3.22	2.28	10.00	CX34-62C	SLP98UH110XV60C	8203144
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.30	2.36	9.70	CX34-62D	EL296UH135XV60D	5947831
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.32	2.36	9.70	CX34-62D	SL280UH135V60D	5947832
XP25-060-230	58,500	19.00	12.50	53,000	33,400	3.30	2.36	9.70	CX34-62D	SLP98UH135XV60D	5947833

## NOTES:

Ratings are AHRI certified to AHRI Standard 210/240 (with 25 ft. of connecting refrigerant lines);

- Cooling Ratings - 95°F outdoor air temperature and 80°F db/67°F wb entering indoor coil air.
- High Temperature Heating Ratings - 47°F db/43°F wb outdoor air temperature and 70°F db entering indoor coil air.
- Low Temperature Heating Ratings - 17°F db/15°F wb outdoor air temperature and 70°F db entering indoor coil air.

All ratings include the use of a blower time delay relay (TDR). All Lennox variable-speed Furnaces and Air Handlers have time delay capabilities. Other Furnaces and Air Handlers may require an optional time delay relay (**58M81**) for field installation. See furnace or air handler specifications to determine if relay is needed.

Also see TXV Substitution Table at the beginning of the Heat Pump AHRI System Matches section.

When used with gas furnaces, a dual-fuel control, a control system with dual-fuel capabilities (LZP-2 or LZP-4), or a thermostat with dual-fuel capabilities must be used (order separately).

To convert HSPF from Region IV to Region V - Divide by 1.15.





PRODUCT CATALOG

July 2016  
Supersedes February 2016

AHRI SYSTEM MATCHES

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-024-230A	24,000	17.00	14.00	21,600	13,500	4.06	2.74	9.60	C33-38A	EL180UH045E36A	8329075
SL18XP1-024-230A	24,000	17.00	14.00	21,600	13,500	4.06	2.74	9.60	C33-38A	EL180UH045XE36A	8329076
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.18	2.80	9.60	C33-38A	SL280UH070V36A	8329077
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.18	2.80	9.60	C33-38A	SL280UH070XV36A	8329078
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	C33-38B	EL180UH070E36B	8329079
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	C33-38B	EL180UH070XE36B	8329080
SL18XP1-024-230A	23,800	17.50	14.00	21,400	13,400	4.04	2.74	9.60	C33-38B	EL195UH045XE36B	8329081
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,500	4.10	2.78	9.60	C33-38B	EL195UH070XE36B	8329082
SL18XP1-024-230A	23,800	17.50	14.00	21,400	13,400	4.04	2.74	9.60	C33-38B	EL296UH045XE36B	8329083
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,400	4.10	2.76	9.60	C33-38B	EL296UH045XV36B	8329084
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,500	4.10	2.78	9.60	C33-38B	EL296UH070XE36B	8329085
SL18XP1-024-230A	23,800	18.00	14.50	21,200	13,300	4.08	2.78	9.60	C33-38B	SL280UH090V36B	8329086
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	C33-38B	SLP98UH070XV36B	8329087
SL18XP1-024-230A	23,600	15.00	12.50	22,200	14,100	3.82	2.58	9.00	C33-38B		8329088
SL18XP1-024-230A	24,000	18.00	14.50	21,600	13,700	4.18	2.86	9.60	CBX27UH-024		8331363
SL18XP1-024-230A	24,000	18.50	15.00	22,200	14,500	4.34	2.98	10.20	CBX27UH-030		8331364
SL18XP1-024-230A	23,600	16.50	13.50	22,000	14,000	3.98	2.70	9.50	CBX32M-030		8331365
SL18XP1-024-230A	24,000	16.50	13.50	22,800	15,000	4.06	2.78	9.60	CBX32M-036		8331366
SL18XP1-024-230A	24,000	18.00	14.50	21,600	13,700	4.20	2.86	9.60	CBX32MV-024/030		8331367
SL18XP1-024-230A	24,000	18.00	14.50	22,400	14,700	4.26	2.92	10.20	CBX32MV-036		8331368
SL18XP1-024-230A	24,000	18.00	15.00	22,400	14,700	4.30	2.94	10.20	CBX40UHV-024		8331369
SL18XP1-024-230A	24,000	18.00	14.50	22,400	14,700	4.26	2.94	10.20	CBX40UHV-030		8331370
SL18XP1-024-230A	24,000	18.00	15.00	22,600	14,800	4.38	2.98	10.20	CBX40UHV-036		8331371
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.88	2.72	9.50	CH33-44/48B	EL180UH070E36B	8329089
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.88	2.72	9.50	CH33-44/48B	EL180UH070XE36B	8329090
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,700	3.80	2.66	9.00	CH33-44/48B	EL195UH045XE36B	8329091
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.86	2.70	9.50	CH33-44/48B	EL195UH070XE36B	8329092
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,700	3.80	2.66	9.00	CH33-44/48B	EL296UH045XE36B	8329093
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.86	2.70	9.50	CH33-44/48B	EL296UH045XV36B	8329094
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.86	2.70	9.50	CH33-44/48B	EL296UH070XE36B	8329095
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.90	2.72	9.50	CH33-44/48B	EL296UH070XV36B	8657241
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,600	3.94	2.72	9.60	CH33-44/48B	SL280UH090V36B	8329096
SL18XP1-024-230A	24,000	18.00	15.00	21,400	13,700	3.90	2.72	9.50	CH33-44/48B	SLP98UH070XV36B	8329097
SL18XP1-024-230A	24,000	15.50	13.00	22,000	14,300	3.58	2.52	9.00	CH33-44/48B		8329098
SL18XP1-024-230A	24,000	17.00	14.00	21,600	13,500	4.06	2.74	9.60	CX34-38A	EL180UH045E36A	8329110
SL18XP1-024-230A	24,000	17.00	14.00	21,600	13,500	4.06	2.74	9.60	CX34-38A	EL180UH045XE36A	8329111
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.18	2.80	9.60	CX34-38A	SL280UH070V36A	8329112
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.18	2.80	9.60	CX34-38A	SL280UH070XV36A	8329113
SL18XP1-024-230A	23,400	15.00	12.50	22,000	14,000	3.78	2.58	9.00	CX34-38A		8329109
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	CX34-38B	EL180UH070E36B	8329114
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	CX34-38B	EL180UH070XE36B	8329115
SL18XP1-024-230A	23,800	17.50	14.00	21,400	13,400	4.04	2.74	9.60	CX34-38B	EL195UH045XE36B	8329116
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,500	4.10	2.78	9.60	CX34-38B	EL195UH070XE36B	8329117
SL18XP1-024-230A	23,800	17.50	14.00	21,400	13,400	4.04	2.74	9.60	CX34-38B	EL296UH045XE36B	8329118
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,400	4.10	2.76	9.60	CX34-38B	EL296UH045XV36B	8329204
SL18XP1-024-230A	24,000	17.50	14.50	21,400	13,500	4.10	2.78	9.60	CX34-38B	EL296UH070XE36B	8329119

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability.

Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	CX34-38B	EL296UH070XV36B	8657242
SL18XP1-024-230A	23,800	18.00	14.50	21,200	13,300	4.08	2.78	9.60	CX34-38B	SL280UH090V36B	8329120
SL18XP1-024-230A	24,000	18.00	14.50	21,400	13,400	4.14	2.78	9.60	CX34-38B	SLP98UH070XV36B	8329121
SL18XP1-030-230A	29,800	16.00	13.50	27,200	17,600	3.86	2.74	9.60	C33-38A	EL180UH045E36A	8329225
SL18XP1-030-230A	29,800	16.00	13.50	27,200	17,600	3.86	2.74	9.60	C33-38A	EL180UH045XE36A	8329226
SL18XP1-030-230A	29,200	14.50	12.00	27,600	18,100	3.62	2.58	9.00	C33-38A		8329224
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	C33-38B	EL180UH070E36B	8329227
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	C33-38B	EL180UH070XE36B	8329228
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	C33-38B	EL180UH090E48B	8329229
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	C33-38B	EL180UH090XE48B	8329230
SL18XP1-030-230A	29,800	16.00	13.00	27,200	17,700	3.86	2.74	9.60	C33-38B	EL195UH045XE36B	8329231
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,700	3.90	2.74	9.60	C33-38B	EL195UH070XE36B	8329232
SL18XP1-030-230A	29,800	16.00	13.00	27,200	17,700	3.86	2.74	9.60	C33-38B	EL296UH045XE36B	8329233
SL18XP1-030-230A	29,600	16.00	13.00	27,200	17,600	3.84	2.72	9.60	C33-38B	EL296UH045XV36B	8329234
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,700	3.90	2.74	9.60	C33-38B	EL296UH070XE36B	8329235
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.86	2.74	9.60	C33-38B	EL296UH070XV36B	8329236
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.88	2.74	9.60	C33-38B	SL280UH070V36A	8329237
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.88	2.74	9.60	C33-38B	SL280UH070XV36A	8329238
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,500	3.94	2.80	9.60	C33-38B	SL280UH090V36B	8329239
SL18XP1-030-230A	29,400	16.00	13.50	26,800	17,400	3.84	2.74	9.60	C33-38B	SL280UH090V48B	8329240
SL18XP1-030-230A	29,400	16.00	13.50	26,800	17,400	3.84	2.74	9.60	C33-38B	SL280UH090XV48B	8329241
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.86	2.74	9.60	C33-38B	SLP98UH070XV36B	8329242
SL18XP1-030-230A	30,000	14.50	12.00	27,600	17,800	3.60	2.50	8.50	C33-43		8329257
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.84	2.70	9.60	C33-43B	EL180UH070E36B	8329243
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.84	2.70	9.60	C33-43B	EL180UH070XE36B	8329244
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,200	3.88	2.72	9.60	C33-43B	EL180UH090E48B	8329245
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,200	3.88	2.72	9.60	C33-43B	EL180UH090XE48B	8329246
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,300	3.80	2.64	9.50	C33-43B	EL195UH045XE36B	8329247
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,400	3.82	2.66	9.50	C33-43B	EL195UH070XE36B	8329248
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,300	3.80	2.64	9.50	C33-43B	EL296UH045XE36B	8329249
SL18XP1-030-230A	30,000	16.00	13.50	27,000	17,200	3.74	2.62	9.00	C33-43B	EL296UH045XV36B	8329250
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,400	3.82	2.66	9.50	C33-43B	EL296UH070XE36B	8329251
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.76	2.64	9.50	C33-43B	EL296UH070XV36B	8329252
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,000	3.80	2.66	9.50	C33-43B	SL280UH090V36B	8329253
SL18XP1-030-230A	30,000	16.50	13.50	26,600	17,000	3.74	2.64	9.50	C33-43B	SL280UH090V48B	8329254
SL18XP1-030-230A	30,000	16.50	13.50	26,600	17,000	3.74	2.64	9.50	C33-43B	SL280UH090XV48B	8329255
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.76	2.64	9.50	C33-43B	SLP98UH070XV36B	8329256
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	C33-43C	EL195UH090XE48C	8329258
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,100	3.84	2.70	9.50	C33-43C	EL296UH090XE48C	8329259
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,000	3.82	2.68	9.50	C33-43C	EL296UH090XV36C	8329260
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,000	3.82	2.68	9.50	C33-43C	SLP98UH090XV36C	8329261
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	C33-50/60C	EL195UH090XE48C	8329262
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	C33-50/60C	EL296UH090XE48C	8329263
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.78	2.68	9.50	C33-50/60C	EL296UH090XV36C	8329264
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.78	2.68	9.50	C33-50/60C	SLP98UH090XV36C	8329265
SL18XP1-030-230A	30,000	14.50	12.00	27,400	17,800	3.52	2.50	9.00	C33-50/60C		8329266
SL18XP1-030-230A	29,800	16.50	13.50	26,000	17,200	3.88	2.78	9.60	CBX27UH-030		8331372
SL18XP1-030-230A	29,800	16.50	13.50	26,000	17,100	3.90	2.78	9.60	CBX27UH-036		8331373
SL18XP1-030-230A	29,600	15.50	13.00	27,600	18,100	3.80	2.74	9.50	CBX32M-030		8331374
SL18XP1-030-230A	29,400	15.00	12.50	26,400	17,700	3.70	2.66	9.00	CBX32M-036		8331375

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-030-230A	29,800	16.00	13.50	27,400	17,800	3.88	2.80	9.60	CBX32MV-024/030		8331376
SL18XP1-030-230A	29,600	15.50	13.00	26,200	17,400	3.78	2.72	9.50	CBX32MV-036		8331377
SL18XP1-030-230A	29,400	15.50	13.00	26,000	17,300	3.74	2.70	9.50	CBX40UHV-024		8331378
SL18XP1-030-230A	29,600	15.50	13.00	26,200	17,400	3.78	2.72	9.50	CBX40UHV-030		8331379
SL18XP1-030-230A	29,600	16.00	13.00	26,200	17,300	3.80	2.72	9.50	CBX40UHV-036		8331380
SL18XP1-030-230A	30,000	16.50	14.00	26,800	16,800	3.84	2.68	9.50	CH33-44/48B	EL180UH070E36B	8329267
SL18XP1-030-230A	30,000	16.50	14.00	26,800	16,800	3.84	2.68	9.50	CH33-44/48B	EL180UH070XE36B	8329268
SL18XP1-030-230A	30,000	17.00	14.00	27,000	16,800	3.90	2.68	9.50	CH33-44/48B	EL180UH090E48B	8329269
SL18XP1-030-230A	30,000	17.00	14.00	27,000	16,800	3.90	2.68	9.50	CH33-44/48B	EL180UH090XE48B	8329270
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,000	3.82	2.62	9.50	CH33-44/48B	EL195UH045XE36B	8329271
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,100	3.86	2.64	9.50	CH33-44/48B	EL195UH070XE36B	8329272
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,000	3.82	2.62	9.50	CH33-44/48B	EL296UH045XE36B	8329273
SL18XP1-030-230A	30,000	16.00	13.00	27,200	17,000	3.82	2.64	9.00	CH33-44/48B	EL296UH045XV36B	8657491
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,100	3.86	2.64	9.50	CH33-44/48B	EL296UH070XE36B	8329274
SL18XP1-030-230A	30,000	16.00	13.50	27,000	16,900	3.84	2.66	9.00	CH33-44/48B	EL296UH070XE36B	8657492
SL18XP1-030-230A	30,000	17.00	14.00	26,800	16,700	3.84	2.66	9.50	CH33-44/48B	SL280UH090V36B	8329275
SL18XP1-030-230A	30,000	16.50	14.00	26,800	16,700	3.80	2.64	9.50	CH33-44/48B	SL280UH090V48B	8329276
SL18XP1-030-230A	30,000	16.50	14.00	26,800	16,700	3.80	2.64	9.50	CH33-44/48B	SL280UH090XV48B	8329277
SL18XP1-030-230A	30,000	16.00	13.50	27,000	16,900	3.84	2.66	9.00	CH33-44/48B	SLP98UH070XV36B	8657493
SL18XP1-030-230A	30,000	15.00	12.50	27,800	17,500	3.64	2.52	9.00	CH33-44/48B		8329278
SL18XP1-030-230A	29,600	16.50	13.50	27,000	18,400	3.90	2.88	9.60	CR33-48B	EL180DF070E36B	8329322
SL18XP1-030-230A	29,400	16.50	13.50	26,800	18,400	3.84	2.86	9.60	CR33-48B	EL180DF090E48B	8329323
SL18XP1-030-230A	29,200	15.50	13.00	27,200	18,600	3.80	2.80	9.60	CR33-48B	EL195DF045XE36B	8329324
SL18XP1-030-230A	29,200	16.00	13.00	27,000	18,600	3.78	2.82	9.60	CR33-48B	EL195DF070XE48B	8331725
SL18XP1-030-230A	29,200	15.50	13.00	27,200	18,600	3.80	2.80	9.60	CR33-48B	EL296DF045XE36B	8329326
SL18XP1-030-230A	29,000	16.00	13.00	26,800	18,400	3.78	2.82	9.60	CR33-48B	EL296DF045XV36B	8329327
SL18XP1-030-230A	29,200	16.00	13.00	27,000	18,600	3.78	2.82	9.60	CR33-48B	EL296DF070XE48B	8329328
SL18XP1-030-230A	29,000	15.50	13.00	27,000	18,500	3.76	2.80	9.60	CR33-48B	EL296DF070XV48B	8329329
SL18XP1-030-230A	29,400	16.00	13.00	27,000	18,400	3.84	2.84	9.60	CR33-48B	SL280DF070V36A	8329330
SL18XP1-030-230A	29,200	16.00	13.00	26,800	18,400	3.80	2.84	9.60	CR33-48B	SL280DF090V48B	8329331
SL18XP1-030-230A	29,000	16.00	13.00	26,800	18,400	3.78	2.82	9.60	CR33-48B	SLP98DF070XV36B	8329332
SL18XP1-030-230A	28,800	14.50	12.00	27,600	19,100	3.64	2.70	9.50	CR33-48B		8329333
SL18XP1-030-230A	28,800	16.00	13.00	26,600	18,200	3.78	2.82	9.60	CR33-48C	SLP98DF090XV36C	8329334
SL18XP1-030-230A	28,800	16.00	13.00	26,600	18,200	3.78	2.82	9.60	CR33-48C	SLP98DF090XV48C	8329335
SL18XP1-030-230A	29,800	16.00	13.50	27,200	17,600	3.86	2.74	9.60	CX34-38A	EL180UH045E36A	8329279
SL18XP1-030-230A	29,800	16.00	13.50	27,200	17,600	3.86	2.74	9.60	CX34-38A	EL180UH045XE36A	8329280
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	CX34-38B	EL180UH070E36B	8329281
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	CX34-38B	EL180UH070XE36B	8329282
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	CX34-38B	EL180UH090E48B	8329283
SL18XP1-030-230A	29,800	16.50	13.50	27,000	17,500	3.92	2.78	9.60	CX34-38B	EL180UH090XE48B	8329284
SL18XP1-030-230A	29,800	16.00	13.00	27,200	17,700	3.86	2.74	9.60	CX34-38B	EL195UH045XE36B	8329285
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,700	3.90	2.74	9.60	CX34-38B	EL195UH070XE36B	8329286
SL18XP1-030-230A	29,800	16.00	13.00	27,200	17,700	3.86	2.74	9.60	CX34-38B	EL296UH045XE36B	8329287
SL18XP1-030-230A	29,600	16.00	13.00	27,200	17,600	3.84	2.72	9.60	CX34-38B	EL296UH045XV36B	8329288
SL18XP1-030-230A	30,000	16.00	13.50	27,400	17,700	3.90	2.74	9.60	CX34-38B	EL296UH070XE36B	8329289
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.86	2.74	9.60	CX34-38B	EL296UH070XV36B	8329290
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.88	2.74	9.60	CX34-38B	SL280UH070V36A	8329291
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.88	2.74	9.60	CX34-38B	SL280UH070XV36A	8329292
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,500	3.94	2.80	9.60	CX34-38B	SL280UH090V36B	8329293
SL18XP1-030-230A	29,400	16.00	13.50	26,800	17,400	3.84	2.74	9.60	CX34-38B	SL280UH090V48B	8329294

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-030-230A	29,400	16.00	13.50	26,800	17,400	3.84	2.74	9.60	CX34-38B	SL280UH090XV48B	8329295
SL18XP1-030-230A	29,600	16.00	13.50	27,000	17,500	3.86	2.74	9.60	CX34-38B	SLP98UH070XV36B	8329296
SL18XP1-030-230A	29,200	14.50	12.00	27,600	18,100	3.62	2.58	9.00	CX34-38B		8329297
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.84	2.70	9.60	CX34-43B	EL180UH070E36B	8329298
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.84	2.70	9.60	CX34-43B	EL180UH070XE36B	8329299
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,200	3.88	2.72	9.60	CX34-43B	EL180UH090E48B	8329300
SL18XP1-030-230A	30,000	16.50	13.50	27,000	17,200	3.88	2.72	9.60	CX34-43B	EL180UH090XE48B	8329301
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,300	3.80	2.64	9.50	CX34-43B	EL195UH045XE36B	8329302
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,400	3.82	2.66	9.50	CX34-43B	EL195UH070XE36B	8329303
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,300	3.80	2.64	9.50	CX34-43B	EL296UH045XE36B	8329304
SL18XP1-030-230A	30,000	16.00	13.50	27,000	17,200	3.74	2.62	9.00	CX34-43B	EL296UH045XV36B	8329305
SL18XP1-030-230A	30,000	16.00	13.50	27,200	17,400	3.82	2.66	9.50	CX34-43B	EL296UH070XE36B	8329306
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.76	2.64	9.50	CX34-43B	EL296UH070XV36B	8329307
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,000	3.80	2.66	9.50	CX34-43B	SL280UH090V36B	8329308
SL18XP1-030-230A	30,000	16.50	13.50	26,600	17,000	3.74	2.64	9.50	CX34-43B	SL280UH090V48B	8329309
SL18XP1-030-230A	30,000	16.50	13.50	26,600	17,000	3.74	2.64	9.50	CX34-43B	SL280UH090XV48B	8329310
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.76	2.64	9.50	CX34-43B	SLP98UH070XV36B	8329311
SL18XP1-030-230A	30,000	14.50	12.00	27,600	17,800	3.60	2.50	8.50	CX34-43B		8329312
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	CX34-43C	EL195UH090XE48C	8329313
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,100	3.84	2.70	9.50	CX34-43C	EL296UH090XE48C	8329314
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,000	3.82	2.68	9.50	CX34-43C	EL296UH090XV36C	8329315
SL18XP1-030-230A	30,000	16.50	14.00	26,800	17,000	3.82	2.68	9.50	CX34-43C	SLP98UH090XV36C	8329316
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	CX34-50/60C	EL195UH090XE48C	8329317
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.82	2.68	9.50	CX34-50/60C	EL296UH090XE48C	8329318
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.78	2.68	9.50	CX34-50/60C	EL296UH090XV36C	8329319
SL18XP1-030-230A	30,000	16.50	13.50	26,800	17,100	3.78	2.68	9.50	CX34-50/60C	SLP98UH090XV36C	8329320
SL18XP1-030-230A	30,000	14.50	12.00	27,400	17,800	3.52	2.50	9.00	CX34-50/60C		8329321
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,400	3.56	2.54	8.50	C33-43B	EL180UH070E36B	8329338
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,400	3.56	2.54	8.50	C33-43B	EL180UH070XE36B	8329339
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.62	2.56	9.00	C33-43B	EL180UH090E48B	8329340
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.62	2.56	9.00	C33-43B	EL180UH090XE48B	8329341
SL18XP1-036-230A	36,000	14.50	12.50	33,600	22,200	3.46	2.48	8.50	C33-43B	EL195UH045XE36B	8329342
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,000	3.50	2.48	8.50	C33-43B	EL195UH070XE36B	8329343
SL18XP1-036-230A	36,000	14.50	12.50	33,600	22,200	3.46	2.48	8.50	C33-43B	EL296UH045XE36B	8329344
SL18XP1-036-230A	36,000	15.10	13.00	33,400	21,800	3.56	2.52	8.50	C33-43B	EL296UH045XV36B	8329345
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,000	3.50	2.48	8.50	C33-43B	EL296UH070XE36B	8329346
SL18XP1-036-230A	36,000	16.00	13.50	32,800	21,600	3.58	2.58	9.00	C33-43B	SL280UH090V36B	8329347
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.62	2.56	9.00	C33-43B	SL280UH090V48B	8329348
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.62	2.56	9.00	C33-43B	SL280UH090XV48B	8329349
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.56	2.54	8.50	C33-43B	SLP98UH070XV36B	8329350
SL18XP1-036-230A	36,000	14.50	12.00	33,800	22,400	3.46	2.48	8.50	C33-43B		8329337
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.64	2.58	9.00	C33-43C	EL180UH090E60C	8329352
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.62	2.58	9.00	C33-43C	EL180UH110E60C	8329353
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.62	2.58	9.00	C33-43C	EL180UH110XE60C	8329354
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-43C	EL195UH090XE48C	8329355
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	C33-43C	EL195UH110XE60C	8329356
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-43C	EL296UH090XE48C	8329357
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-43C	EL296UH090XV36C	8329351
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.56	9.00	C33-43C	EL296UH090XV48C	8329358
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	C33-43C	EL296UH110XE60C	8329359

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	C33-43C	EL296UH110XV48C	8329360
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	C33-43C	EL296UH110XV60C	8329361
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	C33-43C	SL280UH090V60C	8329362
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	C33-43C	SL280UH090XV60C	8329363
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	C33-43C	SL280UH110V60C	8329364
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	C33-43C	SL280UH110XV60C	8329365
SL18XP1-036-230A	36,000	15.50	13.00	33,000	21,600	3.60	2.56	9.00	C33-43C	SLP98UH090XV36C	8329366
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.60	2.58	9.00	C33-43C	SLP98UH090XV48C	8329367
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.66	2.58	9.00	C33-43C	SLP98UH090XV60C	8329368
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	C33-43C	SLP98UH110XV60C	8329369
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	C33-49C	EL180UH090E60C	8329528
SL18XP1-036-230A	36,000	15.50	13.00	33,600	22,200	3.42	2.52	8.50	C33-49C	EL180UH110E60C	8329529
SL18XP1-036-230A	36,000	15.50	13.00	33,600	22,200	3.42	2.52	8.50	C33-49C	EL180UH110XE60C	8329530
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	C33-49C	EL195UH090XE48C	8329531
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.52	2.56	9.00	C33-49C	EL195UH110XE60C	8329532
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	C33-49C	EL296UH090XE48C	8329533
SL18XP1-036-230A	36,000	15.50	13.00	33,800	22,400	3.46	2.54	8.50	C33-49C	EL296UH090XV36C	8329534
SL18XP1-036-230A	36,000	16.00	13.00	33,600	22,200	3.44	2.52	8.50	C33-49C	EL296UH090XV48C	8329535
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.52	2.56	9.00	C33-49C	EL296UH110XE60C	8329536
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.54	2.56	9.00	C33-49C	EL296UH110XV60C	8329537
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.56	2.58	9.00	C33-49C	SL280UH090V60C	8329538
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.56	2.58	9.00	C33-49C	SL280UH090XV60C	8329539
SL18XP1-036-230A	36,000	15.50	13.00	34,000	22,400	3.50	2.54	9.00	C33-49C	SL280UH110V60C	8329540
SL18XP1-036-230A	36,000	15.50	13.00	34,000	22,400	3.50	2.54	9.00	C33-49C	SL280UH110XV60C	8329541
SL18XP1-036-230A	36,000	15.50	13.00	33,800	22,400	3.46	2.54	8.50	C33-49C	SLP98UH090XV36C	8329542
SL18XP1-036-230A	36,000	16.00	13.00	33,600	22,200	3.44	2.52	8.50	C33-49C	SLP98UH090XV48C	8329543
SL18XP1-036-230A	36,000	15.50	13.00	34,200	22,600	3.54	2.56	9.00	C33-49C	SLP98UH090XV60C	8329544
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.54	2.56	9.00	C33-49C	SLP98UH110XV60C	8329545
SL18XP1-036-230A	36,000	14.50	12.00	34,000	22,600	3.42	2.48	8.50	C33-49C		8329546
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-50/60C	EL180UH090E60C	8329370
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,600	3.54	2.56	8.50	C33-50/60C	EL180UH110E60C	8329371
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,600	3.54	2.56	8.50	C33-50/60C	EL180UH110XE60C	8329372
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-50/60C	EL195UH090XE48C	8329373
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.64	2.60	9.00	C33-50/60C	EL195UH110XE60C	8329374
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-50/60C	EL296UH090XE48C	8329375
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-50/60C	EL296UH090XV36C	8329376
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.58	9.00	C33-50/60C	EL296UH090XV48C	8329377
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.64	2.60	9.00	C33-50/60C	EL296UH110XE60C	8329378
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	C33-50/60C	EL296UH110XV48C	8329379
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	C33-50/60C	EL296UH110XV60C	8329380
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.62	9.00	C33-50/60C	SL280UH090V60C	8329381
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.62	9.00	C33-50/60C	SL280UH090XV60C	8329382
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	C33-50/60C	SL280UH110V60C	8329383
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	C33-50/60C	SL280UH110XV60C	8329384
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	C33-50/60C	SLP98UH090XV36C	8329385
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.58	9.00	C33-50/60C	SLP98UH090XV48C	8329386
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.66	2.60	9.00	C33-50/60C	SLP98UH090XV60C	8329387
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	C33-50/60C	SLP98UH110XV60C	8329388
SL18XP1-036-230A	36,000	14.50	12.00	33,800	22,400	3.46	2.48	8.50	C33-50/60C		8329389
SL18XP1-036-230A	35,600	15.50	13.00	33,400	22,200	3.68	2.68	9.50	CBX27UH-036		8331381

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,600	3.78	2.68	9.00	CBX27UH-042		8331382
SL18XP1-036-230A	35,200	14.50	12.00	34,000	22,600	3.54	2.56	9.00	CBX32M-036		8331383
SL18XP1-036-230A	35,200	14.50	12.00	34,000	22,600	3.54	2.56	9.00	CBX32M-042		8331384
SL18XP1-036-230A	36,000	14.50	12.50	33,800	22,200	3.60	2.56	8.50	CBX32M-048		8331385
SL18XP1-036-230A	35,600	15.00	12.50	34,000	22,600	3.64	2.62	9.00	CBX32MV-036		8331386
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,600	3.78	2.68	9.00	CBX32MV-048		8331387
SL18XP1-036-230A	36,000	15.50	12.50	33,600	22,400	3.66	2.66	9.50	CBX40UHV-036		8331388
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.66	2.62	9.00	CBX40UHV-042		8331389
SL18XP1-036-230A	36,000	15.50	13.50	33,400	21,800	3.72	2.64	9.00	CBX40UHV-048		8331390
SL18XP1-036-230A	36,000	15.50	13.00	33,000	21,800	3.54	2.58	8.50	CH33-43B	EL180UH070E36B	8329514
SL18XP1-036-230A	36,000	15.50	13.00	33,000	21,800	3.54	2.58	8.50	CH33-43B	EL180UH070XE36B	8329515
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.58	2.60	9.00	CH33-43B	EL180UH090XE48B	8329516
SL18XP1-036-230A	36,000	14.50	12.50	33,800	22,400	3.48	2.50	8.50	CH33-43B	EL195UH045XE36B	8329517
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,400	3.48	2.52	8.50	CH33-43B	EL195UH070XE36B	8329518
SL18XP1-036-230A	36,000	14.50	12.50	33,800	22,400	3.48	2.50	8.50	CH33-43B	EL296UH045XE36B	8329519
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,200	3.52	2.52	8.50	CH33-43B	EL296UH045XV36B	8329520
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,400	3.48	2.52	8.50	CH33-43B	EL296UH070XE36B	8329521
SL18XP1-036-230A	36,000	15.50	12.50	33,200	22,000	3.50	2.54	8.50	CH33-43B	EL296UH070XV36B	8329522
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,800	3.58	2.60	8.50	CH33-43B	SL280UH090V36B	8329523
SL18XP1-036-230A	36,000	16.00	13.00	33,200	22,000	3.62	2.62	9.00	CH33-43B	SL280UH090V48B	8329524
SL18XP1-036-230A	36,000	16.00	13.00	33,200	22,000	3.62	2.62	9.00	CH33-43B	SL280UH090XV48B	8329525
SL18XP1-036-230A	36,000	15.50	12.50	33,200	22,000	3.50	2.54	8.50	CH33-43B	SLP98UH070XV36B	8329526
SL18XP1-036-230A	36,000	14.50	12.00	34,000	22,600	3.46	2.50	8.50	CH33-43B		8329527
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.68	2.62	9.00	CH33-49	EL180UH090E60C	8329390
SL18XP1-036-230A	36,000	16.00	13.00	32,600	21,600	3.64	2.60	9.00	CH33-49	EL180UH110E60C	8329391
SL18XP1-036-230A	36,000	16.00	13.00	32,600	21,600	3.64	2.60	9.00	CH33-49	EL180UH110XE60C	8329392
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.62	2.60	8.50	CH33-49	EL195UH090XE48C	8329393
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-49	EL195UH110XE60C	8329394
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.62	2.60	8.50	CH33-49	EL296UH090XE48C	8329395
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.62	2.60	9.00	CH33-49	EL296UH090XV36C	8329396
SL18XP1-036-230A	36,000	16.00	13.00	32,600	21,800	3.62	2.62	8.50	CH33-49	EL296UH090XV48C	8329397
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-49	EL296UH110XE60C	8329398
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-49	EL296UH110XV48C	8329399
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-49	EL296UH110XV60C	8329400
SL18XP1-036-230A	36,000	16.00	13.00	32,800	22,000	3.68	2.66	9.00	CH33-49	SL280UH090V60C	8329401
SL18XP1-036-230A	36,000	16.00	13.00	32,800	22,000	3.68	2.66	9.00	CH33-49	SL280UH090XV60C	8329402
SL18XP1-036-230A	36,000	15.50	13.00	32,800	22,000	3.64	2.62	9.00	CH33-49	SL280UH110V60C	8329403
SL18XP1-036-230A	36,000	15.50	13.00	32,800	22,000	3.64	2.62	9.00	CH33-49	SL280UH110XV60C	8329404
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.64	2.60	9.00	CH33-49	SLP98UH090XV36C	8329405
SL18XP1-036-230A	36,000	16.00	13.00	32,600	21,800	3.62	2.62	8.50	CH33-49	SLP98UH090XV48C	8329406
SL18XP1-036-230A	36,000	15.50	13.00	33,000	22,000	3.66	2.62	9.00	CH33-49	SLP98UH090XV60C	8329407
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.68	2.62	9.00	CH33-49	SLP98UH110XV60C	8329408
SL18XP1-036-230A	36,000	14.50	12.00	33,200	22,400	3.40	2.46	8.50	CH33-49		8329409
SL18XP1-036-230A	36,000	15.50	13.00	32,600	21,800	3.58	2.60	8.50	CH33-50/60C	EL180UH090E60C	8329410
SL18XP1-036-230A	36,000	15.50	13.00	32,400	21,600	3.54	2.56	8.50	CH33-50/60C	EL180UH110E60C	8329411
SL18XP1-036-230A	36,000	15.50	13.00	32,400	21,600	3.54	2.56	8.50	CH33-50/60C	EL180UH110XE60C	8329412
SL18XP1-036-230A	36,000	15.50	12.50	32,600	21,800	3.54	2.56	8.50	CH33-50/60C	EL195UH090XE48C	8329413
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.60	2.58	8.50	CH33-50/60C	EL195UH110XE60C	8329414
SL18XP1-036-230A	36,000	15.50	12.50	32,600	21,800	3.54	2.56	8.50	CH33-50/60C	EL296UH090XE48C	8329415
SL18XP1-036-230A	36,000	15.50	13.00	32,600	21,800	3.58	2.60	8.50	CH33-50/60C	EL296UH090XV36C	8329416

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-036-230A	36,000	15.50	13.00	32,400	21,800	3.58	2.60	9.00	CH33-50/60C	EL296UH090XV48C	8329417
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.60	2.58	8.50	CH33-50/60C	EL296UH110XE60C	8329418
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,800	3.64	2.60	9.00	CH33-50/60C	EL296UH110XV48C	8329419
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-50/60C	EL296UH110XV60C	8329420
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-50/60C	SL280UH090V60C	8329421
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-50/60C	SL280UH090XV60C	8329422
SL18XP1-036-230A	36,000	15.50	13.00	32,800	22,000	3.62	2.62	9.00	CH33-50/60C	SL280UH110V60C	8329423
SL18XP1-036-230A	36,000	15.50	13.00	32,800	22,000	3.62	2.62	9.00	CH33-50/60C	SL280UH110XV60C	8329424
SL18XP1-036-230A	36,000	15.50	13.00	32,600	21,800	3.58	2.60	8.50	CH33-50/60C	SLP98UH090XV36C	8329425
SL18XP1-036-230A	36,000	15.50	13.00	32,400	21,800	3.58	2.60	9.00	CH33-50/60C	SLP98UH090XV48C	8329426
SL18XP1-036-230A	36,000	15.50	13.00	33,000	22,000	3.64	2.60	9.00	CH33-50/60C	SLP98UH090XV60C	8329427
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,800	3.66	2.62	9.00	CH33-50/60C	SLP98UH110XV60C	8329428
SL18XP1-036-230A	36,000	14.50	12.00	33,400	22,400	3.44	2.48	8.50	CH33-50/60C		8329429
SL18XP1-036-230A	36,000	16.00	13.50	33,200	22,000	3.82	2.72	9.00	CR33-50/60	EL180DF110E60C	8329430
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.76	2.68	9.00	CR33-50/60	EL195DF090XE48C	8329431
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.78	2.70	9.00	CR33-50/60	EL195DF110XE60C	8329432
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.76	2.68	9.00	CR33-50/60	EL296DF090XE48C	8329433
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.76	2.68	9.00	CR33-50/60	EL296DF090XV60C	8329434
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.78	2.70	9.00	CR33-50/60	EL296DF110XE60C	8329435
SL18XP1-036-230A	36,000	16.00	13.50	33,000	22,000	3.78	2.74	9.00	CR33-50/60	SL280DF110V60C	8329436
SL18XP1-036-230A	36,000	15.50	13.00	33,000	22,000	3.70	2.68	9.00	CR33-50/60	SLP98DF090XV36C	8329437
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.76	2.70	9.00	CR33-50/60	SLP98DF090XV48C	8329438
SL18XP1-036-230A	36,000	15.50	13.00	33,200	22,000	3.76	2.68	9.00	CR33-50/60	SLP98DF090XV60C	8329439
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,200	3.78	2.72	9.00	CR33-50/60	SLP98DF110XV60C	8329440
SL18XP1-036-230A	36,000	14.50	12.00	33,800	22,600	3.54	2.54	8.50	CR33-50/60		8329441
SL18XP1-036-230A	36,000	16.00	13.00	32,800	21,400	3.56	2.54	8.50	CX34-43B	EL180UH070E36B	8329443
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,400	3.56	2.54	8.50	CX34-43B	EL180UH070XE36B	8329444
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.62	2.56	9.00	CX34-43B	EL180UH090E48B	8329445
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.62	2.56	9.00	CX34-43B	EL180UH090XE48B	8329446
SL18XP1-036-230A	36,000	14.50	12.50	33,600	22,200	3.46	2.48	8.50	CX34-43B	EL195UH045XE36B	8329447
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,000	3.50	2.48	8.50	CX34-43B	EL195UH070XE36B	8329448
SL18XP1-036-230A	36,000	14.50	12.50	33,600	22,200	3.46	2.48	8.50	CX34-43B	EL296UH045XE36B	8329449
SL18XP1-036-230A	36,000	15.10	13.00	33,400	21,800	3.56	2.52	8.50	CX34-43B	EL296UH045XV36B	8329450
SL18XP1-036-230A	36,000	15.00	12.50	33,600	22,000	3.50	2.48	8.50	CX34-43B	EL296UH070XE36B	8329451
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.56	2.54	8.50	CX34-43B	EL296UH070XV36B	8657051
SL18XP1-036-230A	36,000	16.00	13.50	32,800	21,600	3.58	2.58	9.00	CX34-43B	SL280UH090V36B	8329452
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.62	2.56	9.00	CX34-43B	SL280UH090V48B	8329453
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.62	2.56	9.00	CX34-43B	SL280UH090XV48B	8329454
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.56	2.54	8.50	CX34-43B	SLP98UH070XV36B	8329455
SL18XP1-036-230A	36,000	14.50	12.00	33,800	22,400	3.46	2.48	8.50	CX34-43B		8329442
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.64	2.58	9.00	CX34-43C	EL180UH090E60C	8329456
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.62	2.58	9.00	CX34-43C	EL180UH110E60C	8329457
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.62	2.58	9.00	CX34-43C	EL180UH110XE60C	8329458
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-43C	EL195UH090XE48C	8329459
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	CX34-43C	EL195UH110XE60C	8329460
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-43C	EL296UH090XE48C	8329461
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-43C	EL296UH090XV36C	8329462
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.56	9.00	CX34-43C	EL296UH090XV48C	8329463
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	CX34-43C	EL296UH110XE60C	8329464
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.66	2.60	9.00	CX34-43C	EL296UH110XV48C	8329465

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	CX34-43C	EL296UH110XV60C	8329466
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	CX34-43C	SL280UH090V60C	8329467
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	CX34-43C	SL280UH090XV60C	8329468
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	CX34-43C	SL280UH110V60C	8329469
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	CX34-43C	SL280UH110XV60C	8329470
SL18XP1-036-230A	36,000	15.50	13.00	33,000	21,600	3.60	2.56	9.00	CX34-43C	SLP98UH090XV36C	8329471
SL18XP1-036-230A	36,000	16.00	13.50	33,000	21,600	3.60	2.58	9.00	CX34-43C	SLP98UH090XV48C	8329472
SL18XP1-036-230A	36,000	15.50	13.00	33,400	21,800	3.66	2.58	9.00	CX34-43C	SLP98UH090XV60C	8329473
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.60	9.00	CX34-43C	SLP98UH110XV60C	8329474
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	CX34-49	EL180UH090E60C	8329475
SL18XP1-036-230A	36,000	15.50	13.00	33,600	22,200	3.42	2.52	8.50	CX34-49	EL180UH110E60C	8329476
SL18XP1-036-230A	36,000	15.50	13.00	33,600	22,200	3.42	2.52	8.50	CX34-49	EL180UH110XE60C	8329477
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	CX34-49	EL195UH090XE48C	8329478
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.52	2.56	9.00	CX34-49	EL195UH110XE60C	8329479
SL18XP1-036-230A	36,000	16.00	13.00	33,800	22,400	3.46	2.54	8.50	CX34-49	EL296UH090XE48C	8329480
SL18XP1-036-230A	36,000	15.50	13.00	33,800	22,400	3.46	2.54	8.50	CX34-49	EL296UH090XV36C	8329481
SL18XP1-036-230A	36,000	16.00	13.00	33,600	22,200	3.44	2.52	8.50	CX34-49	EL296UH090XV48C	8329482
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.52	2.56	9.00	CX34-49	EL296UH110XE60C	8329483
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.54	2.56	9.00	CX34-49	EL296UH110XV60C	8329484
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.56	2.58	9.00	CX34-49	SL280UH090V60C	8329485
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.56	2.58	9.00	CX34-49	SL280UH090XV60C	8329486
SL18XP1-036-230A	36,000	15.50	13.00	34,000	22,400	3.50	2.54	9.00	CX34-49	SL280UH110V60C	8329487
SL18XP1-036-230A	36,000	15.50	13.00	34,000	22,400	3.50	2.54	9.00	CX34-49	SL280UH110XV60C	8329488
SL18XP1-036-230A	36,000	15.50	13.00	33,800	22,400	3.46	2.54	8.50	CX34-49	SLP98UH090XV36C	8329489
SL18XP1-036-230A	36,000	16.00	13.00	33,600	22,200	3.44	2.52	8.50	CX34-49	SLP98UH090XV48C	8329490
SL18XP1-036-230A	36,000	15.50	13.00	34,200	22,600	3.54	2.56	9.00	CX34-49	SLP98UH090XV60C	8329491
SL18XP1-036-230A	36,000	16.00	13.50	34,000	22,400	3.54	2.56	9.00	CX34-49	SLP98UH110XV60C	8329492
SL18XP1-036-230A	36,000	14.50	12.00	34,200	22,800	3.48	2.52	8.50	CX34-49		8329493
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-50/60C	EL180UH090E60C	8329494
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,600	3.54	2.56	8.50	CX34-50/60C	EL180UH110E60C	8329495
SL18XP1-036-230A	36,000	15.50	13.00	32,800	21,600	3.54	2.56	8.50	CX34-50/60C	EL180UH110XE60C	8329496
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-50/60C	EL195UH090XE48C	8329497
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.64	2.60	9.00	CX34-50/60C	EL195UH110XE60C	8329498
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-50/60C	EL296UH090XE48C	8329499
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-50/60C	EL296UH090XV36C	8329500
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.58	9.00	CX34-50/60C	EL296UH090XV48C	8329501
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.64	2.60	9.00	CX34-50/60C	EL296UH110XE60C	8329502
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	CX34-50/60C	EL296UH110XV48C	8329503
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	CX34-50/60C	EL296UH110XV60C	8329504
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.62	9.00	CX34-50/60C	SL280UH090V60C	8329505
SL18XP1-036-230A	36,000	16.00	13.50	33,200	21,800	3.68	2.62	9.00	CX34-50/60C	SL280UH090XV60C	8329506
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	CX34-50/60C	SL280UH110V60C	8329507
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,800	3.64	2.58	9.00	CX34-50/60C	SL280UH110XV60C	8329508
SL18XP1-036-230A	36,000	15.50	13.00	33,200	21,600	3.62	2.56	9.00	CX34-50/60C	SLP98UH090XV36C	8329509
SL18XP1-036-230A	36,000	16.00	13.00	33,000	21,600	3.60	2.58	9.00	CX34-50/60C	SLP98UH090XV48C	8329510
SL18XP1-036-230A	36,000	15.50	13.00	33,400	22,000	3.66	2.60	9.00	CX34-50/60C	SLP98UH090XV60C	8329511
SL18XP1-036-230A	36,000	16.00	13.00	33,200	21,800	3.66	2.60	9.00	CX34-50/60C	SLP98UH110XV60C	8329512
SL18XP1-036-230A	36,000	14.50	12.00	33,800	22,400	3.46	2.48	8.50	CX34-50/60C		8329513
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	C33-43	EL180UH090E48B	8329547
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.36	2.40	8.50	C33-43	EL180UH090E60C	8329555

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	C33-43	EL180UH090XE48B	8329548
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	C33-43	EL180UH110E60C	8329559
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	C33-43	EL180UH110XE60C	8329560
SL18XP1-042-230A	40,000	15.00	12.50	35,200	22,600	3.28	2.36	8.50	C33-43	EL195UH090XE48C	8329561
SL18XP1-042-230A	40,500	15.00	12.50	35,600	22,800	3.36	2.38	8.50	C33-43	EL195UH110XE60C	8329562
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.20	2.30	8.20	C33-43	EL296UH045XV36B	8329554
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.18	2.28	8.20	C33-43	EL296UH070XV36B	8329552
SL18XP1-042-230A	40,000	15.00	12.50	35,200	22,600	3.28	2.36	8.50	C33-43	EL296UH090XE48C	8329563
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	C33-43	EL296UH090XV36C	8329573
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.36	8.50	C33-43	EL296UH090XV48C	8329572
SL18XP1-042-230A	40,000	15.00	12.50	35,000	22,400	3.28	2.34	8.50	C33-43	EL296UH090XV60C	8329564
SL18XP1-042-230A	40,500	15.00	12.50	35,600	22,800	3.36	2.38	8.50	C33-43	EL296UH110XE60C	8329565
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.36	8.50	C33-43	EL296UH110XV48C	8329566
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.38	8.50	C33-43	EL296UH110XV60C	8329567
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	C33-43	SL280UH090V36B	8329549
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.26	2.34	8.50	C33-43	SL280UH090V48B	8329550
SL18XP1-042-230A	40,000	15.10	13.00	35,000	22,400	3.30	2.38	8.50	C33-43	SL280UH090V60C	8329571
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.26	2.34	8.50	C33-43	SL280UH090XV48B	8329551
SL18XP1-042-230A	40,000	15.10	13.00	35,000	22,400	3.30	2.38	8.50	C33-43	SL280UH090XV60C	8329558
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	C33-43	SL280UH110V60C	8329556
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	C33-43	SL280UH110XV60C	8329557
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.18	2.28	8.20	C33-43	SLP98UH070XV36B	8329553
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	C33-43	SLP98UH090XV36C	8329574
SL18XP1-042-230A	40,000	15.10	12.50	35,000	22,400	3.30	2.36	8.50	C33-43	SLP98UH090XV48C	8329568
SL18XP1-042-230A	40,000	15.00	12.50	35,000	22,400	3.28	2.34	8.50	C33-43	SLP98UH090XV60C	8329569
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.38	8.50	C33-43	SLP98UH110XV60C	8329570
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.42	8.50	C33-49	EL180UH090E60C	8329577
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.40	8.50	C33-49	EL180UH110E60C	8329578
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.40	8.50	C33-49	EL180UH110XE60C	8329579
SL18XP1-042-230A	40,500	14.50	12.50	35,400	22,600	3.42	2.40	8.50	C33-49	EL195UH090XE48C	8329590
SL18XP1-042-230A	41,500	14.50	12.50	35,600	22,800	3.46	2.40	8.50	C33-49	EL195UH110XE60C	8329591
SL18XP1-042-230A	40,500	14.50	12.50	35,400	22,600	3.42	2.40	8.50	C33-49	EL296UH090XE48C	8329592
SL18XP1-042-230A	41,000	14.50	12.50	35,400	22,800	3.44	2.40	8.50	C33-49	EL296UH090XV36C	8329593
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,800	3.46	2.44	8.50	C33-49	EL296UH090XV48C	8329580
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.44	2.42	8.50	C33-49	EL296UH090XV60C	8329581
SL18XP1-042-230A	41,500	14.50	12.50	35,600	22,800	3.46	2.40	8.50	C33-49	EL296UH110XE60C	8329594
SL18XP1-042-230A	41,500	15.10	12.50	35,600	22,800	3.50	2.44	8.50	C33-49	EL296UH110XV48C	8329582
SL18XP1-042-230A	41,500	15.10	12.50	35,400	22,800	3.48	2.46	8.50	C33-49	EL296UH110XV60C	8329583
SL18XP1-042-230A	41,000	15.10	13.00	35,200	22,400	3.48	2.44	8.50	C33-49	SL280UH090V60C	8329589
SL18XP1-042-230A	41,000	15.10	13.00	35,200	22,400	3.48	2.44	8.50	C33-49	SL280UH090XV60C	8329587
SL18XP1-042-230A	41,500	15.10	13.00	35,400	22,600	3.50	2.44	9.00	C33-49	SL280UH110V60C	8329575
SL18XP1-042-230A	41,500	15.10	13.00	35,400	22,600	3.50	2.44	9.00	C33-49	SL280UH110XV60C	8329576
SL18XP1-042-230A	41,000	15.00	12.50	35,400	22,800	3.44	2.40	8.50	C33-49	SLP98UH090XV36C	8329588
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.46	2.42	8.50	C33-49	SLP98UH090XV48C	8329584
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.44	2.42	8.50	C33-49	SLP98UH090XV60C	8329585
SL18XP1-042-230A	41,500	15.10	12.50	35,400	22,800	3.48	2.46	8.50	C33-49	SLP98UH110XV60C	8329586
SL18XP1-042-230A	40,500	14.00	11.50	36,200	23,400	3.32	2.32	8.50	C33-49		8329595
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.30	2.36	8.50	C33-50/60C	EL180UH090E60C	8329598
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.28	2.36	8.50	C33-50/60C	EL180UH110E60C	8329599
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.28	2.36	8.50	C33-50/60C	EL180UH110XE60C	8329600

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.24	2.32	8.50	C33-50/60C	EL195UH090XE48C	8329601
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	C33-50/60C	EL195UH110XE60C	8329602
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.24	2.32	8.50	C33-50/60C	EL296UH090XE48C	8329603
SL18XP1-042-230A	39,500	14.50	12.00	35,400	22,800	3.24	2.32	8.50	C33-50/60C	EL296UH090XV36C	8329611
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	C33-50/60C	EL296UH090XV48C	8329604
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.26	2.34	8.50	C33-50/60C	EL296UH090XV60C	8329605
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	C33-50/60C	EL296UH110XE60C	8329606
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	C33-50/60C	EL296UH110XV48C	8329607
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	C33-50/60C	EL296UH110XV60C	8329608
SL18XP1-042-230A	39,500	15.00	12.50	35,000	22,400	3.26	2.34	8.50	C33-50/60C	SL280UH090V60C	8329596
SL18XP1-042-230A	39,500	15.00	12.50	35,000	22,400	3.26	2.34	8.50	C33-50/60C	SL280UH090XV60C	8329597
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	C33-50/60C	SL280UH110V60C	8329613
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	C33-50/60C	SL280UH110XV60C	8329614
SL18XP1-042-230A	39,500	14.50	12.00	35,400	22,800	3.24	2.32	8.50	C33-50/60C	SLP98UH090XV36C	8329612
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	C33-50/60C	SLP98UH090XV48C	8329615
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.26	2.34	8.50	C33-50/60C	SLP98UH090XV60C	8329609
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	C33-50/60C	SLP98UH110XV60C	8329610
SL18XP1-042-230A	41,000	15.50	13.00	36,800	24,000	3.62	2.56	9.00	CBX27UH-042		8331391
SL18XP1-042-230A	41,000	15.50	13.00	36,800	24,000	3.62	2.56	9.00	CBX27UH-048		8331392
SL18XP1-042-230A	41,000	14.50	12.50	37,200	24,400	3.54	2.52	9.00	CBX32M-048		8331393
SL18XP1-042-230A	41,500	15.50	13.00	36,800	24,000	3.64	2.58	9.50	CBX32MV-048		8331394
SL18XP1-042-230A	40,500	15.10	12.50	36,800	24,000	3.58	2.54	9.00	CBX40UHV-042		8331395
SL18XP1-042-230A	41,000	15.50	13.00	36,800	24,000	3.62	2.56	9.00	CBX40UHV-048		8331396
SL18XP1-042-230A	41,000	15.10	12.50	36,200	24,200	3.54	2.56	9.00	CH33-43B	EL180UH090E48B	8329616
SL18XP1-042-230A	41,000	15.10	12.50	36,200	24,200	3.54	2.56	9.00	CH33-43B	EL180UH090XE48B	8329617
SL18XP1-042-230A	41,000	14.50	12.50	36,400	24,400	3.46	2.50	9.00	CH33-43B	EL296UH045XV36B	8329623
SL18XP1-042-230A	41,000	14.50	12.50	36,400	24,400	3.46	2.50	9.00	CH33-43B	EL296UH070XV36B	8329621
SL18XP1-042-230A	41,500	15.10	13.00	36,200	24,200	3.56	2.58	9.00	CH33-43B	SL280UH090V36B	8329620
SL18XP1-042-230A	41,000	15.10	12.50	36,000	24,000	3.54	2.56	9.00	CH33-43B	SL280UH090V48B	8329618
SL18XP1-042-230A	41,000	15.10	12.50	36,000	24,000	3.54	2.56	9.00	CH33-43B	SL280UH090XV48B	8329619
SL18XP1-042-230A	41,000	14.50	12.50	36,400	24,400	3.46	2.50	9.00	CH33-43B	SLP98UH070XV36B	8329622
SL18XP1-042-230A	40,500	14.00	12.00	36,600	24,600	3.44	2.50	9.00	CH33-43B		8329624
SL18XP1-042-230A	41,500	15.50	13.00	35,400	23,000	3.50	2.50	9.00	CH33-49	EL180UH090E60C	8329625
SL18XP1-042-230A	41,000	15.50	13.00	35,400	23,000	3.50	2.50	9.00	CH33-49	EL180UH110E60C	8329626
SL18XP1-042-230A	41,000	15.50	13.00	35,400	23,000	3.50	2.50	9.00	CH33-49	EL180UH110XE60C	8329627
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.46	2.46	9.00	CH33-49	EL195UH090XE48C	8329630
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,200	3.50	2.48	9.00	CH33-49	EL195UH110XE60C	8329631
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.46	2.46	9.00	CH33-49	EL296UH090XE48C	8329632
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.46	2.46	9.00	CH33-49	EL296UH090XV36C	8329643
SL18XP1-042-230A	41,000	15.10	13.00	35,600	23,000	3.48	2.46	9.00	CH33-49	EL296UH090XV48C	8329633
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.48	9.00	CH33-49	EL296UH090XV60C	8329634
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,200	3.50	2.48	9.00	CH33-49	EL296UH110XE60C	8329635
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,200	3.50	2.48	9.00	CH33-49	EL296UH110XV48C	8329636
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,200	3.50	2.48	9.00	CH33-49	EL296UH110XV60C	8329637
SL18XP1-042-230A	41,000	15.50	13.00	35,200	22,800	3.48	2.48	9.00	CH33-49	SL280UH090V60C	8329628
SL18XP1-042-230A	41,000	15.50	13.00	35,200	22,800	3.48	2.48	9.00	CH33-49	SL280UH090XV60C	8329629
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,000	3.50	2.48	9.00	CH33-49	SL280UH110V60C	8329638
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,000	3.50	2.48	9.00	CH33-49	SL280UH110XV60C	8329639
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.46	2.46	9.00	CH33-49	SLP98UH090XV36C	8329644
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.46	9.00	CH33-49	SLP98UH090XV48C	8329640

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.48	9.00	CH33-49	SLP98UH090XV60C	8329641
SL18XP1-042-230A	41,500	15.10	13.00	35,600	23,200	3.50	2.48	9.00	CH33-49	SLP98UH110XV60C	8329642
SL18XP1-042-230A	41,000	14.00	12.00	36,200	23,600	3.38	2.40	9.00	CH33-49		8329645
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.48	9.00	CH33-50/60C	EL180UH090E60C	8329648
SL18XP1-042-230A	41,000	15.10	13.00	35,400	22,800	3.48	2.46	9.00	CH33-50/60C	EL180UH110E60C	8329649
SL18XP1-042-230A	41,000	15.10	13.00	35,400	22,800	3.48	2.46	9.00	CH33-50/60C	EL180UH110XE60C	8329650
SL18XP1-042-230A	40,500	15.10	12.50	35,400	23,000	3.44	2.46	9.00	CH33-50/60C	EL195UH090XE48C	8329914
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.48	2.48	9.00	CH33-50/60C	EL195UH110XE60C	8329651
SL18XP1-042-230A	40,500	15.10	12.50	35,400	23,000	3.44	2.46	9.00	CH33-50/60C	EL296UH090XE48C	8329662
SL18XP1-042-230A	41,000	15.00	12.50	35,600	23,200	3.44	2.46	9.00	CH33-50/60C	EL296UH090XV36C	8329663
SL18XP1-042-230A	41,000	15.10	13.00	35,600	23,000	3.46	2.46	9.00	CH33-50/60C	EL296UH090XV48C	8329652
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.44	2.46	9.00	CH33-50/60C	EL296UH090XV60C	8329653
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.48	2.48	9.00	CH33-50/60C	EL296UH110XE60C	8329654
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.48	2.48	9.00	CH33-50/60C	EL296UH110XV48C	8329655
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.48	2.48	9.00	CH33-50/60C	EL296UH110XV60C	8329656
SL18XP1-042-230A	41,000	15.50	13.00	35,200	22,800	3.48	2.48	9.00	CH33-50/60C	SL280UH090V60C	8329646
SL18XP1-042-230A	41,000	15.50	13.00	35,200	22,800	3.48	2.48	9.00	CH33-50/60C	SL280UH090XV60C	8329647
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.46	9.00	CH33-50/60C	SL280UH110V60C	8329657
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.48	2.46	9.00	CH33-50/60C	SL280UH110XV60C	8329658
SL18XP1-042-230A	41,000	15.00	12.50	35,600	23,200	3.44	2.46	9.00	CH33-50/60C	SLP98UH090XV36C	8329664
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.44	2.46	9.00	CH33-50/60C	SLP98UH090XV48C	8329659
SL18XP1-042-230A	41,000	15.10	13.00	35,400	23,000	3.44	2.46	9.00	CH33-50/60C	SLP98UH090XV60C	8329660
SL18XP1-042-230A	41,000	15.10	12.50	35,600	23,200	3.48	2.48	9.00	CH33-50/60C	SLP98UH110XV60C	8329661
SL18XP1-042-230A	40,500	14.00	12.00	36,200	23,600	3.38	2.38	8.50	CH33-50/60C		8329665
SL18XP1-042-230A	40,500	15.10	13.00	36,600	23,000	3.70	2.56	9.50	CR33-50/60	EL180DF110E60C	8329668
SL18XP1-042-230A	40,000	15.00	12.50	36,600	23,200	3.64	2.54	9.00	CR33-50/60	EL195DF090XE48C	8329673
SL18XP1-042-230A	40,500	15.10	12.50	36,800	23,200	3.70	2.54	9.50	CR33-50/60	EL195DF110XE60C	8329669
SL18XP1-042-230A	40,000	15.00	12.50	36,600	23,200	3.64	2.54	9.00	CR33-50/60	EL296DF090XE48C	8329674
SL18XP1-042-230A	40,500	15.10	12.50	36,800	23,200	3.70	2.54	9.50	CR33-50/60	EL296DF110XE60C	8329670
SL18XP1-042-230A	40,500	15.10	13.00	36,600	23,000	3.72	2.56	9.50	CR33-50/60	SL280DF090V60C	8329667
SL18XP1-042-230A	40,500	15.50	13.00	36,600	23,000	3.74	2.58	9.50	CR33-50/60	SL280DF110V60C	8329666
SL18XP1-042-230A	40,500	14.50	12.50	36,800	23,200	3.66	2.52	9.00	CR33-50/60	SLP98DF090XV36C	8329676
SL18XP1-042-230A	40,500	15.10	13.00	36,600	23,200	3.66	2.54	9.00	CR33-50/60	SLP98DF090XV48C	8329672
SL18XP1-042-230A	40,500	15.00	12.50	37,000	23,400	3.70	2.54	9.00	CR33-50/60	SLP98DF090XV60C	8329675
SL18XP1-042-230A	40,500	15.10	12.50	36,800	23,200	3.70	2.56	9.50	CR33-50/60	SLP98DF110XV60C	8329671
SL18XP1-042-230A	40,000	14.00	12.00	37,400	23,800	3.52	2.46	9.00	CR33-50/60		8329677
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	CX34-43	EL180UH090E48B	8329678
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.36	2.40	8.50	CX34-43	EL180UH090E60C	8329686
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	CX34-43	EL180UH090XE48B	8329679
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	CX34-43	EL180UH110E60C	8329690
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	CX34-43	EL180UH110XE60C	8329691
SL18XP1-042-230A	40,000	15.00	12.50	35,200	22,600	3.28	2.36	8.50	CX34-43	EL195UH090XE48C	8329692
SL18XP1-042-230A	40,500	15.00	12.50	35,600	22,800	3.36	2.38	8.50	CX34-43	EL195UH110XE60C	8329693
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.20	2.30	8.20	CX34-43	EL296UH045XV36B	8329685
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.18	2.28	8.20	CX34-43	EL296UH070XV36B	8329683
SL18XP1-042-230A	40,000	15.00	12.50	35,200	22,600	3.28	2.36	8.50	CX34-43	EL296UH090XE48C	8329694
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	CX34-43	EL296UH090XV36C	8329704
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.36	8.50	CX34-43	EL296UH090XV48C	8329703
SL18XP1-042-230A	40,000	15.00	12.50	35,000	22,400	3.28	2.34	8.50	CX34-43	EL296UH090XV60C	8329695
SL18XP1-042-230A	40,500	15.00	12.50	35,600	22,800	3.36	2.38	8.50	CX34-43	EL296UH110XE60C	8329696

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.36	8.50	CX34-43	EL296UH110XV48C	8329697
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.38	8.50	CX34-43	EL296UH110XV60C	8329698
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	CX34-43	SL280UH090V36B	8329680
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.26	2.34	8.50	CX34-43	SL280UH090V48B	8329681
SL18XP1-042-230A	40,000	15.10	13.00	35,000	22,400	3.30	2.38	8.50	CX34-43	SL280UH090V60C	8329702
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.26	2.34	8.50	CX34-43	SL280UH090XV48B	8329682
SL18XP1-042-230A	40,000	15.10	13.00	35,000	22,400	3.30	2.38	8.50	CX34-43	SL280UH090XV60C	8329689
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	CX34-43	SL280UH110V60C	8329687
SL18XP1-042-230A	40,500	15.10	12.50	35,200	22,600	3.34	2.38	8.50	CX34-43	SL280UH110XV60C	8329688
SL18XP1-042-230A	40,000	14.00	12.00	35,600	23,000	3.18	2.28	8.20	CX34-43	SLP98UH070XV36B	8329684
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	CX34-43	SLP98UH090XV36C	8329705
SL18XP1-042-230A	40,000	15.10	12.50	35,000	22,400	3.30	2.36	8.50	CX34-43	SLP98UH090XV48C	8329699
SL18XP1-042-230A	40,000	15.00	12.50	35,000	22,400	3.28	2.34	8.50	CX34-43	SLP98UH090XV60C	8329700
SL18XP1-042-230A	40,500	15.00	12.50	35,400	22,600	3.34	2.38	8.50	CX34-43	SLP98UH110XV60C	8329701
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.42	8.50	CX34-49	EL180UH090E60C	8329709
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.40	8.50	CX34-49	EL180UH110E60C	8329710
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,600	3.46	2.40	8.50	CX34-49	EL180UH110XE60C	8329711
SL18XP1-042-230A	40,500	14.50	12.50	35,400	22,600	3.42	2.40	8.50	CX34-49	EL195UH090XE48C	8329721
SL18XP1-042-230A	41,500	14.50	12.50	35,600	22,800	3.46	2.40	8.50	CX34-49	EL195UH110XE60C	8329722
SL18XP1-042-230A	40,500	14.50	12.50	35,400	22,600	3.42	2.40	8.50	CX34-49	EL296UH090XE48C	8329723
SL18XP1-042-230A	41,000	14.50	12.50	35,400	22,800	3.44	2.40	8.50	CX34-49	EL296UH090XV36C	8329724
SL18XP1-042-230A	41,000	15.10	12.50	35,400	22,800	3.46	2.44	8.50	CX34-49	EL296UH090XV48C	8329712
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.44	2.42	8.50	CX34-49	EL296UH090XV60C	8329713
SL18XP1-042-230A	41,500	14.50	12.50	35,600	22,800	3.46	2.40	8.50	CX34-49	EL296UH110XE60C	8329725
SL18XP1-042-230A	41,500	15.10	12.50	35,600	22,800	3.50	2.44	8.50	CX34-49	EL296UH110XV48C	8329714
SL18XP1-042-230A	41,500	15.10	12.50	35,400	22,800	3.48	2.46	8.50	CX34-49	EL296UH110XV60C	8329715
SL18XP1-042-230A	41,000	15.10	13.00	35,200	22,400	3.48	2.44	8.50	CX34-49	SL280UH090V60C	8329720
SL18XP1-042-230A	41,000	15.10	13.00	35,200	22,400	3.48	2.44	8.50	CX34-49	SL280UH090XV60C	8329708
SL18XP1-042-230A	41,500	15.10	13.00	35,400	22,600	3.50	2.44	9.00	CX34-49	SL280UH110V60C	8329706
SL18XP1-042-230A	41,500	15.10	13.00	35,400	22,600	3.50	2.44	9.00	CX34-49	SL280UH110XV60C	8329707
SL18XP1-042-230A	41,000	15.00	12.50	35,400	22,800	3.44	2.40	8.50	CX34-49	SLP98UH090XV36C	8329719
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.46	2.42	8.50	CX34-49	SLP98UH090XV48C	8329716
SL18XP1-042-230A	41,000	15.10	12.50	35,200	22,600	3.44	2.42	8.50	CX34-49	SLP98UH090XV60C	8329717
SL18XP1-042-230A	41,500	15.10	12.50	35,400	22,800	3.48	2.46	8.50	CX34-49	SLP98UH110XV60C	8329718
SL18XP1-042-230A	40,500	14.00	11.50	36,200	23,400	3.32	2.32	8.50	CX34-49		8329726
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.30	2.36	8.50	CX34-50/60C	EL180UH090E60C	8329729
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.28	2.36	8.50	CX34-50/60C	EL180UH110E60C	8329730
SL18XP1-042-230A	40,000	14.50	12.50	35,200	22,600	3.28	2.36	8.50	CX34-50/60C	EL180UH110XE60C	8329731
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.24	2.32	8.50	CX34-50/60C	EL195UH090XE48C	8329732
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	CX34-50/60C	EL195UH110XE60C	8329733
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.24	2.32	8.50	CX34-50/60C	EL296UH090XE48C	8329734
SL18XP1-042-230A	39,500	14.50	12.00	35,400	22,800	3.24	2.32	8.50	CX34-50/60C	EL296UH090XV36C	8329744
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	CX34-50/60C	EL296UH090XV48C	8329735
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.26	2.34	8.50	CX34-50/60C	EL296UH090XV60C	8329736
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	CX34-50/60C	EL296UH110XE60C	8329737
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	CX34-50/60C	EL296UH110XV48C	8330124
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	CX34-50/60C	EL296UH110XV60C	8329738
SL18XP1-042-230A	39,500	15.00	12.50	35,000	22,400	3.26	2.34	8.50	CX34-50/60C	SL280UH090V60C	8329727
SL18XP1-042-230A	39,500	15.00	12.50	35,000	22,400	3.26	2.34	8.50	CX34-50/60C	SL280UH090XV60C	8329728
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	CX34-50/60C	SL280UH110V60C	8329739

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.30	2.34	8.50	CX34-50/60C	SL280UH110XV60C	8329740
SL18XP1-042-230A	39,500	14.50	12.00	35,400	22,800	3.24	2.32	8.50	CX34-50/60C	SLP98UH090XV36C	8329745
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,600	3.28	2.34	8.50	CX34-50/60C	SLP98UH090XV48C	8329741
SL18XP1-042-230A	39,500	14.50	12.50	35,200	22,600	3.26	2.34	8.50	CX34-50/60C	SLP98UH090XV60C	8329742
SL18XP1-042-230A	40,000	14.50	12.50	35,400	22,800	3.28	2.36	8.50	CX34-50/60C	SLP98UH110XV60C	8329743
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.68	2.72	9.00	C33-62C	EL180UH090E60C	8329122
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.66	2.70	9.50	C33-62C	EL180UH110E60C	8329125
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.66	2.70	9.50	C33-62C	EL180UH110XE60C	8329126
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.68	9.00	C33-62C	EL195UH090XE48C	8329130
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.64	2.70	9.00	C33-62C	EL195UH110XE60C	8329127
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.68	9.00	C33-62C	EL296UH090XE48C	8329131
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	EL296UH090XV48C	8329132
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	EL296UH090XV60C	8329133
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.64	2.70	9.00	C33-62C	EL296UH110XE60C	8329128
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	EL296UH110XV48C	8329134
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	EL296UH110XV60C	8329135
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.68	2.72	9.00	C33-62C	SL280UH090V60C	8329123
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.68	2.72	9.00	C33-62C	SL280UH090XV60C	8329124
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.66	2.72	9.00	C33-62C	SL280UH110V60C	8329205
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.66	2.72	9.00	C33-62C	SL280UH110XV60C	8329206
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	SLP98UH090XV48C	8329207
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	C33-62C	SLP98UH090XV60C	8329208
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.70	9.00	C33-62C	SLP98UH110XV60C	8329129
SL18XP1-048-230A	47,500	14.00	11.50	46,000	30,800	3.58	2.62	9.00	C33-62C		8329136
SL18XP1-048-230A	48,000	15.10	12.00	45,500	30,200	3.70	2.66	9.00	C33-62D	EL180UH135E60D	8329137
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.62	2.62	9.00	C33-62D	EL195UH135XE60D	8329140
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.62	2.62	9.00	C33-62D	EL296UH135XE60D	8329141
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.64	9.00	C33-62D	EL296UH135XV60D	8329138
SL18XP1-048-230A	47,500	15.10	12.00	45,000	30,000	3.64	2.66	9.00	C33-62D	SL280UH135V60D	8329209
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.64	9.00	C33-62D	SLP98UH135XV60D	8331723
SL18XP1-048-230A	47,500	14.00	11.50	46,000	30,800	3.58	2.58	9.00	C33-62D		8329142
SL18XP1-048-230A	47,500	15.10	12.50	47,000	30,400	3.76	2.68	9.00	CBX27UH-048		8331397
SL18XP1-048-230A	48,000	15.10	12.50	45,500	30,400	3.82	2.76	9.50	CBX27UH-060		8331398
SL18XP1-048-230A	47,500	15.10	12.00	47,000	30,600	3.70	2.66	9.00	CBX32M-048		8331399
SL18XP1-048-230A	48,000	14.50	12.50	46,500	30,400	3.72	2.70	9.00	CBX32M-060		8331400
SL18XP1-048-230A	47,500	15.00	12.00	47,000	30,400	3.70	2.64	9.00	CBX32MV-048		8331401
SL18XP1-048-230A	48,000	15.50	13.00	46,000	30,000	3.78	2.76	9.60	CBX32MV-060		8331402
SL18XP1-048-230A	47,500	15.50	12.50	46,500	30,200	3.74	2.68	9.00	CBX40UHV-048		8331403
SL18XP1-048-230A	48,000	15.50	12.50	46,000	30,000	3.78	2.76	9.50	CBX40UHV-060		8331404
SL18XP1-048-230A	48,000	15.10	12.50	45,000	29,800	3.58	2.58	9.50	CH33-49	EL180UH090E60C	8329143
SL18XP1-048-230A	47,500	15.10	12.50	44,500	29,600	3.52	2.56	9.00	CH33-49	EL180UH110E60C	8329144
SL18XP1-048-230A	47,500	15.10	12.50	44,500	29,600	3.52	2.56	9.00	CH33-49	EL180UH110XE60C	8329145
SL18XP1-048-230A	48,000	14.50	12.00	45,000	29,800	3.54	2.54	9.00	CH33-49	EL195UH090XE48C	8329150
SL18XP1-048-230A	48,000	15.00	12.50	45,000	29,800	3.56	2.56	9.00	CH33-49	EL195UH110XE60C	8329148
SL18XP1-048-230A	48,000	14.50	12.00	45,000	29,800	3.54	2.54	9.00	CH33-49	EL296UH090XE48C	8329151
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-49	EL296UH090XV48C	8329154
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-49	EL296UH090XV60C	8329155
SL18XP1-048-230A	48,000	15.00	12.50	45,000	29,800	3.56	2.56	9.00	CH33-49	EL296UH110XE60C	8329149
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.54	2.56	9.00	CH33-49	EL296UH110XV48C	8329152
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.54	2.56	9.00	CH33-49	EL296UH110XV60C	8329153

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-048-230A	48,000	15.00	12.00	45,000	29,800	3.58	2.58	9.00	CH33-49	SL280UH090V60C	8329146
SL18XP1-048-230A	48,000	15.00	12.00	45,000	29,800	3.58	2.58	9.00	CH33-49	SL280UH090XV60C	8329147
SL18XP1-048-230A	48,000	15.00	12.50	45,000	29,800	3.56	2.56	9.00	CH33-49	SL280UH110V60C	8329210
SL18XP1-048-230A	48,000	15.00	12.00	45,000	29,800	3.56	2.56	9.00	CH33-49	SL280UH110XV60C	8329211
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.54	2.54	9.00	CH33-49	SLP98UH090XV48C	8329212
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-49	SLP98UH090XV60C	8329213
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-49	SLP98UH110XV60C	8329214
SL18XP1-048-230A	48,000	14.00	11.50	45,500	30,400	3.50	2.52	9.00	CH33-49		8329156
SL18XP1-048-230A	47,500	15.00	12.50	44,500	29,600	3.52	2.56	9.00	CH33-50/60C	EL180UH090E60C	8329159
SL18XP1-048-230A	47,500	15.00	12.50	44,500	29,600	3.50	2.56	9.00	CH33-50/60C	EL180UH110E60C	8329160
SL18XP1-048-230A	47,500	15.00	12.50	44,500	29,600	3.50	2.56	9.00	CH33-50/60C	EL180UH110XE60C	8329161
SL18XP1-048-230A	47,500	14.50	12.00	45,000	29,800	3.50	2.54	9.00	CH33-50/60C	EL195UH090XE48C	8329164
SL18XP1-048-230A	47,500	14.50	12.00	45,000	29,800	3.52	2.54	9.00	CH33-50/60C	EL195UH110XE60C	8329162
SL18XP1-048-230A	47,500	14.50	12.00	45,000	29,800	3.50	2.54	9.00	CH33-50/60C	EL296UH090XE48C	8329165
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.50	2.54	9.00	CH33-50/60C	EL296UH090XV48C	8329169
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.50	2.54	9.00	CH33-50/60C	EL296UH090XV60C	8329170
SL18XP1-048-230A	47,500	14.50	12.00	45,000	29,800	3.52	2.54	9.00	CH33-50/60C	EL296UH110XE60C	8329163
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-50/60C	EL296UH110XV48C	8329166
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-50/60C	EL296UH110XV60C	8329167
SL18XP1-048-230A	48,000	15.10	12.50	45,000	29,800	3.60	2.60	9.50	CH33-50/60C	SL280UH090V60C	8329157
SL18XP1-048-230A	48,000	15.10	12.50	45,000	29,800	3.60	2.60	9.50	CH33-50/60C	SL280UH090XV60C	8329158
SL18XP1-048-230A	48,000	15.10	12.50	45,000	29,800	3.60	2.58	9.50	CH33-50/60C	SL280UH110V60C	8329215
SL18XP1-048-230A	48,000	15.10	12.50	45,000	29,800	3.60	2.58	9.50	CH33-50/60C	SL280UH110XV60C	8329216
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-50/60C	SLP98UH090XV48C	8329217
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.50	2.54	9.00	CH33-50/60C	SLP98UH090XV60C	8329336
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.52	2.54	9.00	CH33-50/60C	SLP98UH110XV60C	8329168
SL18XP1-048-230A	47,500	14.00	11.50	45,500	30,400	3.52	2.54	9.00	CH33-50/60C		8329171
SL18XP1-048-230A	48,000	15.00	12.50	45,000	30,600	3.62	2.72	9.00	CH33-62D	EL180UH135E60D	8654268
SL18XP1-048-230A	47,500	14.50	12.00	45,000	31,000	3.52	2.70	9.00	CH33-62D	EL195UH135XE60D	8654266
SL18XP1-048-230A	47,500	14.50	12.00	45,000	31,000	3.52	2.70	9.00	CH33-62D	EL296UH135XE60D	8654267
SL18XP1-048-230A	47,500	15.00	12.50	44,500	30,400	3.56	2.72	9.00	CH33-62D	SL280UH135V60DC	8654269
SL18XP1-048-230A	47,500	14.50	12.50	44,500	30,600	3.54	2.70	9.00	CH33-62D	SLP98UH135XV60D	8654270
SL18XP1-048-230A	47,000	14.00	11.50	45,500	31,400	3.48	2.66	9.00	CH33-62D		8654265
SL18XP1-048-230A	48,000	15.10	12.50	46,500	31,000	3.56	2.68	9.00	CR33-50/60	EL180DF110E60C	8329173
SL18XP1-048-230A	47,500	14.50	12.00	47,000	31,200	3.50	2.62	9.00	CR33-50/60	EL195DF090XE48C	8329179
SL18XP1-048-230A	47,500	14.50	12.50	46,500	31,000	3.50	2.64	9.00	CR33-50/60	EL195DF110XE60C	8329175
SL18XP1-048-230A	47,500	14.50	12.00	47,000	31,200	3.50	2.62	9.00	CR33-50/60	EL296DF090XE48C	8329180
SL18XP1-048-230A	47,500	14.50	12.50	46,500	31,000	3.50	2.64	9.00	CR33-50/60	EL296DF110XE60C	8329176
SL18XP1-048-230A	48,000	15.10	12.50	46,500	31,000	3.56	2.68	9.00	CR33-50/60	SL280DF090V60C	8329174
SL18XP1-048-230A	48,000	15.10	12.50	46,500	30,800	3.60	2.68	9.00	CR33-50/60	SL280DF110V60C	8329172
SL18XP1-048-230A	48,000	14.50	12.00	47,000	31,200	3.54	2.62	9.00	CR33-50/60	SLP98DF090XV60C	8329177
SL18XP1-048-230A	48,000	14.50	12.00	47,000	31,200	3.54	2.64	9.00	CR33-50/60	SLP98DF110XV60C	8329178
SL18XP1-048-230A	47,500	14.00	11.50	47,000	31,600	3.44	2.58	9.00	CR33-50/60		8329181
SL18XP1-048-230A	47,500	14.00	11.50	47,000	31,600	3.44	2.58	9.00	CR33-60		8329218
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,000	3.68	2.72	9.00	CX34-62C	EL180UH090E60C	8329182
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.66	2.70	9.50	CX34-62C	EL180UH110E60C	8329185
SL18XP1-048-230A	47,500	14.50	12.00	45,000	30,000	3.66	2.70	9.50	CX34-62C	EL180UH110XE60C	8329186
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.68	9.00	CX34-62C	EL195UH090XE48C	8329190
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.64	2.70	9.00	CX34-62C	EL195UH110XE60C	8329187
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.68	9.00	CX34-62C	EL296UH090XE48C	8329191

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	EL296UH090XV48C	8329192
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	EL296UH090XV60C	8329193
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.64	2.70	9.00	CX34-62C	EL296UH110XE60C	8329188
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	EL296UH110XV48C	8329194
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	EL296UH110XV60C	8329195
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.68	2.72	9.00	CX34-62C	SL280UH090V60C	8329183
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.68	2.72	9.00	CX34-62C	SL280UH090XV60C	8329184
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.66	2.72	9.00	CX34-62C	SL280UH110V60C	8329219
SL18XP1-048-230A	48,000	14.50	12.00	45,000	30,200	3.66	2.72	9.00	CX34-62C	SL280UH110XV60C	8329220
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	SLP98UH090XV48C	8329221
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.70	9.00	CX34-62C	SLP98UH090XV60C	8329222
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,200	3.66	2.70	9.00	CX34-62C	SLP98UH110XV60C	8329189
SL18XP1-048-230A	47,500	14.00	11.50	46,000	30,800	3.58	2.62	9.00	CX34-62C		8329196
SL18XP1-048-230A	48,000	15.10	12.00	45,500	30,200	3.70	2.66	9.00	CX34-62D	EL180UH135E60D	8329197
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.62	2.62	9.00	CX34-62D	EL195UH135XE60D	8329200
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.62	2.62	9.00	CX34-62D	EL296UH135XE60D	8329201
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.64	9.00	CX34-62D	EL296UH135XV60D	8329198
SL18XP1-048-230A	47,500	15.10	12.00	45,000	30,000	3.64	2.66	9.00	CX34-62D	SL280UH135V60D	8329223
SL18XP1-048-230A	48,000	14.50	12.00	45,500	30,400	3.66	2.64	9.00	CX34-62D	SLP98UH135XV60D	8329199
SL18XP1-048-230A	47,500	14.00	11.50	46,000	30,800	3.58	2.58	9.00	CX34-62D		8329202
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.62	2.60	9.00	C33-62C	EL180UH090E60C	8329005
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	C33-62C	EL180UH110E60C	8329008
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	C33-62C	EL180UH110XE60C	8329009
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.58	2.58	9.00	C33-62C	EL195UH110XE60C	8329012
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.58	2.58	9.00	C33-62C	EL296UH110XE60C	8329013
SL18XP1-060-230A	57,000	14.50	12.00	52,500	35,000	3.58	2.58	9.00	C33-62C	EL296UH110XV60C	8329014
SL18XP1-060-230A	57,000	14.50	12.00	52,500	34,600	3.64	2.60	9.00	C33-62C	SL280UH090V60C	8329006
SL18XP1-060-230A	57,000	14.50	12.00	52,500	34,600	3.64	2.60	9.00	C33-62C	SL280UH090XV60C	8329007
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	C33-62C	SL280UH110V60C	8329010
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	C33-62C	SL280UH110XV60C	8329011
SL18XP1-060-230A	57,000	14.00	11.50	53,000	35,200	3.64	2.60	9.00	C33-62C		8329015
SL18XP1-060-230A	56,000	14.50	12.00	52,000	34,400	3.54	2.54	9.00	C33-62D	EL180UH135E60D	8329017
SL18XP1-060-230A	56,000	14.50	12.00	52,500	34,800	3.52	2.52	9.00	C33-62D	EL195UH135XE60D	8329019
SL18XP1-060-230A	56,000	14.50	12.00	52,500	34,800	3.52	2.52	9.00	C33-62D	EL296UH135XE60D	8329020
SL18XP1-060-230A	55,500	15.00	12.50	51,500	34,000	3.58	2.58	9.00	C33-62D	SL280UH135V60D	8329016
SL18XP1-060-230A	56,000	14.50	12.00	52,000	34,600	3.52	2.54	9.00	C33-62D	SLP98UH135XV60D	8329018
SL18XP1-060-230A	55,500	14.00	11.50	52,500	35,000	3.50	2.54	9.00	C33-62D		8329021
SL18XP1-060-230A	56,000	14.50	12.00	53,500	35,800	3.72	2.74	9.60	CBX27UH-060		8331405
SL18XP1-060-230A	55,500	14.50	11.50	54,000	35,600	3.64	2.66	9.50	CBX32M-060		8331406
SL18XP1-060-230A	56,000	15.00	12.50	53,500	35,200	3.66	2.68	9.50	CBX32MV-060		8331407
SL18XP1-060-230A	55,500	14.50	12.00	53,500	35,200	3.66	2.70	9.50	CBX40UHV-060		8331408
SL18XP1-060-230A	56,000	14.50	12.00	54,000	36,000	3.52	2.62	9.00	CH33-49	EL180UH090E60C	8329026
SL18XP1-060-230A	56,000	14.00	12.00	54,500	36,200	3.54	2.62	9.00	CH33-49	EL180UH110E60C	8329027
SL18XP1-060-230A	56,000	14.00	12.00	54,500	36,200	3.54	2.62	9.00	CH33-49	EL180UH110XE60C	8329028
SL18XP1-060-230A	55,500	14.00	11.50	54,500	36,200	3.52	2.60	9.00	CH33-49	EL195UH110XE60C	8329029
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.48	2.60	9.00	CH33-49	EL296UH090XV60C	8657244
SL18XP1-060-230A	55,500	14.00	11.50	54,500	36,200	3.52	2.60	9.00	CH33-49	EL296UH110XE60C	8329030
SL18XP1-060-230A	56,000	14.00	11.50	54,500	36,200	3.54	2.60	9.00	CH33-49	EL296UH110XV60C	8657245
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,200	3.58	2.64	9.00	CH33-49	SL280UH090V60C	8329022
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,200	3.58	2.64	9.00	CH33-49	SL280UH090XV60C	8329023

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

**AHRI SYSTEM MATCHES**

Model No.	Cooling Cap.	SEER	EER	Heat Capacity		Heat COP		HSPF (IV)	Coil or Air Handler	Furnace	AHRI Ref. Number
				High	Low	High	Low				
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,000	3.56	2.62	9.00	CH33-49	SL280UH110V60C	8329024
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,000	3.56	2.62	9.00	CH33-49	SL280UH110XV60C	8329025
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.48	2.60	9.00	CH33-49	SLP98UH090XV60C	8329031
SL18XP1-060-230A	56,000	14.00	11.50	54,500	36,200	3.54	2.60	9.00	CH33-49	SLP98UH110XV60C	8329032
SL18XP1-060-230A	56,000	14.00	11.50	55,000	36,600	3.56	2.60	9.00	CH33-49		8329033
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.50	2.60	9.00	CH33-50/60C	EL180UH090E60C	8329038
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.48	2.58	9.00	CH33-50/60C	EL180UH110E60C	8329039
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.48	2.58	9.00	CH33-50/60C	EL180UH110XE60C	8329040
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.46	2.58	9.00	CH33-50/60C	EL195UH110XE60C	8329041
SL18XP1-060-230A	55,500	14.00	11.50	54,000	36,000	3.46	2.58	9.00	CH33-50/60C	EL296UH110XE60C	8329042
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,000	3.56	2.62	9.00	CH33-50/60C	SL280UH090V60C	8329034
SL18XP1-060-230A	56,000	14.50	12.00	54,500	36,000	3.56	2.62	9.00	CH33-50/60C	SL280UH090XV60C	8329035
SL18XP1-060-230A	55,500	14.50	11.50	54,000	36,000	3.52	2.62	9.00	CH33-50/60C	SL280UH110V60C	8329036
SL18XP1-060-230A	55,500	14.50	11.50	54,000	36,000	3.52	2.62	9.00	CH33-50/60C	SL280UH110XV60C	8329037
SL18XP1-060-230A	55,000	14.00	11.50	54,000	36,200	3.44	2.58	9.00	CH33-50/60C	SLP98UH090XV60C	8331724
SL18XP1-060-230A	56,000	14.00	11.50	55,000	36,600	3.56	2.62	9.00	CH33-50/60C		8329044
SL18XP1-060-230A	56,000	14.00	11.50	54,000	35,400	3.50	2.56	9.00	CH33-62D	EL180UH135E60D	8329045
SL18XP1-060-230A	56,000	14.00	11.50	54,500	35,800	3.48	2.54	9.00	CH33-62D	EL195UH135XE60D	8329048
SL18XP1-060-230A	56,000	14.00	11.50	54,500	35,800	3.48	2.54	9.00	CH33-62D	EL296UH135XE60D	8329049
SL18XP1-060-230A	56,500	14.00	11.50	54,500	35,600	3.54	2.58	9.00	CH33-62D	EL296UH135XV60D	8329046
SL18XP1-060-230A	56,000	14.50	12.00	53,500	34,800	3.54	2.60	9.00	CH33-62D	SL280UH135V60D	8329203
SL18XP1-060-230A	56,500	14.00	11.50	54,500	35,600	3.54	2.58	9.00	CH33-62D	SLP98UH135XV60D	8329047
SL18XP1-060-230A	56,000	14.00	11.50	55,000	35,800	3.52	2.56	9.00	CH33-62D		8329050
SL18XP1-060-230A	55,000	14.50	12.00	55,000	35,400	3.64	2.70	9.50	CR33-50/60	EL180DF110E60C	8329051
SL18XP1-060-230A	54,500	14.00	11.50	55,000	35,400	3.58	2.64	9.00	CR33-50/60	EL195DF110XE60C	8329053
SL18XP1-060-230A	54,500	14.00	11.50	55,000	35,400	3.58	2.64	9.00	CR33-50/60	EL296DF110XE60C	8329054
SL18XP1-060-230A	55,000	14.00	11.50	55,000	35,400	3.60	2.66	9.50	CR33-50/60	SL280DF090V60C	8329055
SL18XP1-060-230A	55,000	14.50	12.00	55,000	35,200	3.62	2.66	9.50	CR33-50/60	SL280DF110V60C	8329052
SL18XP1-060-230A	54,500	14.00	11.50	55,500	35,800	3.56	2.62	9.00	CR33-50/60		8329056
SL18XP1-060-230A	54,500	14.00	11.50	55,500	35,800	3.56	2.62	9.00	CR33-60		8329057
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.62	2.60	9.00	CX34-62C	EL180UH090E60C	8329058
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	CX34-62C	EL180UH110E60C	8329061
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	CX34-62C	EL180UH110XE60C	8329062
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.58	2.58	9.00	CX34-62C	EL195UH110XE60C	8329065
SL18XP1-060-230A	57,000	14.00	11.50	53,000	35,200	3.60	2.58	9.00	CX34-62C	EL296UH090XV60C	8657494
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.58	2.58	9.00	CX34-62C	EL296UH110XE60C	8329066
SL18XP1-060-230A	57,000	14.50	12.00	52,500	35,000	3.58	2.58	9.00	CX34-62C	EL296UH110XV60C	8329067
SL18XP1-060-230A	57,000	14.50	12.00	52,500	34,600	3.64	2.60	9.00	CX34-62C	SL280UH090V60C	8329059
SL18XP1-060-230A	57,000	14.50	12.00	52,500	34,600	3.64	2.60	9.00	CX34-62C	SL280UH090XV60C	8329060
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	CX34-62C	SL280UH110V60C	8329063
SL18XP1-060-230A	57,000	14.50	12.00	52,000	34,600	3.60	2.60	9.00	CX34-62C	SL280UH110XV60C	8329064
SL18XP1-060-230A	57,000	14.00	11.50	53,000	35,200	3.60	2.58	9.00	CX34-62C	SLP98UH090XV60C	8657495
SL18XP1-060-230A	57,000	14.50	12.00	52,500	35,000	3.58	2.58	9.00	CX34-62C	SLP98UH110XV60C	8657246
SL18XP1-060-230A	57,000	14.00	11.50	53,000	35,200	3.64	2.60	9.00	CX34-62C		8329068
SL18XP1-060-230A	56,000	14.50	12.00	52,000	34,400	3.54	2.54	9.00	CX34-62D	EL180UH135E60D	8329070
SL18XP1-060-230A	56,000	14.50	12.00	52,500	34,800	3.52	2.52	9.00	CX34-62D	EL195UH135XE60D	8329072
SL18XP1-060-230A	56,000	14.50	12.00	52,500	34,800	3.52	2.52	9.00	CX34-62D	EL296UH135XE60D	8329073
SL18XP1-060-230A	55,500	15.00	12.50	51,500	34,000	3.58	2.58	9.00	CX34-62D	SL280UH135V60D	8329069
SL18XP1-060-230A	56,000	14.50	12.00	52,000	34,600	3.52	2.54	9.00	CX34-62D	SLP98UH135XV60D	8329071
SL18XP1-060-230A	55,500	14.00	11.50	52,500	35,000	3.50	2.54	9.00	CX34-62D		8329074

NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



## REVISIONS

Sections	Description of Change
AHRI System Matches	Updated.