

SUBMITTAL DATA - CONTROLS V0CTRL15P-3 + V0CTRL95P-3 + V0CTRL91P-3 VRF Heat Pump & Heat Recovery

IVM Touch Screen Centralized	For: Reference Approval Review Construction	
System Designation:	Date:	
Schedule No.:	Location:	
Location:	Architect:	
Job:	Engineer:	

LVM Touch Screen Centralized Control System

FEATURES AND FUNCTIONS

- · Operation On/Off
- Operation Mode -- Auto / Cool / Heat / Fan
- Fan Speed -- Auto / High / Medium / Low
- · Centralized setpoint control
- Fahrenheit or Celsius temperature scale
- · Full color, touch screen for easy access
- · Remote web access standard
- Remote mobile access to Android[™] phones and IPhone[®]
- Group indoor units together for simultaneous
- · Full time-of-day scheduling
- · Available in 15" models
- · Control up to indoor units 2560 VRF indoor units

WARRANTY

• 1-year limited warranty. *See warranty for details.

SPECIFICATIONS		
PERFORMANCE		
Input Voltage (V)	Touch Screen	100~240 VAC
	Hardware Device	24 VAC
Communication Cabling		18 AWG
		2-conductor
		shielded cable
Ambient Temperature Range		14°F ~ 140°F
Ambient Humidity Range (RH)		20% ~ 85%
Maximum number of LVM Hardware per		10
LVM Touch Screen		10
Number of Communication Ports pe	r LVM	4
Hardware		
Maximum number of Indoor Units pe	er	64
communication port		04
DIMENSIONS		
15" Touch Screen Dimensions (in)	Height	11-1/4
	Width	14-3/8
	Depth	1-3/4







