



SUBMITTAL DATA – INDOOR UNIT

VVCA048H4-2P

VRF HEAT PUMP & HEAT RECOVERY

Job: _____

Location: _____

Schedule No.: _____

System Designation: _____

Engineer: _____

Architect: _____

Date: _____

For: Reference Approval Review Construction

Vertical Air Handler

FEATURES

- Vertical upflow, horizontal-right, and horizontal-left configurations for air discharge
- Painted, galvanized steel cabinet and fully insulated
- Electronic expansion valve
- Front access to ports, electrical components, filter rack, and the internal expansion valve kit
- Direct-drive, variable speed ECM fan motor
- R-410A refrigerant
- Optional Electric Heat

SPECIFICATIONS

PERFORMANCE		
Cooling Capacity ¹ (Btu/h)		48,000
Heating Capacity ¹ (Btu/h)		54,000
Airflow (CFM)	High	1,600
	Medium	1,360
	Low	1,120
Maximum External Static Pressure (in. WC)		0.80
Sound Power (dBA)	High	57
	Medium	54
	Low	52
ELECTRICAL DATA		
Power Supply (V/Hz/Φ)		208-230/60/1
Minimum Circuit Ampacity (MCA)		5.3
Max. Overcurrent Protection (MOCP)		15
Cooling Power Input ² (W)		590
Cooling Rated Current (A)		3.95
Heating Power Input ² (W)		590
Heating Rated Current (A)		3.95
DIMENSIONS		
Unit Dimensions (in)	Height	54-1/2
	Width	22
	Depth	24
Filter Size (not furnished) (in)		20 x 22 x 1
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		5/8
Condensate Drain Connection (in)		3/4
Shipping Weight (lb)		190
Net Weight (lb)		163



ELECTRIC HEATER

<input type="checkbox"/> 5 kW	V8EH0050P-1P
<input type="checkbox"/> 7.5 kW	V8EH0075P-1P
<input type="checkbox"/> 10 kW	V8EH0100P-1P
<input type="checkbox"/> 15 kW	V8EH0150P-1P
<input type="checkbox"/> 20 kW	V8EH0200P-1P

OPTIONAL ACCESSORIES

<input type="checkbox"/> Non-Programmable Controller	V0STAT54P
<input type="checkbox"/> Programmable Controller	V0STAT51P
<input type="checkbox"/> Wireless Handheld Controller	V0STAT52P-1
<input type="checkbox"/> Infrared Sensor	V0SNSR78P-1
<input type="checkbox"/> Hotel Keycard Interface	V0CTRL88P-1

NOTES


1. Cooling and heating capacity data is rated at the following conditions:
Cooling: 80°FDB / 67°FDB Indoor, 95°FDB Outdoor
Heating: 70°FDB Indoor, 47°FDB / 43°FDB Outdoor
2. Power input values are rated at high fan speed.





SUBMITTAL DATA – INDOOR UNIT
VVCA048H4-2P
VRF HEAT PUMP & HEAT RECOVERY

DIMENSIONAL DRAWINGS - INCHES (MM)



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.