

SUBMITTAL DATA - INDOOR UNIT VVCB018H4-3P VRF Heat Pump & Heat Recovery

Job:	Engine	er:			
Location:	Archite	ect:			
Schedule No.:	Location:				
System Designation:	Date:				
	For:	Reference	Approval	Review	Construction

Vertical Air Handler Ducted Indoor Unit

-EATURES			
 Pre Heat Function 	 Optional Electric Heat 	Four Built-In Dry Contacts Relays	Refrigerant R-410A
 Auto Addressing 	Electronic Expansion Valve	 Brazed Connections 	Eight Capacity Sizes from 12,000 to 60,000
 Auto Restart 	 High-Efficiency DC Motor 		Btu/h

WARRANTY

NOTES

conditions:

1.

2.

• 10-year limited warranty.*See warranty for details.

SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity ¹ (Btu/h)		18,000
Heating Capacity ¹ (Btu/h)		21,000
Airflow (CFM)	Low/Medium/High	420/510/600
External Static Pressure (in. WC)		0~0.8
Sound Pressure (dBA)	Low/Medium/High	36.7/39.3/42.2
Vertical Install		
Sound Pressure (dBA)	Low/Medium/High	31.4/35.5/38.2
Horizontal Install		
ELECTRICAL DATA		
Power Supply (Volts/Phase/Hertz)		208/230V-1Ph-
		60Hz
Minimum Circuit Ampacity (MCA)		3.8
Max. Overcurrent Protection (MOC	P)	15
Cooling Power Input ² (W)		57
Cooling Rated Current (A)		0.65
Heating Power Input ² (W)		58
Heating Rated Current (A)		0.65
Indoor Fan Motor Input (W)		60(H:50Pa)
DIMENSIONS		
Unit Dimensions (in)	Height	45-3/4
	Width	19-3/4
	Depth	21-5/8
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		5/8
Condensate Drain Connection (in)		3/4 NPT(I.D.)
Unit Shipping Weight (lb)		147
Unit Net Weight (Ib)		123

Cooling and Heating capacity data is rated at the following

Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor.

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB

Power Input values are rated at high fan speed.



ELECTRIC HEATER	
5 kW (V8EH0050P-1P)	
7.5 kW (V8EH0080P-1P)	
OPTIONAL ACCESSORIES	
Non-Programmable Controller	V0STAT54P-3
Programmable Wired Controller	V0STAT51P-3
Infrared Wireless Controller	V0STAT52P-1
Occupancy Sensor	V0SNSR78P-3
Hotel Keycard Interface	V0CTRL88P-1
HHE Relay Kit	V0CTRL92P-3
Condensate Pumps (Reference Condensate Pump Selection Guide)	-



NOTE - Due to Lennox' opaging commitment to quality. Specifications, Ratings and Dimensions subject to change without national without insurging liability.

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury.

Installation and service must be performed by a qualified installer and servicing agency. 495733 (202010)



SUBMITTAL DATA - INDOOR UNIT VVCB018H4-3P

VRF Heat Pump & Heat Recovery

DIMENSIONAL DRAWINGS - INCHES (MM)

