

Job:
 Location:
 Schedule No.:
 System Designation:

Engineer:
 Architect:
 Location:
 Date:

For: Reference Approval Review Construction

Vertical Air Handler Ducted Indoor Unit

FEATURES

- Pre Heat Function
- Auto Addressing
- Auto Restart
- Optional Electric Heat
- Electronic Expansion Valve
- High-Efficiency DC Motor
- Four Built-In Dry Contacts Relays
- Brazed Connections
- Refrigerant R-410A
- Eight Capacity Sizes from 12,000 to 60,000 Btu/h

WARRANTY

- 10-year limited warranty.*See warranty for details.

SPECIFICATIONS

PERFORMANCE

Cooling Capacity ¹ (Btu/h)		53,500
Heating Capacity ¹ (Btu/h)		60,000
Airflow (CFM)	Low/Medium/High	1260/1530/1800
External Static Pressure (in. WC)		0~0.8
Sound Pressure (dBA)	Low/Medium/High	51/55.7/60.5
Vertical Install		
Sound Pressure (dBA)	Low/Medium/High	46.7/ 51.8/56
Horizontal Install		

ELECTRICAL DATA

Power Supply (Volts/Phase/Hertz)	208/230V-1Ph-60Hz
Minimum Circuit Ampacity (MCA)	7.2
Max. Overcurrent Protection (MOCP)	15
Cooling Power Input ² (W)	585
Cooling Rated Current (A)	4.3
Heating Power Input ² (W)	632
Heating Rated Current (A)	4.5
Indoor Fan Motor Input (W)	466(H:75Pa)

DIMENSIONS

Unit Dimensions (in)	Height	53-3/4
	Width	22
	Depth	24
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		5/8
Condensate Drain Connection (in)		3/4 NPT(I.D.)
Unit Shipping Weight (lb)		189
Unit Net Weight (lb)		163

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:
 Cooling: 80°FDB / 67°FWB Indoor, 95°FDB
 Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor.
2. Power Input values are rated at high fan speed.




ELECTRIC HEATER

5 kW (V8EH0050P-1P)	
7.5 kW (V8EH0080P-1P)	
Non-Programmable Controller	V0STAT54P-3
Programmable Wired Controller	V0STAT51P-3
Infrared Wireless Controller	V0STAT52P-1
Occupancy Sensor	V0SNSR78P-3
Hotel Keycard Interface	VOCTRL88P-1
HHE Relay Kit	VOCTRL92P-3
Condensate Pumps (Reference Condensate Pump Selection Guide)	-



DIMENSIONAL DRAWINGS - INCHES (MM)



NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.